

CS1010 Laboratory 07

Compiler, Multidimensional Arrays, Efficiency, Exercise 5

Zhang Puyu

Group BD04

October 17, 2024

Plan of the Day

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

- 1 Exercise 4 Review
 - Dynamic Arrays
 - Compare Characters
 - Combinatorics
- 2 Introduction to clang
- 3 Multidimensional Arrays
- 4 Big-O
- 5 Selected Problems from Exercise 5

Memory Management

CS1010

Laboratory 07

Zhang Puyu

Exercise 4

Review

Dynamic Arrays

Compare Characters

Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

```
long *long_array = malloc(m);
```

Memory Management

CS1010

Laboratory 07

Zhang Puyu

Exercise 4

Review

Dynamic Arrays

Compare Characters

Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

```
long *long_array = malloc(m);
```

Meaning: Allocate a memory space of **size m** for **long values**!

Memory Management

CS1010

Laboratory 07

Zhang Puyu

Exercise 4

Review

Dynamic Arrays

Compare Characters

Combinatorics

Introduction

to cLang

Multidimensional

Arrays

Big-O

Selected

Problems from

Exercise 5

```
long *long_array = malloc(m);
```

Meaning: Allocate a memory space of **size m** for **long values**!

Question: **How many** long values can be stored in this memory space (i.e. array)?

Memory Management

CS1010

Laboratory 07

Zhang Puyu

Exercise 4

Review

Dynamic Arrays

Compare Characters

Combinatorics

Introduction
to cLang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

```
long *long_array = malloc(m);
```

Meaning: Allocate a memory space of **size m** for **long values**!

Question: **How many** long values can be stored in this memory space (i.e. array)?

Answer: $m / \text{sizeof}(\text{long})$

In 64-bits OS, this evaluates to $\frac{m}{8}$, and $\frac{m}{4}$ in 32-bits OS.

Memory Management

CS1010

Laboratory 07

Zhang Puyu

Exercise 4

Review

Dynamic Arrays

Compare Characters

Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

```
long *long_array = malloc(m);
```

Meaning: Allocate a memory space of **size m** for **long values**!

Question: **How many** long values can be stored in this memory space (i.e. array)?

Answer: $m / \text{sizeof}(\text{long})$

In 64-bits OS, this evaluates to $\frac{m}{8}$, and $\frac{m}{4}$ in 32-bits OS.

So how do we allocate a long array of size n with malloc?

Memory Management

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

```
long *long_array = malloc(m);
```

Meaning: Allocate a memory space of **size m** for **long values**!

Question: **How many** long values can be stored in this memory space (i.e. array)?

Answer: $m / \text{sizeof}(\text{long})$

In 64-bits OS, this evaluates to $\frac{m}{8}$, and $\frac{m}{4}$ in 32-bits OS.

So how do we allocate a long array of size n with malloc?

```
long *long_array = malloc(n * sizeof(long));
```


Memory Management

CS1010
Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

```
long *long_array = calloc(n, m);
```

Memory Management

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

```
long *long_array = calloc(n, m);
```

Meaning: Allocate a memory space for n values, each of size m .

Memory Management

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to `clang`

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

```
long *long_array = calloc(n, m);
```

Meaning: Allocate a memory space for n values, each of size m .

So it is natural to write the above as

```
long *long_array = calloc(n, sizeof(long));
```

Memory Management

CS1010

Laboratory 07

Zhang Puyu

Exercise 4

Review

Dynamic Arrays

Compare Characters

Combinatorics

Introduction

to `clang`

Multidimensional

Arrays

Big-O

Selected

Problems from

Exercise 5

```
long *long_array = calloc(n, m);
```

Meaning: Allocate a memory space for n values, each of size m .

So it is natural to write the above as

```
long *long_array = calloc(n, sizeof(long));
```

Some of you did this:

```
long *long_array = (long *)calloc(n,  
sizeof(long))
```

This is **NOT** necessary!

concat.c: Why Does This Work?

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

```
char *concatenate(char *str1, char *str2) {  
    size_t len1 = length_of(str1);  
    size_t len2 = length_of(str2);  
    char *result = malloc(len1 + len2 + 1);  
    // Copy str1 and str2 into result  
    // Append '\0' at the end of result  
    return result;  
}
```

concat.c: Why Does This Work?

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

```
char *concatenate(char *str1, char *str2) {  
    size_t len1 = length_of(str1);  
    size_t len2 = length_of(str2);  
    char *result = malloc(len1 + len2 + 1);  
    // Copy str1 and str2 into result  
    // Append '\0' at the end of result  
    return result;  
}
```

It seems that the memory size put into `malloc` should be `(len1 + len2 + 1) * sizeof(char)` instead.

concat.c: Why Does This Work?

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

```
char *concatenate(char *str1, char *str2) {  
    size_t len1 = length_of(str1);  
    size_t len2 = length_of(str2);  
    char *result = malloc(len1 + len2 + 1);  
    // Copy str1 and str2 into result  
    // Append '\0' at the end of result  
    return result;  
}
```

It seems that the memory size put into `malloc` should be `(len1 + len2 + 1) * sizeof(char)` instead.

But **this program runs without errors!**

concat.c: Why Does This Work?

CS1010

Laboratory 07

Zhang Puyu

Exercise 4

Review

Dynamic Arrays

Compare Characters

Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

```
char *concatenate(char *str1, char *str2) {  
    size_t len1 = length_of(str1);  
    size_t len2 = length_of(str2);  
    char *result = malloc(len1 + len2 + 1);  
    // Copy str1 and str2 into result  
    // Append '\0' at the end of result  
    return result;  
}
```

It seems that the memory size put into `malloc` should be `(len1 + len2 + 1) * sizeof(char)` instead.

But **this program runs without errors!** Why?

concat.c: Why Does This Work?

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

```
char *concatenate(char *str1, char *str2) {  
    size_t len1 = length_of(str1);  
    size_t len2 = length_of(str2);  
    char *result = malloc(len1 + len2 + 1);  
    // Copy str1 and str2 into result  
    // Append '\0' at the end of result  
    return result;  
}
```

It seems that the memory size put into `malloc` should be `(len1 + len2 + 1) * sizeof(char)` instead.

But **this program runs without errors!** Why?

Answer: `sizeof(char)` happens to be 1! (But still a bad practice to write like this!)

concat.c: Why Does This Work?

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

```
char *concatenate(char *str1, char *str2) {  
    size_t len1 = length_of(str1);  
    size_t len2 = length_of(str2);  
    char *result = calloc(2, len1 + len2 + 1);  
    // Copy str1 and str2 into result  
    return result;  
}
```

concat.c: Why Does This Work?

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

```
char *concatenate(char *str1, char *str2) {  
    size_t len1 = length_of(str1);  
    size_t len2 = length_of(str2);  
    char *result = calloc(2, len1 + len2 + 1);  
    // Copy str1 and str2 into result  
    return result;  
}
```

Tentative questions:

- Allocate 2 elements with size $\text{len1} + \text{len2} + 1$ each???
- Never append `'\0'` to terminate the string???

concat.c: Why Does This Work?

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

```
char *concatenate(char *str1, char *str2) {  
    size_t len1 = length_of(str1);  
    size_t len2 = length_of(str2);  
    char *result = calloc(2, len1 + len2 + 1);  
    // Copy str1 and str2 into result  
    return result;  
}
```

Tentative questions:

- Allocate 2 elements with size `len1 + len2 + 1` each???
- Never append `'\0'` to terminate the string???

Somehow the program still runs correctly. Why?

concat.c: Why Does This Work?

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

```
char *concatenate(char *str1, char *str2) {  
    size_t len1 = length_of(str1);  
    size_t len2 = length_of(str2);  
    char *result = calloc(2, len1 + len2 + 1);  
    // Copy str1 and str2 into result  
    return result;  
}
```

What happens in the backend: `calloc(m, n)` actually calculates mn and allocate a wholesome chunk of memory of size mn .

concat.c: Why Does This Work?

CS1010

Laboratory 07

Zhang Puyu

Exercise 4

Review

Dynamic Arrays

Compare Characters

Combinatorics

Introduction

to clang

Multidimensional

Arrays

Big-O

Selected

Problems from

Exercise 5

```
char *concatenate(char *str1, char *str2) {  
    size_t len1 = length_of(str1);  
    size_t len2 = length_of(str2);  
    char *result = calloc(2, len1 + len2 + 1);  
    // Copy str1 and str2 into result  
    return result;  
}
```

What happens in the backend: `calloc(m, n)` actually calculates mn and allocate a wholesome chunk of memory of size mn .

Since the size of `char` is 1 byte, $2 * (\text{len1} + \text{len2} + 1)$ is **more than what we need**, so we can safely copy over the strings.

concat.c: Why Does This Work?

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

```
char *concatenate(char *str1, char *str2) {  
    size_t len1 = length_of(str1);  
    size_t len2 = length_of(str2);  
    char *result = calloc(2, len1 + len2 + 1);  
    // Copy str1 and str2 into result  
    return result;  
}
```

`calloc` will also fill up the allocated memory space with 0's before returning, so the unused portion of `result` will be full of 0's.

concat.c: Why Does This Work?

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

```
char *concatenate(char *str1, char *str2) {  
    size_t len1 = length_of(str1);  
    size_t len2 = length_of(str2);  
    char *result = calloc(2, len1 + len2 + 1);  
    // Copy str1 and str2 into result  
    return result;  
}
```

`calloc` will also fill up the allocated memory space with 0's before returning, so the unused portion of `result` will be full of 0's.

However, `'\0' == 0`! So this unused portion does not affect the final output array.

concat.c: Why Does This Work?

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

```
char *concatenate(char *str1, char *str2) {  
    size_t len1 = length_of(str1);  
    size_t len2 = length_of(str2);  
    char *result = calloc(2, len1 + len2 + 1);  
    // Copy str1 and str2 into result  
    return result;  
}
```

`calloc` will also fill up the allocated memory space with 0's before returning, so the unused portion of `result` will be full of 0's.

However, `'\0' == 0`! So this unused portion does not affect the final output array.

In conclusion, **passing test cases \neq correct!**

NULL Pointer Checks

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays

Compare Characters

Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

IMPORTANT UPDATE: As of this semester, not doing NULL checks when allocating dynamic arrays **WILL BE PENALISED** in PEs!

NULL Pointer Checks

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

IMPORTANT UPDATE: As of this semester, not doing NULL checks when allocating dynamic arrays **WILL BE PENALISED** in PEs!

What's the difference of the following two ways of checking for NULL pointers?

```
long *a = calloc(10, sizeof(long))
if (a != NULL) {
    // Do something with a
}
return 0;

long *a = calloc(10, sizeof(long))
if (a == NULL) {
    cs1010_println_string("Error")
    return 1;
}
// Do something with a
return 0;
```

NULL Pointer Checks

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

IMPORTANT UPDATE: As of this semester, not doing NULL checks when allocating dynamic arrays **WILL BE PENALISED** in PEs!

What's the difference of the following two ways of checking for NULL pointers?

```
long *a = calloc(10, sizeof(long));  
if (a != NULL) {  
    // Do something with a  
}  
return 0;  
  
long *a = calloc(10, sizeof(long));  
if (a == NULL) {  
    cs1010_println_string("Error  
return 1;  
}  
// Do something with a  
return 0;
```

In the first program, allocation **fails silently** but in the second program we use **error messages** and **non-zero exit value** to **indicate the error!**

char Comparisons

CS1010

Laboratory 07

Zhang Puyu

Exercise 4

Review

Dynamic Arrays

Compare Characters

Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

char Comparisons

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays

Compare Characters

Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

We can use arithmetic comparators and operators **directly** between characters.

char Comparisons

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

We can use arithmetic comparators and operators **directly** between characters.

E.g. in `up.c`, many of you wrote `c >= 97 && c <= 122` to check whether the character `c` is a lower-case alphabet.

char Comparisons

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

We can use arithmetic comparators and operators **directly** between characters.

E.g. in `up.c`, many of you wrote `c >= 97 && c <= 122` to check whether the character `c` is a lower-case alphabet.

Although `'a'` and `'z'` indeed have ASCII codes 97 and 122 respectively, using `c >= 'a' && c <= 'z'` is **much more readable**.

Do the Maths to Simplify Computations

CS1010

Laboratory 07

Zhang Puyu

Exercise 4

Review

Dynamic Arrays

Compare Characters

Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

Do the Maths to Simplify Computations

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

kendall.c asks: given a permutation of integers from 1 to n inclusive, how many distinct pairs (a, b) are there which violate their natural ordering?

Do the Maths to Simplify Computations

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

kendall.c asks: given a permutation of integers from 1 to n inclusive, how many distinct pairs (a, b) are there which violate their natural ordering?

$$\tau = \frac{\text{number of differently ranked pairs}}{\text{number of total pairs}}$$

Do the Maths to Simplify Computations

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

kendall.c asks: given a permutation of integers from 1 to n inclusive, how many distinct pairs (a, b) are there which violate their natural ordering?

$$\tau = \frac{\text{number of differently ranked pairs}}{\text{number of total pairs}}$$

Numerator: Just count with a loop.

Do the Maths to Simplify Computations

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

kendall.c asks: given a permutation of integers from 1 to n inclusive, how many distinct pairs (a, b) are there which violate their natural ordering?

$$\tau = \frac{\text{number of differently ranked pairs}}{\text{number of total pairs}}$$

Numerator: Just count with a loop.

Denominator: Do we need to count it with a loop too?

Do the Maths to Simplify Computations

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

`kendall.c` asks: **given a permutation of integers from 1 to n inclusive, how many distinct pairs (a, b) are there which violate their natural ordering?**

$$\tau = \frac{\text{number of differently ranked pairs}}{\text{number of total pairs}}$$

Numerator: Just count with a loop.

Denominator: Do we need to count it with a loop too?

It's just **the number of ways to choose two integers from n distinct integers!**

Do the Maths to Simplify Computations

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

kendall.c asks: **given a permutation of integers from 1 to n inclusive, how many distinct pairs (a, b) are there which violate their natural ordering?**

$$\tau = \frac{\text{number of differently ranked pairs}}{\text{number of total pairs}}$$

Numerator: Just count with a loop.

Denominator: Do we need to count it with a loop too?

It's just **the number of ways to choose two integers from n distinct integers!**

$$C_2^n = \frac{n!}{2!(n-2)!} = \frac{n(n-1)}{2}.$$

subtract.c

CS1010
Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

This is a variant of a classic problem called **TwoSum** (or **AddTwoNumbers**).

subtract.c

CS1010
Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

This is a variant of a classic problem called **TwoSum** (or **AddTwoNumbers**).

Just like doing **column subtraction**, we want to first “right-align” the two strings (i.e. iterate backwards).

subtract.c

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

This is a variant of a classic problem called **TwoSum** (or **AddTwoNumbers**).

Just like doing **column subtraction**, we want to first “right-align” the two strings (i.e. iterate backwards).

For the i -th digit, if `str1[i] >= str2[i]`:
`ans[i] = str1[i] - str2[i]`.

Otherwise:

Borrow 1 from the previous digit.

(Rather Brief) Introduction to clang

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays

Compare Characters

Combinatorics

**Introduction
to clang**

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

(Rather Brief) Introduction to clang

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

- In CS1010, we hide the details of compilation with Makefile.

Demo with the following program test.c:

```
int main() {  
    return 0;  
}
```

(Rather Brief) Introduction to clang

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

- In CS1010, we hide the details of compilation with Makefile.
- How to do it post-CS1010?

Demo with the following program `test.c`:

```
int main() {  
    return 0;  
}
```

One thing you will notice is that if we compile it with `clang test.c`, we get `a.out` as the executable.

(Rather Brief) Introduction to clang

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

- In CS1010, we hide the details of compilation with Makefile.
- How to do it post-CS1010?
- Two major C/C++ compilers: gcc and clang.

Demo with the following program test.c:

```
int main() {  
    return 0;  
}
```

One thing you will notice is that if we compile it with clang test.c, we get a.out as the executable.

If we wish to rename the compiled program, we use clang test.c -o name.

(Rather Brief) Introduction to clang

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

- In CS1010, we hide the details of compilation with Makefile.
- How to do it post-CS1010?
- Two major C/C++ compilers: gcc and clang.

Demo with the following program test.c:

```
int main() {  
    return 0;  
}
```

One thing you will notice is that if we compile it with clang test.c, we get a.out as the executable.

If we wish to rename the compiled program, we use clang test.c -o name.

CAUTION: clang test.c -o test.c will overwrite your code!

Compilation Errors/Warnings

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

We now try to purposely code something illegal:

```
int main() {  
    main();  
    return 0;  
}
```

and compile again.

Compilation Errors/Warnings

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

We now try to purposely code something illegal:

```
int main() {  
    main();  
    return 0;  
}
```

and compile again.

No warning is generated by default. We have to compile with
`clang -Wall test.c` to enable warnings.

Compilation Errors/Warnings

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

We now try to purposely code something illegal:

```
int main() {  
    main();  
    return 0;  
}
```

and compile again.

No warning is generated by default. We have to compile with
`clang -Wall test.c` to enable warnings.

Compilation Errors/Warnings

CS1010

Laboratory 07

Zhang Puyu

Exercise 4

Review

Dynamic Arrays

Compare Characters

Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

Now try

```
int main() {  
    int *p = NULL;  
    *p = 1;  
    return 0;  
}
```

and compile with `clang -fsanitize=address test.c`
to enable address sanitizer.

Compilation Errors/Warnings

CS1010

Laboratory 07

Zhang Puyu

Exercise 4

Review

Dynamic Arrays

Compare Characters

Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

Now try

```
int main() {  
    int *p = NULL;  
    *p = 1;  
    return 0;  
}
```

and compile with `clang -fsanitize=address test.c`
to enable address sanitizer.

You will notice that the line number of the buggy code is not displayed as expected. To make it visible, we need to use the `-g` flag by calling:

```
clang -fsanitize=address -g test.c
```

External Libraries

CS1010

Laboratory 07

Zhang Puyu

Exercise 4

Review

Dynamic Arrays

Compare Characters

Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

Now try

```
#include <math.h>
```

```
int main() {  
    sqrt(4)  
    return 0;  
}
```

Compiling the above will trigger something called **linker command failure**.

External Libraries

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

Now try

```
#include <math.h>
```

```
int main() {  
    sqrt(4)  
    return 0;  
}
```

Compiling the above will trigger something called **linker command failure**.

This is because we use a program called `ld` to resolve external function calls, and need to tell `clang` where the function `sqrt` can be found (in this case, it is defined in `libm.a` under `/usr/lib`).

External Libraries

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

Now try

```
#include <math.h>
```

```
int main() {  
    sqrt(4)  
    return 0;  
}
```

Compiling the above will trigger something called **linker command failure**.

This is because we use a program called `ld` to resolve external function calls, and need to tell `clang` where the function `sqrt` can be found (in this case, it is defined in `libm.a` under `/usr/lib`).

We will use `clang test.c -lm`.

External Libraries

CS1010
Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

What if we want to use a third-party library like the CS1010 I/O Library?

```
#include "cs1010.h"
```

```
int main() {  
    cs1010_println_long(1);  
    return 0;  
}
```

Since `cs1010.h` is not a standard C library, we need to tell `clang` to look for it under `~cs1010/include` by `clang -I ~cs1010/include test.c`.

External Libraries

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

What if we want to use a third-party library like the CS1010 I/O Library?

```
#include "cs1010.h"
```

```
int main() {  
    cs1010_println_long(1);  
    return 0;  
}
```

Since `cs1010.h` is not a standard C library, we need to tell `clang` to look for it under `~cs1010/include` by `clang -I ~cs1010/include test.c`.

But after doing so, there are still errors! This is because we also need to tell `clang` where to find the function `cs1010_println_long`. Run:
`clang -I ~cs1010/include -L ~cs1010/lib test.c -lcs1010`

Compiler Flags

CS1010
Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to `clang`

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

We can save the compiler flags into a `.txt` file with one flag per line.

Compiler Flags

CS1010
Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to `clang`

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

We can save the compiler flags into a `.txt` file with one flag per line.

A more modernised approach:

<https://code.visualstudio.com/docs/languages/cpp>

An Array of Arrays

CS1010

Laboratory 07

Zhang Puyu

Exercise 4

Review

Dynamic Arrays

Compare Characters

Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

Consider an $(m + 1) \times (n + 1)$ matrix:

$$\mathbf{A} = \begin{bmatrix} a_{00} & a_{01} & a_{02} & \cdots & a_{0n} \\ a_{10} & a_{11} & a_{12} & \cdots & a_{1n} \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ a_{m0} & a_{m1} & a_{m2} & \cdots & a_{mn} \end{bmatrix}.$$

An Array of Arrays

CS1010

Laboratory 07

Zhang Puyu

Exercise 4

Review

Dynamic Arrays

Compare Characters

Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

Consider an $(m+1) \times (n+1)$ matrix:

$$\mathbf{A} = \begin{bmatrix} a_{00} & a_{01} & a_{02} & \cdots & a_{0n} \\ a_{10} & a_{11} & a_{12} & \cdots & a_{1n} \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ a_{m0} & a_{m1} & a_{m2} & \cdots & a_{mn} \end{bmatrix}.$$

It can be re-written as

$$\mathbf{A} = \begin{bmatrix} \mathbf{a}_0 \\ \mathbf{a}_1 \\ \vdots \\ \mathbf{a}_m \end{bmatrix}$$

where each of the \mathbf{a}_i 's is an $1 \times (n+1)$ matrix, i.e., **an array of size $n+1$!**

An Array of Arrays

CS1010

Laboratory 07

Zhang Puyu

Exercise 4

Review

Dynamic Arrays

Compare Characters

Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

Consider an $(m + 1) \times (n + 1)$ matrix:

$$\mathbf{A} = \begin{bmatrix} a_{00} & a_{01} & a_{02} & \cdots & a_{0n} \\ a_{10} & a_{11} & a_{12} & \cdots & a_{1n} \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ a_{m0} & a_{m1} & a_{m2} & \cdots & a_{mn} \end{bmatrix}.$$

It can be re-written as

$$\mathbf{A} = \begin{bmatrix} \mathbf{a}_0 \\ \mathbf{a}_1 \\ \vdots \\ \mathbf{a}_m \end{bmatrix}$$

where each of the \mathbf{a}_i 's is an $1 \times (n + 1)$ matrix, i.e., **an array of size $n + 1$** ! So the matrix is essentially **an array of size $(m + 1)$** whose elements are **arrays of size $(n + 1)$** !

Multidimensional Arrays: Non-contiguous Memory

CS1010
Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

```
long **matrix = calloc(m, sizeof(long *));
if (matrix == NULL) {
    cs1010_println_string("Memory allocation failed");
    return 1;
}
for (long i = 0; i < m; i += 1) {
    matrix[i] = calloc(n, sizeof(long));
    if (matrix[i] == NULL) {
        cs1010_println_string("Memory allocation failed");
        for (long j = 0; j < i; j += 1) {
            free(matrix[j]);
        }
        free(matrix);
        return 1;
    }
}
// Do something with matrix
for (long i = 0; i < n; i += 1) {
    free(matrix[i]);
}
free(matrix);
return 0;
```

Multidimensional Arrays: Contiguous Memory

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

```
long **matrix = calloc(m, sizeof(long *));
if (matrix == NULL) {
    cs1010_println_string("Memory allocation failed");
    return 1;
}
matrix[0] = calloc(m * n, sizeof(long));
if (matrix[0] == NULL) {
    cs1010_println_string("Memory allocation failed");
    free(matrix);
    return 1;
}
for (long i = 1; i < m; i += 1) {
    matrix[i] = matrix[i - 1] + n;
}
// Do something with matrix
free(matrix[0]);
free(matrix);
return 0;
```


Play with Pointers

CS1010
Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

Due to **array decay**, the address of an array is the same as the address of its first element.

Play with Pointers

CS1010
Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

Due to **array decay**, the address of an array is the same as the address of its first element.

Any 2D array `a` is still an array, so `a` is just the **address of its first element**, i.e., `a == &a[0]` (they are the same both in value and in meaning).

Play with Pointers

CS1010
Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

Due to **array decay**, the address of an array is the same as the address of its first element.

Any 2D array `a` is still an array, so `a` is just the **address of its first element**, i.e., `a == &a[0]` (they are the same both in value and in meaning).

However, note that `a[0]` is also an array, so what is `a[0]`?

Play with Pointers

CS1010
Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

Due to **array decay**, the address of an array is the same as the address of its first element.

Any 2D array `a` is still an array, so `a` is just the **address of its first element**, i.e., `a == &a[0]` (they are the same both in value and in meaning).

However, note that `a[0]` is also an array, so what is `a[0]`? It is the **address of the first element of `a[0]`**, i.e., `a[0] == &a[0][0]` (they are the same both in value and in meaning).

Play with Pointers

CS1010
Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

Due to **array decay**, the address of an array is the same as the address of its first element.

Any 2D array `a` is still an array, so `a` is just the **address of its first element**, i.e., `a == &a[0]` (they are the same both in value and in meaning).

However, note that `a[0]` is also an array, so what is `a[0]`? It is the **address of the first element of `a[0]`**, i.e., `a[0] == &a[0][0]` (they are the same both in value and in meaning).

Question: Do you think

1 `a == &a?`

2 `a[0] == &a[0]?`

Play with Pointers

CS1010
Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

Due to **array decay**, the address of an array is the same as the address of its first element.

Any 2D array `a` is still an array, so `a` is just the **address of its first element**, i.e., `a == &a[0]` (they are the same both in value and in meaning).

However, note that `a[0]` is also an array, so what is `a[0]`? It is the **address of the first element of `a[0]`**, i.e., `a[0] == &a[0][0]` (they are the same both in value and in meaning).

Question: Do you think

1 `a == &a?`

2 `a[0] == &a[0]?`

Answer: **No** because they have different types.

Time Complexity Analysis Using Big-O

CS1010

Laboratory 07

Zhang Puyu

Exercise 4

Review

Dynamic Arrays

Compare Characters

Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

Big-O Notation (the Real Definition)

Let f and g be real-valued one-dimensional functions. If there exists some $x_0 \in \mathbb{R}$ such that for all $x > x_0$, we have

$$|f(x)| \leq M g(x)$$

for some $M > 0$, then we say that $f(x)$ is **big-O** of $g(x)$, denoted by $f(x) = O(g(x))$ or $f \in \mathcal{O}(g)$.

Time Complexity Analysis Using Big-O

CS1010

Laboratory 07

Zhang Puyu

Exercise 4

Review

Dynamic Arrays

Compare Characters

Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

Big-O Notation (the Real Definition)

Let f and g be real-valued one-dimensional functions. If there exists some $x_0 \in \mathbb{R}$ such that for all $x > x_0$, we have

$$|f(x)| \leq M g(x)$$

for some $M > 0$, then we say that $f(x)$ is **big-O** of $g(x)$, denoted by $f(x) = O(g(x))$ or $f \in \mathcal{O}(g)$.

In human language, this means that the **growth rate** of f is **at most** a constant multiple of the growth rate of g .

Time Complexity Analysis Using Big-O

CS1010

Laboratory 07

Zhang Puyu

Exercise 4

Review

Dynamic Arrays

Compare Characters

Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

Big-O Notation (the Real Definition)

Let f and g be real-valued one-dimensional functions. If there exists some $x_0 \in \mathbb{R}$ such that for all $x > x_0$, we have

$$|f(x)| \leq M g(x)$$

for some $M > 0$, then we say that $f(x)$ is **big-O** of $g(x)$, denoted by $f(x) = O(g(x))$ or $f \in \mathcal{O}(g)$.

In human language, this means that the **growth rate** of f is **at most** a constant multiple of the growth rate of g .

Meaning of $\mathcal{O}(g)$:

Time Complexity Analysis Using Big-O

CS1010

Laboratory 07

Zhang Puyu

Exercise 4

Review

Dynamic Arrays

Compare Characters

Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

Big-O Notation (the Real Definition)

Let f and g be real-valued one-dimensional functions. If there exists some $x_0 \in \mathbb{R}$ such that for all $x > x_0$, we have

$$|f(x)| \leq M g(x)$$

for some $M > 0$, then we say that $f(x)$ is **big-O** of $g(x)$, denoted by $f(x) = O(g(x))$ or $f \in \mathcal{O}(g)$.

In human language, this means that the **growth rate** of f is **at most** a constant multiple of the growth rate of g .

Meaning of $\mathcal{O}(g)$: it is the set of all functions whose growth rate is different from the growth rate of g by **at most a constant factor**.

Trivial Results

CS1010

Laboratory 07

Zhang Puyu

Exercise 4

Review

Dynamic Arrays

Compare Characters

Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

- For all $c > 0$, $f(x) = O(c) \iff f(x) = O(1)$.
- For all $c > 0$, $f(x) = O(g(x)) \iff f(x) = O(c \cdot g(x))$.
- For all $m, n > 0$,
 $f(x) = O(g(x) + h(x)) \iff f(x) = O(m \cdot g(x) + n \cdot h(x))$.
- For all $a_1, a_2, \dots, a_n > 0$,

$$f(x) = O\left(\sum_{i=1}^n g_i(x)\right) \iff f(x) = O\left(\sum_{i=1}^n a_i g_i(x)\right).$$

The proofs are left to the reader as an exercise.

Some Serious Maths

CS1010

Laboratory 07

Zhang Puyu

Exercise 4

Review

Dynamic Arrays

Compare Characters

Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

Rule of Highest Power

Let $p(x)$ be a polynomial, i.e.,

$$p(x) = a_n x^n + a_{n-1} x^{n-1} + \cdots + a_2 x^2 + a_1 x + a_0,$$

where $n \in \mathbb{N}$ and a_i 's are real constants, then

$$f(x) = O(p(x)) \iff f(x) = O(x^n).$$

The (\Leftarrow) direction is somewhat useless in the context of programming, so we will prove the (\Rightarrow) direction only.

Some Serious Maths

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

Rule of Highest Power

Let $p(x)$ be a polynomial, i.e.,

$$p(x) = a_n x^n + a_{n-1} x^{n-1} + \cdots + a_2 x^2 + a_1 x + a_0,$$

where $n \in \mathbb{N}$ and a_i 's are real constants, then

$$f(x) = O(p(x)) \iff f(x) = O(x^n).$$

Observe that for all $x > 1$,

$$\begin{aligned} p(x) &\leq |a_n| x^n + \cdots + |a_1| x + |a_0| \\ &\leq (|a_n| + |a_{n-1}| + \cdots + |a_0|) x^n \end{aligned}$$

Take $N = (|a_n| + |a_{n-1}| + \cdots + |a_0|)$. Since $f(x) = O(p(x))$, there is some $x_0 \in \mathbb{R}$ and some $M > 0$ such that

$$|f(x)| \leq M p(x)$$

for all $x > x_0$. Take $x' = \max\{x_0, 1\}$, then for all $x > x'$,

$$|f(x)| \leq M p(x) \leq M(N x^n) = MN x^n.$$

Since $MN > 0$, this means $f(x) = O(x^n)$.



Compare Growth Rate (the Problematic Statement)

“We say that $f(n)$ grows faster than $g(n)$ if we can find a n_0 , such that $f(n) > cg(n)$ for all $n > n_0$ and for some constant c .”

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

Compare Growth Rate (the Problematic Statement)

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

“We say that $f(n)$ grows faster than $g(n)$ if we can find a n_0 , such that $f(n) > cg(n)$ for all $n > n_0$ and for some constant c .”

Counter example:

- $f(n) = n^3$,
- $g(n) = 6n^3$.

Compare Growth Rate (the Problematic Statement)

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

“We say that $f(n)$ grows faster than $g(n)$ if we can find a n_0 , such that $f(n) > cg(n)$ for all $n > n_0$ and for some constant c .”

Counter example:

- $f(n) = n^3$,
- $g(n) = 6n^3$.
- Fix $n_0 = 1$, clearly for all $n > 1$, we can fix constant $c = \frac{1}{12}$ and
- $f(n) > cg(n)$.

Compare Growth Rate (the Problematic Statement)

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

"We say that $f(n)$ grows faster than $g(n)$ if we can find a n_0 , such that $f(n) > cg(n)$ for all $n > n_0$ and for some constant c ."

Counter example:

- $f(n) = n^3$,
- $g(n) = 6n^3$.
- Fix $n_0 = 1$, clearly for all $n > 1$, we can fix constant $c = \frac{1}{12}$ and
- $f(n) > cg(n)$.
- However, this is ridiculous because $g(n) \geq f(n)$ for all $n \geq 0$.

Compare Growth Rate (the Problematic Statement)

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

"We say that $f(n)$ grows faster than $g(n)$ if we can find a n_0 , such that $f(n) > cg(n)$ for all $n > n_0$ and for some constant c ."

Counter example:

- $f(n) = n^3$,
- $g(n) = 6n^3$.
- Fix $n_0 = 1$, clearly for all $n > 1$, we can fix constant $c = \frac{1}{12}$ and
- $f(n) > cg(n)$.
- However, this is ridiculous because $g(n) \geq f(n)$ for all $n \geq 0$.
- Both functions are in $\mathcal{O}(n^3)$ so neither should grow faster than the other.

Compare Growth Rate (the Real Way)

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

What do we mean by f grows faster than g :

As $x \rightarrow \infty$, $f(x)$ is **significantly larger** than $g(x)$.

Naturally, we check

$$\lim_{x \rightarrow \infty} \frac{f(x)}{g(x)}.$$

If $\frac{f(x)}{g(x)}$ diverges (i.e. limit “equals” ∞), then f grows faster. If the limit is 0, then g grows faster. If the limit is some non-zero constant, then f and g have the same growth rate.

add.c

CS1010
Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

add.c

CS1010

Laboratory 07

Zhang Puyu

Exercise 4

Review

Dynamic Arrays

Compare Characters

Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

These are just two **fixed-sized 2D arrays** (3×3 matrices). We just need to read them in and perform element-wise addition.

line.c

CS1010
Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

- Make sure you understand the maths part.

line.c

CS1010
Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

- Make sure you understand the maths part.
- Note that the origin is at **top-left** instead of bottom-left.

line.c

CS1010
Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

- Make sure you understand the maths part.
- Note that the origin is at **top-left** instead of bottom-left.
- Note also that the point (x, y) corresponds to the element `matrix[y][x]`.

line.c

CS1010

Laboratory 07

Zhang Puyu

Exercise 4

Review

Dynamic Arrays

Compare Characters

Combinatorics

Introduction

to clang

Multidimensional

Arrays

Big-O

Selected

Problems from

Exercise 5

- Make sure you understand the maths part.
- Note that the origin is at **top-left** instead of bottom-left.
- Note also that the point (x, y) corresponds to the element `matrix[y][x]`.
- `round` function from `math.h` truncates a floating point number to the nearest integer.

line.c

CS1010

Laboratory 07

Zhang Puyu

Exercise 4
Review

Dynamic Arrays
Compare Characters
Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

- Make sure you understand the maths part.
- Note that the origin is at **top-left** instead of bottom-left.
- Note also that the point (x, y) corresponds to the element `matrix[y][x]`.
- `round` function from `math.h` truncates a floating point number to the nearest integer.
- For i from 0 to $x_2 - x_1$, calculate the coordinates $(x_1 + i, y_1 + im)$ and find the indices after rounding.

line.c

CS1010

Laboratory 07

Zhang Puyu

Exercise 4

Review

Dynamic Arrays

Compare Characters

Combinatorics

Introduction

to clang

Multidimensional

Arrays

Big-O

Selected

Problems from

Exercise 5

- Make sure you understand the maths part.
- Note that the origin is at **top-left** instead of bottom-left.
- Note also that the point (x, y) corresponds to the element `matrix[y][x]`.
- `round` function from `math.h` truncates a floating point number to the nearest integer.
- For i from 0 to $x_2 - x_1$, calculate the coordinates $(x_1 + i, y_1 + im)$ and find the indices after rounding.
- Is it possible for the coordinates to be outside of the matrix's boundary?

popular.c

CS1010

Laboratory 07

Zhang Puyu

Exercise 4

Review

Dynamic Arrays

Compare Characters

Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

$$\begin{bmatrix} 1 & & & & & \\ ? & 1 & & & & \\ ? & ? & 1 & & & \\ ? & ? & ? & 1 & & \\ \vdots & \vdots & \vdots & \vdots & \ddots & \\ ? & ? & ? & ? & \dots & 1 \end{bmatrix}$$

popular.c

CS1010

Laboratory 07

Zhang Puyu

Exercise 4

Review

Dynamic Arrays

Compare Characters

Combinatorics

Introduction
to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

$$\begin{bmatrix} 1 & & & & & \\ ? & 1 & & & & \\ ? & ? & 1 & & & \\ ? & ? & ? & 1 & & \\ \vdots & \vdots & \vdots & \vdots & \ddots & \\ ? & ? & ? & ? & \dots & 1 \end{bmatrix}$$

- Understanding the problem: if `matrix[i][j] == 1` and $i \neq j$, it means that i and j are friends.

popular.c

CS1010

Laboratory 07

Zhang Puyu

Exercise 4

Review

Dynamic Arrays

Compare Characters

Combinatorics

Introduction

to clang

Multidimensional

Arrays

Big-O

Selected

Problems from

Exercise 5

$$\begin{bmatrix} 1 & & & & & \\ ? & 1 & & & & \\ ? & ? & 1 & & & \\ ? & ? & ? & 1 & & \\ \vdots & \vdots & \vdots & \vdots & \ddots & \\ ? & ? & ? & ? & \dots & 1 \end{bmatrix}$$

- Understanding the problem: if `matrix[i][j] == 1` and $i \neq j$, it means that i and j are friends.
- Given any x , our task: find out how many integers $i \neq x$ satisfy `matrix[x][i] == 1` or `matrix[i][x] == 1`

popular.c

CS1010

Laboratory 07

Zhang Puyu

Exercise 4

Review

Dynamic Arrays

Compare Characters

Combinatorics

Introduction

to clang

Multidimensional
Arrays

Big-O

Selected
Problems from
Exercise 5

$$\begin{bmatrix} 1 & & & & & \\ ? & 1 & & & & \\ ? & ? & 1 & & & \\ ? & ? & ? & 1 & & \\ \vdots & \vdots & \vdots & \vdots & \ddots & \\ ? & ? & ? & ? & \dots & 1 \end{bmatrix}$$

- Understanding the problem: if `matrix[i][j] == 1` and $i \neq j$, it means that i and j are friends.
- Given any x , our task: find out how many integers $i \neq x$ satisfy `matrix[x][i] == 1` or `matrix[i][x] == 1`
- What does the indices tell you about the “search direction”?