

34-short-Ink video

Finishing off Login and Sign Styles

- lets add another element for boxed-view for the form, and implement that class to Login and Signup

```
<form onSubmit={this.onSubmit.bind(this)} noValidate className="boxed-view__form">
  <input type="email" ref="email" name="email" placeholder="Email"/>
  <input type="password" ref="password" name="password" placeholder="Password"/>
  <button>Create Account</button>
</form>
```

- and the Login.js

```
<form onSubmit={this.onSubmit.bind(this)} noValidate className="boxed-view__form">
  <input type="email" ref="email" name="email" placeholder="Email"/>
  <input type="password" ref="password" name="password" placeholder="Password"/>
  <button>Create Account</button>
</form>
```

- now lets begin start adding some styles to _boxed-view.scss
- first enable flexbox, we then want flex-direction to column

```
.boxed-view {
  align-items: center;
  background: $boxed-view-overlay-bg;
  display: flex;
  justify-content: center;
  height: 100vh;
  width: 100vw;
}

.boxed-view__box {
  background-color: $boxed-view-bg;
```

```
padding: 2.4rem;
text-align: center;
width: 24rem;
}

.boxed-view__form {
display: flex;
flex-direction: column;
}

```

- **now** lets go to _base.scss to start adding more styles to universal selectors
- we are going to be adding styles to all h1 tags and to a tags we dont want the link to have purple color when we have clicked it, we want to overwrite it by giving the color black to it

```
*{
padding: 0;
margin: 0;
}

html {
font-size: 62.5%;
}

body {
font-family: Helvetica, Arial, sans-serif;
font-size: $base-font-size;
}

h1 {
font-weight: 300;
margin-bottom: 1.4rem;
}

a {
color: black;
}

```

- **now** lets style our inputs and we are going to be specific to their type because we don't want to style the checkboxes
- lets change our `$base-font-size` to 1.4 rem

```
a {
  color: black;
}

input[type=text], input[type=email], input[type=password] {
  border: 1px solid #dddddd;
  font-size: $base-font-size;
  margin-bottom: 1.4rem;
  padding: 1rem;
}
```

- **now** lets go to `_variables` to start extractict some common values

```
// Font-size
$base-font-size: 1.4rem;

//form inputs
$input-border: #dddddd;

// Boxed view
$boxed-view-overlay-bg: #dddddd;
$boxed-view-bg: white;
```

- and now we can use that variable where is needed
- since we have to variable with the same value, we can create a color with a given variable, and that can be used as needed, so lets go back to `_variables`

```
//color
$grey: #dddddd;

// Font-size
$base-font-size: 1.4rem;

//form inputs
```

```
$input-border: $grey;
```

```
// Boxed view
```

```
$boxed-view-overlay-bg: $grey;
```

```
$boxed-view-bg: white;
```

- lets create another one for spacing that can be referenced for different situations

```
//color
```

```
$grey: #dddddd;
```

```
//spacing
```

```
$space: 1.4rem;
```

```
// Font-size
```

```
$base-font-size: $space;
```

```
//form inputs
```

```
$input-border: $grey;
```

```
// Boxed view
```

```
$boxed-view-overlay-bg: $grey;
```

```
$boxed-view-bg: white;
```

- and now lets also add that variable to _base

```
*{  
  padding: 0;  
  margin: 0;  
}
```

```
html {  
  font-size: 62.5%;  
}
```

```
body {  
  font-family: Helvetica, Arial, sans-serif;  
  font-size: $base-font-size;
```

```

}

h1 {
  font-weight: 300;
  margin-bottom: $space;
}

a {
  color: black;
}

input[type=text], input[type=email], input[type=password] {
  border: 1px solid $input-border;
  font-size: $base-font-size;
  margin-bottom: $space;
  padding: 1rem;
}

```

- and now lets add some style to the NotFound.js to make it look like the Login and Signup

```

import React from 'react';

export default ()=>{
  return (
    <div className = "boxed-view">
      <div className = "boxed-view__box">
        <h1>Page Not Found</h1>
        <p>Hmmm, we're unable to find that page.</p>
        <a href=".">HEAD HOME</a>
      </div>
    </div>
  );
}

```

- instead of the a tag lets add the Link component to it just like how we did in Login and Signup

```

import React from 'react';
import { Link } from 'react-router';

```

```
export default ()=>{
  return (
    <div className = "boxed-view">
      <div className = "boxed-view__box">
        <h1>Page Not Found</h1>
        <p>Hmmm, we're unable to find that page.</p>
        <Link to="/">HEAD HOME</Link>
      </div>
    </div>
  );
}
```

- and the reason we did the above is to prevent a full refresh when going back to our homepage