

134-Rendering Notes II [video](#)

- lets create a new test file in imports/ui call it NoteListHeader.test.js
- lets start by importing the test modules
- import the named export
- check if we are in the client side
- set up our describe block, which is NoteListHeader
- in our test case we are checking for a button click, and we are going to be simulating a click

```
import React from 'react';

import expect from 'expect';

import { mount } from 'enzyme';

import { Meteor } from 'meteor/meteor';

import { NoteListHeader } from '../NoteListHeader';

if(Meteor.isClient){

  describe('NoteListHeader', function(){

    it('should call meteorCall on click', function(){

      const spy = expect.createSpy();

      const wrapper = mount(<NoteListHeader meteorCall={spy}/>);

      wrapper.find('button').simulate('click');

      expect(spy).toHaveBeenCalled('notes.insert');

    });

  });

}
```

- go to NoteListHeader.js to set up a propTypes

```
import React from 'react';

import { Meteor } from 'meteor/meteor';

import { createContainer } from 'meteor/react-meteor-data';

import PropTypes from 'prop-types';
```

```

export const NoteListHeader = (props)=>{

  return (

    <div>

      <button onClick = {()}=>{

        props.meteorCall('notes.insert');

      }>Create Note</button>

    </div>

  );

};

NoteListHeader.propTypes = {

  meteorCall : PropTypes.func.isRequired

};

export default createContainer(()=>{

  return {

    meteorCall : Meteor.call

  };

},NoteListHeader);

```

- go to github.com to setup a new repository and call it notes-meteor-course
- now go to the terminal and open up a new tab

```

joses-MacBook-Pro:notes mendoza$ git remote -v

origin  git@github.com:mendozarriif/meteor-course-boilerplate.git (fetch)
origin  git@github.com:mendozarriif/meteor-course-boilerplate.git (push)

```

- since we have the wrong name up above, we don't this to called meteor-course-boilerplate, so lets remove it

```

joses-MacBook-Pro:notes mendoza$ git remote remove origin

```

- **rerun remote -v**
- **this time nothing shows up**

```

joses-MacBook-Pro:notes mendoza$ git remote -v

```

```
joses-MacBook-Pro:notes mendoza$
```

- now we can go ahead and copy the two lines from github and paste them in the terminal

```
joses-MacBook-Pro:notes mendoza$ git remote add origin git@github.com:mendozarriff/notes-meteor-course.git
```

```
joses-MacBook-Pro:notes mendoza$ git push -u origin master
```

- **run git status**

```
joses-MacBook-Pro:notes mendoza$ git status
```

- **now lets add everything**

```
joses-MacBook-Pro:notes mendoza$ git add .
```

- **then commit**

```
joses-MacBook-Pro:notes mendoza$ git commit -m "Add meteor methods and basic react components"
```

- **and then git push to push everything to github**

```
joses-MacBook-Pro:notes mendoza$ git push
```

-