

# ENSF 608:

# Understanding and Mapping the Relational Data Model

**Dr. Emily Marasco**


Fall 2021

Textbook: Fundamentals of Database Systems, 7<sup>th</sup> Ed., Elmasri & Navathe


# Goals during Mapping

- Preserve all information (that includes all attributes)
- Maintain the constraints to the extent possible
  - Relational model cannot preserve all constraints
    - e.g., max cardinality ratio such as 1:10 in ER; exhaustive classification into subtypes, e.g., STUDENTS are specialized into Domestic and Foreign)
- Minimize null values
- Minimize data redundancy

# Figure 9.1 The ER Conceptual Schema Diagram for the COMPANY Database



# Figure 9.2 Result of Mapping the COMPANY ER Schema into a Relational Database Schema



# ER-to-Relational Mapping Algorithm (1 of 14)

- Step 1: Mapping of Regular Entity Types.
  - For each regular (strong) entity type  $E$  in the ER schema, create a relation  $R$  that includes all the simple attributes of  $E$ .
  - Choose one of the key attributes of  $E$  as the primary key for  $R$ .
  - If the chosen key of  $E$  is composite, the set of simple attributes that form it will together form the primary key of  $R$ .

# ER-to-Relational Mapping Algorithm (2 of 14)

- Example: We create the relations EMPLOYEE, DEPARTMENT, and PROJECT in the relational schema corresponding to the regular entities in the ER diagram.
  - SSN, DNUMBER, and PNUMBER are the primary keys for the relations EMPLOYEE, DEPARTMENT, and PROJECT as shown.

## EMPLOYEE

Fname	Minit	Lname	<u>Ssn</u>	Bdate	Address	Sex	Salary	Super_ssn	Dno
-------	-------	-------	------------	-------	---------	-----	--------	-----------	-----

## DEPARTMENT

Dname	<u>Dnumber</u>	Mgr_ssn	Mgr_start_date
-------	----------------	---------	----------------

## PROJECT

Pname	<u>Pnumber</u>	<u>Plocation</u>	Dnum
-------	----------------	------------------	------

# ER-to-Relational Mapping Algorithm (3 of 14)

- **Step 2: Mapping of Weak Entity Types**
  - For each weak entity type  $W$  in the ER schema with owner entity type  $E$ , create a relation  $R$  & include all simple attributes (or simple components of composite attributes) of  $W$  as attributes of  $R$ .
  - Also, include as foreign key attributes of  $R$  the primary key attribute(s) of the relation(s) that correspond to the owner entity type(s).
  - The primary key of  $R$  is the **combination** of the primary key(s) of the owner(s) and the partial key of the weak entity type  $W$ , if any.

# ER-to-Relational Mapping Algorithm (4 of 14)

- **Example:** Create the relation DEPENDENT in this step to correspond to the weak entity type DEPENDENT.
  - Include the primary key SSN of the EMPLOYEE relation as a foreign key attribute of DEPENDENT (renamed to ESSN).
  - The primary key of the DEPENDENT relation is the combination {ESSN, DEPENDENT\_NAME} because DEPENDENT\_NAME is the partial key of DEPENDENT.

DEPENDENT

<u>Essn</u>	<u>Dependent_name</u>	Sex	Bdate	Relationship
-------------	-----------------------	-----	-------	--------------




# ER-to-Relational Mapping Algorithm (5 of 14)

- **Step 3: Mapping of Binary 1:1 Relation Types**
  - For each binary 1:1 relationship type  $R$  in the ER schema, identify the relations  $S$  and  $T$  that correspond to the entity types participating in  $R$ .
- There are three possible approaches:
  1. **Foreign Key ( 2 relations) approach:** Choose one of the relations-say  $S$ -and include a foreign key in  $S$  the primary key of  $T$ . It is better to choose an entity type with total participation in  $R$  in the role of  $S$ .
    - Example: 1:1 relation MANAGES is mapped by choosing the participating entity type DEPARTMENT to serve in the role of  $S$ , because its participation in the MANAGES relationship type is total.

# ER-to-Relational Mapping Algorithm (6 of 14)

- 2. Merged relation (1 relation) option:** An alternate mapping of a 1:1 relationship type is possible by merging the two entity types and the relationship into a single relation. This may be appropriate when both participations are total.
- 3. Cross-reference or relationship relation ( 3 relations) option:** The third alternative is to set up a third relation  $R$  for the purpose of cross-referencing the primary keys of the two relations  $S$  and  $T$  representing the entity types.



## DEPARTMENT

Dname	<u>Dnumber</u>	Mgr_ssn	Mgr_start_date
-------	----------------	---------	----------------

# ER-to-Relational Mapping Algorithm (7 of 14)

- Step 4: Mapping of Binary 1:N Relationship Types.
  - For each regular binary 1:N relationship type  $R$ , identify the relation  $S$  that represent the participating entity type at the N-side of the relationship type.
  - Include as foreign key in  $S$  the primary key of the relation  $T$  that represents the other entity type participating in  $R$ .
  - Include any simple attributes of the 1:N relation type as attributes of  $S$ .

# ER-to-Relational Mapping Algorithm (8 of 14)

- Example: 1:N relationship types WORKS\_FOR, CONTROLS, and SUPERVISION in the figure.
  - For WORKS\_FOR we include the primary key DNUMBER of the DEPARTMENT relation as foreign key in the EMPLOYEE relation and call it DNO.
- An alternative approach is to use a Relationship relation (cross referencing relation) – this is rarely done.

## EMPLOYEE

Fname	Minit	Lname	<u>Ssn</u>	Bdate	Address	Sex	Salary	Super_ssn	Dno
-------	-------	-------	------------	-------	---------	-----	--------	-----------	-----

# ER-to-Relational Mapping Algorithm (9 of 14)

- **Step 5: Mapping of Binary M:N Relationship Types.**
  - For each regular binary M:N relationship type  $R$ , **create a new relation  $S$**  to represent  $R$ . This is a **relationship relation**.
  - Include as foreign key attributes in  $S$  the primary keys of the relations that represent the participating entity types; **their combination will form the primary key** of  $S$ .
  - Also include any simple attributes of the M:N relationship type (or simple components of composite attributes) as attributes of  $S$ .

# ER-to-Relational Mapping Algorithm (10 of 14)

- Example: The M:N relationship type WORKS\_ON from the ER diagram is mapped by creating a relation WORKS\_ON in the relational database schema.
  - The primary keys of the PROJECT and EMPLOYEE relations are included as foreign keys in WORKS\_ON and renamed PNO and ESSN, respectively.
  - Attribute HOURS in WORKS\_ON represents the HOURS attribute of the relation type. The primary key of the WORKS\_ON relation is the combination of the foreign key attributes {ESSN, PNO}.

WORKS\_ON

<u>Essn</u>	<u>Pno</u>	Hours
-------------	------------	-------

# ER-to-Relational Mapping Algorithm (11 of 14)

- **Step 6: Mapping of Multivalued attributes.**
  - For each multivalued attribute  $A$ , create a new relation  $R$ .
  - This relation  $R$  will include an attribute corresponding to  $A$ , plus the primary key attribute  $K$ -as a foreign key in  $R$ -of the relation that represents the entity type of relationship type that has  $A$  as an attribute.
  - The primary key of  $R$  is the combination of  $A$  and  $K$ . If the multivalued attribute is composite, we include its simple components.




# ER-to-Relational Mapping Algorithm (12 of 14)

- **Example:** The relation DEPT\_LOCATIONS is created.
  - The attribute DLOCATION represents the multivalued attribute LOCATIONS of DEPARTMENT, while DNUMBER-as foreign key-represents the primary key of the DEPARTMENT relation.
  - The primary key of  $R$  is the combination of {DNUMBER, DLOCATION}.


DEPT\_LOCATIONS

<u>Dnumber</u>	<u>Dlocation</u>
----------------	------------------

# Figure 9.1 The ER Conceptual Schema Diagram for the COMPANY Database



# Figure 9.2 Result of Mapping the COMPANY ER Schema into a Relational Database Schema




# ER-to-Relational Mapping Algorithm (13 of 14)

- **Step 7: Mapping of  $N$ -ary Relationship Types.**
  - For each  $n$ -ary relationship type  $R$ , where  $n > 2$ , create a new relationship  $S$  to represent  $R$ .
  - Include as foreign key attributes in  $S$  the primary keys of the relations that represent the participating entity types.
  - Also include any simple attributes of the  $n$ -ary relationship type (or simple components of composite attributes) as attributes of  $S$ .


# ER-to-Relational Mapping Algorithm (14 of 14)

- **Example:** The relationship type SUPPLY in the ER on the next slide.
  - This can be mapped to the relation SUPPLY shown in the relational schema, whose primary key is the combination of the three foreign keys {SNAME, PART NO, PROJNAME}

# Figure 3.17 Ternary Relationship: Supply



# Mapping the *n*-ary relationship type SUPPLY



# Summary of Mapping Constructs and Constraints

**Table 9.1** Correspondence between ER and Relational Models

ER Model	Relational Model
Entity type	<b>Entity</b> relation
1:1 or 1:N relationship type	Foreign key (or <b>relationship</b> relation)
M:N relationship type	<b>Relationship</b> relation and <b>two</b> foreign keys
<i>n</i> -ary relationship type	<b>Relationship</b> relation and <i>n</i> foreign keys
Simple attribute	Attribute
Composite attribute	Set of simple component attributes
Multivalued attribute	Relation and foreign key
Value set	Domain
Key attribute	Primary (or secondary) key