

INFO1110 & COMP9001: Introduction to Programming

School of Information Technologies, University of Sydney



COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

WARNING

This material has been reproduced and communicated to you by or on behalf of the University of Sydney pursuant to Part VB of the Copyright Act 1968 (**the Act**).

The material in this communication may be subject to copyright under the Act. Any further copying or communication of this material by you may be the subject of copyright protection under the Act.

Do not remove this notice.

Lecture 12: File Input/Output

Open, Read/Write, Close

Files are an idea that makes information storage simple for users.

What kinds of file are these?

- hello.py
- family.jpg
- addresses.db
- birthdaylist.txt

Files contain information

There are no rules about what information is stored in a file. Text, images, binary data

The file name suffix^[1] is there for the operating system to *identify* which program should be associated when opening the file.


A unix/linux tool called `file` can scan the contents of a file and determine its type

```
~> file HelloWorld.java
HelloWorld.java: ASCII C++ program text
~> file HelloWorld.class
HelloWorld.class: compiled Java class data, version 50.0 (Java 1.6)
~> file runButton.png
runButton.png: PNG image, 30 x 24, 8-bit/color RGBA, non-interlaced
~> file hello.py
hello.py: ASCII text
~> file hello.pyc
hello.cpython-36.pyc: data
```

^[1]those final letters after the full stop

Location of Files

There is a *path* associated with files



You can refer to the file with a *Relative* path, or *Absolute* path

Where is calzone.jpg?

To read from or write to from a file you need several things

- 1 The file has to be there
- 2 The file has to be available — it must be opened
- 3 You must have access to it
- 4 You must know what to read/write

Once you've finished with a file you should *always* close it.

Creating a File Object

First we need to create an File Object

File object: *An abstract representation of a file.*

Consider the example where we open the file called README

```
1 file_variable = open("README", "r")
```

What can go wrong here?

Will this compile?

Will this run?

Next we will need some kind of access to it. There are *many* different ways to access a file, but the easiest is the `readline()` method

`readline()`: A method to read exactly one line of text that is delimited by a new line character (default). A String object is returned. Where the string object is empty, there is no more data in the file

```
1 file_variable = open("README", "r")
2 one_line = file_variable.readline()
3 print("first line of file is : " + one_line)
```

Something is missing in this code

Accessing the File (cont.)

There are *uncaught exception* that “must be caught” or dealt with when using files.

This is where the idea of *exceptions* are important.

Suppose you have to read one integer from a file called numbers.txt and print it to console

```
12
```

What could go wrong with the following code?

Reading Integer from File

```
1  import sys
2
3  # read in one line of the file, convert to an integer and print
4  # includes error correction
5  the_file = open(sys.argv[1], 'r')
6  the_integer = int(the_file.readline())
7  the_file.close()
8
9  print("the number is:" + str(the_integer))
10 print("all done")
```

Compiles? Works?

Reading Integer from File

Array bounds checking

Expecting file to exist

Expecting data to be there

Always expect integer

Didn't close file

Reading Integer from File

```
1  import sys
2  # read in one line of the file, convert to an integer and print
3  # includes error correction
4  try:
5      the_file = open(sys.argv[1], 'r')
6      the_integer = int(the_file.readline())
7      the_file.close()
8  except IndexError:
9      pass
10 except FileNotFoundError:
11     pass
12 except TypeError:
13     pass
14 except NoMoreDataError:
15     pass
16 finally:
17     pass
18
19 print("the number is:" + str(the_integer))
20 print("all done")
```

Compiles? Works?

Switch the flag to open the file in write mode

```
1 the_file = open(sys.argv[1], 'w')
```

`f.write(string)` writes the contents of `string` to the file, returning `None`.
Don't forget the new line character!

```
1 the_file = open(sys.argv[1], 'w')
2 the_file.write("10")
3 the_file.close()
```

Potential data loss - If the file exists then it will be truncated to zero size; otherwise, a new file will be created.

Writing numbers to File

```
1 import sys
2 import math
3
4 def write_numbers(outfile, numbers):
5     if outfile == None or numbers == None:
6         return
7
8     for num in numbers:
9         the_string = "{}\n".format(num)
10        outfile.write(the_string)
11
12 outfilename = "numbers_output.txt"
13 outfile = open(outfilename, 'w')
14 numbers = [ 1.0, 3.14, math.sqrt(2), 14.0/1.0 ]
15 write_numbers(outfile, numbers)
16 outfile.close()
```

Reading numbers from File

```
1 import sys
2 import math
3
4 def read_numbers(infile, numbers):
5     if infile == None or numbers == None:
6         return
7
8     done = False
9     while not done:
10         line = infile.readline()
11         if not line:
12             break
13         numbers.append( int(line) )
14
15 infilename = "numbers_input.txt"
16 infile = open(infilename, 'r')
17 numbers_in = []
18 read_numbers(infile, numbers_in)
19 infile.close()
20 print("numbers in:")
21 print(numbers_in)
```


Often a file contains many different parts. These need to be loaded into memory for the program to do useful work.

Example: read a file and separate the numerical data from text

The following file is "points.txt", it contains 2D point data of exactly 20 locations

```
4, 12
5, 3
18, 19
43, 27
...
140, 0
```

You are to extract the coordinates and store them in a list of 2-tuples
[(4,12), (5,3), (18,19), .. (140,0)]

Reading Point data

```
1 def read_points(infile):
2     points = [None]*20
3     location = 0
4     line_num = 0
5     try:
6         infile = open(infile, 'r')
7
8         done = False
9         while not done:
10
11             line = infile.readline()
12             if not line:
13                 break
14             line_num += 1
15
16             # ???
17
18         infile.close()
19     except FileNotFoundError as fnfe:
20         myerr("file {} not found\n".format(infile))
```

Reading Point data

```
1 # extract tokens from one line
2 tokens = line.split(',')
3 if len(tokens) < 2:
4     # bad line, skip to next line
5     myerr("less than 2 tokens on line #{}\n".format(line_num))
6     continue
7
8 # parse integers from 1st and 2nd tokens
9 try:
10     x = int(tokens[0].strip())
11     y = int(tokens[1].strip())
12
13     # create a new point with data
14     pair = (x,y)
15     # update the array
16     points[location] = pair;
17     location = location + 1;
18
19 except ValueError as ve:
20     # bad number, skip to next line
21     myerr("could not convert to int on line #{}\n".format(line_num))
22     continue
```

What is the output when using the previous text file `points_perfect.txt`:

```
~> python PointFileReader.py points_perfect.txt
```

If we change the input file

```
1, 2
3,
4 4
a , 5
      8      ,      7
1600, , 14 ...

9, 14, 32, 57
# frivolous comments!
```

What is the output?

Reading Point data

```
1 def myerr(s):
2     sys.stderr.write(s)
3
4 def read_points(infilename):
5     points = [None]*20
6     location = 0
7     line_num = 0
8     try:
9         infile = open(infilename , 'r')
10
11         done = False
12         while not done:
13
14             line = infile.readline()
15             if not line:
16                 break
17             line_num += 1
18
19             # extract tokens from one line
20             tokens = line.split(',')
21             if len(tokens) < 2:
```

Reading Point data (cont.)

```
22         # bad line, skip to next line
23         myerr("less than 2 tokens on line #{ }\n".format(line_num
24         continue
25
26     # parse integers from 1st and 2nd tokens
27     try:
28         x = int(tokens[0].strip())
29         y = int(tokens[1].strip())
30
31         # create a new point with data
32         pair = (x,y)
33
34         # update the array
35         points[location] = pair;
36         location = location + 1;
37
38     except ValueError as ve:
39         # bad number, skip to next line
40         myerr("could not convert to int on line #{ }\n".format(li
41         continue
42
```

Reading Point data (cont.)

```
43     infile.close()
44
45     print("read {} lines".format(line_num))
46     print("successfully entered {} points".format(location))
47
48
49     i = 0
50     while i < 20:
51         if points[i] != None:
52             print("point[{index}]: {x} {y}".format(
53                 index=i, x=points[i][0], y=points[i][1]))
54             i += 1
55
56     except FileNotFoundError as fnfe:
57         myerr("file {} not found\n".format(infilename))
58
59     #read_points("points_perfect.txt")
60     #read_points("points_missing.txt")
61     #read_points("points_non_numbers.txt")
62     read_points("points_horror.txt")
```