



Intracardiac echocardiography catheters

© 2020 Koninklijke Philips N.V. All rights reserved. Philips Healthcare reserves the right to make changes in specifications and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.

Instructions for Use
VeriSight & VeriSight Pro
Intracardiac echocardiography (ICE) catheters

The diagram illustrates the components and dimensions of the VeriSight and VeriSight Pro ICE catheters. Key features include:

- Ultrasound Transducer:** Located at the proximal end of the catheter.
- Clutch Knob:** A control knob located near the transducer.
- Articulating Segment:** A 7.5 cm segment of the catheter that allows for flexibility.
- Working Length:** The total length of the catheter is 90 cm, with a 9F (French) diameter.
- Distal Tip:** The tip of the catheter is 2 cm long.
- Neutral Position Indicators:** Markers on the catheter to indicate its neutral position.
- Steering Wheels:** Two wheels used to steer the catheter tip.
- PIM Connector:** A connector at the distal end of the catheter.
- IPX7:** A rating indicating the catheter's waterproofing capabilities.
- D000214618.B:** A reference code for the device.

Volcano Corporation
3721 Valley Centre Drive, Suite 500
San Diego, CA 92130 USA
(800) 228-4728
IGTD.CustomerInquiry@philips.com

	ISO 15223-1, 5.15.: Batch code
	ISO 15223-1, 5.1.6: Catalogue number
	ISO 15223-1, 5.1.7: Serial number
	ISO 15223-1, 5.1.1: Manufacturer/Manufactured for:
	ISO 15223-1, 5.2.8: Do not use if package damaged
	ISO 15223-1, 5.2.3: Sterilized using ethylene oxide
	ISO 15223-1, 5.3.4: Keep dry
	ISO 15223-1, 5.3.2: Keep away from sunlight
	ISO 15223-1, 5.4.2: Do not re-use
	ISO 15223-1, 5.2.6: Do not re-sterilize
	ISO 15223-1, 5.6.3: Non-pyrogenic
	IEC 60878, 2794: Use by date
	IEC 60878, 2794: Packaging unit
	IEC 60601-1, Table D.2, Symbol 10: Follow instructions for use
	21 CFR 801.15(c)(1)(i)F: Prescription only
	Not made with natural rubber latex
	Part number
	IEC 60417, 5336: Defibrillation-proof patient connection (Type CF applied part)
	IEC 60529: Indicates that the device is protected against the effects of immersion

Refer to www.usa.philips.com/a-w/symbols/igt for complete symbol glossary.