

CloudTask API Error Reference Guide

Category: Technical | Version: 1.0 | Document ID: api_error_guide

1. Authentication Errors

- Error 401 (Unauthorized): The API token is missing, invalid, or expired. Generate a new token from Settings > Developer > API Tokens.
- Error 403 (Forbidden): The authenticated user does not have permission to perform this action (for example, a Viewer role attempting to create a task).

2. Request Errors

- Error 400 (Bad Request): The request body is malformed or missing required fields. Check that the Content-Type header is set to application/json.
- Error 404 (Not Found): The requested resource (task, project, or workspace ID) does not exist or was deleted.
- Error 422 (Unprocessable Entity): The request is well-formed but contains invalid values, such as an invalid due_date format. Dates must be in ISO 8601 format.

3. Rate Limiting

3.1 The CloudTask API allows 100 requests per minute per API token on the Pro plan, and 500 requests per minute on the Business plan.

3.2 Exceeding the limit returns Error 429 (Too Many Requests) along with a Retry-After header indicating how many seconds to wait before retrying.

4. Server Errors

- Error 500 (Internal Server Error): An unexpected error occurred on CloudTask's servers. These are automatically logged and monitored; if the error persists for more than 10 minutes, check the status page at status.cloudtask.com.
- Error 503 (Service Unavailable): The API is temporarily down for scheduled maintenance, which is always announced in advance on the status page.

5. Webhook Delivery Failures

If a configured webhook endpoint returns a non-2xx response, CloudTask retries delivery up to 5 times with exponential backoff over 24 hours before marking the webhook as failed.