

Public Vendor Page False “Not Taking Orders” Fix

Date: 2026-07-08
Status: Complete

Summary

The public customer vendor page (`/[podSlug]/[vendorSlug]`) and pod vendor grid used `loadVendorReadinessBundles()` for orderability, but that loader did **not** populate `squareConnectionReady` on `posSummary` . Square vendors therefore failed `isVendorSetupPosReady()` on public surfaces while dashboard/setup (via `loadVendorDashboardContext`) correctly showed them as open.

Root cause

Surface	Data loader	<code>squareConnectionReady</code> on <code>posSummary</code>
Dashboard / setup	<code>loadVendorDashboardContext</code>	✅ Loaded via <code>evaluateSquareConnectionHealth</code>
Public vendor page	<code>loadVendorReadinessBundles</code>	❌ Missing
Pod customer page	<code>loadVendorReadinessBundles</code>	❌ Missing
Cart / checkout validation	<code>loadVendorReadinessBundles</code>	❌ Missing

Public orderability path:

```
renderVendorMenuCustomerPage
  → loadVendorReadinessBundles
  → getVendorOrderabilityInPod
  → getVendorOrderabilityState
  → getVendorOperationalMissingItems
  → isVendorPosReady → isVendorSetupPosReady
  → square mode requires squareConnectionReady === true
```

With `squareConnectionReady` undefined, Square vendors were always blocked with "Not accepting orders right now" despite healthy OAuth connection.

`squareOrderRoutingEnabled` was NOT the public blocker — it is only checked by `isVendorRoutingOperationalReady()` (admin injection / post-payment routing). The public page never read that flag; the bug was the missing connection health field.

Fix

1. `loadVendorReadinessBundles ( vendor-readiness-validation.server.ts )`

For vendors with `orderRoutingMode === "square"`, batch-load `evaluateSquareConnectionHealth()` and set:

```
posSummary.squareConnectionReady = health.isReady
```

2. `Explicit customer orderability helper ( vendor-readiness-states.ts )`

Added `isVendorCustomerOrderable()` as a named alias for `getVendorOrderabilityState().orderable`.

3. `Revalidation ( revalidate-vendor-pod-surfaces.server.ts )`

Added `revalidateVendorCustomerOrderingSurfaces(vendorId)` and wired it to:

- Square OAuth callback
- Square location select / disconnect actions
- Menu import publish
- Vendor pause toggle
- Customer ordering hours update

Ensures public pod/vendor pages refresh after orderability-affecting changes.

Readiness function separation (unchanged intent, now aligned)

Function	Purpose
----------	---------

<code>isVendorCustomerOrderable / getVendorOrderabilityState</code>	Public/cart/checkout — can customer order now?
<code>isVendorSetupPosReady</code>	Vendor setup checklist — connection ready (not admin injection)
<code>isVendorRoutingOperationalReady</code>	Post-payment Square injection — requires <code>squareOrderRoutingEnabled</code> + full injection prerequisites

Admin `squareOrderRoutingEnabled` does **not** block public ordering.

Menu source

No change required. `menuItemDeliverectIdMatchesMenuSource` already accepts `sq:prod:*` IDs for `menuSource=open_order`. Published Square-imported menus load via existing customer menu cache.

Files changed

File	Change
<code>src/lib/vendor-readiness-validation.server.ts</code>	Load <code>squareConnectionReady</code> for Sq vendors
<code>src/lib/vendor-readiness-states.ts</code>	<code>isVendorCustomerOrderable()</code>
<code>src/lib/revalidate-vendor-pod-surfaces.server.ts</code>	<code>revalidateVendorCustomerOrdering</code>
<code>src/actions/vendor-square-connect.actions.ts</code>	Revalidate public surfaces
<code>src/app/api/integrations/square/oauth/callback/route.ts</code>	Revalidate after OAuth
<code>src/app/api/vendor/.../menu-imports/.../publish/route.ts</code>	Revalidate after publish
<code>src/app/api/vendor/.../pause/route.ts</code>	Revalidate after pause
<code>src/app/api/vendor/.../customer-ordering-hours/route.ts</code>	Revalidate after hours
Tests	<code>vendor-readiness-states.test.ts</code> , <code>readiness-validation.server.test.ts</code>

Unchanged: checkout, payouts, Square injection, Deliverect/manual routing, admin injection gate.

Poke Sea expected state

When Square OAuth + location are healthy, menu published, Stripe ready, hours open, not paused:

- Dashboard: open ✓
 - Setup: ready ✓
 - Public page: **orderable** ✓ (add-to-cart enabled)
 - Post-payment Square injection: still requires admin `squareOrderRoutingEnabled` (unchanged)
-

Tests / QA

#	Scenario	Status
1	Dashboard/setup open → public orderable with bundle fix	✓
2	<code>squareOrderRoutingEnabled</code> not a public blocker	✓
3	Square connected + admin injection off → public orderable	✓
4	Missing Square connection blocks public ordering	✓
5	<code>sq:prod:*</code> menu IDs accepted (<code>vendor-menu-source.test.ts</code>)	✓ (existing)
6	Closed hours / paused / no menu still block	✓ (existing)
7	Deliverect/manual unchanged	✓
8	Build passes	✓

Known limitations

1. Public ordering can succeed before admin enables Square order injection; paid orders may fail routing until admin toggles (by design — manual recovery remains).
2. `evaluateSquareConnectionHealth` runs per Square vendor when loading readiness bundles (acceptable for pod pages with few vendors; same cost as dashboard).