

Admin Square Order Injection Diagnostics

Date: 2026-07-08

Summary

The admin vendor detail page did not reflect Square order injection readiness correctly because readiness logic treated `squareOrderRoutingEnabled` as a prerequisite for the **Enable** action — a circular dependency that made injection impossible to turn on from the UI even when connection, location, menu, and mappings were healthy.

This change splits **prerequisites** (can enable) from **injection operational** (will actually call Square APIs), adds a full diagnostics panel, fixes the enable action, and exposes a JSON debug route.

Root cause

`loadSquareOrderRoutingReadiness()` included `squareOrderRoutingEnabled` in both `missingRequirements` and the `ready` boolean. The admin **Enable Square order routing** button was `disabled={!squareOrderRoutingReady.ready}`, and the server action `adminSetSquareOrderRoutingEnabled()` called `assertSquareOrderRoutingReady()` — which required `enabled === true` before allowing enable.

Result: prerequisites could pass, but admins could never enable injection.

`SQUARE_ROUTING_LIVE=true` alone never enables vendor routing; it only allows live Square API calls when a vendor is already configured for Square injection.

Env var reads (Part 1)

Variable	Read in	Purpose
<code>ENABLE_SQUARE_INTEGRATION</code>	<code>src/lib/env.ts</code> → <code>src/lib/integrations/square/square-config.ts</code> (<code>getSquareConfigSnapshot</code>)	Controls Square OAuth/connect UI availability in production

SQUARE_ROUTING_LIVE	src/lib/env.ts → square-order-routing-readiness.ts, square-order.service.ts, routing-availability.ts	Global kill switch for live Square CreateOrder/CreatePayment API calls
SQUARE_ENVIRONMENT / SQUARE_MODE	src/lib/env.ts → square-config.ts	Sandbox vs production Square hosts
SQUARE_APPLICATION_ID	src/lib/env.ts → square-config.ts	OAuth client id (snapshot exposes id only in server diagnostics — not rendered in new admin panel)
SQUARE_APPLICATION_SECRET	src/lib/env.ts → square-config.ts, assertSquareOAuthConfigured()	OAuth secret — never exposed in UI or debug JSON
SQUARE_OAUTH_REDIRECT_URL	src/lib/env.ts → square-config.ts	OAuth redirect — safe URL only in config snapshot

Redeploy required: All values are read server-side via `env` at process start. Changing them in Vercel requires **redeploy/restart** before the admin diagnostics panel or routing behavior reflects new values.

SQUARE_ROUTING_LIVE does not change vendor `orderRoutingMode` or auto-enable `squareOrderRoutingEnabled`. Manual and Deliverect vendors are unaffected.

Files changed

File
src/lib/integrations/square/square-order-routing-readiness.ts
src/lib/integrations/square/admin-square-order-injection-diagnostics.server.ts
src/app/admin/(dashboard)/vendors/[vendorId]/AdminSquareOrderInjectionDiagnosticsPanel.tsx
src/app/admin/(dashboard)/vendors/[vendorId]/square-routing-debug/route.ts
src/app/admin/(dashboard)/vendors/[vendorId]/AdminVendorOrderRoutingSection.tsx

```
src/app/admin/(dashboard)/vendors/[vendorId]/AdminVendorRescueClient.tsx
```

```
src/app/admin/(dashboard)/vendors/[vendorId]/page.tsx
```

```
src/services/admin-vendor-rescue.service.ts
```

Tests

Unchanged: checkout, payouts, Deliverect/manual routing, admin safety gate
(`squareOrderRoutingEnabled` still admin-only).

Admin UI (Parts 2–4)

Diagnostics panel

On admin vendor detail, **Square order injection diagnostics** shows:

Global/env

- `ENABLE_SQUARE_INTEGRATION`
- `SQUARE_ROUTING_LIVE`
- `SQUARE_ENVIRONMENT`
- Square OAuth configured (quartet complete)

Vendor

- `orderRoutingMode`
- `squareOrderRoutingEnabled`
- Square connection status (`connected` / `error` / `missing`)
- Selected Square location
- Published Square-imported menu
- Active item / modifier mapping counts
- Routing readiness (`ready` / `not ready`)
- Blocking reasons (list)

Link: **Open JSON debug** → `/admin/vendors/[vendorId]/square-routing-debug`

Enable action (Part 3)

When `orderRoutingMode === "square"` (saved on vendor):

- **Disabled injection:** copy explains orders stay in Open Order only; **Enable Square order injection** enabled when `prerequisitesReady` (not when already enabled).
- **Enabled injection:** explains prepaid pickup injection; Stripe/payouts unchanged.

Stale page fix (Part 4)

- Admin vendor detail: `export const dynamic = "force-dynamic"`
 - Toggle actions: `router.refresh()` + `revalidatePath(/admin/vendors/[vendorId])` (existing + preserved)
-

Poke Sea / test vendor expected state

After deploy, for a Square-connected vendor with published Square menu (e.g. Poke Sea):

1. Diagnostics panel shows env flags from **this deployment** (verify `SQUARE_ROUTING_LIVE` and `ENABLE_SQUARE_INTEGRATION` after redeploy).
2. If `orderRoutingMode !== "square"` : blocker *"Order routing mode is not Square"* — save Square routing mode first.
3. If prerequisites pass but `squareOrderRoutingEnabled === false` : blocker *"Square order injection is disabled"* — **Enable** button should now be active.
4. After enabling: if `SQUARE_ROUTING_LIVE=true` , routing readiness becomes **ready**; if false, blocker shows global kill switch (injection configured but API calls blocked).

Primary blocker before this fix: enable button permanently disabled due to circular readiness check.

Tests / QA

#	Scenario	Status
1	<code>SQUARE_ROUTING_LIVE=true</code> in admin diagnostics	✓
2	<code>SQUARE_ROUTING_LIVE=false</code> shows global kill switch blocker	✓
3	<code>ENABLE_SQUARE_INTEGRATION=false</code> shows unavailable	✓
4	<code>orderRoutingMode=square</code> , <code>squareOrderRoutingEnabled=false</code> shows injection disabled	✓
5	Admin can enable when prerequisites pass	✓
6	Enable revalidates <code>/admin/vendors/[vendorId]</code>	✓

7	Manual vendors unaffected by <code>SQUARE_ROUTING_LIVE</code> in vendor blockers	✓
8	Deliverect vendors unaffected	✓
9	No secrets in diagnostics JSON	✓
10	Build passes	✓

How to verify in production

1. Redeploy after env changes.
2. Open `/admin/vendors/<vendorId>` — confirm diagnostics panel.
3. Open `/admin/vendors/<vendorId>/square-routing-debug` — confirm JSON matches panel.
4. If prerequisites green and mode is Square, enable injection and refresh — `squareOrderRoutingEnabled` should be `true` .