

Modules

Modules refer to a file containing Python statements and definitions.

A file containing Python code, for e.g.: abc.py, is called a module and its module name would be "abc".

We use modules to break down large programs into small manageable and organized files. Furthermore, modules provide reusability of code.

We can define our most used functions in a module and import it, instead of copying their definitions into different programs.

How to import a module?

We use the import keyword to do this.

```
In [1]: import example #imported example module
```

```
-----  
ModuleNotFoundError                                Traceback (most recent call last)  
<ipython-input-1-b0fe4c474e13> in <module>()  
----> 1 import example #imported example module
```

```
ModuleNotFoundError: No module named 'example'
```

```
-----  
NOTE: If your import is failing due to a missing package, you can  
manually install dependencies using either !pip or !apt.
```

```
To view examples of installing some common dependencies, click the  
"Open Examples" button below.  
-----
```

Using the module name we can access the function using dot (.) operation.

```
In [ ]: example.add(10, 20)
```

```
Out[ ]: 30
```

Python has a lot of standard modules available.

<https://docs.python.org/3/py-modindex.html> (<https://docs.python.org/3/py-modindex.html>)

Examples:

```
In [ ]: import math  
        print(math.pi)
```

```
3.141592653589793
```

```
In [ ]: import datetime  
        datetime.datetime.now()
```

```
Out[ ]: datetime.datetime(2017, 10, 18, 20, 47, 20, 606228)
```

import with renaming

```
In [ ]: import math as m  
        print(m.pi)
```

```
3.141592653589793
```

from...import statement

We can import specific names form a module without importing the module as a whole.

```
In [ ]: from datetime import datetime  
        datetime.now()
```

```
Out[ ]: datetime.datetime(2017, 10, 18, 20, 47, 38, 17242)
```

import all names

```
In [ ]: from math import *  
        print("Value of PI is " + str(pi))
```

```
Value of PI is 3.141592653589793
```

dir() built in function

We can use the dir() function to find out names that are defined inside a module.

```
In [ ]: dir(example)
```

```
Out[ ]: ['__builtins__',  
         '__cached__',  
         '__doc__',  
         '__file__',  
         '__loader__',  
         '__name__',  
         '__package__',  
         '__spec__',  
         'add']
```

```
In [ ]: print(example.add.__doc__)
```

This program adds two numbers and return the result