

# Formal Methods in Software Development

## Propositional Logic - refresher

Mădălina Eraşcu

West University of Timișoara  
Faculty of Mathematics and Informatics

Based on slides of the lecture Satisfiability Checking (Erika Ábrahám), RTWH Aachen

October 18, 2018

The slides are partly taken from:

[www.decision-procedures.org/slides/](http://www.decision-procedures.org/slides/)

# Propositional logic - Outline

- Syntax of propositional logic
- Semantics of propositional logic
- Satisfiability and validity
- Normal forms
- Enumeration and deduction

# Propositional logic - Outline

- Syntax of propositional logic
- Semantics of propositional logic
- Satisfiability and validity
- Normal forms
- Enumeration and deduction

# Syntax of propositional logic

**Abstract syntax** of well-formed propositional formulae:

# Syntax of propositional logic

**Abstract syntax** of well-formed propositional formulae:

$$\varphi := a \mid (\neg\varphi) \mid (\varphi \wedge \varphi)$$

Let  $AP$  is a set of (atomic) **propositions** (Boolean variables). Then  $a \in AP$ .  
We write **PropForm** for the set of all propositional logic formulae.

# Syntax of propositional logic

**Abstract syntax** of well-formed propositional formulae:

$$\varphi := a \mid (\neg\varphi) \mid (\varphi \wedge \varphi)$$

Let  $AP$  is a set of (atomic) **propositions** (Boolean variables). Then  $a \in AP$ . We write **PropForm** for the set of all propositional logic formulae.

**Syntactic sugar:**

# Syntax of propositional logic

**Abstract syntax** of well-formed propositional formulae:

$$\varphi := a \mid (\neg\varphi) \mid (\varphi \wedge \varphi)$$

Let  $AP$  is a set of (atomic) **propositions** (Boolean variables). Then  $a \in AP$ . We write **PropForm** for the set of all propositional logic formulae.

**Syntactic sugar:**

$$\perp :=$$



# Syntax of propositional logic

**Abstract syntax** of well-formed propositional formulae:

$$\varphi := a \mid (\neg\varphi) \mid (\varphi \wedge \varphi)$$

Let  $AP$  is a set of (atomic) **propositions** (Boolean variables). Then  $a \in AP$ . We write **PropForm** for the set of all propositional logic formulae.

**Syntactic sugar:**

$$\perp := (a \wedge \neg a)$$

# Syntax of propositional logic

**Abstract syntax** of well-formed propositional formulae:

$$\varphi := a \mid (\neg\varphi) \mid (\varphi \wedge \varphi)$$

Let  $AP$  is a set of (atomic) **propositions** (Boolean variables). Then  $a \in AP$ . We write **PropForm** for the set of all propositional logic formulae.

**Syntactic sugar:**

$$\begin{array}{ll} \perp & := (a \wedge \neg a) \\ \top & := \end{array}$$

# Syntax of propositional logic

**Abstract syntax** of well-formed propositional formulae:

$$\varphi := a \mid (\neg\varphi) \mid (\varphi \wedge \varphi)$$

Let  $AP$  is a set of (atomic) **propositions** (Boolean variables). Then  $a \in AP$ . We write **PropForm** for the set of all propositional logic formulae.

**Syntactic sugar:**

$$\begin{aligned}\perp &:= (a \wedge \neg a) \\ \top &:= (a \vee \neg a)\end{aligned}$$

# Syntax of propositional logic

**Abstract syntax** of well-formed propositional formulae:

$$\varphi := a \mid (\neg\varphi) \mid (\varphi \wedge \varphi)$$

Let  $AP$  is a set of (atomic) **propositions** (Boolean variables). Then  $a \in AP$ .  
We write **PropForm** for the set of all propositional logic formulae.

**Syntactic sugar:**

$$\begin{aligned} \perp &:= (a \wedge \neg a) \\ \top &:= (a \vee \neg a) \\ ( \varphi_1 \vee \varphi_2 ) &:= \end{aligned}$$

# Syntax of propositional logic

**Abstract syntax** of well-formed propositional formulae:

$$\varphi := a \mid (\neg\varphi) \mid (\varphi \wedge \varphi)$$

Let  $AP$  is a set of (atomic) **propositions** (Boolean variables). Then  $a \in AP$ .  
We write **PropForm** for the set of all propositional logic formulae.

**Syntactic sugar:**

$$\begin{aligned} \perp &:= (a \wedge \neg a) \\ \top &:= (a \vee \neg a) \\ ( \varphi_1 \vee \varphi_2 ) &:= \neg((\neg\varphi_1) \wedge (\neg\varphi_2)) \end{aligned}$$

# Syntax of propositional logic

**Abstract syntax** of well-formed propositional formulae:

$$\varphi := a \mid (\neg\varphi) \mid (\varphi \wedge \varphi)$$

Let  $AP$  is a set of (atomic) **propositions** (Boolean variables). Then  $a \in AP$ .  
We write **PropForm** for the set of all propositional logic formulae.

**Syntactic sugar:**

$$\begin{aligned} \perp &:= (a \wedge \neg a) \\ \top &:= (a \vee \neg a) \\ ( \varphi_1 \vee \varphi_2 ) &:= \neg((\neg\varphi_1) \wedge (\neg\varphi_2)) \\ ( \varphi_1 \rightarrow \varphi_2 ) &:= \end{aligned}$$

# Syntax of propositional logic

**Abstract syntax** of well-formed propositional formulae:

$$\varphi := a \mid (\neg\varphi) \mid (\varphi \wedge \varphi)$$

Let  $AP$  is a set of (atomic) **propositions** (Boolean variables). Then  $a \in AP$ .  
We write **PropForm** for the set of all propositional logic formulae.

**Syntactic sugar:**

$$\begin{aligned} \perp &:= (a \wedge \neg a) \\ \top &:= (a \vee \neg a) \\ ( \varphi_1 \vee \varphi_2 ) &:= \neg((\neg\varphi_1) \wedge (\neg\varphi_2)) \\ ( \varphi_1 \rightarrow \varphi_2 ) &:= ((\neg\varphi_1) \vee \varphi_2) \end{aligned}$$

# Syntax of propositional logic

**Abstract syntax** of well-formed propositional formulae:

$$\varphi := a \mid (\neg\varphi) \mid (\varphi \wedge \varphi)$$

Let  $AP$  is a set of (atomic) **propositions** (Boolean variables). Then  $a \in AP$ . We write **PropForm** for the set of all propositional logic formulae.

**Syntactic sugar:**

$$\begin{aligned} \perp &:= (a \wedge \neg a) \\ \top &:= (a \vee \neg a) \\ (\varphi_1 \vee \varphi_2) &:= \neg((\neg\varphi_1) \wedge (\neg\varphi_2)) \\ (\varphi_1 \rightarrow \varphi_2) &:= ((\neg\varphi_1) \vee \varphi_2) \\ (\varphi_1 \leftrightarrow \varphi_2) &:= \end{aligned}$$



# Syntax of propositional logic

**Abstract syntax** of well-formed propositional formulae:

$$\varphi := a \mid (\neg\varphi) \mid (\varphi \wedge \varphi)$$

Let  $AP$  is a set of (atomic) **propositions** (Boolean variables). Then  $a \in AP$ .  
We write **PropForm** for the set of all propositional logic formulae.

**Syntactic sugar:**

$$\begin{aligned} \perp &:= (a \wedge \neg a) \\ \top &:= (a \vee \neg a) \\ (\varphi_1 \vee \varphi_2) &:= \neg((\neg\varphi_1) \wedge (\neg\varphi_2)) \\ (\varphi_1 \rightarrow \varphi_2) &:= ((\neg\varphi_1) \vee \varphi_2) \\ (\varphi_1 \leftrightarrow \varphi_2) &:= ((\varphi_1 \rightarrow \varphi_2) \wedge (\varphi_2 \rightarrow \varphi_1)) \end{aligned}$$

# Syntax of propositional logic

**Abstract syntax** of well-formed propositional formulae:

$$\varphi := a \mid (\neg\varphi) \mid (\varphi \wedge \varphi)$$

Let  $AP$  is a set of (atomic) **propositions** (Boolean variables). Then  $a \in AP$ . We write **PropForm** for the set of all propositional logic formulae.

**Syntactic sugar:**

$$\begin{aligned} \perp &:= (a \wedge \neg a) \\ \top &:= (a \vee \neg a) \\ (\varphi_1 \vee \varphi_2) &:= \neg((\neg\varphi_1) \wedge (\neg\varphi_2)) \\ (\varphi_1 \rightarrow \varphi_2) &:= ((\neg\varphi_1) \vee \varphi_2) \\ (\varphi_1 \leftrightarrow \varphi_2) &:= ((\varphi_1 \rightarrow \varphi_2) \wedge (\varphi_2 \rightarrow \varphi_1)) \\ (\varphi_1 \oplus \varphi_2) &:= \end{aligned}$$

# Syntax of propositional logic

**Abstract syntax** of well-formed propositional formulae:

$$\varphi := a \mid (\neg\varphi) \mid (\varphi \wedge \varphi)$$

Let  $AP$  is a set of (atomic) **propositions** (Boolean variables). Then  $a \in AP$ . We write **PropForm** for the set of all propositional logic formulae.

**Syntactic sugar:**

$$\begin{aligned} \perp &:= (a \wedge \neg a) \\ \top &:= (a \vee \neg a) \\ (\varphi_1 \vee \varphi_2) &:= \neg((\neg\varphi_1) \wedge (\neg\varphi_2)) \\ (\varphi_1 \rightarrow \varphi_2) &:= ((\neg\varphi_1) \vee \varphi_2) \\ (\varphi_1 \leftrightarrow \varphi_2) &:= ((\varphi_1 \rightarrow \varphi_2) \wedge (\varphi_2 \rightarrow \varphi_1)) \\ (\varphi_1 \oplus \varphi_2) &:= (\varphi_1 \leftrightarrow (\neg\varphi_2)) \end{aligned}$$

- Examples of **well-formed** formulae:

- $(\neg a)$
- $(\neg(\neg a))$
- $(a \wedge (b \wedge c))$
- $(a \rightarrow (b \rightarrow c))$

- Examples of **well-formed** formulae:

- $(\neg a)$
- $(\neg(\neg a))$
- $(a \wedge (b \wedge c))$
- $(a \rightarrow (b \rightarrow c))$

- We omit parentheses whenever we may restore them through operator precedence:

binds stronger



$\neg \quad \wedge \quad \vee \quad \rightarrow \quad \leftrightarrow$

chaining the same operator: left binds stronger

e.g.,  $a \rightarrow b \rightarrow c$  means  $((a \rightarrow b) \rightarrow c)$

# Propositional logic - Outline

- Syntax of propositional logic
- Semantics of propositional logic
- Satisfiability and validity
- Normal forms
- Enumeration and deduction

**Structures** for predicate logic:

- The **domain** is  $\mathbb{B} = \{0, 1\}$ .
- The **interpretation** assigns Boolean values to the variables:

$$\alpha : AP \rightarrow \{0, 1\}$$

We call these special interpretations **assignments** and use *Assign* to denote the set of all assignments.

**Structures** for predicate logic:

- The **domain** is  $\mathbb{B} = \{0, 1\}$ .
- The **interpretation** assigns Boolean values to the variables:

$$\alpha : AP \rightarrow \{0, 1\}$$

We call these special interpretations **assignments** and use *Assign* to denote the set of all assignments.

**Example:**  $AP = \{a, b\}, \alpha(a) = 0, \alpha(b) = 1$



# Semantics I: Truth tables

- **Truth tables** define the semantics (=meaning) of the operators. They can be used to define the semantics of formulae inductively over their structure.

# Semantics I: Truth tables

- **Truth tables** define the semantics (=meaning) of the operators. They can be used to define the semantics of formulae inductively over their structure.
- Convention: 0 = false, 1 = true

# Semantics I: Truth tables

- **Truth tables** define the semantics (=meaning) of the operators.  
They can be used to define the semantics of formulae inductively over their structure.
- Convention: 0 = false, 1 = true

$p$	$q$	$\neg p$	$p \wedge q$	$p \vee q$	$p \rightarrow q$	$p \leftrightarrow q$	$p \oplus q$
0	0	1	0	0	1	1	0
0	1	1	0	1	1	0	1
1	0	0	0	1	0	0	1
1	1	0	1	1	1	1	0

# Semantics I: Truth tables

- **Truth tables** define the semantics (=meaning) of the operators. They can be used to define the semantics of formulae inductively over their structure.
- Convention: 0 = false, 1 = true

$p$	$q$	$\neg p$	$p \wedge q$	$p \vee q$	$p \rightarrow q$	$p \leftrightarrow q$	$p \oplus q$
0	0	1	0	0	1	1	0
0	1	1	0	1	1	0	1
1	0	0	0	1	0	0	1
1	1	0	1	1	1	1	0

Each possible assignment is covered by a line of the truth table.

$\alpha$  satisfies  $\varphi$  iff in the line for  $\alpha$  and the column for  $\varphi$  the entry is 1.

- Let  $\varphi$  be defined as  $(a \vee (b \rightarrow c))$ .

# Semantics I: Example

- Let  $\varphi$  be defined as  $(a \vee (b \rightarrow c))$ .
- Let  $\alpha : \{a, b, c\} \rightarrow \{0, 1\}$  be an assignment with  $\alpha(a) = 0$ ,  $\alpha(b) = 0$ , and  $\alpha(c) = 1$ .

# Semantics I: Example

- Let  $\varphi$  be defined as  $(a \vee (b \rightarrow c))$ .
- Let  $\alpha : \{a, b, c\} \rightarrow \{0, 1\}$  be an assignment with  $\alpha(a) = 0$ ,  $\alpha(b) = 0$ , and  $\alpha(c) = 1$ .
- Q: Does  $\alpha$  satisfy  $\varphi$ ?



# Semantics I: Example

- Let  $\varphi$  be defined as  $(a \vee (b \rightarrow c))$ .
- Let  $\alpha : \{a, b, c\} \rightarrow \{0, 1\}$  be an assignment with  $\alpha(a) = 0$ ,  $\alpha(b) = 0$ , and  $\alpha(c) = 1$ .
- Q: Does  $\alpha$  satisfy  $\varphi$ ?
- A1: Replace values of  $\alpha$  in  $\varphi$ .

## Semantics II: Satisfaction relation

**Satisfaction relation:**  $\models \subseteq \text{Assign} \times \text{PropForm}$

Instead of  $(\alpha, \varphi) \in \models$  we write  $\alpha \models \varphi$  and say that

- $\alpha$  satisfies  $\varphi$  or
- $\varphi$  holds for  $\alpha$  or
- $\alpha$  is a model of  $\varphi$ .

## Semantics II: Satisfaction relation

**Satisfaction relation:**  $\models \subseteq \text{Assign} \times \text{PropForm}$

Instead of  $(\alpha, \varphi) \in \models$  we write  $\alpha \models \varphi$  and say that

- $\alpha$  satisfies  $\varphi$  or
- $\varphi$  holds for  $\alpha$  or
- $\alpha$  is a model of  $\varphi$ .

$\models$  is defined recursively:

## Semantics II: Satisfaction relation

**Satisfaction relation:**  $\models \subseteq \text{Assign} \times \text{PropForm}$

Instead of  $(\alpha, \varphi) \in \models$  we write  $\alpha \models \varphi$  and say that

- $\alpha$  satisfies  $\varphi$  or
- $\varphi$  holds for  $\alpha$  or
- $\alpha$  is a model of  $\varphi$ .

$\models$  is defined recursively:

$$\alpha \models p$$

# Semantics II: Satisfaction relation

**Satisfaction relation:**  $\models \subseteq \text{Assign} \times \text{PropForm}$

Instead of  $(\alpha, \varphi) \in \models$  we write  $\alpha \models \varphi$  and say that

- $\alpha$  satisfies  $\varphi$  or
- $\varphi$  holds for  $\alpha$  or
- $\alpha$  is a model of  $\varphi$ .

$\models$  is defined recursively:

$$\alpha \models p \quad \text{iff} \quad \alpha(p) = \text{true}$$

# Semantics II: Satisfaction relation

**Satisfaction relation:**  $\models \subseteq \text{Assign} \times \text{PropForm}$

Instead of  $(\alpha, \varphi) \in \models$  we write  $\alpha \models \varphi$  and say that

- $\alpha$  satisfies  $\varphi$  or
- $\varphi$  holds for  $\alpha$  or
- $\alpha$  is a model of  $\varphi$ .

$\models$  is defined recursively:

$$\begin{array}{ll} \alpha \models p & \text{iff } \alpha(p) = \text{true} \\ \alpha \models \neg\varphi & \end{array}$$

# Semantics II: Satisfaction relation

**Satisfaction relation:**  $\models \subseteq \text{Assign} \times \text{PropForm}$

Instead of  $(\alpha, \varphi) \in \models$  we write  $\alpha \models \varphi$  and say that

- $\alpha$  satisfies  $\varphi$  or
- $\varphi$  holds for  $\alpha$  or
- $\alpha$  is a model of  $\varphi$ .

$\models$  is defined recursively:

$$\begin{array}{ll} \alpha \models p & \text{iff } \alpha(p) = \text{true} \\ \alpha \models \neg\varphi & \text{iff } \alpha \not\models \varphi \end{array}$$

# Semantics II: Satisfaction relation

**Satisfaction relation:**  $\models \subseteq \text{Assign} \times \text{PropForm}$

Instead of  $(\alpha, \varphi) \in \models$  we write  $\alpha \models \varphi$  and say that

- $\alpha$  satisfies  $\varphi$  or
- $\varphi$  holds for  $\alpha$  or
- $\alpha$  is a model of  $\varphi$ .

$\models$  is defined recursively:

$\alpha \models p$                       iff     $\alpha(p) = \text{true}$

$\alpha \models \neg\varphi$                   iff     $\alpha \not\models \varphi$

$\alpha \models \varphi_1 \wedge \varphi_2$



# Semantics II: Satisfaction relation

**Satisfaction relation:**  $\models \subseteq \text{Assign} \times \text{PropForm}$

Instead of  $(\alpha, \varphi) \in \models$  we write  $\alpha \models \varphi$  and say that

- $\alpha$  satisfies  $\varphi$  or
- $\varphi$  holds for  $\alpha$  or
- $\alpha$  is a model of  $\varphi$ .

$\models$  is defined recursively:

$\alpha \models p$	iff	$\alpha(p) = \text{true}$
$\alpha \models \neg \varphi$	iff	$\alpha \not\models \varphi$
$\alpha \models \varphi_1 \wedge \varphi_2$	iff	$\alpha \models \varphi_1$ and $\alpha \models \varphi_2$

# Semantics II: Satisfaction relation

**Satisfaction relation:**  $\models \subseteq \text{Assign} \times \text{PropForm}$

Instead of  $(\alpha, \varphi) \in \models$  we write  $\alpha \models \varphi$  and say that

- $\alpha$  satisfies  $\varphi$  or
- $\varphi$  holds for  $\alpha$  or
- $\alpha$  is a model of  $\varphi$ .

$\models$  is defined recursively:

$\alpha \models p$	<i>iff</i>	$\alpha(p) = \text{true}$
$\alpha \models \neg \varphi$	<i>iff</i>	$\alpha \not\models \varphi$
$\alpha \models \varphi_1 \wedge \varphi_2$	<i>iff</i>	$\alpha \models \varphi_1$ and $\alpha \models \varphi_2$
$\alpha \models \varphi_1 \vee \varphi_2$		

## Semantics II: Satisfaction relation

**Satisfaction relation:**  $\models \subseteq \text{Assign} \times \text{PropForm}$

Instead of  $(\alpha, \varphi) \in \models$  we write  $\alpha \models \varphi$  and say that

- $\alpha$  satisfies  $\varphi$  or
- $\varphi$  holds for  $\alpha$  or
- $\alpha$  is a model of  $\varphi$ .

$\models$  is defined recursively:

$\alpha \models p$	<i>iff</i>	$\alpha(p) = \text{true}$
$\alpha \models \neg \varphi$	<i>iff</i>	$\alpha \not\models \varphi$
$\alpha \models \varphi_1 \wedge \varphi_2$	<i>iff</i>	$\alpha \models \varphi_1$ <i>and</i> $\alpha \models \varphi_2$
$\alpha \models \varphi_1 \vee \varphi_2$	<i>iff</i>	$\alpha \models \varphi_1$ <i>or</i> $\alpha \models \varphi_2$

# Semantics II: Satisfaction relation

**Satisfaction relation:**  $\models \subseteq \text{Assign} \times \text{PropForm}$

Instead of  $(\alpha, \varphi) \in \models$  we write  $\alpha \models \varphi$  and say that

- $\alpha$  satisfies  $\varphi$  or
- $\varphi$  holds for  $\alpha$  or
- $\alpha$  is a model of  $\varphi$ .

$\models$  is defined recursively:

$\alpha \models p$	<i>iff</i>	$\alpha(p) = \text{true}$
$\alpha \models \neg \varphi$	<i>iff</i>	$\alpha \not\models \varphi$
$\alpha \models \varphi_1 \wedge \varphi_2$	<i>iff</i>	$\alpha \models \varphi_1$ <i>and</i> $\alpha \models \varphi_2$
$\alpha \models \varphi_1 \vee \varphi_2$	<i>iff</i>	$\alpha \models \varphi_1$ <i>or</i> $\alpha \models \varphi_2$
$\alpha \models \varphi_1 \rightarrow \varphi_2$		

# Semantics II: Satisfaction relation

**Satisfaction relation:**  $\models \subseteq \text{Assign} \times \text{PropForm}$

Instead of  $(\alpha, \varphi) \in \models$  we write  $\alpha \models \varphi$  and say that

- $\alpha$  satisfies  $\varphi$  or
- $\varphi$  holds for  $\alpha$  or
- $\alpha$  is a model of  $\varphi$ .

$\models$  is defined recursively:

$\alpha \models p$	<i>iff</i>	$\alpha(p) = \text{true}$
$\alpha \models \neg \varphi$	<i>iff</i>	$\alpha \not\models \varphi$
$\alpha \models \varphi_1 \wedge \varphi_2$	<i>iff</i>	$\alpha \models \varphi_1$ <i>and</i> $\alpha \models \varphi_2$
$\alpha \models \varphi_1 \vee \varphi_2$	<i>iff</i>	$\alpha \models \varphi_1$ <i>or</i> $\alpha \models \varphi_2$
$\alpha \models \varphi_1 \rightarrow \varphi_2$	<i>iff</i>	$\alpha \models \varphi_1$ <i>implies</i> $\alpha \models \varphi_2$

# Semantics II: Satisfaction relation

**Satisfaction relation:**  $\models \subseteq \text{Assign} \times \text{PropForm}$

Instead of  $(\alpha, \varphi) \in \models$  we write  $\alpha \models \varphi$  and say that

- $\alpha$  satisfies  $\varphi$  or
- $\varphi$  holds for  $\alpha$  or
- $\alpha$  is a model of  $\varphi$ .

$\models$  is defined recursively:

$\alpha \models p$	<i>iff</i>	$\alpha(p) = \text{true}$
$\alpha \models \neg \varphi$	<i>iff</i>	$\alpha \not\models \varphi$
$\alpha \models \varphi_1 \wedge \varphi_2$	<i>iff</i>	$\alpha \models \varphi_1$ <i>and</i> $\alpha \models \varphi_2$
$\alpha \models \varphi_1 \vee \varphi_2$	<i>iff</i>	$\alpha \models \varphi_1$ <i>or</i> $\alpha \models \varphi_2$
$\alpha \models \varphi_1 \rightarrow \varphi_2$	<i>iff</i>	$\alpha \models \varphi_1$ <i>implies</i> $\alpha \models \varphi_2$
$\alpha \models \varphi_1 \leftrightarrow \varphi_2$		

## Semantics II: Satisfaction relation

**Satisfaction relation:**  $\models \subseteq \text{Assign} \times \text{PropForm}$

Instead of  $(\alpha, \varphi) \in \models$  we write  $\alpha \models \varphi$  and say that

- $\alpha$  satisfies  $\varphi$  or
- $\varphi$  holds for  $\alpha$  or
- $\alpha$  is a model of  $\varphi$ .

$\models$  is defined recursively:

$\alpha \models p$	<i>iff</i>	$\alpha(p) = \text{true}$
$\alpha \models \neg \varphi$	<i>iff</i>	$\alpha \not\models \varphi$
$\alpha \models \varphi_1 \wedge \varphi_2$	<i>iff</i>	$\alpha \models \varphi_1$ <i>and</i> $\alpha \models \varphi_2$
$\alpha \models \varphi_1 \vee \varphi_2$	<i>iff</i>	$\alpha \models \varphi_1$ <i>or</i> $\alpha \models \varphi_2$
$\alpha \models \varphi_1 \rightarrow \varphi_2$	<i>iff</i>	$\alpha \models \varphi_1$ <i>implies</i> $\alpha \models \varphi_2$
$\alpha \models \varphi_1 \leftrightarrow \varphi_2$	<i>iff</i>	$\alpha \models \varphi_1$ <i>iff</i> $\alpha \models \varphi_2$

## Semantics II: Satisfaction relation

**Satisfaction relation:**  $\models \subseteq \text{Assign} \times \text{PropForm}$

Instead of  $(\alpha, \varphi) \in \models$  we write  $\alpha \models \varphi$  and say that

- $\alpha$  satisfies  $\varphi$  or
- $\varphi$  holds for  $\alpha$  or
- $\alpha$  is a model of  $\varphi$ .

$\models$  is defined recursively:

$\alpha \models p$	iff	$\alpha(p) = \text{true}$
$\alpha \models \neg\varphi$	iff	$\alpha \not\models \varphi$
$\alpha \models \varphi_1 \wedge \varphi_2$	iff	$\alpha \models \varphi_1$ and $\alpha \models \varphi_2$
$\alpha \models \varphi_1 \vee \varphi_2$	iff	$\alpha \models \varphi_1$ or $\alpha \models \varphi_2$
$\alpha \models \varphi_1 \rightarrow \varphi_2$	iff	$\alpha \models \varphi_1$ implies $\alpha \models \varphi_2$
$\alpha \models \varphi_1 \leftrightarrow \varphi_2$	iff	$\alpha \models \varphi_1$ iff $\alpha \models \varphi_2$

**Note:** More elegant but semantically equivalent to truth tables.



## Semantics II: Example

- Let  $\varphi$  be defined as  $(a \vee (b \rightarrow c))$ .

## Semantics II: Example

- Let  $\varphi$  be defined as  $(a \vee (b \rightarrow c))$ .
- Let  $\alpha : \{a, b, c\} \rightarrow \{0, 1\}$  be an assignment with  $\alpha(a) = 0$ ,  $\alpha(b) = 0$ , and  $\alpha(c) = 1$ .

## Semantics II: Example

- Let  $\varphi$  be defined as  $(a \vee (b \rightarrow c))$ .
- Let  $\alpha : \{a, b, c\} \rightarrow \{0, 1\}$  be an assignment with  $\alpha(a) = 0$ ,  $\alpha(b) = 0$ , and  $\alpha(c) = 1$ .
- Q: Does  $\alpha$  satisfy  $\varphi$ ?

## Semantics II: Example

- Let  $\varphi$  be defined as  $(a \vee (b \rightarrow c))$ .
- Let  $\alpha : \{a, b, c\} \rightarrow \{0, 1\}$  be an assignment with  $\alpha(a) = 0$ ,  $\alpha(b) = 0$ , and  $\alpha(c) = 1$ .
- Q: Does  $\alpha$  satisfy  $\varphi$ ?

A2: Compute with the satisfaction relation:

$$\alpha \models (a \vee (b \rightarrow c))$$

$$\text{iff } \alpha \models a \text{ or } \alpha \models (b \rightarrow c)$$

$$\text{iff } \alpha \models a \text{ or } (\alpha \models b \text{ implies } \alpha \models c)$$

$$\text{iff } 0 \text{ or } (0 \text{ implies } 1)$$

$$\text{iff } 0 \text{ or } 1$$

$$\text{iff } 1$$

- Using the satisfaction relation we can define an **algorithm** for the problem to decide whether an assignment  $\alpha : AP \rightarrow \{0, 1\}$  is a model of a propositional logic formula  $\varphi \in PropForm$ :

## Semantics III: The algorithmic view

- Using the satisfaction relation we can define an **algorithm** for the problem to decide whether an assignment  $\alpha : AP \rightarrow \{0, 1\}$  is a model of a propositional logic formula  $\varphi \in PropForm$ :

```
Eval( $\alpha$ ,  $\varphi$ ) {  
    if  $\varphi \equiv a$  return  $\alpha(a)$ ;  
    if  $\varphi \equiv (\neg\varphi_1)$  return not Eval( $\alpha$ ,  $\varphi_1$ );  
    if  $\varphi \equiv (\varphi_1 \text{ op } \varphi_2)$   
        return Eval( $\alpha$ ,  $\varphi_1$ ) [op] Eval( $\alpha$ ,  $\varphi_2$ );  
}
```

## Semantics III: The algorithmic view

- Using the satisfaction relation we can define an **algorithm** for the problem to decide whether an assignment  $\alpha : AP \rightarrow \{0, 1\}$  is a model of a propositional logic formula  $\varphi \in PropForm$ :

```
Eval( $\alpha$ ,  $\varphi$ ) {  
    if  $\varphi \equiv a$  return  $\alpha(a)$ ;  
    if  $\varphi \equiv (\neg\varphi_1)$  return not Eval( $\alpha$ ,  $\varphi_1$ );  
    if  $\varphi \equiv (\varphi_1 \text{ op } \varphi_2)$   
        return Eval( $\alpha$ ,  $\varphi_1$ )  $\llbracket \text{op} \rrbracket$  Eval( $\alpha$ ,  $\varphi_2$ );  
}
```

- Equivalent to the  $\models$  relation, but from the algorithmic view.

- Recall our example

- $\varphi = (a \vee (b \rightarrow c))$

- $\alpha : \{a, b, c\} \rightarrow \{0, 1\}$  with  $\alpha(a) = 0$ ,  $\alpha(b) = 0$ , and  $\alpha(c) = 1$ .



# Semantics III: Example

- Recall our example

- $\varphi = (a \vee (b \rightarrow c))$

- $\alpha : \{a, b, c\} \rightarrow \{0, 1\}$  with  $\alpha(a) = 0$ ,  $\alpha(b) = 0$ , and  $\alpha(c) = 1$ .

- $Eval(\alpha, \varphi) =$

# Semantics III: Example

- Recall our example

- $\varphi = (a \vee (b \rightarrow c))$

- $\alpha : \{a, b, c\} \rightarrow \{0, 1\}$  with  $\alpha(a) = 0$ ,  $\alpha(b) = 0$ , and  $\alpha(c) = 1$ .

- $Eval(\alpha, \varphi) = Eval(\alpha, a) \text{ or } Eval(\alpha, b \rightarrow c) =$

- Recall our example

- $\varphi = (a \vee (b \rightarrow c))$

- $\alpha : \{a, b, c\} \rightarrow \{0, 1\}$  with  $\alpha(a) = 0$ ,  $\alpha(b) = 0$ , and  $\alpha(c) = 1$ .

- $Eval(\alpha, \varphi) = Eval(\alpha, a) \text{ or } Eval(\alpha, b \rightarrow c) =$   
 $0 \text{ or } (Eval(\alpha, b) \text{ implies } Eval(\alpha, c)) =$

- Recall our example

- $\varphi = (a \vee (b \rightarrow c))$

- $\alpha : \{a, b, c\} \rightarrow \{0, 1\}$  with  $\alpha(a) = 0$ ,  $\alpha(b) = 0$ , and  $\alpha(c) = 1$ .

- $$\begin{aligned} \text{Eval}(\alpha, \varphi) &= \text{Eval}(\alpha, a) \text{ or } \text{Eval}(\alpha, b \rightarrow c) = \\ &0 \text{ or } (\text{Eval}(\alpha, b) \text{ implies } \text{Eval}(\alpha, c)) = \\ &0 \text{ or } (0 \text{ implies } 1) = \end{aligned}$$

- Recall our example

- $\varphi = (a \vee (b \rightarrow c))$

- $\alpha : \{a, b, c\} \rightarrow \{0, 1\}$  with  $\alpha(a) = 0$ ,  $\alpha(b) = 0$ , and  $\alpha(c) = 1$ .

- $$\begin{aligned} \text{Eval}(\alpha, \varphi) &= \text{Eval}(\alpha, a) \text{ or } \text{Eval}(\alpha, b \rightarrow c) = \\ &0 \text{ or } (\text{Eval}(\alpha, b) \text{ implies } \text{Eval}(\alpha, c)) = \\ &0 \text{ or } (0 \text{ implies } 1) = \\ &0 \text{ or } 1 = \end{aligned}$$

- Recall our example

- $\varphi = (a \vee (b \rightarrow c))$

- $\alpha : \{a, b, c\} \rightarrow \{0, 1\}$  with  $\alpha(a) = 0$ ,  $\alpha(b) = 0$ , and  $\alpha(c) = 1$ .

- $$\begin{aligned} \text{Eval}(\alpha, \varphi) &= \text{Eval}(\alpha, a) \text{ or } \text{Eval}(\alpha, b \rightarrow c) = \\ &0 \text{ or } (\text{Eval}(\alpha, b) \text{ implies } \text{Eval}(\alpha, c)) = \\ &0 \text{ or } (0 \text{ implies } 1) = \\ &0 \text{ or } 1 = \\ &1 \end{aligned}$$

- Recall our example

- $\varphi = (a \vee (b \rightarrow c))$

- $\alpha : \{a, b, c\} \rightarrow \{0, 1\}$  with  $\alpha(a) = 0$ ,  $\alpha(b) = 0$ , and  $\alpha(c) = 1$ .

- $$\begin{aligned} \text{Eval}(\alpha, \varphi) &= \text{Eval}(\alpha, a) \text{ or } \text{Eval}(\alpha, b \rightarrow c) = \\ &0 \text{ or } (\text{Eval}(\alpha, b) \text{ implies } \text{Eval}(\alpha, c)) = \\ &0 \text{ or } (0 \text{ implies } 1) = \\ &0 \text{ or } 1 = \\ &1 \end{aligned}$$

- Hence,  $\alpha \models \varphi$ .

# Satisfying assignments

- Intuition: each formula specifies a **set of assignments** satisfying it.



# Satisfying assignments

- Intuition: each formula specifies a **set of assignments** satisfying it.
- Remember: *Assign* denotes the set of all assignments.

# Satisfying assignments

- Intuition: each formula specifies a **set of assignments** satisfying it.
- Remember: *Assign* denotes the set of all assignments.
- Function ***sat* : *PropForm*  $\rightarrow 2^{Assign}$**   
(a formula  $\rightarrow$  set of its satisfying assignments)

# Satisfying assignments

- Intuition: each formula specifies a **set of assignments** satisfying it.
- Remember: *Assign* denotes the set of all assignments.
- Function  **$sat : PropForm \rightarrow 2^{Assign}$**   
(a formula  $\rightarrow$  set of its satisfying assignments)
- Recursive definition:

# Satisfying assignments

- Intuition: each formula specifies a **set of assignments** satisfying it.
- Remember: *Assign* denotes the set of all assignments.
- Function ***sat* : *PropForm*  $\rightarrow 2^{Assign}$**   
(a formula  $\rightarrow$  set of its satisfying assignments)
- Recursive definition:

$$sat(a) \quad =$$

# Satisfying assignments

- Intuition: each formula specifies a **set of assignments** satisfying it.
- Remember: *Assign* denotes the set of all assignments.
- Function ***sat* : PropForm  $\rightarrow 2^{Assign}$**   
(a formula  $\rightarrow$  set of its satisfying assignments)
- Recursive definition:

$$sat(a) = \{\alpha \mid \alpha(a) = 1\}, \quad a \in AP$$

# Satisfying assignments

- Intuition: each formula specifies a **set of assignments** satisfying it.
- Remember: *Assign* denotes the set of all assignments.
- Function ***sat* : PropForm  $\rightarrow$   $2^{Assign}$**   
(a formula  $\rightarrow$  set of its satisfying assignments)
- Recursive definition:

$$\begin{aligned} sat(a) &= \{\alpha \mid \alpha(a) = 1\}, \quad a \in AP \\ sat(\neg\varphi_1) &= \end{aligned}$$

# Satisfying assignments

- Intuition: each formula specifies a **set of assignments** satisfying it.
- Remember: *Assign* denotes the set of all assignments.
- Function ***sat* : PropForm  $\rightarrow 2^{Assign}$**   
(a formula  $\rightarrow$  set of its satisfying assignments)
- Recursive definition:

$$\begin{aligned} \text{sat}(a) &= \{\alpha \mid \alpha(a) = 1\}, \quad a \in AP \\ \text{sat}(\neg\varphi_1) &= \text{Assign} \setminus \text{sat}(\varphi_1) \end{aligned}$$

# Satisfying assignments

- Intuition: each formula specifies a **set of assignments** satisfying it.
- Remember: *Assign* denotes the set of all assignments.
- Function  **$sat : PropForm \rightarrow 2^{Assign}$**   
(a formula  $\rightarrow$  set of its satisfying assignments)
- Recursive definition:

$$\begin{aligned} sat(a) &= \{\alpha \mid \alpha(a) = 1\}, \quad a \in AP \\ sat(\neg\varphi_1) &= Assign \setminus sat(\varphi_1) \\ sat(\varphi_1 \wedge \varphi_2) &= \end{aligned}$$



# Satisfying assignments

- Intuition: each formula specifies a **set of assignments** satisfying it.
- Remember: *Assign* denotes the set of all assignments.
- Function ***sat* : PropForm  $\rightarrow 2^{\text{Assign}}$**   
(a formula  $\rightarrow$  set of its satisfying assignments)
- Recursive definition:

$$\text{sat}(a) = \{\alpha \mid \alpha(a) = 1\}, \quad a \in AP$$

$$\text{sat}(\neg\varphi_1) = \text{Assign} \setminus \text{sat}(\varphi_1)$$

$$\text{sat}(\varphi_1 \wedge \varphi_2) = \text{sat}(\varphi_1) \cap \text{sat}(\varphi_2)$$

# Satisfying assignments

- Intuition: each formula specifies a **set of assignments** satisfying it.
- Remember: *Assign* denotes the set of all assignments.
- Function ***sat* : PropForm  $\rightarrow 2^{Assign}$**   
(a formula  $\rightarrow$  set of its satisfying assignments)
- Recursive definition:

$$sat(a) = \{\alpha \mid \alpha(a) = 1\}, \quad a \in AP$$

$$sat(\neg\varphi_1) = Assign \setminus sat(\varphi_1)$$

$$sat(\varphi_1 \wedge \varphi_2) = sat(\varphi_1) \cap sat(\varphi_2)$$

$$sat(\varphi_1 \vee \varphi_2) =$$

# Satisfying assignments

- Intuition: each formula specifies a **set of assignments** satisfying it.
- Remember: *Assign* denotes the set of all assignments.
- Function  **$sat : PropForm \rightarrow 2^{Assign}$**   
(a formula  $\rightarrow$  set of its satisfying assignments)
- Recursive definition:

$$sat(a) = \{\alpha \mid \alpha(a) = 1\}, \quad a \in AP$$

$$sat(\neg\varphi_1) = Assign \setminus sat(\varphi_1)$$

$$sat(\varphi_1 \wedge \varphi_2) = sat(\varphi_1) \cap sat(\varphi_2)$$

$$sat(\varphi_1 \vee \varphi_2) = sat(\varphi_1) \cup sat(\varphi_2)$$

# Satisfying assignments

- Intuition: each formula specifies a **set of assignments** satisfying it.
- Remember: *Assign* denotes the set of all assignments.
- Function  **$sat : PropForm \rightarrow 2^{Assign}$**   
(a formula  $\rightarrow$  set of its satisfying assignments)
- Recursive definition:

$$\begin{aligned} sat(a) &= \{\alpha \mid \alpha(a) = 1\}, \quad a \in AP \\ sat(\neg\varphi_1) &= Assign \setminus sat(\varphi_1) \\ sat(\varphi_1 \wedge \varphi_2) &= sat(\varphi_1) \cap sat(\varphi_2) \\ sat(\varphi_1 \vee \varphi_2) &= sat(\varphi_1) \cup sat(\varphi_2) \\ sat(\varphi_1 \rightarrow \varphi_2) &= \end{aligned}$$

# Satisfying assignments

- Intuition: each formula specifies a **set of assignments** satisfying it.
- Remember: *Assign* denotes the set of all assignments.
- Function  **$sat : PropForm \rightarrow 2^{Assign}$**   
(a formula  $\rightarrow$  set of its satisfying assignments)
- Recursive definition:

$$sat(a) = \{\alpha \mid \alpha(a) = 1\}, \quad a \in AP$$

$$sat(\neg\varphi_1) = Assign \setminus sat(\varphi_1)$$

$$sat(\varphi_1 \wedge \varphi_2) = sat(\varphi_1) \cap sat(\varphi_2)$$

$$sat(\varphi_1 \vee \varphi_2) = sat(\varphi_1) \cup sat(\varphi_2)$$

$$sat(\varphi_1 \rightarrow \varphi_2) = (Assign \setminus sat(\varphi_1)) \cup sat(\varphi_2)$$

# Satisfying assignments

- Intuition: each formula specifies a **set of assignments** satisfying it.
- Remember: *Assign* denotes the set of all assignments.
- Function  **$sat : PropForm \rightarrow 2^{Assign}$**   
(a formula  $\rightarrow$  set of its satisfying assignments)
- Recursive definition:

$$\begin{aligned} sat(a) &= \{\alpha \mid \alpha(a) = 1\}, \quad a \in AP \\ sat(\neg\varphi_1) &= Assign \setminus sat(\varphi_1) \\ sat(\varphi_1 \wedge \varphi_2) &= sat(\varphi_1) \cap sat(\varphi_2) \\ sat(\varphi_1 \vee \varphi_2) &= sat(\varphi_1) \cup sat(\varphi_2) \\ sat(\varphi_1 \rightarrow \varphi_2) &= (Assign \setminus sat(\varphi_1)) \cup sat(\varphi_2) \end{aligned}$$

- For  $\varphi \in PropForm$  and  $\alpha \in Assign$  it holds that

$$\alpha \models \varphi \quad \text{iff} \quad \alpha \in sat(\varphi)$$

# Satisfying assignments: Example

$$\text{sat}(\textcolor{red}{a} \vee (\textcolor{blue}{b} \rightarrow \textcolor{green}{c})) =$$

# Satisfying assignments: Example

$$\begin{aligned} \text{sat}(\textcolor{red}{a} \vee (\textcolor{blue}{b} \rightarrow \textcolor{green}{c})) &= \\ \textcolor{red}{\text{sat}(\textcolor{red}{a})} \cup \text{sat}(\textcolor{blue}{b} \rightarrow \textcolor{green}{c}) \end{aligned}$$



# Satisfying assignments: Example

$$\text{sat}(a \vee (b \rightarrow c)) =$$

$$\text{sat}(a) \cup \text{sat}(b \rightarrow c) =$$

$$\text{sat}(a) \cup ((\text{Assign} \setminus \text{sat}(b)) \cup \text{sat}(c))$$

# Satisfying assignments: Example

$$\text{sat}(\textcolor{red}{a} \vee (\textcolor{blue}{b} \rightarrow \textcolor{green}{c})) =$$

$$\textcolor{red}{\text{sat}(\textcolor{red}{a})} \cup \text{sat}(\textcolor{blue}{b} \rightarrow \textcolor{green}{c}) =$$

$$\textcolor{red}{\text{sat}(\textcolor{red}{a})} \cup ((\textcolor{blue}{Assign} \setminus \textcolor{blue}{\text{sat}(\textcolor{blue}{b})}) \cup \textcolor{green}{\text{sat}(\textcolor{green}{c})}) =$$

$$\{\alpha \in \textcolor{red}{Assign} \mid \alpha(\textcolor{red}{a}) = 1\} \cup$$

$$\{\alpha \in \textcolor{blue}{Assign} \mid \alpha(\textcolor{blue}{b}) = 0\} \cup$$

$$\{\alpha \in \textcolor{green}{Assign} \mid \alpha(\textcolor{green}{c}) = 1\}$$

# Satisfying assignments: Example

$$\text{sat}(a \vee (b \rightarrow c)) =$$

$$\text{sat}(a) \cup \text{sat}(b \rightarrow c) =$$

$$\text{sat}(a) \cup ((\text{Assign} \setminus \text{sat}(b)) \cup \text{sat}(c)) =$$

$$\{\alpha \in \text{Assign} \mid \alpha(a) = 1\} \cup$$

$$\{\alpha \in \text{Assign} \mid \alpha(b) = 0\} \cup$$

$$\{\alpha \in \text{Assign} \mid \alpha(c) = 1\} =$$

$$\{\alpha \in \text{Assign} \mid \alpha(a) = 1 \text{ or } \alpha(b) = 0 \text{ or } \alpha(c) = 1\}$$

# Short summary for propositional logic

- **Syntax** of propositional formulae  $\varphi \in PropForm$ :

$$\varphi := AP \mid (\neg\varphi) \mid (\varphi \wedge \varphi)$$

- **Semantics:**

- **Assignments**  $\alpha \in Assign$ :

$$\alpha : AP \rightarrow \{0, 1\}$$

$$\alpha \in 2^{AP}$$

$$\alpha \in \{0, 1\}^{AP}$$

- **Satisfaction relation:**

$$\models \subseteq Assign \times PropForm \quad , \quad (\text{e.g., } \alpha \models \varphi)$$

$$\models \subseteq 2^{Assign} \times PropForm \quad , \quad (\text{e.g., } \{\alpha_1, \dots, \alpha_n\} \models \varphi)$$

$$\models \subseteq PropForm \times PropForm, \quad (\text{e.g., } \varphi_1 \models \varphi_2)$$

$$sat : PropForm \rightarrow 2^{Assign} \quad , \quad (\text{e.g., } sat(\varphi))$$

# Propositional logic - Outline

- Syntax of propositional logic
- Semantics of propositional logic
- Satisfiability and validity
- Normal forms
- Enumeration and deduction

# Semantic classification of formulae

- A formula  $\varphi$  is called **valid** if  $\text{sat}(\varphi) = \text{Assign}$ .  
(Also called a **tautology**).

# Semantic classification of formulae

- A formula  $\varphi$  is called **valid** if  $\text{sat}(\varphi) = \text{Assign}$ .  
(Also called a **tautology**).
- A formula  $\varphi$  is called **satisfiable** if  $\text{sat}(\varphi) \neq \emptyset$ .


# Semantic classification of formulae

- A formula  $\varphi$  is called **valid** if  $\text{sat}(\varphi) = \text{Assign}$ .  
(Also called a **tautology**).
- A formula  $\varphi$  is called **satisfiable** if  $\text{sat}(\varphi) \neq \emptyset$ .
- A formula  $\varphi$  is called **unsatisfiable** if  $\text{sat}(\varphi) = \emptyset$ .  
(Also called a **contradiction**).



# Semantic classification of formulae

- A formula  $\varphi$  is called **valid** if  $\text{sat}(\varphi) = \text{Assign.}$   
(Also called a **tautology**).
- A formula  $\varphi$  is called **satisfiable** if  $\text{sat}(\varphi) \neq \emptyset$ .
- A formula  $\varphi$  is called **unsatisfiable** if  $\text{sat}(\varphi) = \emptyset$ .  
(Also called a **contradiction**).



# Some notations

# Some notations

- We can write:
  - $\models \varphi$  when  $\varphi$  is valid

- We can write:
  - $\models \varphi$  when  $\varphi$  is valid
  - $\not\models \varphi$  when  $\varphi$  is not valid

- We can write:
  - $\models \varphi$  when  $\varphi$  is valid
  - $\not\models \varphi$  when  $\varphi$  is not valid
  - $\not\models \neg\varphi$  when  $\varphi$  is

- We can write:
  - $\models \varphi$  when  $\varphi$  is **valid**
  - $\not\models \varphi$  when  $\varphi$  is **not valid**
  - $\not\models \neg \varphi$  when  $\varphi$  is **satisfiable**

- We can write:
  - $\models \varphi$  when  $\varphi$  is **valid**
  - $\not\models \varphi$  when  $\varphi$  is **not valid**
  - $\models \neg \varphi$  when  $\varphi$  is **satisfiable**
  - $\models \neg \varphi$  when  $\varphi$  is

- We can write:
  - $\models \varphi$  when  $\varphi$  is **valid**
  - $\not\models \varphi$  when  $\varphi$  is **not valid**
  - $\models \neg \varphi$  when  $\varphi$  is **satisfiable**
  - $\models \neg \varphi$  when  $\varphi$  is **unsatisfiable**



# Examples

- $(x_1 \wedge x_2) \rightarrow (x_1 \vee x_2)$

# Examples

■  $(x_1 \wedge x_2) \rightarrow (x_1 \vee x_2)$

is valid

# Examples

- $(x_1 \wedge x_2) \rightarrow (x_1 \vee x_2)$

is valid

- $(x_1 \vee x_2) \rightarrow x_1$

# Examples

- $(x_1 \wedge x_2) \rightarrow (x_1 \vee x_2)$

is valid

- $(x_1 \vee x_2) \rightarrow x_1$

is satisfiable

# Examples

- $(x_1 \wedge x_2) \rightarrow (x_1 \vee x_2)$

is **valid**

- $(x_1 \vee x_2) \rightarrow x_1$

is **satisfiable**

- $(x_1 \wedge x_2) \wedge \neg x_1$

# Examples

- $(x_1 \wedge x_2) \rightarrow (x_1 \vee x_2)$

is valid

- $(x_1 \vee x_2) \rightarrow x_1$

is satisfiable

- $(x_1 \wedge x_2) \wedge \neg x_1$

is unsatisfiable

■ Here are some valid formulae:

■  $\models a \wedge 1 \leftrightarrow a$

■  $\models a \wedge 0 \leftrightarrow 0$

- Here are some valid formulae:
  - $\models a \wedge 1 \leftrightarrow a$
  - $\models a \wedge 0 \leftrightarrow 0$
  - $\models \neg\neg a \leftrightarrow a$  (double-negation rule)



- Here are some valid formulae:
  - $\models a \wedge 1 \leftrightarrow a$
  - $\models a \wedge 0 \leftrightarrow 0$
  - $\models \neg\neg a \leftrightarrow a$  (double-negation rule)
  - $\models a \wedge (b \vee c) \leftrightarrow (a \wedge b) \vee (a \wedge c)$

- Here are some valid formulae:

- $\models a \wedge 1 \leftrightarrow a$
- $\models a \wedge 0 \leftrightarrow 0$
- $\models \neg\neg a \leftrightarrow a$  (double-negation rule)
- $\models a \wedge (b \vee c) \leftrightarrow (a \wedge b) \vee (a \wedge c)$

- Some more (De Morgan rules):

- $\models \neg(a \wedge b) \leftrightarrow (\neg a \vee \neg b)$
- $\models \neg(a \vee b) \leftrightarrow (\neg a \wedge \neg b)$

# The satisfiability problem for propositional logic

- The **satisfiability problem** for propositional logic is as follows:

*Given an input propositional formula  $\varphi$ , decide whether  $\varphi$  is satisfiable.*

# The satisfiability problem for propositional logic

- The **satisfiability problem** for propositional logic is as follows:

*Given an input propositional formula  $\varphi$ , decide whether  $\varphi$  is satisfiable.*

- This problem is decidable but **NP-complete**.

# The satisfiability problem for propositional logic

- The **satisfiability problem** for propositional logic is as follows:

*Given an input propositional formula  $\varphi$ , decide whether  $\varphi$  is satisfiable.*

- This problem is decidable but **NP-complete**.
- An algorithm that always terminates for each propositional logic formula with the correct answer is called a **decision procedure** for propositional logic.


# The satisfiability problem for propositional logic

- The **satisfiability problem** for propositional logic is as follows:

*Given an input propositional formula  $\varphi$ , decide whether  $\varphi$  is satisfiable.*

- This problem is decidable but **NP-complete**.
- An algorithm that always terminates for each propositional logic formula with the correct answer is called a **decision procedure** for propositional logic.

**Goal:** Design and implement such a decision procedure:




# The satisfiability problem for propositional logic

- The **satisfiability problem** for propositional logic is as follows:

*Given an input propositional formula  $\varphi$ , decide whether  $\varphi$  is satisfiable.*

- This problem is decidable but **NP-complete**.
- An algorithm that always terminates for each propositional logic formula with the correct answer is called a **decision procedure** for propositional logic.

**Goal:** Design and implement such a decision procedure:



**Note:** A formula  $\varphi$  is valid iff  $\neg\varphi$  is unsatisfiable.

# Propositional logic - Outline

- Syntax of propositional logic
- Semantics of propositional logic
- Satisfiability and validity
- Normal forms
- Enumeration and deduction



# Propositional logic - Outline

- Syntax of propositional logic
- Semantics of propositional logic
- Satisfiability and validity
- Normal forms
- Enumeration and deduction

- Definition: A **literal** is either a variable or a negation of a variable.

- Definition: A **literal** is either a variable or a negation of a variable.
- Example:  $\varphi = \neg(a \vee \neg b)$   
Variables:  $AP(\varphi) = \{a, b\}$   
Literals:  $lit(\varphi) = \{a, \neg b\}$

- Definition: A **literal** is either a variable or a negation of a variable.
- Example:  $\varphi = \neg(a \vee \neg b)$   
Variables:  $AP(\varphi) = \{a, b\}$   
Literals:  $lit(\varphi) = \{a, \neg b\}$
- Note: Equivalent formulae can have different literals.

- Definition: A **literal** is either a variable or a negation of a variable.

- Example:  $\varphi = \neg(a \vee \neg b)$

Variables:  $AP(\varphi) = \{a, b\}$

Literals:  $lit(\varphi) = \{a, \neg b\}$

- Note: Equivalent formulae can have different literals.

Example:  $\varphi' = \neg a \wedge b$

Literals:  $lit(\varphi') = \{\neg a, b\}$

- Definition: a **term** is a conjunction of literals
  - Example:  $(a \wedge \neg b \wedge c)$

- Definition: a **term** is a conjunction of literals
  - Example:  $(a \wedge \neg b \wedge c)$
- Definition: a **clause** is a disjunction of literals
  - Example:  $(a \vee \neg b \vee c)$

# Negation Normal Form (NNF)

- Definition: A formula is in **Negation Normal Form (NNF)** iff
  - (1) it contains only  $\neg$ ,  $\wedge$  and  $\vee$  as connectives and
  - (2) only variables are negated.



# Negation Normal Form (NNF)

- Definition: A formula is in **Negation Normal Form (NNF)** iff
  - (1) it contains only  $\neg$ ,  $\wedge$  and  $\vee$  as connectives and
  - (2) only variables are negated.
- Examples:
  - $\varphi_1 = \neg(a \vee \neg b)$  is **not** in NNF
  - $\varphi_2 = \neg a \wedge b$  is **in** NNF

- Every formula can be converted to NNF in linear time:
  - Eliminate all connectives other than  $\wedge$ ,  $\vee$ ,  $\neg$
  - Use De Morgan and double-negation rules to push negations to operands

- Every formula can be converted to NNF in linear time:
  - Eliminate all connectives other than  $\wedge$ ,  $\vee$ ,  $\neg$
  - Use De Morgan and double-negation rules to push negations to operands
- **Example:**  $\varphi = \neg(a \rightarrow \neg b)$ 
  - Eliminate ' $\rightarrow$ ':  $\varphi = \neg(\neg a \vee \neg b)$

- Every formula can be converted to NNF in linear time:
  - Eliminate all connectives other than  $\wedge$ ,  $\vee$ ,  $\neg$
  - Use De Morgan and double-negation rules to push negations to operands
- **Example:**  $\varphi = \neg(a \rightarrow \neg b)$ 
  - Eliminate ' $\rightarrow$ ':  $\varphi = \neg(\neg a \vee \neg b)$
  - Push negation using De Morgan:  $\varphi = (\neg\neg a \wedge \neg\neg b)$

- Every formula can be converted to NNF in linear time:
  - Eliminate all connectives other than  $\wedge$ ,  $\vee$ ,  $\neg$
  - Use De Morgan and double-negation rules to push negations to operands
- **Example:**  $\varphi = \neg(a \rightarrow \neg b)$ 
  - Eliminate ' $\rightarrow$ ':  $\varphi = \neg(\neg a \vee \neg b)$
  - Push negation using De Morgan:  $\varphi = (\neg\neg a \wedge \neg\neg b)$
  - Use double-negation rule:  $\varphi = (a \wedge b)$

# Disjunctive Normal Form (DNF)

- Definition: A formula is said to be in **Disjunctive Normal Form (DNF)** iff it is a disjunction of terms.

# Disjunctive Normal Form (DNF)

- Definition: A formula is said to be in **Disjunctive Normal Form (DNF)** iff it is a disjunction of terms.
- In other words, it is a formula of the form

$$\bigvee_i \left( \bigwedge_j l_{i,j} \right)$$

where  $l_{i,j}$  is the  $j$ -th literal in the  $i$ -th term.

# Disjunctive Normal Form (DNF)

- Definition: A formula is said to be in **Disjunctive Normal Form (DNF)** iff it is a disjunction of terms.
- In other words, it is a formula of the form

$$\bigvee_i \left( \bigwedge_j l_{i,j} \right)$$

where  $l_{i,j}$  is the  $j$ -th literal in the  $i$ -th term.

- Example:

$$\varphi = (a \wedge \neg b \wedge c) \vee (\neg a \wedge d) \vee (b) \text{ is in DNF}$$



# Disjunctive Normal Form (DNF)

- Definition: A formula is said to be in **Disjunctive Normal Form (DNF)** iff it is a disjunction of terms.
- In other words, it is a formula of the form

$$\bigvee_i \left( \bigwedge_j l_{i,j} \right)$$

where  $l_{i,j}$  is the  $j$ -th literal in the  $i$ -th term.

- Example:

$$\varphi = (a \wedge \neg b \wedge c) \vee (\neg a \wedge d) \vee (b) \text{ is in DNF}$$

- DNF is a special case of NNF.

# Converting to DNF

- Every formula can be converted to DNF in **exponential** time and space:

- 1 Convert to NNF

- 2 Distribute disjunctions following the rule:

$$\models \varphi_1 \wedge (\varphi_2 \vee \varphi_3) \leftrightarrow (\varphi_1 \wedge \varphi_2) \vee (\varphi_1 \wedge \varphi_3)$$

# Converting to DNF

- Every formula can be converted to DNF in **exponential** time and space:

- 1 Convert to NNF

- 2 Distribute disjunctions following the rule:

$$\models \varphi_1 \wedge (\varphi_2 \vee \varphi_3) \leftrightarrow (\varphi_1 \wedge \varphi_2) \vee (\varphi_1 \wedge \varphi_3)$$

- **Example:**

$$\begin{aligned}\varphi &= (a \vee b) \wedge (\neg c \vee d) \\ &= ((a \vee b) \wedge (\neg c)) \vee ((a \vee b) \wedge d) \\ &= (a \wedge \neg c) \vee (b \wedge \neg c) \vee (a \wedge d) \vee (b \wedge d)\end{aligned}$$

# Converting to DNF

- Every formula can be converted to DNF in **exponential** time and space:

- 1 Convert to NNF

- 2 Distribute disjunctions following the rule:

$$\models \varphi_1 \wedge (\varphi_2 \vee \varphi_3) \leftrightarrow (\varphi_1 \wedge \varphi_2) \vee (\varphi_1 \wedge \varphi_3)$$

- **Example:**

$$\begin{aligned}\varphi &= (a \vee b) \wedge (\neg c \vee d) \\ &= ((a \vee b) \wedge (\neg c)) \vee ((a \vee b) \wedge d) \\ &= (a \wedge \neg c) \vee (b \wedge \neg c) \vee (a \wedge d) \vee (b \wedge d)\end{aligned}$$

- Now consider  $\varphi_n = (a_1 \vee b_1) \wedge (a_2 \vee b_2) \wedge \dots \wedge (a_n \vee b_n)$ .
- **Q:** How many clauses will the DNF have?

# Converting to DNF

- Every formula can be converted to DNF in **exponential** time and space:

- 1 Convert to NNF

- 2 Distribute disjunctions following the rule:

$$\models \varphi_1 \wedge (\varphi_2 \vee \varphi_3) \leftrightarrow (\varphi_1 \wedge \varphi_2) \vee (\varphi_1 \wedge \varphi_3)$$

- **Example:**

$$\begin{aligned}\varphi &= (a \vee b) \wedge (\neg c \vee d) \\ &= ((a \vee b) \wedge (\neg c)) \vee ((a \vee b) \wedge d) \\ &= (a \wedge \neg c) \vee (b \wedge \neg c) \vee (a \wedge d) \vee (b \wedge d)\end{aligned}$$

- Now consider  $\varphi_n = (a_1 \vee b_1) \wedge (a_2 \vee b_2) \wedge \dots \wedge (a_n \vee b_n)$ .

- **Q:** How many clauses will the DNF have?

**A:**  $2^n$

- Q: Is the following DNF formula satisfiable?

$$(a_1 \wedge a_2 \wedge \neg a_1) \vee (a_2 \wedge a_1) \vee (a_2 \wedge \neg a_3 \wedge a_3)$$

- Q: Is the following DNF formula satisfiable?

$$(a_1 \wedge a_2 \wedge \neg a_1) \vee (a_2 \wedge a_1) \vee (a_2 \wedge \neg a_3 \wedge a_3)$$

A: Yes, because the term  $a_2 \wedge a_1$  is satisfiable.

- Q: Is the following DNF formula satisfiable?

$$(a_1 \wedge a_2 \wedge \neg a_1) \vee (a_2 \wedge a_1) \vee (a_2 \wedge \neg a_3 \wedge a_3)$$

A: Yes, because the term  $a_2 \wedge a_1$  is satisfiable.

- Q: What is the complexity of the satisfiability check of DNF formulae?



- Q: Is the following DNF formula satisfiable?

$$(a_1 \wedge a_2 \wedge \neg a_1) \vee (a_2 \wedge a_1) \vee (a_2 \wedge \neg a_3 \wedge a_3)$$

A: Yes, because the term  $a_2 \wedge a_1$  is satisfiable.

- Q: What is the complexity of the satisfiability check of DNF formulae?

A: Linear (time and space).

- Q: Is the following DNF formula satisfiable?

$$(a_1 \wedge a_2 \wedge \neg a_1) \vee (a_2 \wedge a_1) \vee (a_2 \wedge \neg a_3 \wedge a_3)$$

A: Yes, because the term  $a_2 \wedge a_1$  is satisfiable.

- Q: What is the complexity of the satisfiability check of DNF formulae?

A: Linear (time and space).

- Q: Can there be any polynomial transformation into DNF?

- Q: Is the following DNF formula satisfiable?

$$(a_1 \wedge a_2 \wedge \neg a_1) \vee (a_2 \wedge a_1) \vee (a_2 \wedge \neg a_3 \wedge a_3)$$

A: Yes, because the term  $a_2 \wedge a_1$  is satisfiable.

- Q: What is the complexity of the satisfiability check of DNF formulae?

A: Linear (time and space).

- Q: Can there be any polynomial transformation into DNF?

- A: No, it would violate the NP-completeness of the problem.

# Conjunctive Normal Form (CNF)

- Definition: A formula is said to be in **Conjunctive Normal Form (CNF)** iff it is a conjunction of clauses.

# Conjunctive Normal Form (CNF)

- Definition: A formula is said to be in **Conjunctive Normal Form (CNF)** iff it is a conjunction of clauses.
- In other words, it is a formula of the form

$$\bigwedge_i \left( \bigvee_j l_{i,j} \right)$$

where  $l_{i,j}$  is the  $j$ -th literal in the  $i$ -th clause.

# Conjunctive Normal Form (CNF)

- Definition: A formula is said to be in **Conjunctive Normal Form (CNF)** iff it is a conjunction of clauses.
- In other words, it is a formula of the form

$$\bigwedge_i \left( \bigvee_j l_{i,j} \right)$$

where  $l_{i,j}$  is the  $j$ -th literal in the  $i$ -th clause.

- Example:

$$\varphi = (a \vee \neg b \vee c) \wedge (\neg a \vee d) \wedge (b) \text{ is in CNF}$$

# Conjunctive Normal Form (CNF)

- Definition: A formula is said to be in **Conjunctive Normal Form (CNF)** iff it is a conjunction of clauses.
- In other words, it is a formula of the form

$$\bigwedge_i \left( \bigvee_j l_{i,j} \right)$$

where  $l_{i,j}$  is the  $j$ -th literal in the  $i$ -th clause.

- Example:

$$\varphi = (a \vee \neg b \vee c) \wedge (\neg a \vee d) \wedge (b) \text{ is in CNF}$$

- Also CNF is a special case of NNF.

- Every formula can be converted to CNF in **exponential** time and space:

- 1 Convert to NNF

- 2 Distribute disjunctions following the rule:

$$\models \varphi_1 \vee (\varphi_2 \wedge \varphi_3) \leftrightarrow (\varphi_1 \vee \varphi_2) \wedge (\varphi_1 \vee \varphi_3)$$



- Every formula can be converted to CNF in **exponential** time and space:

- 1 Convert to NNF

- 2 Distribute disjunctions following the rule:

$$\models \varphi_1 \vee (\varphi_2 \wedge \varphi_3) \leftrightarrow (\varphi_1 \vee \varphi_2) \wedge (\varphi_1 \vee \varphi_3)$$

- Consider the formula  $\varphi = (a_1 \wedge b_1) \vee (a_2 \wedge b_2)$ .

Transformation:  $(a_1 \vee a_2) \wedge (a_1 \vee b_2) \wedge (b_1 \vee a_2) \wedge (b_1 \vee b_2)$

- Every formula can be converted to CNF in **exponential** time and space:

- 1 Convert to NNF

- 2 Distribute disjunctions following the rule:

$$\models \varphi_1 \vee (\varphi_2 \wedge \varphi_3) \leftrightarrow (\varphi_1 \vee \varphi_2) \wedge (\varphi_1 \vee \varphi_3)$$

- Consider the formula  $\varphi = (a_1 \wedge b_1) \vee (a_2 \wedge b_2)$ .

Transformation:  $(a_1 \vee a_2) \wedge (a_1 \vee b_2) \wedge (b_1 \vee a_2) \wedge (b_1 \vee b_2)$

- Now consider  $\varphi_n = (a_1 \wedge b_1) \vee (a_2 \wedge b_2) \vee \dots \vee (a_n \wedge b_n)$ .

Q: How many clauses does the resulting CNF have?

- Every formula can be converted to CNF in **exponential** time and space:

- 1 Convert to NNF

- 2 Distribute disjunctions following the rule:

$$\models \varphi_1 \vee (\varphi_2 \wedge \varphi_3) \leftrightarrow (\varphi_1 \vee \varphi_2) \wedge (\varphi_1 \vee \varphi_3)$$

- Consider the formula  $\varphi = (a_1 \wedge b_1) \vee (a_2 \wedge b_2)$ .

Transformation:  $(a_1 \vee a_2) \wedge (a_1 \vee b_2) \wedge (b_1 \vee a_2) \wedge (b_1 \vee b_2)$

- Now consider  $\varphi_n = (a_1 \wedge b_1) \vee (a_2 \wedge b_2) \vee \dots \vee (a_n \wedge b_n)$ .

Q: How many clauses does the resulting CNF have?

A:  $2^n$

# Converting to CNF: Tseitin's encoding

- Every formula can be converted to CNF in **linear** time and space if new variables are added.
- The original and the converted formulae are **not equivalent** but **equisatisfiable**.  
Two formulae are equisatisfiable if both are, or are not, satisfiable simultaneously.

# Converting to CNF: Tseitin's encoding

- Every formula can be converted to CNF in **linear** time and space if new variables are added.
- The original and the converted formulae are **not equivalent** but **equisatisfiable**.  
Two formulae are equisatisfiable if both are, or are not, satisfiable simultaneously.

- Consider the formula

$$\varphi = (a \rightarrow (b \wedge c))$$


# Converting to CNF: Tseitin's encoding

- Every formula can be converted to CNF in **linear** time and space if new variables are added.
- The original and the converted formulae are **not equivalent** but **equisatisfiable**.  
Two formulae are equisatisfiable if both are, or are not, satisfiable simultaneously.

- Consider the formula

$$\varphi = (a \rightarrow (b \wedge c))$$

Parse tree:



# Converting to CNF: Tseitin's encoding


- Every formula can be converted to CNF in **linear** time and space if new variables are added.
- The original and the converted formulae are **not equivalent** but **equisatisfiable**.  
Two formulae are equisatisfiable if both are, or are not, satisfiable simultaneously.

- Consider the formula

$$\varphi = (a \rightarrow (b \wedge c))$$

- Associate a new auxiliary variable with each gate.

Parse tree:




# Converting to CNF: Tseitin's encoding

- Every formula can be converted to CNF in **linear** time and space if new variables are added.
- The original and the converted formulae are **not equivalent** but **equisatisfiable**.  
Two formulae are equisatisfiable if both are, or are not, satisfiable simultaneously.

- Consider the formula  
$$\varphi = (a \rightarrow (b \wedge c))$$
- Associate a new auxiliary variable with each gate.
- Add constraints that define these new variables.

Parse tree:






# Converting to CNF: Tseitin's encoding

- Every formula can be converted to CNF in **linear** time and space if new variables are added.
- The original and the converted formulae are **not equivalent** but **equisatisfiable**.  
Two formulae are equisatisfiable if both are, or are not, satisfiable simultaneously.

- Consider the formula  
$$\varphi = (a \rightarrow (b \wedge c))$$
- Associate a new auxiliary variable with each gate.
- Add constraints that define these new variables.
- Finally, enforce the root node.

Parse tree:




# Converting to CNF: Tseitin's encoding

- Need to satisfy:

$$(h_1 \leftrightarrow (a \rightarrow h_2)) \wedge$$

$$(h_2 \leftrightarrow (b \wedge c)) \wedge$$

$$(h_1)$$



- Each gate encoding has a CNF representation with 3 or 4 clauses.

- Need to satisfy:

$$(h_1 \leftrightarrow (a \rightarrow h_2)) \wedge (h_2 \leftrightarrow (b \wedge c)) \wedge (h_1)$$

- Need to satisfy:

$$(h_1 \leftrightarrow (a \rightarrow h_2)) \wedge (h_2 \leftrightarrow (b \wedge c)) \wedge (h_1)$$

- First:  $(h_1 \vee a) \wedge (h_1 \vee \neg h_2) \wedge (\neg h_1 \vee \neg a \vee h_2)$

- Need to satisfy:

$$(h_1 \leftrightarrow (a \rightarrow h_2)) \wedge (h_2 \leftrightarrow (b \wedge c)) \wedge (h_1)$$

- First:  $(h_1 \vee a) \wedge (h_1 \vee \neg h_2) \wedge (\neg h_1 \vee \neg a \vee h_2)$
- Second:  $(\neg h_2 \vee b) \wedge (\neg h_2 \vee c) \wedge (h_2 \vee \neg b \vee \neg c)$

- Let's go back to

$$\varphi_n = (x_1 \wedge y_1) \vee (x_2 \wedge y_2) \vee \cdots \vee (x_n \wedge y_n)$$

- Let's go back to

$$\varphi_n = (x_1 \wedge y_1) \vee (x_2 \wedge y_2) \vee \cdots \vee (x_n \wedge y_n)$$

- With Tseitin's encoding we need:

- n auxiliary variables  $h_1, \dots, h_n$ .
- Each adds 3 constraints.
- Top clause:  $(h_1 \vee \cdots \vee h_n)$

- Let's go back to

$$\varphi_n = (x_1 \wedge y_1) \vee (x_2 \wedge y_2) \vee \cdots \vee (x_n \wedge y_n)$$

- With Tseitin's encoding we need:

- $n$  auxiliary variables  $h_1, \dots, h_n$ .
- Each adds 3 constraints.
- Top clause:  $(h_1 \vee \cdots \vee h_n)$

- Hence, we have

- $3n + 1$  clauses, instead of  $2^n$ .
- $3n$  variables rather than  $2n$ .



# Propositional logic - Outline

- Syntax of propositional logic
- Semantics of propositional logic
- Satisfiability and validity
- Normal forms

# Two classes of algorithms for validity

# Two classes of algorithms for validity

- Q: Is  $\varphi$  satisfiable? (Is  $\neg\varphi$  valid?)

# Two classes of algorithms for validity

- **Q**: Is  $\varphi$  satisfiable? (Is  $\neg\varphi$  valid?)
- Complexity: **NP-Complete** (Cook's theorem)

# Two classes of algorithms for validity

- Q: Is  $\varphi$  satisfiable? (Is  $\neg\varphi$  valid?)
- Complexity: **NP-Complete** (Cook's theorem)
- Two classes of algorithms for finding out:

# Two classes of algorithms for validity

- **Q:** Is  $\varphi$  satisfiable? (Is  $\neg\varphi$  valid?)
- Complexity: **NP-Complete** (Cook's theorem)
- Two classes of algorithms for finding out:
  - Enumeration of possible solutions (Truth tables etc.)
  - Deduction

# Two classes of algorithms for validity

- **Q:** Is  $\varphi$  satisfiable? (Is  $\neg\varphi$  valid?)
- Complexity: **NP-Complete** (Cook's theorem)
- Two classes of algorithms for finding out:
  - Enumeration of possible solutions (Truth tables etc.)
  - Deduction
- More generally (beyond propositional logic):

# Two classes of algorithms for validity

- **Q:** Is  $\varphi$  satisfiable? (Is  $\neg\varphi$  valid?)
- Complexity: **NP-Complete** (Cook's theorem)
- Two classes of algorithms for finding out:
  - Enumeration of possible solutions (Truth tables etc.)
  - Deduction
- More generally (beyond propositional logic):
  - **Enumeration** is possible only in some logics.
  - **Deduction** cannot necessarily be fully automated.



# The satisfiability problem

- Given a formula  $\varphi$ , is  $\varphi$  satisfiable?

# The satisfiability problem

- Given a formula  $\varphi$ , is  $\varphi$  satisfiable?

Enumeration the first:

# The satisfiability problem

- Given a formula  $\varphi$ , is  $\varphi$  satisfiable?

Enumeration the first:

```
Boolean SAT( $\varphi$ ){  
    for all  $\alpha \in Assign$   
        if Eval( $\alpha, \varphi$ ) return true;  
    return false;  
}
```

# The satisfiability problem

- Given a formula  $\varphi$ , is  $\varphi$  satisfiable?

Enumeration the first:

```
Boolean SAT( $\varphi$ ){  
    for all  $\alpha \in Assign$   
        if Eval( $\alpha, \varphi$ ) return true;  
    return false;  
}
```

Enumeration the second:

# The satisfiability problem

- Given a formula  $\varphi$ , is  $\varphi$  satisfiable?

Enumeration the first:

```
Boolean SAT( $\varphi$ ){  
    for all  $\alpha \in Assign$   
        if Eval( $\alpha, \varphi$ ) return true;  
    return false;  
}
```

Enumeration the second:

Use substitution to eliminate all variables one by one:

# The satisfiability problem

- Given a formula  $\varphi$ , is  $\varphi$  satisfiable?

Enumeration the first:

```
Boolean SAT( $\varphi$ ){  
    for all  $\alpha \in Assign$   
        if Eval( $\alpha, \varphi$ ) return true;  
    return false;  
}
```

Enumeration the second:

Use substitution to eliminate all variables one by one:

$$\varphi \quad \text{iff} \quad \varphi[0/a] \vee \varphi[1/a]$$

# The satisfiability problem

- Given a formula  $\varphi$ , is  $\varphi$  satisfiable?

Enumeration the first:

```
Boolean SAT( $\varphi$ ) {  
    for all  $\alpha \in Assign$   
        if Eval( $\alpha, \varphi$ ) return true;  
    return false;  
}
```

Enumeration the second:

Use substitution to eliminate all variables one by one:

$$\varphi \quad \text{iff} \quad \varphi[0/a] \vee \varphi[1/a]$$

- Q: What is the difference?

# The satisfiability problem

- Given a formula  $\varphi$ , is  $\varphi$  satisfiable?

Enumeration the first:

```
Boolean SAT( $\varphi$ ) {  
    for all  $\alpha \in \text{Assign}$   
        if Eval( $\alpha$ ,  $\varphi$ ) return true;  
    return false;  
}
```

Enumeration the second:

Use substitution to eliminate all variables one by one:

$$\varphi \quad \text{iff} \quad \varphi[0/a] \vee \varphi[1/a]$$

- Q: What is the difference?  
A: Branching on complete vs. partial assignments.



# Deduction requires axioms and inference rules

## ■ Inference rules:

$$\frac{\textit{Antecedents}}{\textit{Consequents}} \quad (\textit{rule name})$$

Meaning: If all antecedents hold then at least one of the consequents can be derived.

# Deduction requires axioms and inference rules

## ■ Inference rules:

$$\frac{\textit{Antecedents}}{\textit{Consequents}} \quad (\textit{rule name})$$

Meaning: If all antecedents hold then at least one of the consequents can be derived.

## ■ Examples:

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (\textit{Trans})$$

$$\frac{a \rightarrow b \quad a}{b} \quad (\textit{M.P.})$$

- **Axioms** are inference rules with no antecedents, e.g.,

$$\frac{}{a \rightarrow (b \rightarrow a)} \quad (H1)$$

- **Axioms** are inference rules with no antecedents, e.g.,

$$\frac{}{a \rightarrow (b \rightarrow a)} \quad (H1)$$

- A **proof system** consists of a set of axioms and inference rules.

- Let  $\mathcal{H}$  be a proof system.
- $\Gamma \vdash_{\mathcal{H}} \varphi$  means: There is a proof of  $\varphi$  in system  $\mathcal{H}$  whose premises are included in  $\Gamma$
- $\vdash_{\mathcal{H}}$  is called the **provability (derivability) relation**.

# Example

- Let  $\mathcal{H}$  be the proof system comprised of the rules **Trans** and **M.P.** that we saw earlier:

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (\text{Trans})$$

$$\frac{a \rightarrow b \quad a}{b} \quad (\text{M.P.})$$

- Does the following relation hold?

$$a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow e, a \vdash_{\mathcal{H}} e$$

# Deductive proof: Example

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (Trans) \quad \frac{a \rightarrow b \quad a}{b} \quad (M.P.)$$

$$a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow e, a \vdash_{\mathcal{H}} e$$

# Deductive proof: Example

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (Trans) \quad \frac{a \rightarrow b \quad a}{b} \quad (M.P.)$$

$a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow e, a \vdash_{\mathcal{H}} e$

1.  $a \rightarrow b$



# Deductive proof: Example

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (Trans) \quad \frac{a \rightarrow b \quad a}{b} \quad (M.P.)$$

$a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow e, a \vdash_{\mathcal{H}} e$

1.  $a \rightarrow b$  *premise*

# Deductive proof: Example

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (Trans) \quad \frac{a \rightarrow b \quad a}{b} \quad (M.P.)$$

$a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow e, a \vdash_{\mathcal{H}} e$

1.  $a \rightarrow b$  *premise*
2.  $b \rightarrow c$

# Deductive proof: Example

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (Trans) \quad \frac{a \rightarrow b \quad a}{b} \quad (M.P.)$$

$a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow e, a \vdash_{\mathcal{H}} e$

1.  $a \rightarrow b$  *premise*
2.  $b \rightarrow c$  *premise*

# Deductive proof: Example

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (Trans) \quad \frac{a \rightarrow b \quad a}{b} \quad (M.P.)$$

$a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow e, a \vdash_{\mathcal{H}} e$

1.  $a \rightarrow b$  *premise*
2.  $b \rightarrow c$  *premise*
3.  $a \rightarrow c$

# Deductive proof: Example

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (Trans) \quad \frac{a \rightarrow b \quad a}{b} \quad (M.P.)$$

$a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow e, a \vdash_{\mathcal{H}} e$

1.  $a \rightarrow b$  *premise*
2.  $b \rightarrow c$  *premise*
3.  $a \rightarrow c$  1, 2, *Trans*

# Deductive proof: Example

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (Trans) \quad \frac{a \rightarrow b \quad a}{b} \quad (M.P.)$$

$a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow e, a \vdash_{\mathcal{H}} e$

1.  $a \rightarrow b$  *premise*
2.  $b \rightarrow c$  *premise*
3.  $a \rightarrow c$  1, 2, *Trans*
4.  $c \rightarrow d$

# Deductive proof: Example

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (Trans) \quad \frac{a \rightarrow b \quad a}{b} \quad (M.P.)$$

$a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow e, a \vdash_{\mathcal{H}} e$

1.  $a \rightarrow b$  *premise*
2.  $b \rightarrow c$  *premise*
3.  $a \rightarrow c$  1, 2, *Trans*
4.  $c \rightarrow d$  *premise*

# Deductive proof: Example

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (Trans) \quad \frac{a \rightarrow b \quad a}{b} \quad (M.P.)$$

$a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow e, a \vdash_{\mathcal{H}} e$

1.  $a \rightarrow b$  *premise*
2.  $b \rightarrow c$  *premise*
3.  $a \rightarrow c$  1, 2, *Trans*
4.  $c \rightarrow d$  *premise*
5.  $d \rightarrow e$



# Deductive proof: Example

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (Trans) \quad \frac{a \rightarrow b \quad a}{b} \quad (M.P.)$$

$a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow e, a \vdash_{\mathcal{H}} e$

1.  $a \rightarrow b$  *premise*
2.  $b \rightarrow c$  *premise*
3.  $a \rightarrow c$  1, 2, *Trans*
4.  $c \rightarrow d$  *premise*
5.  $d \rightarrow e$  *premise*

# Deductive proof: Example

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (Trans) \quad \frac{a \rightarrow b \quad a}{b} \quad (M.P.)$$

$a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow e, a \vdash_{\mathcal{H}} e$

1.  $a \rightarrow b$  *premise*
2.  $b \rightarrow c$  *premise*
3.  $a \rightarrow c$  1, 2, *Trans*
4.  $c \rightarrow d$  *premise*
5.  $d \rightarrow e$  *premise*
6.  $c \rightarrow e$

# Deductive proof: Example

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (Trans) \quad \frac{a \rightarrow b \quad a}{b} \quad (M.P.)$$

$a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow e, a \vdash_{\mathcal{H}} e$

1.  $a \rightarrow b$  *premise*
2.  $b \rightarrow c$  *premise*
3.  $a \rightarrow c$  1, 2, *Trans*
4.  $c \rightarrow d$  *premise*
5.  $d \rightarrow e$  *premise*
6.  $c \rightarrow e$  4, 5, *Trans*

# Deductive proof: Example

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (Trans) \quad \frac{a \rightarrow b \quad a}{b} \quad (M.P.)$$

$a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow e, a \vdash_{\mathcal{H}} e$

1.  $a \rightarrow b$  *premise*
2.  $b \rightarrow c$  *premise*
3.  $a \rightarrow c$  1, 2, *Trans*
4.  $c \rightarrow d$  *premise*
5.  $d \rightarrow e$  *premise*
6.  $c \rightarrow e$  4, 5, *Trans*
7.  $a \rightarrow e$

# Deductive proof: Example

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (Trans) \quad \frac{a \rightarrow b \quad a}{b} \quad (M.P.)$$

$a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow e, a \vdash_{\mathcal{H}} e$

1.  $a \rightarrow b$  *premise*
2.  $b \rightarrow c$  *premise*
3.  $a \rightarrow c$  1, 2, *Trans*
4.  $c \rightarrow d$  *premise*
5.  $d \rightarrow e$  *premise*
6.  $c \rightarrow e$  4, 5, *Trans*
7.  $a \rightarrow e$  3, 6, *Trans*

# Deductive proof: Example

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (Trans) \quad \frac{a \rightarrow b \quad a}{b} \quad (M.P.)$$

$a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow e, a \vdash_{\mathcal{H}} e$

1.  $a \rightarrow b$  *premise*
2.  $b \rightarrow c$  *premise*
3.  $a \rightarrow c$  1, 2, *Trans*
4.  $c \rightarrow d$  *premise*
5.  $d \rightarrow e$  *premise*
6.  $c \rightarrow e$  4, 5, *Trans*
7.  $a \rightarrow e$  3, 6, *Trans*
8.  $a$

# Deductive proof: Example

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (Trans) \quad \frac{a \rightarrow b \quad a}{b} \quad (M.P.)$$

$a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow e, a \vdash_{\mathcal{H}} e$

1.  $a \rightarrow b$  *premise*
2.  $b \rightarrow c$  *premise*
3.  $a \rightarrow c$  1, 2, *Trans*
4.  $c \rightarrow d$  *premise*
5.  $d \rightarrow e$  *premise*
6.  $c \rightarrow e$  4, 5, *Trans*
7.  $a \rightarrow e$  3, 6, *Trans*
8.  $a$  *premise*

# Deductive proof: Example

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (Trans) \quad \frac{a \rightarrow b \quad a}{b} \quad (M.P.)$$

$a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow e, a \vdash_{\mathcal{H}} e$

1.  $a \rightarrow b$  *premise*
2.  $b \rightarrow c$  *premise*
3.  $a \rightarrow c$  1, 2, *Trans*
4.  $c \rightarrow d$  *premise*
5.  $d \rightarrow e$  *premise*
6.  $c \rightarrow e$  4, 5, *Trans*
7.  $a \rightarrow e$  3, 6, *Trans*
8.  $a$  *premise*
9.  $e$




# Deductive proof: Example

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (Trans) \quad \frac{a \rightarrow b \quad a}{b} \quad (M.P.)$$

$a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow e, a \vdash_{\mathcal{H}} e$

1.  $a \rightarrow b$  *premise*
2.  $b \rightarrow c$  *premise*
3.  $a \rightarrow c$  1, 2, *Trans*
4.  $c \rightarrow d$  *premise*
5.  $d \rightarrow e$  *premise*
6.  $c \rightarrow e$  4, 5, *Trans*
7.  $a \rightarrow e$  3, 6, *Trans*
8.  $a$  *premise*
9.  $e$  7, 8, *M.P.*

# Proof graph



- For a given proof system  $\mathcal{H}$ ,

- For a given proof system  $\mathcal{H}$ ,
  - **Soundness:** Does  $\vdash$  conclude “correct” conclusions from premises?

- For a given proof system  $\mathcal{H}$ ,
  - **Soundness:** Does  $\vdash$  conclude “correct” conclusions from premises?
  - **Completeness:** Can we conclude all true statements with  $\mathcal{H}$ ?

- For a given proof system  $\mathcal{H}$ ,
  - **Soundness**: Does  $\vdash$  conclude “correct” conclusions from premises?
  - **Completeness**: Can we conclude all true statements with  $\mathcal{H}$ ?
- **Correct with respect to what?**

- For a given proof system  $\mathcal{H}$ ,
  - **Soundness:** Does  $\vdash$  conclude “correct” conclusions from premises?
  - **Completeness:** Can we conclude all true statements with  $\mathcal{H}$ ?
- **Correct with respect to what?**

With respect to the semantic definition of the logic. In the case of propositional logic truth tables give us this.

- Let  $\mathcal{H}$  be a proof system

*Soundness of  $\mathcal{H}$  :*



# Soundness and completeness

- Let  $\mathcal{H}$  be a proof system

*Soundness of  $\mathcal{H}$ :*      if  $\vdash_{\mathcal{H}} \varphi$  then  $\models \varphi$

# Soundness and completeness

- Let  $\mathcal{H}$  be a proof system

*Soundness of  $\mathcal{H}$ :*      if  $\vdash_{\mathcal{H}} \varphi$  then  $\models \varphi$

*Completeness of  $\mathcal{H}$ :*

# Soundness and completeness

- Let  $\mathcal{H}$  be a proof system

*Soundness of  $\mathcal{H}$ :*      if  $\vdash_{\mathcal{H}} \varphi$  then  $\models \varphi$

*Completeness of  $\mathcal{H}$ :*    if  $\models \varphi$  then  $\vdash_{\mathcal{H}} \varphi$

# Soundness and completeness

- Let  $\mathcal{H}$  be a proof system

*Soundness of  $\mathcal{H}$ :*      if  $\vdash_{\mathcal{H}} \varphi$  then  $\models \varphi$

*Completeness of  $\mathcal{H}$ :*    if  $\models \varphi$  then  $\vdash_{\mathcal{H}} \varphi$

- How to prove soundness and completeness?

## Example: Hilbert axiom system (H)

- Let H be (M.P.) together with the following axiom schemes:

$$\overline{a \rightarrow (b \rightarrow a)} \quad (H1)$$

$$\overline{((a \rightarrow (b \rightarrow c)) \rightarrow ((a \rightarrow b) \rightarrow (a \rightarrow c)))} \quad (H2)$$

$$\overline{(\neg b \rightarrow \neg a) \rightarrow (a \rightarrow b)} \quad (H3)$$

- H is **sound and complete** for propositional logic.

- To prove soundness of  $H$ , prove the soundness of its axioms and inference rules (easy with truth-tables).

- To prove soundness of H, prove the soundness of its axioms and inference rules (easy with truth-tables).

For example:

$a$	$b$	$a \rightarrow (b \rightarrow a)$
0	0	1
0	1	1
1	0	1
1	1	1

- To prove soundness of  $H$ , prove the soundness of its axioms and inference rules (easy with truth-tables).

For example:

$a$	$b$	$a \rightarrow (b \rightarrow a)$
0	0	1
0	1	1
1	0	1
1	1	1

- Completeness: harder, but possible.



# The resolution proof system

# The resolution proof system

- The **resolution** inference rule for CNF:

$$\frac{(I \vee l_1 \vee l_2 \vee \dots \vee l_n) \quad (\neg I \vee l'_1 \vee \dots \vee l'_m)}{(l_1 \vee \dots \vee l_n \vee l'_1 \vee \dots \vee l'_m)} \text{ Resolution}$$

- **Example:**

$$\frac{(a \vee b) \quad (\neg a \vee c)}{(b \vee c)}$$


- We first see some example proofs, before proving soundness and completeness.

# Proof by resolution

- Let  $\varphi = (a_1 \vee a_3) \wedge (\neg a_1 \vee a_2 \vee a_5) \wedge (\neg a_1 \vee a_4) \wedge (\neg a_1 \vee \neg a_4)$
- We want to prove  $\varphi \rightarrow (a_3)$

# Proof by resolution


- Let  $\varphi = (a_1 \vee a_3) \wedge (\neg a_1 \vee a_2 \vee a_5) \wedge (\neg a_1 \vee a_4) \wedge (\neg a_1 \vee \neg a_4)$
- We want to prove  $\varphi \rightarrow (a_3)$



- Resolution is a sound and complete proof system for CNF.
- If the input formula is unsatisfiable, there exists a proof of the empty clause.

# Example

Let  $\varphi = (a_1 \vee a_3) \wedge (\neg a_1 \vee a_2) \wedge (\neg a_1 \vee a_4) \wedge (\neg a_1 \vee \neg a_4) \wedge (\neg a_3)$ .



# Soundness and completeness of resolution

- Soundness

# Soundness and completeness of resolution

- **Soundness** is straightforward. Just prove by truth table that

$$\models ((\varphi_1 \vee a) \wedge (\varphi_2 \vee \neg a)) \rightarrow (\varphi_1 \vee \varphi_2).$$



# Soundness and completeness of resolution

- **Soundness** is straightforward. Just prove by truth table that

$$\models ((\varphi_1 \vee a) \wedge (\varphi_2 \vee \neg a)) \rightarrow (\varphi_1 \vee \varphi_2).$$

- **Completeness** is a bit more involved.

# Soundness and completeness of resolution

- **Soundness** is straightforward. Just prove by truth table that

$$\models ((\varphi_1 \vee a) \wedge (\varphi_2 \vee \neg a)) \rightarrow (\varphi_1 \vee \varphi_2).$$

- **Completeness** is a bit more involved.

Basic idea: Use resolution for **variable elimination**.

$$\begin{aligned} & (a \vee \varphi_1) \wedge \dots \wedge (a \vee \varphi_n) \wedge \\ & (\neg a \vee \psi_1) \wedge \dots \wedge (\neg a \vee \psi_m) \wedge \\ & \quad R \\ & \Leftrightarrow \\ & (\varphi_1 \vee \psi_1) \wedge \dots \wedge (\varphi_1 \vee \psi_m) \wedge \\ & \quad \dots \\ & (\varphi_n \vee \psi_1) \wedge \dots \wedge (\varphi_n \vee \psi_m) \wedge \\ & \quad R \end{aligned}$$

where  $\varphi_i$  ( $i = 1, \dots, n$ ),  $\psi_j$  ( $j = 1, \dots, m$ ), and  $R$  contains neither  $a$  nor  $\neg a$ .