

Formal Languages and Automata Theory, SS 2020. Homework 7 (due Week 10)

- Design ε -NFAs for the following languages. Try to use ε -transitions to simplify your design.
 - The set of strings consisting of zero or more a 's, followed by zero or more b 's, followed by zero or more c 's.
 - The set of strings that consist of either 01 repeated one or more times or 010 repeated zero or more times.
- Construct the ε -NFAs for the following r.e. Then transform them into DFAs.
 - $a|b|c$
 - $io|ma$
 - $(a|b)b^*$
 - $a^*b|c^*$
 - $(0|1)^*01(0|1)^*$
- Specify the languages represented by the following regular expressions:
 - $(11|0)^*(00|1)^*$;
 - $(1|01|001)^*(\varepsilon|0|00)$;
 - $10|(0|11)0^*1$;
 - $((0|1)(0|1))^*$;
 - $01^*|1$;
 - $((11)^*|101)^*$.
- Build the ε -NFAs that recognize the languages specified at the previous exercise.
- Consider the DFA from Course 8 - slide 20. Minimize it using the Table Filling Algorithm. Show all the steps of the algorithm.
- Consider the following transition table for a DFA:

	0	1
$\rightarrow A$	B	A
B	A	C
C	D	B
$*D$	D	A
E	D	F
F	G	E
G	F	G
H	G	D

Construct the minimum-state equivalent DFA.

7. Minimize the following DFA using state equivalence method:

	0	1
$\rightarrow A$	B	E
B	C	F
$*C$	D	H
D	E	H
E	F	I
$*F$	G	B
G	H	B
H	I	C
$*I$	A	E