


Ficha de producto

Philips - TRUE CIRCLE RC 1xLED20S/830 PSP



Р	19.6 W				
$\Phi_{L\acute{ampara}}$	2000 lm				
Φ _{Luminaria}	1999 lm				
η	99.96 %				
Rendimiento lumínico	102.0 lm/W				
ССТ	3000 K				
CRI	100				



CDL polar

Techo		70	70	50	50	30	70	70	50	50	30
ρ Paredes		50	30	50	30	30	50	30	50	30	30
Suelo		20	20	20	20	20	20	20	20	20	20
Tamaño del local X Y		Mirado en perpendicular al eje de lámpara				Mirado longitudinalmente al eje de lámpara					
2H	2H	18.4	19.7	18.7	19.9	20.1	18.4	19.7	18.7	19.9	20.
	3H	19.7	20.9	20.1	21.2	21.4	19.7	20.9	20.1	21.2	21.
	4H	20.3	21.4	20.7	21.7	22.0	20.3	21.4	20.7	21.7	22.
	6H	20.8	21.8	21.1	22.1	22.4	20.8	21.8	21.1	22.1	22.
	8H	20.9	21.9	21.3	22.2	22.5	20.9	21.9	21.3	22.2	22.
	12H	21.0	22.0	21.4	22.3	22.6	21.0	22.0	21.4	22.3	22.
4H	2H	19.0	20.1	19.3	20.4	20.6	19.0	20.1	19.3	20.4	20.
	3H	20.5	21.5	20.9	21.8	22.1	20.5	21.5	20.9	21.8	22.
	4H	21.3	22.1	21.7	22.5	22.8	21.3	22.1	21.7	22.5	22.
	6H	21.8	22.6	22.3	23.0	23.4	21.8	22.6	22.3	23.0	23.
	8H	22.0	22.7	22.5	23.1	23.5	22.0	22.7	22.5	23.1	23.
	12H	22.2	22.8	22.6	23.2	23.7	22.2	22.8	22.6	23.2	23.
8H	4H	21.5	22.2	22.0	22.6	23.0	21.5	22.2	22.0	22.6	23.
	6H	22.3	22.8	22.7	23.3	23.7	22.3	22.8	22.7	23.3	23.
	8H	22.6	23.1	23.0	23.5	24.0	22.6	23.1	23.0	23.5	24.
	12H	22.8	23.2	23.3	23.7	24.2	22.8	23.2	23.3	23.7	24.
12H	4H	21.6	22.2	22.0	22.6	23.0	21.6	22.2	22.0	22.6	23.
	6H	22.3	22.8	22.8	23.3	23.8	22.3	22.8	22.8	23.3	23.
	8H	22.7	23.1	23.2	23.6	24.1	22.7	23.1	23.2	23.6	24.
Variación de	la posición	del espec	tador para	separacio	ones S ent	re luminar	ias				
S = 1.		+0.1 / -0.2				+0.1 / -0.2					
S = 1.5H +0.2 / -0.4				+0.2 / -0.4							
S = 2.0H +0.4 / -0.8				+0.4 / -0.8							
Tabla estándar BK06					BK06						
Sumando de corrección 5.5					5.5						

Diagrama UGR (SHR: 0.25)

1