RPractical

Merel Camral

2026-11-11

Part A:Basic Operations

```
#A1
v <- seq(from = 5, to = 50, by = 5)
(length(v))
```

```
## [1] 10
```

```
(sum(v))
```

```
## [1] 275
```

```
(mean(v))
```

```
## [1] 27.5
```

```
#A2
w <- rep(c(1, 2, 3), times = 4)
z <- rep(c(1, 2, 3), each = 4)
(w)
```

```
##  [1] 1 2 3 1 2 3 1 2 3 1 2 3
```

```
(z)
```

```
##  [1] 1 1 1 1 2 2 2 2 3 3 3 3
```

```
#A3
(17 %% 5)
```

```
## [1] 2
```

```
(17 %/% 5)
```

```
## [1] 3
```

```
(17 ^ 5)
```

```
## [1] 1419857
```

```
(sqrt(144))
```

```
## [1] 12
```

```
(round(pi, 3))
```

```
## [1] 3.142
```

```
#A4
a <- c(2,4,6,8)
b <- c(1,3,5,7)
```

```
(a + b)
```

```
## [1]  3  7 11 15
```

```
(a * b)
```

```
## [1]  2 12 30 56
```

```
(a > b)
```

```
## [1] TRUE TRUE TRUE TRUE
```

```
(sum (a * b))
```

```
## [1] 100
```

```
#A5
students <- paste("Student", 1:3, sep = "-")
print(students)
```

```
## [1] "Student-1" "Student-2" "Student-3"
```

```
(42)
```

```
## [1] 42
```

```
(42L)
```

```
## [1] 42
```

```
("42")
```

```
## [1] "42"
```

```
(4i)
```

```
## [1] 0+4i
```

```
(TRUE)
```

```
## [1] TRUE
```

Part B: Data Frames and Conditional Statements

```
#B1

students <- data.frame(
  id = 1:8,
  name = c("Alice", "Bruno", "Chen", "Dini", "Elif", "Fazil", "Grace", "Hiro"),
  sex = c("F", "M", "M", "F", "F", "M", "F", "M"),
  section = c("A", "B", "A", "C", "B", "C", "A", "B"),
  midterm = c(78, 85, 92, 67, 74, 88, 95, 58),
  final = c(82, 79, 90, 71, 80, 91, 93, 65),
  attendance = c(85, 88, 100, 72, 90, 85, 98, 60),
  stringsAsFactors = FALSE
)
```

```
#B2
str(students)
```

```
## 'data.frame':    8 obs. of  7 variables:
##  $ id        : int  1 2 3 4 5 6 7 8
##  $ name      : chr  "Alice" "Bruno" "Chen" "Dini" ...
```

```
##  $ sex       : chr  "F" "M" "M" "F" ...
##  $ section   : chr  "A" "B" "A" "C" ...
##  $ midterm   : num  78 85 92 67 74 88 95 58
##  $ final     : num  82 79 90 71 80 91 93 65
##  $ attendance: num  85 88 100 72 90 85 98 60
```

```
dim(students)
```

```
## [1] 8 7
```

```
colnames(students)
```

```
## [1] "id"         "name"       "sex"        "section"    "midterm"
## [6] "final"      "attendance"
```

```
summary(students)
```

```
##        id              name               sex             section     midterm
##  Min.   :1.00   Length   :8   Length   :8   Length   :8   Min.   :58.00
##  1st Qu.:2.75   N.unique :8   N.unique :2   N.unique :3   1st Qu.:72.25
##  Median :4.50   N.blank  :0   N.blank  :0   N.blank  :0   Median :81.50
##  Mean   :4.50   Min.nchar:4   Min.nchar:1   Min.nchar:1   Mean   :79.62
##  3rd Qu.:6.25   Max.nchar:5   Max.nchar:1   Max.nchar:1   3rd Qu.:89.00
##  Max.   :8.00                                            Max.   :95.00
##      final         attendance
##  Min.   :65.00   Min.   : 60.00
##  1st Qu.:77.00   1st Qu.: 81.75
##  Median :81.00   Median : 86.50
##  Mean   :81.38   Mean   : 84.75
##  3rd Qu.:90.25   3rd Qu.: 92.00
##  Max.   :93.00   Max.   :100.00
```

```
#B3
students$average <- round((students$midterm + students$final) / 2, 1)
```

```
#B4
students$passed <- students$average >= 70 & students$attendance >= 75
```

```
#B5
students$standing <- ifelse(students$average >= 90, "Honors",
                            ifelse(students$average >= 75, "Good", "Needs Support"))
```

```
#B6
classify <- function(score) {
  if (score >= 85) {
    return("Distinction")
  } else if (score >= 70) {
    return("Merit")
  } else if (score >= 50) {
    return("Pass")
  } else {
    return("Fail")
  }
}

test_scores <- c(90, 75, 55, 40)
result <- sapply(test_scores, classify)
(result)
```

```
## [1] "Distinction" "Merit"       "Pass"        "Fail"
```

Part C: rbind() and cbind()

```
#C1
new_students <- data.frame(
id = c(9, 10),
name = c("Ines", "Jamal"),
sex = c("F", "M"),
section = c("C", "A"),
midterm = c(81, 70),
final = c(84, 68),
attendance = c(92, 80),
stringsAsFactors = FALSE
)
new_students$average <- round((new_students$midterm + new_students$final) / 2, 1)
new_students$passed <- new_students$average >= 70 & new_students$attendance >= 75
new_students$standing <- ifelse(new_students$average >= 90, "Honors",
  ifelse(new_students$average >= 75, "Good", "Needs Support"))

students_all <- rbind(students, new_students)
```

```
#C2
quiz <- c(8, 7, 10, 6, 7, 9, 10, 5, 8, 6)

students_all <- cbind(students_all, quiz)
class(students_all)
```

```
## [1] "data.frame"
```

```
#C3
m <- cbind(midterm = students_all$midterm, final = students_all$final)
m <- rbind(m, mean = colMeans(m))
```

```
#C4
#Explaination
#If you try to combine data frames with different column names using rbind(), the program will crash wi

tryCatch(rbind(students, bad), error = function(e) {
message("rbind failed: ", conditionMessage(e));
NULL
})
```

```
## rbind failed: object 'bad' not found
```

```
## NULL
```

Part D: Subsetting

```
#D1
students_all$name
```

```
##  [1] "Alice" "Bruno" "Chen"  "Dini"  "Elif"  "Fazil" "Grace" "Hiro"  "Ines"
## [10] "Jamal"
```

```
students_all[["name"]]
```

```
##  [1] "Alice" "Bruno" "Chen"  "Dini"  "Elif"  "Fazil" "Grace" "Hiro"  "Ines"
## [10] "Jamal"
```

```r
students_all[, "name"]
```

```
##  [1] "Alice" "Bruno" "Chen"  "Dini"  "Elif"  "Fazil" "Grace" "Hiro"  "Ines"
## [10] "Jamal"
```

```r
#D2
students_all[2:5, c("name", "midterm", "final")]
```

```
##    name midterm final
## 2 Bruno      85    79
## 3  Chen      92    90
## 4  Dini      67    71
## 5  Elif      74    80
```

```r
#D3
students_all[students_all$attendance > 90, ]
```

```
##   id  name sex section midterm final attendance average passed standing quiz
## 3  3  Chen   M       A      92    90        100    91.0   TRUE   Honors   10
## 7  7 Grace   F       A      95    93         98    94.0   TRUE   Honors   10
## 9  9  Ines   F       C      81    84         92    82.5   TRUE     Good    8
```

```r
#D4
subset(students_all,
sex == "F" & (section == "A" | section == "C") & final >= 75,
select = c(name, section, final))
```

```
##    name section final
## 1 Alice       A    82
## 7 Grace       A    93
## 9  Ines       C    84
```

```r
#D5
students_all$name[which.max(students_all$average)]
```

```
## [1] "Grace"
```

```r
students_all$name[which.min(students_all$average)]
```

```
## [1] "Hiro"
```

```r
#D6
sorted_students <- students_all[order(-students_all$average), ]
head(sorted_students, 3)
```

```
##   id  name sex section midterm final attendance average passed standing quiz
## 7  7 Grace   F       A      95    93         98    94.0   TRUE   Honors   10
## 3  3  Chen   M       A      92    90        100    91.0   TRUE   Honors   10
## 6  6 Fazil   M       C      88    91         85    89.5   TRUE     Good    9
```

Part E: Basic Factors

```r
#E1
students_all$section <- factor(students_all$section)
students_all$sex <- factor(students_all$sex)

levels(students_all$section)
```

```
## [1] "A" "B" "C"
```

```r
levels(students_all$sex)
```

```
## [1] "F" "M"
```

```r
#E2
table(students_all$sex, students_all$section)
```

```
##
##     A B C
##   F 2 1 2
##   M 2 2 1
```

```r
# What is the output?
# The output is a two-way frequency matrix (contingency table) showing the cross-tabulated. Counts of s
```

```r
#E3
as.integer(students_all$sex)
```

```
##  [1] 1 2 2 1 1 2 1 2 1 2
```

```r
# Comment explanation:
# The integers represent the underlying numerical indices used by R to store factor levels. Since facto
```

```r
#E4
sex_label <- factor(students_all$sex, levels = c("F", "M"), labels = c("Female", "Male"))
students_all$sex_label <- sex_label
levels(students_all$sex_label)
```

```
## [1] "Female" "Male"
```

```r
#E5
summary(students_all$sex_label)
```

```
## Female   Male
##      5      5
```

```r
mean(students_all$average[students_all$sex_label == "Female"])
```

```
## [1] 80.5
```

```r
mean(students_all$average[students_all$sex_label == "Male"])
```

```
## [1] 78.6
```