

Introduction

(<https://livecode.com/docs/9-5-0/introduction/>)

Lessons

(<https://livecode.com/docs/9-5-0/lessons/>)

FAQ (<https://livecode.com/docs/9-5-0/faq/>)

Language

(<https://livecode.com/docs/9-5-0/language/>)

Education Curriculum

(<https://livecode.com/docs/9-5-0/education-curriculum/>)

Deployment

(<https://livecode.com/docs/9-5-0/deployment/>)

Components

(<https://livecode.com/docs/9-5-0/components/>)

Tooling

(<https://livecode.com/docs/9-5-0/tooling/>)

Core Concepts

(<https://livecode.com/docs/9-5-0/core-concepts/>)

Programming A User Interface

(<https://livecode.com/docs/9-5-0/core-concepts/programming-a-user-interface/>)

Error Handling And Debugging

(<https://livecode.com/docs/9-5-0/core-concepts/error-handling-and-debugging/>)

Processing Text And Data



Improve this documentation

([https://github.com/livecode/livecode-ide/blob/develop-](https://github.com/livecode/livecode-ide/blob/develop-9.5/Documentation/guides/Working%20with%20Media.md)

[9.5/Documentation/guides/Working%20with%20Media.md](https://github.com/livecode/livecode-ide/blob/develop-9.5/Documentation/guides/Working%20with%20Media.md))

# Working with Media

## Introduction

One of the most popular uses for LiveCode is to create full blown multimedia applications. Even if you aren't creating a traditional multimedia application, many applications require a compelling user interface.

This chapter details LiveCode's media support. We discuss the image features and capabilities: how to import and export images in a variety of formats, how to manipulate images within LiveCode, working with masks, the clipboard and screen capture, right through to animated GIFs. We detail the vector graphic features and explain how to manipulate

Introductio

Bitmap

Images

Working  
with Vector  
Graphics

Working  
with Video

Working  
with  
Sounds

Working  
with Visual  
Transition  
Effects

Creating  
Custom  
Skins

(<https://livecode.com/docs/9-5-0/core-concepts/processing-text-and-data/>)

Working With Databases

(<https://livecode.com/docs/9-5-0/core-concepts/working-with-databases/>)

Working With Media

(<https://livecode.com/docs/9-5-0/core-concepts/working-with-media/>)

Printing In LiveCode

(<https://livecode.com/docs/9-5-0/core-concepts/printing-in-livecode/>)

Transferring Information

(<https://livecode.com/docs/9-5-0/core-concepts/transferring-information/>)

Language Comparison

(<https://livecode.com/docs/9-5-0/language-comparison/>)

Extending LiveCode

(<https://livecode.com/docs/9-5-0/extending-livecode/>)

Whats New?

(<https://livecode.com/docs/9-5-0/whats-new/>)

vector graphics by script. We then cover the video and audio feature set. Then we show you how to create custom themed buttons. Finally we given an overview of the support for visual transition effects.

## Bitmap Images

LiveCode supports a wide variety of image formats, including the popular PNG and JPEG formats. PNG images are space efficient and have full support for alpha channels. JPEG images are good for displaying photos. For more details see the table below.

Format	Export	Mask	Comments
PNG	Yes	Yes, 1-bit or alpha channels	Supports gamma adjustment, supports alpha channels, supports interlacing
JPEG	Yes	No	Supports progressive JPEGs; lossy compression. Export allows you to set the level of compression

<b>GIF</b>	Yes	1-bit	GIF87a and GIF89a; supports animation; supports interlaced GIFs; maximum 256 colors
<b>BMP</b>	No	No	Uncompressed
<b>PBM</b>	Yes	No	1-bit (black and white)
<b>PGM</b>	No	No	Grayscale
<b>PPM</b>	No	No	
<b>XBM</b>	No	No	
<b>XPM</b>	No	No	1-bit (black and white)
<b>XWD</b>	No	No	
<b>PICT</b>	No	No	uncompressed

As you can see from the table above, a number of the supported image formats can also be exported by LiveCode.

You can modify images using LiveCode's paint tools, or manipulate the binary data by script or using an external.

You can create images from any of LiveCode's native objects, including buttons, fields and graphics. These can then be exported in a number of formats. You can copy images from the clipboard or export images to the clipboard.

LiveCode can capture a portion of the screen, or the entire screen.

## Importing Images

To import an image, choose File -> Import As Control -> Image File. Select the image file you want to import. This will import the image file into a new image object on the current card. This is equivalent to executing the **import paint** command in the Message Box.

**Note:** If you want to reuse an image throughout your application, for example as part of a custom skin for your application, create a substack and import all your images into that. You can then reference them throughout your stack file. For more information, see the section Creating Custom Skins, below.

## Importing Referenced Images

To reference an image file on disk choose File -> New Referenced Control -> Image File. This creates an image object on the current card and sets its **fileName** property to the path of the image file you selected.

Referenced images do not expand the size of your stack and are only loaded from disk into memory when you navigate to the current card or otherwise display them on screen. Referenced images are ideal where you want to update the image in an image editor and see the changes in LiveCode without having to re-import.

You may wish to consider creating a folder next to your stack file to contain image files then using the Inspector to modify the file path to the image to be a referenced path. This allows you to move the stack and folder of images together onto a different system. for more information on referenced file paths, see the section *File Name Specifications and Paths*.

You can use the standalone builder to copy referenced images into a directory

(updating each image's **fileName** property) or to copy referenced images into your stack. For more information see the chapter *Deploying your Application*.

**Important:** You cannot use the paint tools or manipulate the binary data of referenced images. You must import them first. If you want to modify the original file, you can make changes then export the image – see below for more details.

## Import using Screen Capture

To import an image by capturing a portion of the screen, choose File -> Import As Control -> Snapshot. Select the region of the screen you want to import.

To take a screen capture by script, use the **import snapshot** command. To specify a section of the screen to import from without displaying the crosshairs use **import snapshot from rect:**

```
import snapshot
from
100,100,200,200
```

This will create an image object on the current card from the rectangular area specified.

### Creating Images

To create an image, drag an image object from the Tools palette to your stack. You may now paint on the image using the paint tools, set the `fileName` reference to an image or manipulate the binary data of the image.

### Using the Paint Tools

To access the paint tools, press the fold out triangle at the bottom right of the Tools palette.




Figure 85 – The Graphic Tools

Tool	Usage	Keyboard Modifiers
------	-------	--------------------

Select	Drag to select a rectangular area of an image	Shift constraints to a square; command / control duplicates selection
Bucket	Fills shapes with color. Will fill any pixel connected to the pixel you click with the brush color	Control-click to fill with transparency
Spray can	Draw an airbrushed color using the brush shape	Control-click to spray with transparency
Eraser	Remove color from an area leaving it transparent. Uses the brush shape	
Polygon	Draw polygon shape (hold down on the rectangle shape to select this shape)	Shift constraints lines angles to multiples of 22.5°; control creates transparency
Line	Draw a straight line	Shift constraints lines angles



		to multiples of 22.5°; control creates transparency
Freehand	Draw a freehand curve (hold down on the line shape to select this shape). If the filled option is chosen the beginning and end of the curve are joined automatically when you finish drawing	Alt / option prevents drawing line border; control creates transparency
Pencil	Draw a single-pixel- width freehand line	Control creates transparency
Brush	Draw brush strokes using the brush shape	Control creates transparency; command click to magnify
Fill (brush) color	Select a color to fill shapes or use with the brush tools	

Line color	Select a color to draw lines or use with the pencil tool
Brush shape	Choose a brush shape for use with the brush, eraser and airbrush tools

To magnify an image, right click it with the pointer tool and choose Magnify from the menu.

When you edit an image, it will be recompressed into the format specified by the **paintCompression** global property.

## Scripting with the Paint Tools

Painting by script can be useful if you want the user to be able to see each paint action. If you want to manipulate the data of an image more efficiently off screen, see the next section.

To control the paint tools by script, create an image then choose the paint tool you want to use. Set the

appropriate brush, pattern or line size then use the drag command to paint.

The following example creates an image, chooses the brush tool, selects a small circular brush shape, selects a red color, then draws a line:

```
-- set the size
of the image
set the rect of the
templateImage to
100,100,400,400
create image
choose brush tool
set the brush to 8
set the brushColor
to red -- could
use an RGB
triplet here
set the dragSpeed
to 20 -- very slow
drag from 120,120
to 300,300
```

For more information, see the entries for the **templateImage**, **tool**, **brush**, **brushColor**, **brushPattern**, **dragSpeed**, **penColor** and **penPattern** in the *LiveCode Dictionary*.

You may reduce the size of an image using the **crop** command.

You may rotate an image using the **rotate** command.

To adjust the quality of the scaling algorithm used when scaling an image, set the **resizeQuality** property before setting the image's rect.

## Manipulating Binary Image Data

To manipulate the binary data of an image, use the image's **imageData** property. This property returns the color and transparency value of each pixel in the image in a consistent format regardless of the format the image is saved in. The **imageData** is stored as binary, with each pixel represented by 4 bytes. To convert it to and from RGB values use the **byteToNum** and **numToByte** functions.

For example, the numeric value of the red, green and blue channels respectively for the tenth pixel are given by the expressions:

```
charToNum(char (4 *  
9 + 2 of the  
imageData of image  
<image>)  
charToNum(char (4 *  
9 + 3 of the  
imageData of image  
<image>)  
charToNum(char (4 *  
9 + 4 of the  
imageData of image  
<image>)
```

To manipulate the binary data of an image using an external, use the **imagePixMapID** property.

When you set the **imageData** of an image the image will be recompressed into the format specified by the **paintCompression** global property.

## Rendering an Image from Objects

Use the **import snapshot** command to create an image from objects or a region of a stack. Instead of specifying a rectangle in global coordinates (as described above) specify a stack or object.

**Note:** Unlike screen capturing, the stack or object you specify to import an image from does not need to be displayed on screen. You can create a layout off screen in an invisible stack then render it into an image.

To import a snapshot of a region of a stack:

```
import snapshot  
from  
100,100,200,200 of  
stack "Layout"
```

To import a snapshot of an object:

```
import snapshot  
from button 5 of  
stack "objects"
```

The import snapshot command creates a new image in the current **defaultStack**. The image is encoded using the current **paintCompression** format.

To save this snapshot directly to a file instead of creating an image, use the export snapshot command:

```
export snapshot  
from the  
selectedObject to  
file "snap.jpg" as  
JPEG
```

## Exporting Images

To export an image in the current format that it is stored in, put it into a binary file using the URL commands. The following example prompts the user to select a file then export the image into it:

```
ask file "Select a  
file:"  
put image "picture"  
into URL  
("binfile:" & it)
```

To export an image in a different format, use the **export** command.

```
export image  
"picture" to file  
"picture.png" as  
PNG
```

You may also export an image to a variable. See the **export** command in the *LiveCode Dictionary* for more information.

## Copying and Pasting Images

To copy an image internally without using the system clipboard, simply put it into a variable or into another image.

```
put image 1 into  
image 2
```

To recompress the image in a different format, use the **export** command to export it to a variable then put that variable into an image.

To copy an image to the clipboard, use the **copy** command.

```
copy image 1
```

To paste an image from the clipboard, use the **paste** command.



To transfer the binary data of an image to and from the clipboard get and set the **clipBoardData["image"]** property. See the **clipBoardData** entry in the *LiveCode Dictionary* for more information.

## Working with Animated GIFs

You can import an animated GIF image in the same way you import other images.

Set the **repeatCount** property to specify how often to play the animation. Setting the **repeatCount** to 0 pauses the animation and setting it to -1 causes it to repeat forever.

To change the current frame set the **currentFrame** property.

**Note:** If you use an animated GIF as a button icon, it will play simultaneously in each button it is used for.

## Working with Vector Graphics

In addition to bitmap graphics, LiveCode also supports vector graphics. You can create vector graphics using the graphics tools, or by script. You can manipulate them interactively in the IDE or by script. You can relayer them, export a description of them or convert them to bitmap format.

**Tip:** Animation Engine is a 3<sup>rd</sup> party library that includes a set of functions for programming interactive graphic animations. See the Related Software section of our web site for more information.

## The Vector Graphic Tools

To see the graphic tools, unfold the triangle at the bottom right of the tools palette. The graphics tools are located above the paint tools on the tools palette. The graphic tools operate in the same way as the paint tools, except that each time

you draw a shape a new graphic object is created. Unlike paint graphics, you can resize and adjust graphic objects after you have created them. For more information on the individual shapes, see the section on *Paint Tools*, above.

## Creating Graphics by Script

To create graphics by script, set properties of the **templateGraphic** then use the **create graphic** command. For more information on template objects, see the section *Creating objects off screen using the template objects* in Chapter 7.

## Manipulating graphics by script

Because each graphic is an individual object, you manipulate its appearance by setting properties rather than using the drag commands (as with the paint tools, above). You can control all properties of the graphic object by script including the rectangle, line and fill properties. You can change a

graphic from one type to another (e.g. a rectangle to an oval) by setting its **style** property.

The polygon style of graphic has a **points** property which allows you to set the individual points of a line.

Simple motion can be applied using the **move** command. For example, to move a graphic 100 pixels to the right asynchronously:

```
move graphic 1  
relative 100,0  
without waiting
```

For more information, see the **move** command in the LiveCode Dictionary.

To program a more complex animation effect, calculate the changes to the points or rectangles and set these values using timer based messaging. The following example scales a graphic named "rectangle" down by 100 pixels over the course of 1 second.

```
local sCount
on mouseUp
    put 0 into
    sCount
    scaleGraphic
end mouseUp

on scaleGraphic
    add 1 to sCount
    if sCount > 100
then exit
    scaleGraphic
    get the rect of
    graphic "rectangle"
    add 1 to item 1
    of it
    add 1 to item 2
    of it
    subtract 1
    from item 3 of it
    subtract 1
    from item 4 of it
    set the rect of
    graphic "rectangle"
    to it
    send
    "scaleGraphic" to
    me in 10
    milliseconds
end scaleGraphic
```

See the section on *Timer based messaging* for more information on using timers.

## Working with Video

LiveCode supports playback of video with the player object. On Windows *DirectShow* is supported. Media format support in the new Windows player control depends on which codecs are installed. A list of the file

formats and compression types available as standard ([https://msdn.microsoft.com/en-us/library/ms787745\(VS.85\).aspx](https://msdn.microsoft.com/en-us/library/ms787745(VS.85).aspx)) on Windows is available in the MSDN documentation

On Mac OS X systems, the player object uses the AV Foundation framework.

On Linux Systems, the player object can play back video using *mplayer*. There are some functionality limitations: the **alwaysBuffer**, **startTime**, **endTime**, **showController** and **playSelection** properties have no effect, and **play step forward/play step back** do not work reliably.

In addition to these features, LiveCode has built-in support for the animated GIF format. Animated GIF files can be played back without 3<sup>rd</sup> party software. See above for more information. Other formats supported by plug-ins in web browsers can be played back using *revBrowser* (e.g. Flash). See the topic on *revBrowser* for more information.

## The Player Object

Use the player object to play and interact with video and audio. To create a player object, drag one onto your stack from the Tools palette. To select a movie file to play, open the Inspector for the player object and select a file to use as the source. Doing this sets the player's **fileName** property.

To *stream* a movie from an Internet server, set the **fileName** property to the URL address of the stream.

To play a player, use the **start** and **stop** commands.

```
start player 1  
stop player 1
```

The following table describes commonly used player properties:

Property Name	Function	Example
<b>alwaysBuffer</b>	Forces the player to be buffered, allowing objects to be drawn on top and the current frame to	set the <code>alwaysBuffer</code> of player 1 to true

	be printed	
<b>showController</b>	Shows or hides the player controller	set the showController player 1 to fa
<b>currentTime</b>	Sets the current frame	set the currentTime of player 1 to 10
<b>duration &amp; timeScale</b>	The duration of the movie and the number of intervals per second of a movie	put (the durat of me/the timeScale of m into tRunTime
<b>currentTimeChanged</b>	Message sent when the current frame changes	on currentTimeCha pInterval
		put pInterval field "Time Co
		end currentTimeCha
<b>startTime</b>	The start time of the selection	set the startT of player 1 to
<b>endTime</b>	The end time of the selection	set the endTime of player 1 to 1000
<b>showSelection</b>	Show the selection in the	set the showSelection player 1 to tr



	controller	
<b>playSelection</b>	Play only the selection	set the playSelection of player 1 to tr
<b>playRate</b>	The speed to play the movie. Set this to -1 to play backwards	set the playRa of player 1 to
<b>looping</b>	Causes playback to loop	set the loopin player 1 to tr
<b>playLoudness</b>	Set the volume	set the playLoudNess o player 1 to 50
<b>tracks</b>	List of tracks within the movie	put the tracks player 1 into tTracksList
<b>enabledTracks</b>	Enable or disable tracks	Set the enabledTracks player 1 to 3
<b>callbacks</b>	A list of messages to be sent when the movie reaches specified time points	set the callba of player 1 to "1000, nextSce

The following properties can be used to control a QTVR movie: **pan**, **tilt**, **zoom**,

**currentNode**,  
**nodeChanged**, **hotspots**,  
and **hotSpotClicked**.

For more information on any  
of these terms, see the  
*LiveCode Dictionary*.

## Working with Sounds

In addition to playing back  
sound in a wide variety of  
formats using the player  
object, LiveCode has in-built  
support for playback of WAV,  
AIFF and AU format audio  
clips.

**Note:** We recommend  
you use the player  
object for playing audio  
as it supports a wide  
range of formats and  
compression types.  
Use the audio clip when  
you need basic audio  
playback on systems  
that do not have any of  
the 3<sup>rd</sup> party libraries  
supported by the player  
object installed.

### Importing an Audio Clip

To import an audioClip  
choose File -> Import as  
Control -> Audio File. This  
will import the selected audio  
file into the current stack as  
an audioClip.

## Playing an Audio Clip

To play an audio clip:

```
play audioClip 1
```

To stop playing

```
play stop
```

To set the volume:

```
-- sets the  
volume to 50%  
set the  
playLoudness of  
audioclip 1 to 50
```

## Working with Visual Transition Effects

LiveCode supports visual  
transition effects when  
changing card or hiding and  
showing objects. There are  
three types of effect support:  
built-in effects which work on

all platforms, QuickTime effects which work on older Mac OS X systems and Core Image effects which work on Mac OS X.

Use the **visual effect** command to display a visual effect. To go to the next card with a dissolve transition effect:

```
visual effect  
dissolve slow go  
next card
```

To make changes to objects on the screen with a visual effect (e.g. hide, show or move them), first lock the screen, then make the changes, then unlock the screen:

```
lock screen  
hide image 1  
show image 3  
unlock screen with  
visual effect  
"wipe right"
```

To choose a QuickTime effect using the effect chooser dialog use:

```
answer effect
-- store the
visual effect as
a custom property
set the cEffect of
this stack to it
```

Then:

```
visual effect (the
cEffect of this
stack)
go next card
```

For more information on visual effects, see the **visual effect** command in the *LiveCode Dictionary*. To try out the different visual effects available in an interactive format see the Multimedia Workshop (<http://www.runrev.com/developers/exploring-revolution/multimedia/>)

## Creating Custom Skins

In addition to its support for system native controls, LiveCode allows you the ability to create an entirely custom look, or skin, for your application. All of the built-in elements can be replaced with themed graphics

allowing you to create rich multimedia. For example, LiveCode buttons support "icons" of unlimited size which can be used to replace the native appearance of a button entirely. Windows can be irregularly shaped and even contain holes and alpha mask (variable) transparency. All of LiveCode's objects support a variety of transfer modes or inks. Stacks can take over the entire screen or be displayed with a backdrop.

## Custom Themed Buttons

To create a custom button, first create a regular button. Open the *Inspector* for the button and set its style to *Transparent*. Turn off the *Show Name* property. Next, switch to the *Icons & Border* pane in the *Inspector*. Turn off the *Hilite Border* property. You can now select any image you have imported to use as an icon for the button. To set the mouse down state, set the *hilite* icon. To set the roll over state set the *hover* icon.

A button "icon" may be an image of any size in LiveCode, allowing a completely custom look.

**Tip:** To use the same set of images as icons throughout your stack file, create a substack and import all your theme images into it. Set the ID property of each image to a high value (between 10,000 and 100,000) so that it will be unique. You can now reference that image anywhere in your application. If you want to change theme, you only need to replace that image with another image and give it the same ID.

Any object in LiveCode can behave like a button. For example, if you want to create a graphic that responds when a user clicks on it, create the graphic and add a **mouseUp** handler to it, in the same way you would with a button.

## Irregular Windows

To create an irregularly shaped window, import or create an image that has a transparency mask. Then use the *Stack Inspector* to choose that image as the stack's *Shape*. To change the shape by script, set the **windowShape** property.

Many modern window managers support alpha blended windows (variable degrees of transparency). To create a window with an alpha channel, import a PNG that contains an alpha channel and set the **windowShape** to this image.

## Blend Modes (transfer modes or inks)

Blend modes determine how an object's colors combine with the colors of the pixels underneath the object to determine how the object's color is displayed. To set the blend mode of an object, use the *Blending* pane in the *Inspector* or set the object's **ink** property. All objects in LiveCode support blend modes, with the exception of stacks.



```
set the ink of  
image "picture" to  
"blendBurn"
```

For more information, see the **ink** entry in the LiveCode Dictionary.

To set the degree of transparency, set the object's

**blendLevel**

property. All LiveCode objects (including stacks) support `blendLevel` :

```
set the blendLevel  
of button 1 to 50  
-- sets a button  
to 50%  
transparent
```

## Full screen mode

A stack can be displayed as full screen by setting its **fullScreen** property to true:

```
set the fullScreen  
of this stack to  
true
```

Set this property back to `false` to exit full screen mode.

If you want to hide or show the menu bar on Mac OS X use the **hide menuBar** or **show menuBar** commands.

Similarly, use **hide taskbar** and **show taskbar** on Windows systems to hide and show the taskbar.

## Displaying a Backdrop

To display a backdrop set the **backDrop** global property. You may set the backDrop to a solid color or to the ID of an image.

```
set the backDrop to  
"black"
```

To remove the **backDrop**:

```
set the backDrop to  
none
```

Offline (Leave a message)