

Using MergJSON to move data from a data grid to a Mongo db

Asked 6 years, 5 months ago Active 6 years, 5 months ago Viewed 78 times

2 ▲ After I successfully implemented the retrieval of documents from my local mongo server, I began trying the opposite, sending data stored in a data grid (DG) to the server, so I created a card with:

- a DG (DG_02) with two columns, _id and Nombre, a field (E),
- a script with a mouseup handler,

that:

put the dgData **of** DG_02 into pArray2

puts the 5th element **of** pArray2, into pArray,

(I just want to try this with only one element for now)

sets pForceRootType, pPretty parameters **for** the **MergJSON function**

call the function ArrayToJSON

put tJSON in fiel "E" to see what the **function** is returning

Construct the string for use with the shell command

put the result in rmongo to see the server answer

The whole script

on mouseUp

```
local dbText
put the dgData of grp "DG_02" into pArray2
put pArray2[5] into pArray    <-- Only the 5th element of the array
put "string" into tipo
put "false" into bonito
```

```
put ArrayToJSON(pArray, tipo, bonito) into tJSON
put tJSON into fld "E"
put "db.nueva.insert("& tJSON & ");" into dbText

put shell("C:\mongodb\bin\mongo.exe --eval" && "" & dbText & "" )
into rmongo

put rmongo

end mouseUp
```

These are my observations when executing the script, modifying the parameter pForceRootType for the function:

When tipo is set to Object field "E" gets: {"Nombre":"Sofia","_id":1012}

When tipo is set to String, field "E" gets: {"Nombre":"Sofia","_id":"001012"}

In both cases (tipo = string or tipo = object) rmongo, show this in the message:

MongoDB shell version: 2.2.7

connecting to: test

```
db.nueva.insert({Nombre:Sofia,_id:001012});
```

The document is not inserted.

When trying the insert directly in the shell, I can see that in order to do a successful insert, the

By using our site, you acknowledge that you have read and understand our Cookie Policy, Privacy Policy, and our Terms of Service.



I will appreciate your guide with this, thank you in advance, Javier

[mongodb](#) [livecode](#)

edited Mar 23 '14 at 2:12



z--

2,015

13

32

asked Mar 22 '14 at 14:29



Javier

75

5

1 Answer

Active

Oldest

Votes



The JSON returned by ArrayToJSON has appropriate quotes as you can see in the text of field

"E".

0

My best guess is you need to escape the strings for the shell call so try:

replace quote **with** `"^"` in tJSON

Of course then it's no longer safe to have a quote in any of your strings.

answered Mar 22 '14 at 20:19



[Monte Goulding](#)

2,215 1 16 25

Just want to thank for editing my post,Hannes. I'll try to be more careful formating my posts. Monte, thank you for your help. – [Javier](#) Mar 23 '14 at 2:39

You are welcome, may I ask you to add an explanation what the variables are for? – [z--](#) Mar 23 '14 at 11:29

Hannes, the variables bonito and tipo, are arguments for the MergJSON function that returns a JSON from an Array. Are you asking for the purpose of these? – [Javier](#) Mar 24 '14 at 13:27
