




US 20200280629A1

(19) **United States**(12) **Patent Application Publication****Yao et al.**(10) **Pub. No.: US 2020/0280629 A1**(43) **Pub. Date: Sep. 3, 2020**(54) **DIALER WITH REAL-TIME REVERSE
LOOK-UP INCLUDING SOCIAL DATA****H04M 1/725** (2006.01)**H04M 1/57** (2006.01)(71) Applicant: **Facebook, Inc.**, Menlo Park, CA (US)(52) **U.S. Cl.****CPC** **H04M 3/4211** (2013.01); **G06F 21/6245**
(2013.01); **G06Q 10/107** (2013.01); **G06Q**
50/01 (2013.01); **H04M 1/72583** (2013.01);
H04M 3/42102 (2013.01); **H04M 1/575**
(2013.01); **H04M 2203/655** (2013.01); **H04M**
1/72552 (2013.01)(72) Inventors: **Rose Yao**, San Francisco, CA (US);
Brandon Walkin, San Francisco, CA
(US)(73) Assignee: **Facebook, Inc.**, Menlo Park, CA (US)(21) Appl. No.: **16/875,528**(22) Filed: **May 15, 2020****Related U.S. Application Data**(63) Continuation of application No. 15/432,851, filed on
Feb. 14, 2017, now Pat. No. 10,666,794, which is a
continuation of application No. 13/215,018, filed on
Aug. 22, 2011, now Pat. No. 9,626,656.**Publication Classification**(51) **Int. Cl.****H04M 3/42** (2006.01)**G06F 21/62** (2006.01)**G06Q 10/10** (2006.01)**G06Q 50/00** (2006.01)

(57)

ABSTRACT

Methods and systems that include, by a client computing device of a first user of a social-networking system, receiving from the first user an identifier associated with an intended recipient to which outgoing communication is to be initiated, wherein the identifier is received via a user interface of an application, identifying, based on the intended recipient, social information relevant to the first user, and displaying, in the user interface, the social information that is relevant to the first user. The identifier may include a phone number or an email address of the intended recipient. The social information may include a name of the intended recipient, and/or a social-network profile of the intended recipient. The intended recipient may be a second user of the social-networking system, and the social information may be identified based on how many degrees of separation there are between the first user and the second user.






FIG. 1

FIG. 2
(PRIOR ART)




FIG. 3




FIG. 4







FIG. 5








FIG. 8




FIG. 9

DIALER WITH REAL-TIME REVERSE LOOK-UP INCLUDING SOCIAL DATA

PRIORITY

[0001] The present application claims the benefit of priority to U.S. Non-Provisional patent application Ser. No. 15/432,851 (filed on Feb. 14, 2017), which itself claims priority to U.S. Non-Provisional patent application Ser. No. 13/215,018 (filed on Aug. 22, 2011).

TECHNICAL FIELD

[0002] The present disclosure relates generally to integration of information stored remotely at a social networking system into a real-time reverse lookup dialer application.

BACKGROUND

[0003] The advent of social networking and ubiquitous wireless data networks allow a user of the social network to remotely retrieve an enormous amount of profile data for his or her contacts, or friends, on the social network with little to no latency. The integration of mobile devices using wireless data networks allows the integration of relevant information stored on social networking systems into call dialer screens, enhancing the user experience when making voice calls or composing short message service (SMS) or email messages.

BRIEF DESCRIPTION OF THE DRAWINGS

[0004] FIG. 1 illustrates an example social networking environment.

[0005] FIG. 2 illustrates an example prior art dialer interface.

[0006] FIG. 3 illustrates an example interface implementing a reverse lookup for a friend of the user.

[0007] FIG. 4 illustrates an example interface implementing a reverse lookup for a non-friend of the user.

[0008] FIG. 5 illustrates an example interface implementing a reverse lookup for a business or hub.

[0009] FIG. 6 is a flowchart illustrating an example method of displaying social information for a dialed contact.

[0010] FIG. 7 is a call flow diagram depicting the interaction between a mobile device and server in accordance with one embodiment of the invention.

[0011] FIG. 8 illustrates an example computing system.

[0012] FIG. 9 illustrates an example mobile device.

[0013] The figures depict various embodiments of the present invention for purposes of illustration only. One skilled in the art will readily recognize from the following discussion that alternative embodiments of the structures and methods illustrated herein may be employed without departing from the principles of the invention described herein.

DETAILED DESCRIPTION OF EXAMPLE EMBODIMENT(S)

Overview

[0014] Particular embodiments relate to a dialer application that pulls profile information from a social networking system. The dialer application determines whether the dialed number is associated with a friend of the user account associated with the mobile or computing device, and

depending on whether the recipient is a friend, displays various information that is deemed to be relevant to the user making the call.

[0015] Implementations of the present invention extend these concepts by allowing a dialer application to make the determination locally, and display friend data that is cached locally on the mobile device. Furthermore, in the scenario where the recipient is not a friend of the member of the social network, the social networking system may still pull public profile information for display to the user making the call. Further, when the outgoing number is not associated with any particular user, but a hub page representing a business, the social network may also pull information from the hub page for display to the user. Thus the application provides a user making a call immediate, socially relevant information that he or she may reference during the call.

[0016] FIG. 1 is a high-level block diagram of an integrated messaging system according to one embodiment. FIG. 1 illustrates a social networking system 100, mobile device 180, wireless cellular network 300, third-party website 190, third-party communication service 210, and public-switched telephone network 310. It is understood that wireless cellular network 300 represents multiple wireless cellular networks provided by a plurality of carriers. FIG. 1 also includes offline storage 200 that is local to mobile device 180. Mobile device 180 is depicted as a mobile phone, but mobile device 180 may comprise any type of computing device, including mobile phone, laptop, netbook tablet, cable box, television, etc. Mobile device 180 is any computing device capable of receiving a call, whether it is a VoIP call through a packet-based data network 180, or a voice call from circuit-switched networks such as PSTN 310. Mobile device 180 has one or more memories capable of storing call, text, and other messaging data, depicted in FIG. 1 as offline storage 200.

[0017] Mobile device 180 interacts with external websites 190 and other service providers 210 through a web browser residing on the client device, or a dedicated application local to mobile device 180. For example, mobile device 180 may interact with third-party instant VoIP service 210, such as Google Voice™ or Skype™, by visiting and logging into their account via a web browser, or by installing and running a dedicated application. The same applies for video calls via third-party service providers 210 such as Apple FaceTime™ or Tango. This disclosure contemplates any type of third-party service provider 210 connected to network 170 or PSTN 300.

[0018] A user of mobile device 180 interacts with social networking system 100 via an application, such as a web browser or a native application, to perform operations such as browsing content, posting and sending messages, retrieving and sorting messages received from other users, and the like. Messages can be in any electronic message format such as electronic mail (“e-mail”) messages, chat messages, comments left on a user’s webpage, and short message service (SMS) text messages. Messages can contain plain text, or they can contain other content such as pictures, videos, and attachments. Each user has a mailbox that includes messages that are both sent and received by the user. Mobile device 180 may also use an application or browser to pull and view profile information for various user nodes and hubs in social networking system 100.

[0019] Mobile device 180, connected through wireless network 300, may also interact with other client devices

through the circuit-switched, or non-data, portion of wireless network **300**. For example, a user at mobile device **180** may transmit and receive a non-VoIP call to a cellular phone or landline in PSTN **310**, transmit and receive a text or multimedia message through the SMS or MMS channels, or receive push notifications through the SMS control channel.

[0020] Additionally, third party website **190** can also interact with the social networking system **100** via a system-provided application programming interface (API) **50**. For example, the third party website can perform operations supported by the API, such as delivering messages to the social network system **100**, retrieving messages stored by the social networking system **100**, and obtaining social information about users of the social networking system **100**.

[0021] Social networking system **100** comprises an object store **110**, and a graph information store **120**. Object store **110** stores information on objects, such as users, represented in or by the social networking environment **100**. Graph information store **120** stores information on the relationships of the objects in object store **110**.

[0022] In particular embodiments, the social graph information includes a first set of user nodes that each correspond to a respective user, and a second set of concept nodes that each correspond to a respective concept. As used herein, a “user” may be an individual (human user), an entity (e.g., an enterprise, business, or third party application), or a group (e.g., of individuals or entities) that interacts or communicates with or over such a social network environment. As used herein, a “concept” may refer to virtually anything that a user may declare or otherwise demonstrate an interest in, a like towards, or a relationship with, such as, by way of example, a sport, a sports team, a genre of music, a musical composer, a hobby, a business (enterprise), an entity, a group, a third party application, a celebrity, a person who is not a registered user, etc. In particular embodiments, each node has, represents, or is represented by, a corresponding web page (“profile page”) hosted or accessible in the social network environment.

[0023] By way of example, a user node may have a corresponding user profile page in which the corresponding user can add content, make declarations, and otherwise express him or herself, while a concept node may have a corresponding concept profile page (“hub”) in which a plurality of users can add content, make declarations, and express themselves, particularly in relation to the concept. In particular embodiments, the social graph information further includes a plurality of edges that each define or represent a connection between a corresponding pair of nodes in the social graph. In particular embodiments, profile information for user nodes is stored in user store **111**, while hub page information for concepts, such as businesses, is stored in hubs store **115**. Nodes directly connected by a friend edge are considered one degree of separation away, and are listed as “friends” on the social network. Users of the social network may specify elements or portions of their profile which may be viewed only by friends, or friends of friends (second degree contacts). In particular embodiments, users may define privacy settings that only allow certain groups or individual members of the social network to view portions of their profile. For further detail on hubs, please see U.S. patent application Ser. No. 12/763,171 titled, “Integrated Social Network Environment,” previously filed on Apr. 19, 2010 and fully incorporated by reference herein.

[0024] FIG. 2 illustrates an example prior art interface **200** displayed to a user when the user’s client (or mobile) device **180** makes a call. In particular embodiments, interface **200** is a touch screen that includes numeric keypad **201** for entering a phone number. In particular embodiments, interface **200** may include a physical keypad. Interface **200** also includes a button **202** to add a given dialed number to a list of contacts, and a call button **203** that initiates communication to the dialed number. As discussed earlier, in particular embodiments, one or more of these touchscreen interfaces may be substituted for physical buttons. Interface **200** also includes display area **204** that displays the inputted telephone number. Display area **204** allows the user to visually verify that he or she has entered the correct number, to the extent that the user has memorized the correct number, before initiating a voice call via call button **203**.

[0025] FIG. 3 illustrates an example interface **300** displayed to the user of mobile device **180** when the user inputs a phone number associated with one of the user’s friends on social networking system **100**. Instead of merely displaying the entered number, as in display area **204**, interface **300** includes display area **302** that displays relevant information about a member of the social networking system whose phone number matches the entered number. In particular embodiments, the relevant social information is stored remotely on the social networking server, and the information is pulled by mobile device **180** for display. In particular embodiments, the relevant social information is pre-cached by mobile device **180** and stored in offline storage **200**. The dialer application, upon retrieving the relevant social information on the particular member, such as the member’s name, displays the information in display area **302**. In particular embodiments, relevant social information may include the profile picture **301** of the particular member. In particular embodiments, dialer application may display an indicator **303** as to what type of number the user has entered. For example, in FIG. 3, the entered number is the mobile phone number of the particular member. This allows the user to quickly verify that he or she has entered an appropriate number for the particular member, such as entering the particular member’s office number during working hours. In particular embodiments, the dialer application may also display user-selectable button **304** in display area **302**. When actuated, user-selectable button **304** causes the dialer application, or alternatively, another application residing on mobile device **180**, such as a browser or dedicated social networking application, to display the profile associated with the member displayed in display area **302**. The user may desire to, prior to hitting call button **304**, quickly browse the intended recipients profile page for milestones, such as birthdays, job placements, etc. or random information from status updates, check-ins, and the like for small-talk subject matter, thus facilitating the appearance that the user is deeply engaged or genuinely concerned with the life of the intended call recipient.

[0026] Additionally, a user may more quickly visually verify that he or she has entered the correct number even in the situation where the user has incorrectly memorized the number. For example, if the user intends to call Francis Luu, enters the number, but fails to see profile information for Francis Luu, the user immediately knows he or she has entered an incorrect number.

[0027] FIG. 4 illustrates an example interface **400** displayed to the user of mobile device **180** when the user enters

a number associated with a member of social networking system **100** that is not one of the users first degree contacts or friends. Interface **400** is substantially similar to interface **300**, and displays the intended recipient's name, entered phone number, and type of phone number. In particular embodiments, interface **400** also includes mutual friend indicator **401** that displays how many mutual friends, or shared first-degree connections, the user and intended recipient have on social network **100**. In particular embodiments, mutual friend indicator **401** is selectable, and when selected, the dialer application displays the mutual friends to the user. Interface **400** also includes user-selectable button **402** that operates in substantially the same manner to user-selectable button **304**.

[0028] In all cases where the users actuates user-selectable button **304** and **402** to view the intended recipient's social networking profile, the information displayed to the user is subject to one or more privacy policies maintained by social networking system **100**. For example, the intended recipient may only choose to display some information publicly, or to members of certain networks. Thus, where the user and intended call recipient are not friends, the information displayed to the user is limited to the privacy settings of the intended recipient and the relationship information between the two stored in the social graph. Even in the scenario where the user and the intended call recipient are friends, or first-degree contacts, the intended recipient may have privacy settings limiting the display of any given piece of information from any given member or groups of members. The social data displayed to the user by the dialer application is limited by these policies and the relationship information between the user and the recipient stored in the social graph.

[0029] FIG. 5 illustrates an example interface **500** displayed to the user of mobile device **180** when the user enters a number that is associated with a non-user entity in social networking system **100**. For example, a local business may choose to create a profile page, or a hub page, representing the business on social networking system **100**. If the entered phone number matches the phone number listed on the local business's hub page, dialer application may display information relating to the hub page to the user. In particular embodiments, the local business does not have to explicitly create the hub page. In particular embodiments, a user may create the hub page for the business, or social networking system **100** may create the hub page by accessing online directories or yellowpages. Hub pages may be associated with any entity that is not a user. For example, in particular embodiments, hub pages may be associated with businesses, governmental entities, celebrities, specific places, affinity groups, and the like. So long as the hub page has a phone number associated with it, the dialer application will display relevant social information pulled from the hub page to the user entering a matching number.

[0030] Interface **500** contains socially relevant information retrieved from the hub page associated with the entered number. In particular embodiments, interface **500** includes the name **501** of the entity associated with the hub page, in this example, "Delfina Restaurant." Interface **500** may also include the entered number **502**, and, in particular embodiments, socially-relevant information **503** tailored to the specific user of mobile device **180**. For example, in FIG. 5, **503** displays how many of the user's friends "like" the detected entity. In particular embodiments, temporally-sensitive social information, such as if friends of the user

recently checked into the physical location associated with the hub page, may have a higher priority than other social information. This disclosure contemplates any ranking of display of any relevant social information on interface **500**.

[0031] Interface **500** similarly includes user-selectable button **504**, which, when actuated, displays the hub page or a portion thereof to the user. In particular embodiments, mobile-specific information retrieved from the hub page, such as a map to the physical location associated with the hub page, hours of operation, or the like, may be displayed. This disclosure contemplates the display of any suitable portion of the hub page associated with the entered phone number.

[0032] The dialer application displays interfaces **300**, **400**, and **500** substantially simultaneously with the user's input of a user identifier. Although the foregoing examples describe a user entering a phone number, this disclosure contemplates all types of communications and associated user identifiers. In particular embodiments, this outgoing communication is a SMS or MMS text message, and the user identifier is a phone number. In particular embodiments, the outgoing communication is a VoIP call, and the communication source is an account (generally a username) for the VoIP service. In particular embodiments, the communication is a video chat, and the communication is an account (usually a username) for the video chat service. In other embodiments, the incoming communication is an e-mail, direct message from a third-party site, instant message, SMS/MMS message, and the like. Although this disclosure primarily pertains to real-time full-duplex communications, all other forms of communication are contemplated.

[0033] FIG. 6 is a flowchart illustrating an example method of displaying social dialer screens **300**, **400**, and **500**. At step **601**, mobile device **180** receives, via a user interface, touchscreen, or physical buttons, an identifier of an intended recipient, in this example, the phone number of a recipient of a voice call. As disclosed, this disclosure contemplates any form of communication, and is not limited to real-time full-duplex communications. For didactic purposes, however, FIG. 6 assumes the communication is a voice call.

[0034] At Step **602**, mobile device **180** performs a reverse lookup of the stored contacts in offline storage **200**. Reverse lookups are well-known in the art and are not discussed in detail here. In particular embodiments, dialer application performs the reverse lookup substantially in real-time, narrowing the potentially matching contacts as each digit is entered by the user. In particular embodiments, the dialer application performs the reverse lookup only after all the digits, for example, ten digits in the United States, have been received. This disclosure contemplates any manner or algorithm for performing a reverse lookup.

[0035] If the dialer application at Step **602** determines, as a result of the reverse lookup, that the phone number matches a number stored in association with a friend of the user whose data is pre-cached in offline storage **200**, dialer application displays the relevant social information at Step **603**. The pre-caching of social information may occur at any given time. In particular embodiments, the information is downloaded and stored whenever the user adds a new friend on social networking system **100**. In particular embodiments, the information is downloaded and stored periodically. In particular embodiments, the information is downloaded and stored in response to a synchronization

operation. This disclosure contemplates any manner of timing the download and storage, or pre-caching, of friend information. In particular embodiments, because the relevant social information is relatively limited, it is possible to efficiently store all the user's contacts in offline storage **200**.

[0036] If the dialer application at Step **602** determines, as a result of the reverse lookup, that the phone number does not match the numbers stored in association with any of the users friends in offline storage **200**, the dialer application transmits the entered number to social networking system **100** at Step **603**. In particular embodiments, the dialer application also transmits a user identifier of the member account associated with the user of mobile device **180** to the server. In particular embodiments, the user of mobile device **180** associates a social networking user ID with mobile device **180** when he or she first uses the device, and the user ID is transmitted through a specialized application on mobile device **180**. In other embodiments, the user ID is explicitly transmitted in all transmissions to the social networking system **100**. In other embodiments, the user ID is associated on the server-side of the social networking system with a client device identifier, such as a phone number, IMSI, IMEI, or the like. Regardless, the social networking system associates mobile device **180** with a particular member, called the "user" in this disclosure for purposes of simplicity.

[0037] In particular embodiments, mobile device **180** maintains an always-on connection via network **170** to the servers of social networking system **100**. In particular embodiments, mobile device **180** initiates a connection with social networking system **100** via network **170** when the dialer application is launched. This disclosure contemplates any suitable manner of connection initialization and management known those of ordinary skill in the art.

[0038] At Step **604**, an application residing on one or more servers of social networking system **100** receives the entered number. As will be discussed with regard to FIG. 7, the server need not receive the entire number simultaneously to begin the reverse lookup. Given the vast number of phone numbers stored in social networking system **100**, it may be beneficial to begin the reverse lookup as soon as the first digit is received by mobile device **180**.

[0039] At Step **606**, the application residing on one or more of the servers performs a reverse lookup for users or other entities associated with the received phone number, and determines whether a matching entity resides in social networking system **100** at Step **607**. User store **111** and hubs store **115** may store phone numbers in conjunction with particular members or concept nodes of the social network. The application attempts to match the number with a number existing in user store **111** or concept store **118**. After finding a match, the application looks up the social networking user identifier for the user or concept node associated with the number. In particular embodiments, member phone numbers (or other identifiers) may be stored by the user on his or her own profile. In other embodiments, a first user may store phone numbers for a second user in his or her own online phonebook. Naturally, in such a scenario, the reverse lookup would return the user ID of the second user. In particular embodiments, the IDs represent user or concept nodes in the social graph.

[0040] If the server cannot find a match, then the process ends at Step **608**. In particular embodiments, at Step **608**, mobile device **180** displays the prior art dialer screen

depicted in FIG. 2. In particular embodiments, mobile device **180** displays the prior art dialer screen depicted in FIG. 2 until social data is received from the server.

[0041] If the application residing on one or more servers of social networking system **100** determines that the received number matches one associated with an entity of social networking **100**, at Step **609** the application assesses the relationship between the user transmitting the number and the entity associated with the number by accessing social graph network store **120**. The application residing on one or more of the servers of social networking system **100** accesses the graph network store to determine the relationship, if any, between the calling user node and the recipient node.

[0042] As discussed earlier, the user's access to the member's information depends on one or more privacy policies of social networking system **100**, or one or more privacy policies of a member associated with the received number. After analyzing the social relationship between the user and the entity matching the received number, the application transmits the relevant social information, subject to the aforementioned privacy policies, to mobile device **180** in Step **610**.

[0043] At Step **611**, mobile device **180** displays the received social information as depicted in FIGS. 3-5. Because of the latency of network **170**, it is possible that the user may be ready to call before the social information is received from the servers of social networking system **100**. In such a case, the social information is simply not displayed. In particular embodiments, dialer application displays a "loading" icon on interfaces **400** or **500** to indicate that a match has been found, and that the download of socially relevant information is in progress.

[0044] FIG. 7 is a call flow diagram between client/mobile device **180** and one or more servers **700** of social networking system **100** in accordance with one embodiment of the invention. As previously discussed, due to the sheer number of stored profiles and phone numbers in user store **111**, it may not be feasible to begin the reverse lookup process of Step **606** after the user has entered the full phone number. Thus, in particular embodiments, it may be beneficial to begin the reverse lookup process on the server as each digit is received. In Step **701**, the user enters the first digit through the dialpad, in this case "7", and immediately mobile device **180** transmits the number "7" to server **700**.

[0045] In Step **701a**, server **700**, immediately upon receiving the first digit ("7"), eliminates all stored phone numbers beginning with digits other than "7" from the set of potential matches. Similarly, in step **702**, the user enters the second digit of the phone number, in this example "1", and mobile device **180** immediately transmits the digit to server **700**. Similarly, in Step **702a**, server **700** narrows the set of potential matching phone numbers to numbers beginning with "71." This process repeats itself until Step **704**, where the last digit is received. In this example, the number is a U.S. 10-digit phone number, but this disclosure contemplates phone numbers or identifiers of any length. Additionally, although not shown, this disclosure contemplates sending a "delete" or "back" command from mobile device **180** to server **700** if the user chooses to delete the previous number due to mistakes in entry.

[0046] At Step **705**, an application residing on server **700** obtains the result of the reverse lookup corresponding to a user ID identifying a specific user or entity of social net-

working system **100**. Subject to the privacy check of Step **609**, the application residing on server **700** obtains the socially relevant information, and in Step **706** transmits the information back to client/mobile device **180**. In this manner, it is possible to dramatically reduce the time required to perform the server-side reverse lookup.

[0047] FIG. **8** illustrates an example computer system **800**, which may be used with some embodiments of the present invention. This disclosure contemplates any suitable number of computer systems **800**. This disclosure contemplates computer system **800** taking any suitable physical form. Where appropriate, computer system **800** may include one or more computer systems **800**; be unitary or distributed; span multiple locations; span multiple machines; or reside in a cloud, which may include one or more cloud components in one or more networks. Where appropriate, one or more computer systems **800** may perform without substantial spatial or temporal limitation one or more steps of one or more methods described or illustrated herein.

[0048] In particular embodiments, computer system **800** includes a processor **802**, memory **804**, storage **806**, an input/output (I/O) interface **808**, a communication interface **810**, and a bus **812**. Although this disclosure describes and illustrates a particular computer system having a particular number of particular components in a particular arrangement, this disclosure contemplates any suitable computer system having any suitable number of any suitable components in any suitable arrangement.

[0049] In particular embodiments, processor **802** includes hardware for executing instructions, such as those making up a computer program. Although this disclosure describes and illustrates a particular processor, this disclosure contemplates any suitable processor.

[0050] In particular embodiments, memory **804** includes main memory for storing instructions for processor **802** to execute or data for processor **802** to operate on. As an example and not by way of limitation, computer system **800** may load instructions from storage **806** or another source (such as, for example, another computer system **800**) to memory **804**. One or more memory buses (which may each include an address bus and a data bus) may couple processor **802** to memory **804**. Bus **812** may include one or more memory buses, as described below. Although this disclosure describes and illustrates particular memory, this disclosure contemplates any suitable memory.

[0051] In particular embodiments, storage **806** includes mass storage for data or instructions. Storage **806** may be internal or external to computer system **800**, where appropriate. This disclosure contemplates mass storage **806** taking any suitable physical form. Where appropriate, storage **806** may include one or more storages **806**. Although this disclosure describes and illustrates particular storage, this disclosure contemplates any suitable storage.

[0052] In particular embodiments, I/O interface **808** includes hardware, software, or both providing one or more interfaces for communication between computer system **800** and one or more I/O devices. One or more of these I/O devices may enable communication between a person and computer system **800**. This disclosure contemplates any suitable I/O devices and any suitable I/O interfaces **808** for them. Although this disclosure describes and illustrates a particular I/O interface, this disclosure contemplates any suitable I/O interface.

[0053] In particular embodiments, communication interface **810** includes hardware, software, or both providing one or more interfaces for communication (such as, for example, packet-based communication) between computer system **800** and one or more other computer systems **800** or one or more networks. This disclosure contemplates any suitable network and any suitable communication interface **810** for it. Although this disclosure describes and illustrates a particular communication interface, this disclosure contemplates any suitable communication interface.

[0054] In particular embodiments, bus **812** includes hardware, software, or both coupling components of computer system **800** to each other. Although this disclosure describes and illustrates a particular bus, this disclosure contemplates any suitable bus or interconnect.

[0055] The client-side functionality described above can be implemented as a series of instructions stored on a computer-readable storage medium that, when executed, cause a programmable processor to implement the operations described above.

[0056] While mobile device **180** may be implemented in a variety of different hardware and computing systems, FIG. **9** shows a schematic representation of the main components of an example computing platform **902**, according to various particular embodiments. Multipoint sensing devices generally include a controller **904** which may comprise a microcontroller or one or more processors configured to execute instructions and to carry out operations associated with a computing platform. Controller **904** may optionally contain a cache memory unit for temporary local storage of instructions, data, or computer addresses. By way of example, using instructions retrieved from memory, controller **904** may control the reception and manipulation of input and output data between components of computing platform **902**.

[0057] Controller **904** together with a suitable operating system may operate to execute instructions in the form of computer code and produce and use data. The operating system, other computer code (including control client **908** described below) and/or data may be physically stored within a memory block **906** that is operatively coupled to controller **904**.

[0058] Memory block **906** encompasses one or more storage media and generally provides a place to store computer code (e.g., software and/or firmware) and data that are used by the computing platform **902**. By way of example, any of a number of suitable memory cards may be loaded into computing platform **902** on a temporary or permanent basis.

[0059] Controller **904** is also generally coupled to a variety of interfaces such as graphics control, video interface, input interface, output interface, and storage interface, and network interface, and these interfaces in turn are coupled to the appropriate devices. In certain embodiments, Controller **904** may be connected to an input structure **914** and display **916** may be provided together, such as in the case of a touchscreen where a touch sensitive mechanism is provided in conjunction with the display **916**.

[0060] Electric signals (e.g., analog) may be produced by microphone **910** and fed to earpiece **912**. Controller **904** may receive instruction signals from input structure **914** and control the operation of display **916**. Audio signals may be transmitted and received by means of an antenna **918** that may be connected through a radio interface **920** or audio input interface such as microphone **924** to codec **922** con-

figured to process signals under control of controller **904**. Additionally, multipoint sensing devices may be powered power source **932**.

[0061] Mobile device may also include one or more user input devices **934** (other than input structure **914**) that are operatively coupled to the controller **904**. Generally, input devices **934** are configured to transfer data, commands and responses from the outside world into multipoint sensing devices.

[0062] Display device **916** is generally configured to display a graphical user interface (GUI) that provides an easy to use visual interface between a user of the computing platform **902** and the operating system or application(s) running on the mobile device.

[0063] Herein, reference to a computer-readable storage medium encompasses one or more non-transitory, tangible computer-readable storage media possessing structure. As an example and not by way of limitation, a computer-readable storage medium may include a semiconductor-based or other integrated circuit (IC) (such, as for example, a field-programmable gate array (FPGA) or an application-specific IC (ASIC)), a hard disk, an HDD, a hybrid hard drive (HHD), an optical disc, an optical disc drive (ODD), a magneto-optical disc, a magneto-optical drive, magnetic tape, a holographic storage medium, a solid-state drive (SSD), a RAM-drive, a SECURE DIGITAL card, a SECURE DIGITAL drive, or another suitable computer-readable storage medium or a combination of two or more of these, where appropriate. Herein, reference to a computer-readable storage medium excludes any medium that is not eligible for patent protection under 35 U.S.C. § 101.

[0064] The present disclosure encompasses all changes, substitutions, variations, alterations, and modifications to the example embodiments herein that a person having ordinary skill in the art would comprehend. Similarly, where appropriate, the appended claims encompass all changes, substitutions, variations, alterations, and modifications to the example embodiments herein that a person having ordinary skill in the art would comprehend.

[0065] The foregoing description of the embodiments of the invention has been presented for the purpose of illustration; it is not intended to be exhaustive or to limit the invention to the precise forms disclosed. Persons skilled in the relevant art can appreciate that many modifications and variations are possible in light of the above disclosure. For example, although the foregoing embodiments have been described in the context of a social network system, it will apparent to one of ordinary skill in the art that the invention may be used with any electronic social network service and, even if it is not provided through a website. The invention is thus not limited to any particular type of communication system, network, protocol, format or application.

[0066] Some portions of this description describe the embodiments of the invention in terms of algorithms and symbolic representations of operations on information. These algorithmic descriptions and representations are commonly used by those skilled in the data processing arts to convey the substance of their work effectively to others skilled in the art. These operations, while described functionally, computationally, or logically, are understood to be implemented by computer programs or equivalent electrical circuits, microcode, or the like. Furthermore, it has also proven convenient at times, to refer to these arrangements of operations as modules, without loss of generality. The

described operations and their associated modules may be embodied in software, firmware, hardware, or any combinations thereof.

[0067] Any of the steps, operations, or processes described herein may be performed or implemented with one or more hardware or software modules, alone or in combination with other devices.

[0068] Embodiments of the invention may also relate to an apparatus for performing the operations herein. This apparatus may be specially constructed for the required purposes, and/or it may comprise a general-purpose computing device selectively activated or reconfigured by a computer program stored in the computer. Such a computer program may be stored in a tangible computer readable storage medium or any type of media suitable for storing electronic instructions, and coupled to a computer system bus. Furthermore, any computing systems referred to in the specification may include a single processor or may be architectures employing multiple processor designs for increased computing capability.

[0069] While the foregoing processes and mechanisms can be implemented by a wide variety of physical systems and in a wide variety of network and computing environments, the server or computing systems described below provide example computing system architectures for didactic, rather than limiting, purposes.

[0070] Finally, the language used in the specification has been principally selected for readability and instructional purposes, and it may not have been selected to delineate or circumscribe the inventive subject matter. It is therefore intended that the scope of the invention be limited not by this detailed description, but rather by any claims that issue on an application based hereon. Accordingly, the disclosure of the embodiments of the invention is intended to be illustrative, but not limiting, of the scope of the invention, which is set forth in the following claims.

What is claimed is:

1. A method, comprising:

by a client computing device of a first user of a social-networking system:

receiving, via a user interface of the computing device, an identifier associated with an intended recipient to which outgoing communication is to be initiated;

displaying, in the user interface in response to receiving the identifier, social information about a member of the social networking system whose identification matches the identifier;

displaying, in the user interface, an indicator as to a type of identifier received; and

displaying, in the user interface, a user interface element that is user-selectable to display, when actuated, a social-network profile associated with the member.

2. The method of claim 1, wherein the identifier comprises a phone number or an email address of the intended recipient.

3. The method of claim 1, wherein the social information comprises a name of the intended recipient, a social-network profile of the intended recipient, or a combination thereof.

4. The method of claim 1, wherein the intended recipient is a second user of the social-networking system, and the social information is identified based on how many degrees of separation there are between the first user and the second user

5. The method of claim 4, wherein the social information comprises a count of how many first-degree connections are shared between the first user and the second user in the social-networking system.

6. The method of claim 4, wherein the count of how many first-degree connections are shared comprises a count of mutual friends of the first user and the second user.

7. The method of claim 4, wherein the first-degree connections that are shared between the first user and the second user comprise mutual friends of the first user and the second user.

8. The method of claim 4, wherein the social information is subject to one or more privacy policies associated with the intended recipient in the social-networking system.

9. The method of claim 8, wherein:

there are two or more degrees of separation between the first user and the second user, and
the social information is limited to public information in the social-networking system.

10. The method of claim 8, wherein:

there are two or more degrees of separation between the first user and the second user, and
the social information is limited to the one or more privacy policies of the intended recipient and relationship information that associates the first user and the second user.

11. The method of claim 8, wherein:

there is one degree of separation between the first user and the second user, and
the one or more privacy policies limit the display of one or more pieces of the social information from one or more members of the social-networking system.

12. The method of claim 1, wherein:

the intended recipient represents an entity that is associated with a page in the social-networking system, the page is associated with the identifier, and
the one or more pieces of social information are associated with the page.

13. The method of claim 12, wherein the social networking system creates the page by accessing one or more online directories, and the entity comprises a business, governmental entity, celebrity, place, or a combination thereof.

14. The method of claim 12, wherein:

the one or more actions performed on the social-networking system with respect to the intended recipient by one or more other users who are social connections of the first user comprise “liking” the entity, and
the social information comprises a count of how many friends of the first user in the social-networking system “like” the entity.

15. The method of claim 12, wherein the one or more actions performed on the social-networking system with respect to the intended recipient at one or more associated times comprise one or more check-ins to a physical location associated with the page.

16. The method of claim 15, wherein the temporally-sensitive piece of social information indicates that one or more friends of the first user have recently checked into the physical location associated with the page.

17. The method of claim 12, wherein the social information comprises a map to a physical location associated with the page, hours of operation of the entity, or a combination thereof.

18. The method of claim 1, wherein the outgoing communication comprises a text message, a VoIP call, a video chat, or a combination thereof.

19. One or more computer-readable non-transitory storage media embodying software that is operable when executed to:

receive, via a user interface of the computing device, an identifier associated with an intended recipient to which outgoing communication is to be initiated;

display, in the user interface in response to receiving the identifier, social information about a member of the social networking system whose identification matches the identifier;

display, in the user interface, an indicator as to a type of identifier received; and

display, in the user interface, a user interface element that is user-selectable to display, when actuated, a social-network profile associated with the member.

20. A system comprising: one or more processors; and a memory coupled to the processors comprising instructions executable by the processors, the processors being operable when executing the instructions to:

receive, via a user interface of the computing device, an identifier associated with an intended recipient to which outgoing communication is to be initiated;

display, in the user interface in response to receiving the identifier, social information about a member of the social networking system whose identification matches the identifier;

display, in the user interface, an indicator as to a type of identifier received; and

display, in the user interface, a user interface element that is user-selectable to display, when actuated, a social-network profile associated with the member.

* * * * *