



HOARD DOORS

Vaultvane 100

Assembly Instructions — keep for future reference (and for the next dragon).



TIME

30 minutes

PEOPLE

1 dragon

DIFFICULTY

2 of 5 claws

TOOLS

One claw

READ BEFORE BREATHING

Assemble in a well-ventilated cave with no open hoard nearby. Keep knights, goblins and small children at least one tail-length away. Some adhesives set instantly at dragon temperatures — hold your breath during steps that mention glue.



What's in the box

Check every part before you start. Missing a part? Check under yourself first.

★ PARTS LIST

Ref	Part	Qty
A	Door slab	1
B	Hinge post	2
C	Counterweight arm	1
D	Latch	1
E	Service hatch	1
H1	Anchor bolt	12
H2	Hinge pin	4

★ HARDWARE, ACTUAL SIZE



H1 Anchor bolt
x 12



H2 Hinge pin
x 4




Steps 1 to 3

Work on a flat surface. Take your time.

1

Measure the cave mouth


Twice. Stone does not stretch, and neither does regret.



2

Set the hinge posts


Fix posts B to the rock with anchor bolts H1. Level them, or the door swings on its own all night.



3

Hang the slab

Lift slab A onto the posts and drop in hinge pins H2. This is a two-dragon step.






Steps 4 to 6

Nearly there. Resist the urge to breathe on it.

4

Fit the counterweight arm

Arm C hooks over the top of the slab. Adjust until the door holds halfway open on its own.



5

Install the latch

Latch D at snout height, not knight height.



6

Add the service hatch

Hatch E at the base, for goblins and deliveries.



★ TROUBLESHOOTING

Problem	Fix
Door swings shut on its own	Counterweight arm is set too short. Lengthen one notch.
Latch won't catch	The posts are out of level. Re-check with the bubble.
A knight got in	The hatch was left open. Goblins deny everything.