

Class 20 + DSA 04

Sorting, Props and State

seattle-javascript-401n14

Holiday Break!



Holiday Break

<div>Monday DEC 23 2019</div> <div>Co-working</div>	<div>Tuesday DEC 24 2019</div> <div>Lecture</div>	<div>Wednesday DEC 25 2019</div> <div>Lab</div>	<div>Thursday DEC 26 2019</div> <div>Co-working</div>	<div>Friday DEC 27 2019</div> <div></div>	<div>Saturday DEC 28 2019</div> <div>Lecture + Lab</div>	<div>Sunday DEC 29 2019</div> <div></div>
<div>Monday DEC 30 2019</div> <div>Co-working</div>	<div>Tuesday DEC 31 2019</div> <div>Lecture</div>	<div>Wednesday JAN 01 2020</div> <div>Lab</div>	<div>Thursday JAN 02 2020</div> <div>Co-working</div>	<div>Friday JAN 03 2020</div> <div></div>	<div>Saturday JAN 04 2020</div> <div>Lecture + Lab</div>	<div>Sunday JAN 05 2020</div> <div></div>



Lab 19 Review



Code Challenge 19

Review



Vocab Review!



What is a CSS Preprocessor?



What is a Sass Partial?



What is a Mixin?



What is snapshot testing?




What is mount testing?




What is big-o?



Big-O Complexity Chart



Big-O Complexity Chart



Merge Sort

- Step 1 - If there is only one element in the array, it's already sorted so return
- Step 2 - Divide the array **recursively** into two halves until you can't divide
- Step 3 - Merge the smaller lists into a combined list in sorted order


```
function mergeSort(arr, sIndx, eIndx)
  if sIndx >= eIndx // array of size 1 or less
    return;
  let midpoint = Math.floor((sIndx + eIndx) / 2);
  mergeSort(arr, sIndx, midpoint);
  mergeSort(arr, midpoint, eIndx);
  merge(arr, sIndx, midpoint, eIndx);
```




Merge Sort

```
function merge(arr, sIndx, mid, eIndx)
  let merged = [];
  let j = mid + 1;
  for i = 0; i <= mid; i++
    while arr[i] > arr[j] && j < arr.length
      merged.push(arr[j]);
      j++;
    merged.push(arr[i]);
  for i = 0; i < merged.length; i++
    arr[sIndx + i] = merged[i];
```







$sIdx = 0$ $eIdx = 3$
 $mid = \text{Math.floor}(0 + 3 / 2) = 1$
 $\text{mergeSort}(arr, 0, 1) / \text{mergeSort}(arr, 2, 3)$




$sIdx = 0$ $eIdx = 1$
 $mid = 0$
 $\text{mergeSort}(arr, 0, 0) /$
 $\text{mergeSort}(arr, 1, 1)$




$sIdx = 2$ $eIdx = 3$
 $mid = 2$
 $\text{mergeSort}(arr, 2, 2) /$
 $\text{mergeSort}(arr, 3, 3)$




return;



return;




return;






return

$\text{merge}(arr, 0, 0, 1)$



$\text{merge}(arr, 2, 2, 3)$





merge(arr, 0, 1, 3)
merged = []; j = 2; i = 0
arr[0] > arr[2] ✓

2 > 1

merged.push(arr[2])
merged = [1] j++ = 3
arr[0] > arr[3] ✗

2 < 3

merged.push(arr[0])
merged = [1, 2] j = 3 i = 1
arr[1] > arr[3] ✓

4 > 3

```
function merge(arr, sIdx, mid, eIdx)
  let merged = [];
  let j = mid + 1;
  for (i = 0; i <= mid; i++)
    while (arr[i] > arr[j] &&
           j < arr.length)
      merged.push(arr[j]);
      j++;
    merged.push(arr[i]);
```

merged.push(arr[3])
merged = [1, 2, 3] j++ = 4
j < arr.length ✗

4 = 4

merged.push(arr[1])
merged = [1, 2, 3, 4]

Merge Sort

- Recursive `mergeSort` function with a `merge` function that has a `while` loop nested in a `for` loop
- Confusing structure = confusing complexity
- Use tally mark tactic for a small input
- A relationship that is hard to articulate is *usually* `logn` based
- Merge sort is `nlogn` - better than Insertion sort



**We'll resume
sorting next class!**



Props and State (Again)

- **Props** are like function parameters, where the “functions” are either functional or class components
- **State** is like local variables which are meant to be dynamic
- React is structured like HTML where you have **parent** components containing **child** components



<App>

<P>

<Counter>

<button>

<div>

<button>

<div>

Parent to Child

- If a parent has local state variables, they can pass them to child components using props
- Even better, **props can contain anything!**
 - Functions
 - Static variables
 - Strings
 - Any valid JavaScript object



Child to Parent

- Unfortunately, there's really no way for a child component to send data back up to the parent
- The exception is through callback / handler functions
- Mostly, the child will not be able to directly communicate with the parent
- We'll learn ways to get around this in the future
 - The child will write data to a shared space that the parent can access



Why Do We Care?

- A big component of writing UI in React is that we can make pieces of our UI **generic** and **reusable**
- We usually view our child components as “**dumb**”
 - They don't have a state
 - They don't care about where they're being used
 - They usually just take parameters and display them in a cool way
- Our parent components are “**smart**”
 - Maintain state
 - Have more complex logic



Why Do We Care?

- By thinking in this way, we can ensure that we're breaking up our components correctly
- We should minimize “smart” components where we can, because they're usually not reusable
- We need to get used to building components that are completely independent from our application, so we can spread them around!
 - Counter you can add anywhere
 - Converter you can add anywhere
 - Form elements you can add anywhere



Demo

Let's play around with props and state to see how we can make smart and dumb components.



Lab 20 Preview



What's Next:

- Due by Midnight Tomorrow:
 - **Learning Journal 20**
- Due by Midnight Thursday:
 - **Code Challenge 20**
- Due by Saturday 9am:
 - **Lab 20**
 - **Reading Class 21**
- Next Class on Tuesday: **Class 21 - Routing and Component Composition**





Questions?

