



PERFORMANCE YOU CAN COUNT ON

HOSIERY

Merrow toe-closing and finishing machines produce a seam that's strong, neat and comfortable.

Merrow knows hosiery. In fact our machines were developed in close cooperation with the hosiery industry. Attractive and durable, the flat-butted stitches and precision overedge produced by Merrow's hosiery line are found on the majority of socks and hose produced today. Our experience and know-how offer you a proven solution.



MG-3D



MG-3DU



MG-4D-45



MG-4D-67



MERROW[®]
MACHINE COMPANY
MADE IN U.S.A. SINCE 1938

240 DAY STREET
NEWINGTON, CT USA
06111-1241
TEL: 860-666-0109
FAX: 860-666-7730
INTERNET: www.merrow.com
E-MAIL: info@merrow.com



PERFORMANCE YOU CAN COUNT ON

HOSIERY

APPLICATIONS: Toe closing for men's and women's hosiery and attaching lace on the top of women's socks, or inserting strip elastic or cut rubber tape with the overedge stitch.

	MG-3D	MG-3DU	MG-4D-45	MG-4D-67
Application	Lace attaching on top of sock	Toe closing narrow stitch	<i>Light to medium toe closing</i>	Medium to heavy toe closing
Seam type	505	505	514	514
Standard seam width	N/A	N/A	1/8" (3.1750mm)	1/4" (6.3500mm)
Seam width range	1/32"-1/16" (.79375-1.5875mm)	1/16"-3/32" (1.5875-2.3813mm)	1/8"-3/16" (3.1750-4.7625mm)	1/8"-5/16" (3.1750-7.9375mm)
Standard stitch eccentric	20	28	Dependent on needle count	Dependent on needle count
Stitch eccentric range	16-30	24-36	see above	see above
Standard needle Needle range	1SDTF 0DT-2DT	1SDTF 0DT-1SDTF	B00SDT B00DE-B1SDT	A2SD A0D-A3D
Looper, hook, supplementary thread carrier	1 upper looper (eye) 1 lower looper (eye)	1 upper looper (eye) 1 lower looper (eye)	1 upper looper (blind) 1 lower looper (eye)	1 upper looper (blind) 1 lower looper (eye)
Needle thread	70-1 or 12-2 nylon thread	70-1	50-1	70-1 or 100-1
Looper or supplementary thread carrier thread	same	same	70-1 or 2	70-2
Number of threads	3	3	3	3
Speed	5500 RPM	5500 RPM	5500 RPM	5500 RPM
Installation	Non-submerged	Non-submerged	Non-submerged	Non-submerged

The expertly engineered **tension control** in the Merrow Hosiery machines minimizes yarn breakage and produces a superior stitch. Easy threading saves set-up time, and the machines are easy to adjust and service. Highly finished parts and automatic lubrication round out the advantages of these thoroughbred performers.

MERROW

MACHINE COMPANY
MADE IN U.S.A. SINCE 1838

240 DAY STREET, NEWINGTON, CT USA 06111-1241

TEL: 860-666-0109 FAX: 860-666-7730

INTERNET: www.merrow.com E-MAIL: info@merrow.com