This is CS50

1. Stand up and think of the number 1.

1. Stand up and think of the number 1.
2. Pair off with someone standing, add their number to yours, and remember the sum.

1. Stand up and think of the number 1.
2. Pair off with someone standing, add their number to yours, and remember the sum.
3. One of you should then sit down.

1. Stand up and think of the number 1.
2. Pair off with someone standing, add their number to yours, and remember the sum.
3. One of you should then sit down.
4. If still standing, go back to step 2.

Lists

Contacts

Search

B

Bowser

Bowser Jr.

D

Daisy

Diddy Kong

Donkey Kong

L

Luigi

M

Mario

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z #


J
John Harvard
message
call
mail
J
Contact Photo & Poster
mobile
+1 (949) 468-2750
Notes
Send Message
Share Contact
Add to Favorites


n
time to solve
size of problem


n
n/2
time to solve
size of problem


n
n/2
log2 n
time to solve
size of problem

8BBI2
D9HXT
4G85
8BBI2
D9HXT
4G85


8BB12
D9HXT
4G85



1	5	10	20	50	100	500




[0]
[1]
[2]
[3]
[4]
[5]
[6]



[0] [1] [2] [3] [4] [5] [6]

searching


input →
→ output


output


bool

algorithm

MONOPOLY
20
10
5
50
1
100
500


50
MONOPOLY®
BRAND
50
50

linear search

```
For each door from left to right
    If 50 is behind door
        Return true
Return false
```

```
For each door from left to right
    If 50 is behind door
        Return true
    Else
        Return false
```

```
For each door from left to right
    If 50 is behind door
        Return true
Return false
```

```
For i from 0 to n-1
    If 50 is behind doors[i]
        Return true
Return false
```


50
MONOPOLY®
BRAND
50
50

binary search

```
If 50 is behind middle door
    Return true
Else if 50 < middle door
    Search left half
Else if 50 > middle door
    Search right half
```

```
If no doors left

If 50 is behind middle door
    Return true
Else if 50 < middle door
    Search left half
Else if 50 > middle door
    Search right half
```

```
If no doors left
    Return false
If 50 is behind middle door
    Return true
Else if 50 < middle door
    Search left half
Else if 50 > middle door
    Search right half
```

```
If no doors left
    Return false
If 50 is behind doors[middle]
    Return true
Else if 50 < doors[middle]
    Search doors[0] through doors[middle - 1]
Else if 50 > doors[middle]
    Search doors[middle + 1] through doors[n - 1]
```

running time


time to solve
size of problem


n
n/2
log2n
time to solve
size of problem


$O(n)$
$O(n/2)$
$O(\log_2 n)$
time to solve
size of problem


$O(n)$
$O(n)$
$O(\log_2 n)$
time to solve
size of problem


O(n)
O(n)
O(log n)
time to solve
size of problem


$O(n)$
time to solve
$O(\log n)$
size of problem

O

$O(n^2)$

$O(n \log n)$

$O(n)$

$O(\log n)$

$O(1)$

$O(n^2)$

$O(n \log n)$

$O(n)$ linear search

$O(\log n)$

$O(1)$

$O(n^2)$

$O(n \log n)$

$O(n)$ linear search

$O(\log n)$ binary search

$O(1)$

Ω

$\Omega(n^2)$

$\Omega(n \log n)$

$\Omega(n)$

$\Omega(\log n)$

$\Omega(1)$

$\Omega(n^2)$

$\Omega(n \log n)$

$\Omega(n)$

$\Omega(\log n)$

$\Omega(1)$ linear search

$\Omega(n^2)$

$\Omega(n \log n)$

$\Omega(n)$

$\Omega(\log n)$

$\Omega(1)$ linear search, binary search

⊖

$\Theta(n^2)$

$\Theta(n \log n)$

$\Theta(n)$

$\Theta(\log n)$

$\Theta(1)$

asymptotic notation

linear search

string.h

manual.cs50.io/#string.h

strcmp

data structures

```
person people[2];
```

```
string name;
string number;
```

```
typedef struct
{
    string name;
    string number;
}
person;
```

```
typedef struct
{
    string name;
    string number;
} person;
```

sorting


input →
→ output


unsorted →
→ output

unsorted → [redacted] → sorted

7 2 5 4 1 6 0 3 → → sorted

7 2 5 4 1 6 0 3 → [ ] → 0 1 2 3 4 5 6 7

30 BAGS
30 BAGS
NO HFCS
NO Artificial Colors or Flavors
meiji
Hello PANDA
Chocolate
WITH OTHER NATURAL FLAVORS
Bite Size
Crème Center with Crunchy Shell
CHOCOLATE FUN WITH A CRACKER CRUNCH.
Made in USA
30 - 0.75 OZ (21g) BAGS
NET WT 22.5 OZ (1 LB 6.5 OZ) 638g
Each Bag is Packaged for Resale

7 2 5 4 1 6 0 3

selection sort



[0] [1] [2] ... [n-3] [n-2] [n-1]

```
For i from 0 to n-1
    Find smallest number between numbers[i] and numbers[n-1]
    Swap smallest number with numbers[i]
```

7 2 5 4 1 6 0 3

7 2 5 4 1 6 0 3

[i]

7	2	5	4	1	6	0	3
[i]							[n-1]

7	2	5	4	1	6	0	3
[i]							[n-1]

7	2	5	4	1	6	0	3
[i]							[n-1]

7	2	5	4	1	6	0	3
[i]							[n-1]

7	2	5	4	1	6	0	3
[i]							[n-1]

2 5 4 1 6 0 3

[i] [n-1]

0	2	5	4	1	6	3
[i]						[n-1]

0	2	5	4	1	6	7	3
[i]							[n-1]

0	2	5	4	1	6	7	3
[i]							[n-1]

0	2	5	4	1	6	7	3
	[i]						[n-1]

$(n - 1)$

$(n - 1) + (n - 2)$

$$(n - 1) + (n - 2) + (n - 3)$$

$$(n - 1) + (n - 2) + (n - 3) + \ldots + 1$$

$$(n - 1) + (n - 2) + (n - 3) + \ldots + 1$$

$$n(n - 1)/2$$

$(n - 1) + (n - 2) + (n - 3) + \ldots + 1$

$n(n - 1)/2$

$(n^2 - \mathrm{n})/2$

$(n - 1) + (n - 2) + (n - 3) + \ldots + 1$

$n(n - 1)/2$

$(n^2 - \mathrm{n})/2$

$n^2/2 - n/2$

$(n - 1) + (n - 2) + (n - 3) + \ldots + 1$

$n(n - 1)/2$

$(n^2 - \mathrm{n})/2$

$n^2/2 - n/2$

$O(n^2)$

$O(n^2)$

$O(n \log n)$

$O(n)$

$O(\log n)$

$O(1)$

$O(n^2)$ selection sort

$O(n \log n)$

$O(n)$

$O(\log n)$

$O(1)$

```
For i from 0 to n-1
    Find smallest number between numbers[i] and numbers[n-1]
    Swap smallest number with numbers[i]
```



[0] [1] [2] ... [n-3] [n-2] [n-1]

$\Omega(n^2)$

$\Omega(n \log n)$

$\Omega(n)$

$\Omega(\log n)$

$\Omega(1)$

$\Omega(n^2)$ selection sort

$\Omega(n \log n)$

$\Omega(n)$

$\Omega(\log n)$

$\Omega(1)$

$\Theta(n^2)$

$\Theta(n \log n)$

$\Theta(n)$

$\Theta(\log n)$

$\Theta(1)$

$\Theta(n^2)$ selection sort

$\Theta(n \log n)$

$\Theta(n)$

$\Theta(\log n)$

$\Theta(1)$

bubble sort



[0] [1] [2] ... [n-3] [n-2] [n-1]

```
Repeat n times
    For i from 0 to n-2
        If numbers[i] and numbers[i+1] out of order
            Swap them
```

```
Repeat n-1 times
    For i from 0 to n-2
        If numbers[i] and numbers[i+1] out of order
            Swap them
```

7 2 5 4 1 6 0 3

7 2 5 4 1 6 0 3

[i] [i+1]

2 7 5 4 1 6 0 3

[i] [i+1]

2 7 5 4 1 6 0 3

[i] [i+1]

2 5 7 4 1 6 0 3

[i] [i+1]

2 5 7 4 1 6 0 3

[i] [i+1]

2 5 4 7 1 6 0 3

[i] [i+1]

2 5 4 7 1 6 0 3

[i] [i+1]

2 5 4 1 7 6 0 3

[i] [i+1]

2 5 4 1 7 6 0 3

[i] [i+1]

2 5 4 1 6 7 0 3

[i] [i+1]

2 5 4 1 6 7 0 3

[i] [i+1]

2 5 4 1 6 0 7 3

[i] [i+1]

2 5 4 1 6 0 7 3

[i] [i+1]

2 5 4 1 6 0 3 7

[i] [i+1]

2 5 4 1 6 0 3 7

[i] [i+1]

```
Repeat n-1 times
    For i from 0 to n-2
        If numbers[i] and numbers[i+1] out of order
            Swap them
```

```
Repeat n-1 times  n-1
    For i from 0 to n-2
        If numbers[i] and numbers[i+1] out of order
            Swap them
```

```
Repeat n-1 times  n-1
    For i from 0 to n-2  n-1
        If numbers[i] and numbers[i+1] out of order
            Swap them
```

```
Repeat n-1 times  n-1
    For i from 0 to n-2  n-1
        If numbers[i] and numbers[i+1] out of order  1
            Swap them
```

```
Repeat n-1 times  n-1
    For i from 0 to n-2  n-1
        If numbers[i] and numbers[i+1] out of order  4
            Swap them
```

```
Repeat n-1 times  n-1
    For i from 0 to n-2  n-1
        If numbers[i] and numbers[i+1] out of order
            Swap them
```

$(n - 1) \times (n - 1)$

$(n - 1) \times (n - 1)$

$n^2 - 1n - 1n + 1$

$(n - 1) \times (n - 1)$

$n^2 - 1n - 1n + 1$

$n^2 - 2n + 1$

$(n - 1) \times (n - 1)$

$n^2 - 1n - 1n + 1$

$n^2 - 2n + 1$

$O(n^2)$

$O(n^2)$

$O(n \log n)$

$O(n)$

$O(\log n)$

$O(1)$

$O(n^2)$ bubble sort

$O(n \log n)$

$O(n)$

$O(\log n)$

$O(1)$

```
Repeat n-1 times
    For i from 0 to n-2
        If numbers[i] and numbers[i+1] out of order
            Swap them
```

```
Repeat n-1 times
    For i from 0 to n-2
        If numbers[i] and numbers[i+1] out of order
            Swap them
    If no swaps
        Quit
```

$\Omega(n^2)$

$\Omega(n \log n)$

$\Omega(n)$

$\Omega(\log n)$

$\Omega(1)$

$\Omega(n^2)$

$\Omega(n \log n)$

$\Omega(n)$ bubble sort

$\Omega(\log n)$

$\Omega(1)$

recursion

```
If no doors left
    Return false
If number behind middle door
    Return true
Else if number < middle door
    Search left half
Else if number > middle door
    Search right half
```

```
If no doors left
    Return false
If number behind middle door
    Return true
Else if number < middle door
    Search left half
Else if number > middle door
    Search right half
```

```
1   Pick up phone book
2   Open to middle of phone book
3   Look at page
4   If person is on page
5       Call person
6   Else if person is earlier in book
7       Open to middle of left half of book
8       Go back to line 3
9   Else if person is later in book
10      Open to middle of right half of book
11      Go back to line 3
12  Else
13      Quit
```

```
1   Pick up phone book
2   Open to middle of phone book
3   Look at page
4   If person is on page
5       Call person
6   Else if person is earlier in book
7       Open to middle of left half of book
8       Go back to line 3
9   Else if person is later in book
10      Open to middle of right half of book
11      Go back to line 3
12  Else
13      Quit
```

```
1   Pick up phone book
2   Open to middle of phone book
3   Look at page
4   If person is on page
5       Call person
6   Else if person is earlier in book
7       Open to middle of left half of book
8       Go back to line 3
9   Else if person is later in book
10      Open to middle of right half of book
11      Go back to line 3
12  Else
13      Quit
```

```
Pick up phone book
Open to middle of phone book
Look at page
If person is on page
    Call person
Else if person is earlier in book
    Search left half of book

Else if person is later in book
    Search right half of book

Else
    Quit
```

```
Pick up phone book
Open to middle of phone book
Look at page
If person is on page
    Call person
Else if person is earlier in book
    Search left half of book
Else if person is later in book
    Search right half of book
Else
    Quit
```



google.com/search?q=recursion

merge sort

Sort left half of numbers
Sort right half of numbers
Merge sorted halves

```
If only one number
    Quit
Else
    Sort left half of numbers
    Sort right half of numbers
    Merge sorted halves
```

```
If only one number
    Quit
Else
    Sort left half of numbers
    Sort right half of numbers
    Merge sorted halves
```

1 3 4 6 0 2 5 7

```
If only one number
    Quit
Else
    Sort left half of numbers
    Sort right half of numbers
    Merge sorted halves
```

6 3 4 1 5 2 7 0

6 3 4 1 5 2 7 0

6	3	4	1	5	2	7	0


5270
6341


5270
41
63


5270
41
3
6


5270
41
6
3


5270
41
3
6


5270
41
36


5270
36
41


5270
36
1
4


5270
36
4
1


5270
36
1
4


5270
36
14


5270
1
36
4


5270
13
6
4


5270
134
6

				5	2	7	0

1	3	4	6


1346
5270


1346
70
52


1346
70
2
5


1346
70
5
2


1 3 4 6
7 0
2
5


1346
70
25


1 3 4 6
2 5
7 0


1 3 4 6
2 5
0
7


1 3 4 6
2 5
7
0


1 3 4 6
2 5
0
7


1 3 4 6
2 5
0 7


1 3 4 6
0
2 5
7


1 3 4 6
0 2
5
7


1 3 4 6
0 2 5
7


1 3 4 6
0 2 5 7


0
1 3 4 6
2 5 7


0 1
3 4 6
2 5 7


0 1 2
3 4 6
5 7


0 1 2 3
4 6
5 7


0 1 2 3 4
6
5 7


0 1 2 3 4 5
6
7

0	1	2	3	4	5	6	

7

0	1	2	3	4	5	6	7

0 1 2 3 4 5 6 7

$O(n^2)$

$O(n \log n)$

$O(n)$

$O(\log n)$

$O(1)$


6 3 4 1 5 2 7 0
6 3 4 1
5 2 7 0
6 3
4 1
5 2
7 0
6
3
4
1
5
2
7
0


6 3 4 1 5 2 7 0
6 3 4 1
5 2 7 0
6 3
4 1
5 2
7 0
6
3
4
1
5
2
7
0

$$\log_2 n$$

$$\log_2 8$$

$$\log_2 2^3$$

3


6 3 4 1 5 2 7 0
6 3 4 1
5 2 7 0
6 3
4 1
5 2
7 0
6
3
4
1
5
2
7
0

$$n \log_2 n$$

$n \log n$

$O(n^2)$

$O(n \log n)$ merge sort

$O(n)$

$O(\log n)$

$O(1)$

$\Omega(n^2)$

$\Omega(n \log n)$ merge sort

$\Omega(n)$

$\Omega(\log n)$

$\Omega(1)$

$\Theta(n^2)$

$\Theta(n \log n)$ merge sort

$\Theta(n)$

$\Theta(\log n)$

$\Theta(1)$



This is CS50