

# Divide-and-Conquer: Quick Sort

Alexander S. Kulikov

Steklov Institute of Mathematics at St. Petersburg  
Russian Academy of Sciences

**Algorithmic Design and Techniques**  
**Algorithms and Data Structures**

# Outline

- 1 Overview
- 2 Algorithm
- 3 Random Pivot
- 4 Running Time Analysis
- 5 Equal Elements
- 6 Final Remarks

# Quick Sort

- comparison based algorithm
- running time:  $O(n \log n)$  (on average)
- efficient in practice

## Example: quick sort

6	4	8	2	9	3	9	4	7	6	1
---	---	---	---	---	---	---	---	---	---	---

## Example: quick sort

6	4	8	2	9	3	9	4	7	6	1
---	---	---	---	---	---	---	---	---	---	---

partition with respect to  $x = A[1]$   
in particular,  $x$  is in its final position

1	4	2	3	4	6	6	9	7	8	9
---	---	---	---	---	---	---	---	---	---	---

$\leq 6$

$> 6$

## Example: quick sort

6	4	8	2	9	3	9	4	7	6	1
---	---	---	---	---	---	---	---	---	---	---

partition with respect to  $x = A[1]$   
in particular,  $x$  is in its final position

1	4	2	3	4	6	6	9	7	8	9
---	---	---	---	---	---	---	---	---	---	---

sort the two parts recursively

1	2	3	4	4	6	6	7	8	9	9
---	---	---	---	---	---	---	---	---	---	---

# Outline

- 1 Overview
- 2 **Algorithm**
- 3 Random Pivot
- 4 Running Time Analysis
- 5 Equal Elements
- 6 Final Remarks

QuickSort( $A, \ell, r$ )

if  $\ell \geq r$ :

    return

$m \leftarrow \text{Partition}(A, \ell, r)$


$\{A[m] \text{ is in the final position}\}$


QuickSort( $A, \ell, m - 1$ )

QuickSort( $A, m + 1, r$ )









## Partitioning: example

- the pivot is  $x = A[\ell]$

## Partitioning: example

- the pivot is  $x = A[\ell]$
- move  $i$  from  $\ell + 1$  to  $r$  maintaining the following invariant:

## Partitioning: example


- the pivot is  $x = A[\ell]$
- move  $i$  from  $\ell + 1$  to  $r$  maintaining the following invariant:
  - $A[k] \leq x$  for all  $\ell + 1 \leq k \leq j$

## Partitioning: example

- the pivot is  $x = A[\ell]$
- move  $i$  from  $\ell + 1$  to  $r$  maintaining the following invariant:
  - $A[k] \leq x$  for all  $\ell + 1 \leq k \leq j$
  - $A[k] > x$  for all  $j + 1 \leq k \leq i$

# Partitioning: example


- the pivot is  $x = A[\ell]$
- move  $i$  from  $\ell + 1$  to  $r$  maintaining the following invariant:
  - $A[k] \leq x$  for all  $\ell + 1 \leq k \leq j$
  - $A[k] > x$  for all  $j + 1 \leq k \leq i$






# Partitioning: example

- the pivot is  $x = A[\ell]$
- move  $i$  from  $\ell + 1$  to  $r$  maintaining the following invariant:
  - $A[k] \leq x$  for all  $\ell + 1 \leq k \leq j$
  - $A[k] > x$  for all  $j + 1 \leq k \leq i$




# Partitioning: example

- the pivot is  $x = A[\ell]$
- move  $i$  from  $\ell + 1$  to  $r$  maintaining the following invariant:
  - $A[k] \leq x$  for all  $\ell + 1 \leq k \leq j$
  - $A[k] > x$  for all  $j + 1 \leq k \leq i$




# Partitioning: example

- the pivot is  $x = A[\ell]$
- move  $i$  from  $\ell + 1$  to  $r$  maintaining the following invariant:
  - $A[k] \leq x$  for all  $\ell + 1 \leq k \leq j$
  - $A[k] > x$  for all  $j + 1 \leq k \leq i$




# Partitioning: example

- the pivot is  $x = A[\ell]$
- move  $i$  from  $\ell + 1$  to  $r$  maintaining the following invariant:
  - $A[k] \leq x$  for all  $\ell + 1 \leq k \leq j$
  - $A[k] > x$  for all  $j + 1 \leq k \leq i$




# Partitioning: example

- the pivot is  $x = A[\ell]$
- move  $i$  from  $\ell + 1$  to  $r$  maintaining the following invariant:
  - $A[k] \leq x$  for all  $\ell + 1 \leq k \leq j$
  - $A[k] > x$  for all  $j + 1 \leq k \leq i$




# Partitioning: example

- the pivot is  $x = A[\ell]$
- move  $i$  from  $\ell + 1$  to  $r$  maintaining the following invariant:
  - $A[k] \leq x$  for all  $\ell + 1 \leq k \leq j$
  - $A[k] > x$  for all  $j + 1 \leq k \leq i$




# Partitioning: example

- the pivot is  $x = A[\ell]$
- move  $i$  from  $\ell + 1$  to  $r$  maintaining the following invariant:
  - $A[k] \leq x$  for all  $\ell + 1 \leq k \leq j$
  - $A[k] > x$  for all  $j + 1 \leq k \leq i$



# Partitioning: example


- the pivot is  $x = A[\ell]$
- move  $i$  from  $\ell + 1$  to  $r$  maintaining the following invariant:
  - $A[k] \leq x$  for all  $\ell + 1 \leq k \leq j$
  - $A[k] > x$  for all  $j + 1 \leq k \leq i$






# Partitioning: example

- the pivot is  $x = A[\ell]$
- move  $i$  from  $\ell + 1$  to  $r$  maintaining the following invariant:
  - $A[k] \leq x$  for all  $\ell + 1 \leq k \leq j$
  - $A[k] > x$  for all  $j + 1 \leq k \leq i$




# Partitioning: example

- the pivot is  $x = A[\ell]$
- move  $i$  from  $\ell + 1$  to  $r$  maintaining the following invariant:
  - $A[k] \leq x$  for all  $\ell + 1 \leq k \leq j$
  - $A[k] > x$  for all  $j + 1 \leq k \leq i$




# Partitioning: example

- the pivot is  $x = A[\ell]$
- move  $i$  from  $\ell + 1$  to  $r$  maintaining the following invariant:
  - $A[k] \leq x$  for all  $\ell + 1 \leq k \leq j$
  - $A[k] > x$  for all  $j + 1 \leq k \leq i$




# Partitioning: example

- the pivot is  $x = A[\ell]$
- move  $i$  from  $\ell + 1$  to  $r$  maintaining the following invariant:
  - $A[k] \leq x$  for all  $\ell + 1 \leq k \leq j$
  - $A[k] > x$  for all  $j + 1 \leq k \leq i$




# Partitioning: example

- the pivot is  $x = A[\ell]$
- move  $i$  from  $\ell + 1$  to  $r$  maintaining the following invariant:
  - $A[k] \leq x$  for all  $\ell + 1 \leq k \leq j$
  - $A[k] > x$  for all  $j + 1 \leq k \leq i$




# Partitioning: example

- the pivot is  $x = A[\ell]$
- move  $i$  from  $\ell + 1$  to  $r$  maintaining the following invariant:
  - $A[k] \leq x$  for all  $\ell + 1 \leq k \leq j$
  - $A[k] > x$  for all  $j + 1 \leq k \leq i$




# Partitioning: example

- the pivot is  $x = A[\ell]$
- move  $i$  from  $\ell + 1$  to  $r$  maintaining the following invariant:
  - $A[k] \leq x$  for all  $\ell + 1 \leq k \leq j$
  - $A[k] > x$  for all  $j + 1 \leq k \leq i$



## Partitioning: example


- the pivot is  $x = A[\ell]$
- move  $i$  from  $\ell + 1$  to  $r$  maintaining the following invariant:
  - $A[k] \leq x$  for all  $\ell + 1 \leq k \leq j$
  - $A[k] > x$  for all  $j + 1 \leq k \leq i$
- in the end, move  $A[\ell]$  to its final place






# Partitioning: example

- the pivot is  $x = A[\ell]$
- move  $i$  from  $\ell + 1$  to  $r$  maintaining the following invariant:
  - $A[k] \leq x$  for all  $\ell + 1 \leq k \leq j$
  - $A[k] > x$  for all  $j + 1 \leq k \leq i$
- in the end, move  $A[\ell]$  to its final place



## Partitioning: example

- the pivot is  $x = A[\ell]$
- move  $i$  from  $\ell + 1$  to  $r$  maintaining the following invariant:
  - $A[k] \leq x$  for all  $\ell + 1 \leq k \leq j$
  - $A[k] > x$  for all  $j + 1 \leq k \leq i$
- in the end, move  $A[\ell]$  to its final place



## Partition( $A, \ell, r$ )

```
x ← A[ℓ]    {pivot}
j ← ℓ
for i from ℓ + 1 to r:
    if A[i] ≤ x:
        j ← j + 1
        swap A[j] and A[i]
    {A[ℓ + 1...j] ≤ x, A[j + 1...i] > x}
swap A[ℓ] and A[j]
return j
```

# Outline

- 1 Overview
- 2 Algorithm
- 3 Random Pivot**
- 4 Running Time Analysis
- 5 Equal Elements
- 6 Final Remarks

# Unbalanced Partitions

- $T(n) = n + T(n - 1)$ :

$$T(n) = n + (n-1) + (n-2) + \dots = \Theta(n^2)$$

# Unbalanced Partitions

- $T(n) = n + T(n - 1):$

$$T(n) = n + (n-1) + (n-2) + \dots = \Theta(n^2)$$

- $T(n) = n + T(n - 5) + T(4):$

$$T(n) \geq n + (n-5) + (n-10) + \dots = \Theta(n^2)$$

# Balanced Partitions

- $T(n) = 2T(n/2) + n$ :

$$T(n) = \Theta(n \log n)$$

# Balanced Partitions

- $T(n) = 2T(n/2) + n$ :

$$T(n) = \Theta(n \log n)$$

- $T(n) = T(n/10) + T(9n/10) + n$ :

$$T(n) = \Theta(n \log n)$$




# Balanced Partitions

$$T(n) = T(n/10) + T(9n/10) + O(n)$$


# Balanced Partitions

$$T(n) = T(n/10) + T(9n/10) + O(n)$$



# Balanced Partitions

$$T(n) = T(n/10) + T(9n/10) + O(n)$$



$$T(n) = O(n \log n)$$

# Random Pivot

RandomizedQuickSort( $A, \ell, r$ )

if  $\ell \geq r$ :

    return

$k \leftarrow$  random number between  $\ell$  and  $r$

    swap  $A[\ell]$  and  $A[k]$

$m \leftarrow \text{Partition}(A, \ell, r)$


    { $A[m]$  is in the final position}

    RandomizedQuickSort( $A, \ell, m - 1$ )

    RandomizedQuickSort( $A, m + 1, r$ )

# Why Random?

half of the elements of  $A$  guarantees a balanced partition:



## Theorem

Assume that all the elements of  $A[1 \dots n]$  are pairwise different. Then the average running time of `RandomizedQuickSort(A)` is  $O(n \log n)$  while the worst case running time is  $O(n^2)$ .

## Theorem

Assume that all the elements of  $A[1 \dots n]$  are pairwise different. Then the average running time of `RandomizedQuickSort(A)` is  $O(n \log n)$  while the worst case running time is  $O(n^2)$ .

## Remark

Averaging is over random numbers used by the algorithm, but not over the inputs.

# Outline

- 1 Overview
- 2 Algorithm
- 3 Random Pivot
- 4 Running Time Analysis**
- 5 Equal Elements
- 6 Final Remarks




# Proof Ideas: Comparisons

- the running time is proportional to the number of comparisons made

# Proof Ideas: Comparisons

- the running time is proportional to the number of comparisons made
- balanced partition are better since they reduce the number of comparisons needed:



# Proof Ideas: Probability

$A$	5	1	8	9	2	4	7	3	6
$A'$	1	2	3	4	5	6	7	8	9

# Proof Ideas: Probability

$A$	5	1	8	9	2	4	7	3	6
$A'$	1	2	3	4	5	6	7	8	9

Prob (1 and 9 are compared) =

# Proof Ideas: Probability

$A$	5	1	8	9	2	4	7	3	6
$A'$	1	2	3	4	5	6	7	8	9

$$\text{Prob}(1 \text{ and } 9 \text{ are compared}) = \frac{2}{9}$$

# Proof Ideas: Probability

$A$	5	1	8	9	2	4	7	3	6
$A'$	1	2	3	4	5	6	7	8	9

$$\text{Prob}(1 \text{ and } 9 \text{ are compared}) = \frac{2}{9}$$

$$\text{Prob}(3 \text{ and } 4 \text{ are compared}) =$$

# Proof Ideas: Probability

$A$	5	1	8	9	2	4	7	3	6
$A'$	1	2	3	4	5	6	7	8	9

$$\text{Prob}(1 \text{ and } 9 \text{ are compared}) = \frac{2}{9}$$

$$\text{Prob}(3 \text{ and } 4 \text{ are compared}) = 1$$

# Proof

- let, for  $i < j$ ,

$$\chi_{ij} = \begin{cases} 1 & A'[i] \text{ and } A'[j] \text{ are compared} \\ 0 & \text{otherwise} \end{cases}$$



# Proof

- let, for  $i < j$ ,

$$\chi_{ij} = \begin{cases} 1 & A'[i] \text{ and } A'[j] \text{ are compared} \\ 0 & \text{otherwise} \end{cases}$$

- for all  $i < j$ ,  $A'[i]$  and  $A'[j]$  are either compared exactly once or not compared at all (as we compare with a pivot)

# Proof

- let, for  $i < j$ ,

$$\chi_{ij} = \begin{cases} 1 & A'[i] \text{ and } A'[j] \text{ are compared} \\ 0 & \text{otherwise} \end{cases}$$

- for all  $i < j$ ,  $A'[i]$  and  $A'[j]$  are either compared exactly once or not compared at all (as we compare with a pivot)
- this, in particular, implies that the worst case running time is  $O(n^2)$

# Proof (continued)

- crucial observation:  $\chi_{ij} = 1$  iff the first selected pivot in  $A'[i \dots j]$  is  $A'[i]$  or  $A'[j]$

# Proof (continued)

- crucial observation:  $\chi_{ij} = 1$  iff the first selected pivot in  $A'[i \dots j]$  is  $A'[i]$  or  $A'[j]$
- then  $\text{Prob}(\chi_{ij}) = \frac{2}{j-i+1}$  and  $E(\chi_{ij}) = \frac{2}{j-i+1}$

## Proof (continued)

Then (the expected value of) the running time is

$$\begin{aligned} \mathbb{E} \sum_{i=1}^n \sum_{j=i+1}^n \chi_{ij} &= \sum_{i=1}^n \sum_{j=i+1}^n \mathbb{E}(\chi_{ij}) \\ &= \sum_{i < j} \frac{2}{j - i + 1} \\ &\leq 2n \cdot \left( \frac{1}{2} + \frac{1}{3} + \dots + \frac{1}{n} \right) \\ &= \Theta(n \log n) \end{aligned}$$

# Outline

- 1 Overview
- 2 Algorithm
- 3 Random Pivot
- 4 Running Time Analysis
- 5 Equal Elements**
- 6 Final Remarks

# Equal Elements

- what if all the elements of the given array are equal to each other?

# Equal Elements

- what if all the elements of the given array are equal to each other?
- quick sort visualization



# Equal Elements

- what if all the elements of the given array are equal to each other?
- quick sort visualization
- the array is always split into two parts of size 0 and  $n - 1$

# Equal Elements

- what if all the elements of the given array are equal to each other?
- quick sort visualization
- the array is always split into two parts of size 0 and  $n - 1$
- $T(n) = n + T(n - 1) + T(0)$  and hence  $T(n) = \Theta(n^2)$ !

To handle equal elements, we replace the line

$$m \leftarrow \text{Partition}(A, \ell, r)$$

with the line


$$(m_1, m_2) \leftarrow \text{Partition3}(A, \ell, r)$$

such that

- for all  $\ell \leq k \leq m_1 - 1$ ,  $A[k] < x$
- for all  $m_1 \leq k \leq m_2$ ,  $A[k] = x$
- for all  $m_2 + 1 \leq k \leq r$ ,  $A[k] > x$



$(m_1, m_2) \leftarrow \text{Partition3}(A, \ell, r)$



## RandomizedQuickSort( $A, \ell, r$ )

if  $\ell \geq r$ :

return

$k \leftarrow$  random number between  $\ell$  and  $r$

swap  $A[\ell]$  and  $A[k]$

$(m_1, m_2) \leftarrow \text{Partition3}(A, \ell, r)$

$\{A[m_1 \dots m_2] \text{ is in final position}\}$

RandomizedQuickSort( $A, \ell, m_1 - 1$ )

RandomizedQuickSort( $A, m_2 + 1, r$ )

# Outline

- 1 Overview
- 2 Algorithm
- 3 Random Pivot
- 4 Running Time Analysis
- 5 Equal Elements
- 6 Final Remarks

# Tail Recursion Elimination

QuickSort( $A, \ell, r$ )

while  $\ell < r$ :

$m \leftarrow \text{Partition}(A, \ell, r)$

    QuickSort( $A, \ell, m - 1$ )

$\ell \leftarrow m + 1$

## QuickSort( $A, \ell, r$ )

while  $\ell < r$ :

$m \leftarrow \text{Partition}(A, \ell, r)$

    if  $(m - \ell) < (r - m)$ :

        QuickSort( $A, \ell, m - 1$ )

$\ell \leftarrow m + 1$

    else:

        QuickSort( $A, m + 1, r$ )

$r \leftarrow m - 1$



## QuickSort( $A, \ell, r$ )

```
while  $\ell < r$ :  
     $m \leftarrow \text{Partition}(A, \ell, r)$   
    if  $(m - \ell) < (r - m)$ :  
        QuickSort( $A, \ell, m - 1$ )  
         $\ell \leftarrow m + 1$   
    else:  
        QuickSort( $A, m + 1, r$ )  
         $r \leftarrow m - 1$ 
```

Worst-case space requirement:  $O(\log n)$

# Intro Sort

- runs quick sort with a simple deterministic pivot selection heuristic (say, median of the first, middle, and last element)

# Intro Sort

- runs quick sort with a simple deterministic pivot selection heuristic (say, median of the first, middle, and last element)
- if the recursion depth exceeds a certain threshold  $c \log n$  the algorithm switches to heap sort

# Intro Sort

- runs quick sort with a simple deterministic pivot selection heuristic (say, median of the first, middle, and last element)
- if the recursion depth exceeds a certain threshold  $c \log n$  the algorithm switches to heap sort
- the running time is  $O(n \log n)$  in the worst case

# Conclusion

- Quick sort is a comparison based algorithm

# Conclusion

- Quick sort is a comparison based algorithm
- Running time:  $O(n \log n)$  on average,  $O(n^2)$  in the worst case

# Conclusion

- Quick sort is a comparison based algorithm
- Running time:  $O(n \log n)$  on average,  $O(n^2)$  in the worst case
- Efficient in practice