

Minimum Bisection is NP-hard on Unit Disk Graphs

Josep Díaz¹ George B. Mertzios²

¹Universitat Politècnica de Catalunya, Spain.

²School of Engineering and Computing Sciences, Durham University, UK.

MFCS 2014

Graph partitioning

Graph partitioning:

- appropriately partitioning the vertices of a graph into subsets that fulfill certain conditions

Many practical applications:

- computer vision
- image processing
- VLSI layout design
- parallel computing
 - evenly distribute the computational load to processors, while minimizing processor communication
- sub-routine in many *divide-and-conquer* algorithms

For an overview: [Bichot, Siarry, *Graph Partitioning*, 2011]

Graph partitioning - terminology

Definition

Given a graph $G = (V, E)$ and $k \geq 2$, a **balanced k -partition** of G is a partition of V into sets V_1, V_2, \dots, V_k such that $|V_i| \leq \left\lceil \frac{|V|}{k} \right\rceil$, $1 \leq i \leq k$.

Graph partitioning - terminology

Definition

Given a graph $G = (V, E)$ and $k \geq 2$, a **balanced k -partition** of G is a partition of V into sets V_1, V_2, \dots, V_k such that $|V_i| \leq \left\lceil \frac{|V|}{k} \right\rceil$, $1 \leq i \leq k$.

The **cut size** of this partition is the **number of edges** of G with endpoints on V_i and V_j , where $i \neq j$.

Graph partitioning - terminology

Definition

Given a graph $G = (V, E)$ and $k \geq 2$, a **balanced k -partition** of G is a partition of V into sets V_1, V_2, \dots, V_k such that $|V_i| \leq \left\lceil \frac{|V|}{k} \right\rceil$, $1 \leq i \leq k$.

The **cut size** of this partition is the **number of edges** of G with endpoints on V_i and V_j , where $i \neq j$.

- For $k = 2$: **bisection** of G

Problem (MIN-BISECTION)

Input: a graph G

*Goal: compute a **bisection** of G with the **minimum** possible **size** (also known as the **bisection width** of G)*

Minimum bisection

MIN-BISECTION is **NP-hard**:

- on general graphs [Garey, Johnson, 1979]
- on everywhere dense graphs ($\deg(v) = \Omega(n)$ for every vertex v)
- on bounded maximum degree graphs [MacGregor, 1978]
- on d -regular graphs [Bui, Chaudhuri, Leighton, Sipser, 1987]

Minimum bisection

MIN-BISECTION is **NP-hard**:

- on general graphs [Garey, Johnson, 1979]
- on everywhere dense graphs ($\deg(v) = \Omega(n)$ for every vertex v)
- on bounded maximum degree graphs [MacGregor, 1978]
- on d -regular graphs [Bui, Chaudhuri, Leighton, Sipser, 1987]

Due to its wide applications:

- many **heuristics** and **exact algorithms** appeared since the 70's
[Kernighan, Lin, *Bell System Technical Journal*, 1978]
[Delling et al., *ALLENEX*, 2012]

On the positive side (theoretically):

- **fixed parameter tractable** [Cygan et al., *STOC*, 2014]
- the currently best **approximation ratio** is $O(\log n)$
[Räcke, *STOC*, 2008]

Minimum bisection

MIN-BISECTION is solvable in **polynomial** time:

- on trees and hypercubes [MacGregor, *PhD thesis - Berkeley*, 1978]
[Díaz, Petit, Serna, *ACM Comp. Surveys*, 2002]
- on graphs with bounded treewidth
[Jansen et al., *SIAM Journal on Computing*, 2005]
- on solid grid graphs (no holes)
 - in $O(n^5)$ -time [Papadimitriou, Sideri, *Math. Systems Theory*, 1996]
(and $O(n^{5+2h})$ -time for a grid graph with h holes)
 - in $O(n^4)$ -time [Feldmann, Widmayer, *ESA*, 2011]

Minimum bisection

MIN-BISECTION is solvable in **polynomial** time:

- on trees and hypercubes [MacGregor, *PhD thesis - Berkeley*, 1978]
[Díaz, Petit, Serna, *ACM Comp. Surveys*, 2002]
- on graphs with bounded treewidth
[Jansen et al., *SIAM Journal on Computing*, 2005]
- on solid grid graphs (no holes)
 - in $O(n^5)$ -time [Papadimitriou, Sideri, *Math. Systems Theory*, 1996]
(and $O(n^{5+2h})$ -time for a grid graph with h holes)
 - in $O(n^4)$ -time [Feldmann, Widmayer, *ESA*, 2011]

Open problems so far:

- **planar** graphs

Minimum bisection

MIN-BISECTION is solvable in **polynomial** time:

- on trees and hypercubes [MacGregor, *PhD thesis - Berkeley*, 1978]
[Díaz, Petit, Serna, *ACM Comp. Surveys*, 2002]
- on graphs with bounded treewidth
[Jansen et al., *SIAM Journal on Computing*, 2005]
- on solid grid graphs (no holes)
 - in $O(n^5)$ -time [Papadimitriou, Sideri, *Math. Systems Theory*, 1996]
(and $O(n^{5+2h})$ -time for a grid graph with h holes)
 - in $O(n^4)$ -time [Feldmann, Widmayer, *ESA*, 2011]

Open problems so far:

- **planar** graphs
- **grid** graphs with **arbitrary** number of **holes**

Minimum bisection

MIN-BISECTION is solvable in **polynomial** time:

- on trees and hypercubes [MacGregor, *PhD thesis - Berkeley*, 1978]
[Díaz, Petit, Serna, *ACM Comp. Surveys*, 2002]
- on graphs with bounded treewidth
[Jansen et al., *SIAM Journal on Computing*, 2005]
- on solid grid graphs (no holes)
 - in $O(n^5)$ -time [Papadimitriou, Sideri, *Math. Systems Theory*, 1996]
(and $O(n^{5+2h})$ -time for a grid graph with h holes)
 - in $O(n^4)$ -time [Feldmann, Widmayer, *ESA*, 2011]

Open problems so far:

- **planar** graphs
- **grid** graphs with **arbitrary** number of **holes**
- **unit disk** graphs

Minimum bisection

The first two problems are equivalent:

- MIN-BISECTION on planar \leq MIN-BISECTION on grid with holes [Papadimitriou, Sideri, *Math. Systems Theory*, 1996]
- MIN-BISECTION on grid with holes \leq MIN-BISECTION on planar (subclass)

Minimum bisection

The first two problems are equivalent:

- MIN-BISECTION on planar \leq MIN-BISECTION on grid with holes [Papadimitriou, Sideri, *Math. Systems Theory*, 1996]
- MIN-BISECTION on grid with holes \leq MIN-BISECTION on planar (subclass)

Furthermore:

- MIN-BISECTION on planar graphs with max. degree 4 \leq MIN-BISECTION on unit disk graphs [Díaz et al., *Journal of Algorithms*, 2001]

Minimum bisection

The first two problems are equivalent:

- MIN-BISECTION on planar \leq MIN-BISECTION on grid with holes [Papadimitriou, Sideri, *Math. Systems Theory*, 1996]
- MIN-BISECTION on grid with holes \leq MIN-BISECTION on planar (subclass)

Furthermore:

- MIN-BISECTION on planar graphs with max. degree 4 \leq MIN-BISECTION on unit disk graphs [Díaz et al., *Journal of Algorithms*, 2001]

Therefore, for MIN-BISECTION:

- planar graphs \Leftrightarrow grid with holes \leq unit disk graphs

Minimum bisection

The first two problems are equivalent:

- MIN-BISECTION on planar \leq MIN-BISECTION on grid with holes [Papadimitriou, Sideri, *Math. Systems Theory*, 1996]
- MIN-BISECTION on grid with holes \leq MIN-BISECTION on planar (subclass)

Furthermore:

- MIN-BISECTION on planar graphs with max. degree 4 \leq MIN-BISECTION on unit disk graphs [Díaz et al., *Journal of Algorithms*, 2001]

Therefore, for MIN-BISECTION:

- planar graphs \Leftrightarrow grid with holes \leq unit disk graphs

Our result:


Theorem

MIN-BISECTION is *NP-complete* on unit disk graphs.

Disk graphs and unit disk graphs

Definition

A graph $G = (V, E)$ is a **disk graph** if we can assign every **vertex** $v \in V$ to a **disk** D_v in the plane such that $uv \in E$ if and only if $D_u \cap D_v \neq \emptyset$.




Disk graphs and unit disk graphs

Definition

A graph $G = (V, E)$ is a **disk graph** if we can assign every **vertex** $v \in V$ to a **disk** D_v in the plane such that $uv \in E$ if and only if $D_u \cap D_v \neq \emptyset$.

A disk graph G is a **unit disk graph** if it can be drawn in such a way that every disk D_v has **equal radius** (e.g. **radius 1**).



Disk graphs and unit disk graphs

Alternative Definition

A disk graph $G = (V, E)$ is a **unit disk graph** if we can associate every vertex $v \in V$ to a point p_v in the plane, such that $uv \in E$ if and only if the distance between p_u and p_v is at most a fixed constant c (e.g. $c = 1$).

- we use the first definition with the **unit disks**

Disk graphs and unit disk graphs

Alternative Definition

A disk graph $G = (V, E)$ is a **unit disk graph** if we can associate every **vertex** $v \in V$ to a **point** p_v in the plane, such that $uv \in E$ if and only if the **distance** between p_u and p_v is at most a **fixed** constant c (e.g. $c = 1$).

- we use the first definition with the **unit disks**

(Unit) disk graphs: appear naturally in wireless communication networks

- **center** of a disk \longrightarrow the **position** of a device (phone, antenna, ...)
- **radius** \longrightarrow the **distance** that a wireless signal can reach
- the **bisection width** determines the communication **bandwidth**

Disk graphs and unit disk graphs

Alternative Definition

A disk graph $G = (V, E)$ is a **unit disk graph** if we can associate every vertex $v \in V$ to a **point** p_v in the plane, such that $uv \in E$ if and only if the **distance** between p_u and p_v is at most a **fixed** constant c (e.g. $c = 1$).

- we use the first definition with the **unit disks**

(Unit) disk graphs: appear naturally in wireless communication networks

- **center** of a disk \rightarrow the **position** of a device (phone, antenna, ...)
- **radius** \rightarrow the **distance** that a wireless signal can reach
- the **bisection width** determines the communication **bandwidth**

Theorem (Kratochvíl, 1996; Breu et al., 1998)

Given a graph G , it is NP-hard to decide whether G is a (unit) disk graph.

- but (unit) disk graphs usually come along with a given representation

MIN-BISECTION on unit disk graphs

Theorem

MIN-BISECTION is *NP-complete* on *unit disk* graphs.

Proof: reduction from a variant of *maximum satisfiability*

Problem (monotone Max-XOR(3))

Input:

- an *XOR-formula* ϕ with variables x_1, x_2, \dots, x_n , i.e. a boolean formula that is the *conjunction* of *XOR-clauses* of the form $(x_i \oplus x_k)$
- ϕ is *monotone*, i.e. no variable is negated
- every *variable* x_i appears in *exactly 3 clauses* of ϕ

Goal:

- compute a truth assignment that XOR-satisfies most clauses of ϕ

MIN-BISECTION on unit disk graphs

Overview of the reduction

- A clause $(x_i \oplus x_k)$ is **XOR-satisfied** if:
 - either $x_i = 0$ and $x_k = 1$
 - or $x_i = 1$ and $x_k = 0$
- We can decide in **polynomial** time whether ϕ is **XOR-satisfiable**, but:

Lemma

Monotone Max-XOR(3) is NP-hard.

MIN-BISECTION on unit disk graphs

Overview of the reduction

- A clause $(x_i \oplus x_k)$ is **XOR-satisfied** if:
 - either $x_i = 0$ and $x_k = 1$
 - or $x_i = 1$ and $x_k = 0$
- We can decide in **polynomial** time whether ϕ is **XOR-satisfiable**, but:

Lemma

Monotone Max-XOR(3) is NP-hard.

- Given a monotone XOR(3)-formula ϕ with n variables, we construct:
 - an auxiliary **unit disk graph** G_n from n and
 - a **unit disk graph** H_ϕ from G_n and ϕ

MIN-BISECTION on unit disk graphs

Overview of the reduction

- A clause $(x_i \oplus x_k)$ is **XOR-satisfied** if:
 - either $x_i = 0$ and $x_k = 1$
 - or $x_i = 1$ and $x_k = 0$
- We can decide in **polynomial** time whether ϕ is **XOR-satisfiable**, but:

Lemma

Monotone Max-XOR(3) is NP-hard.

- Given a monotone XOR(3)-formula ϕ with n variables, we construct:
 - an auxiliary **unit disk graph** G_n from n and
 - a **unit disk graph** H_ϕ from G_n and ϕ


Theorem

ϕ a **truth assignment** that XOR-satisfies at **least** k clauses

$\Leftrightarrow H_\phi$ has a **bisection** with value at **most** $2n^4(n-1) + 3n - 2k$.


The auxiliary unit disk graph G_n

- For every **variable** x_i :
 - we define two (non-straight) lines $T_{i,0}$ and $T_{i,1}$ (called **tracks** of x_i)



The auxiliary unit disk graph G_n

- For every **variable** x_i :
 - we define two (non-straight) lines $T_{i,0}$ and $T_{i,1}$ (called **tracks of x_i**)
- If $i \neq k$ then:
 - the tracks $T_{i,j}$ and $T_{k,\ell}$ intersect in exactly one point



The auxiliary unit disk graph G_n

- For every **variable** x_i :
 - we define two (non-straight) lines $T_{i,0}$ and $T_{i,1}$ (called **tracks of x_i**)
- If $i \neq k$ then:
 - the tracks $T_{i,j}$ and $T_{k,\ell}$ intersect in exactly one point
- The centers of all unit disks of G_n lie on some track $T_{i,j}$
- Every track has the same number of disk centers

The auxiliary unit disk graph G_n

- For every **variable** x_i :
 - we define two (non-straight) lines $T_{i,0}$ and $T_{i,1}$ (called **tracks of** x_i)
- If $i \neq k$ then:
 - the tracks $T_{i,j}$ and $T_{k,\ell}$ intersect in exactly one point
- The centers of all unit disks of G_n lie on some track $T_{i,j}$
- Every track has the same number of disk centers
- Intuition of the construction:
 - $x_i = 0 \iff$ the disks of $T_{i,0}$ (resp. $T_{i,1}$) are **blue** (resp. **red**)

The auxiliary unit disk graph G_n

- For every **variable** x_i :
 - we define two (non-straight) lines $T_{i,0}$ and $T_{i,1}$ (called **tracks of x_i**)
- If $i \neq k$ then:
 - the tracks $T_{i,j}$ and $T_{k,\ell}$ intersect in exactly one point
- The centers of all unit disks of G_n lie on some track $T_{i,j}$
- Every track has the same number of disk centers
- Intuition of the construction:
 - $x_i = 0 \Leftrightarrow$ the disks of $T_{i,0}$ (resp. $T_{i,1}$) are **blue** (resp. **red**)
 - $x_i = 1 \Leftrightarrow$ the disks of $T_{i,0}$ (resp. $T_{i,1}$) are **red** (resp. **blue**)


The auxiliary unit disk graph G_n

- For every **variable** x_i :
 - we define two (non-straight) lines $T_{i,0}$ and $T_{i,1}$ (called **tracks of x_i**)
- If $i \neq k$ then:
 - the tracks $T_{i,j}$ and $T_{k,\ell}$ intersect in exactly one point
- The centers of all unit disks of G_n lie on some track $T_{i,j}$
- Every track has the same number of disk centers
- Intuition of the construction:
 - $x_i = 0 \Leftrightarrow$ the disks of $T_{i,0}$ (resp. $T_{i,1}$) are **blue** (resp. **red**)
 - $x_i = 1 \Leftrightarrow$ the disks of $T_{i,0}$ (resp. $T_{i,1}$) are **red** (resp. **blue**)
- **Main challenge** at every **intersection point p** of **two tracks**:
 - arrange the disk centers such that every track has the **same color** on **both sides** of p
 - this should happen **regardless** of the color of the other track!

The auxiliary unit disk graph G_n

Solution to this challenge:


- use **large cliques** (i.e. disks centered closely to each other)
- ① At the **intersection point p** of two tracks $T_{i,j}$ and $T_{k,\ell}$:



The auxiliary unit disk graph G_n

Solution to this challenge:

- use **large cliques** (i.e. disks centered closely to each other)
- ② At the **bend point** p of a tracks $T_{i,j}$:



The auxiliary unit disk graph G_n

Solution to this challenge:

- use **large cliques** (i.e. disks centered closely to each other)

Therefore:

Lemma

Let \mathcal{B} be a **bisection** of G_n with **size less than n^6** .

Then for every track $T_{i,j}$, **all disks** on $T_{i,j}$ have the **same color** in \mathcal{B} .

The auxiliary unit disk graph G_n

Solution to this challenge:

- use **large cliques** (i.e. disks centered closely to each other)

Therefore:

Lemma

Let \mathcal{B} be a **bisection** of G_n with **size less than n^6** .

Then for every track $T_{i,j}$, **all disks** on $T_{i,j}$ have the **same color** in \mathcal{B} .

Furthermore, we can prove:

Lemma

Let \mathcal{B} be a **minimum bisection** of G_n with **size less than n^6** . Then, for every $1 \leq i \leq n$, the tracks $T_{i,0}$ and $T_{i,1}$ have **different colors** in \mathcal{B} .

The auxiliary unit disk graph G_n

Solution to this challenge:

- use **large cliques** (i.e. disks centered closely to each other)

Therefore:

Lemma

Let \mathcal{B} be a **bisection** of G_n with **size less than n^6** .

Then for every track $T_{i,j}$, **all disks** on $T_{i,j}$ have the **same color** in \mathcal{B} .

Furthermore, we can prove:

Lemma

Let \mathcal{B} be a **minimum bisection** of G_n with **size less than n^6** . Then, for every $1 \leq i \leq n$, the tracks $T_{i,0}$ and $T_{i,1}$ have **different colors** in \mathcal{B} .

Thus, as long as we keep the size of a bisection less than n^6 :


- **truth assignments** of $\phi \longleftrightarrow$ **minimum bisections** of G_n

Construction of the unit disk graph H_ϕ from G_n

- G_n depends **only** on the **number** of variables in ϕ


Construction of the unit disk graph H_ϕ from G_n

- G_n depends **only** on the **number** of variables in ϕ
- For every **XOR-clause** $(x_i \oplus x_k)$, where $i < k$:
 - **locally perturb** the disk centers on the intersection of $T_{i,0}$ and $T_{k,1}$



Construction of the unit disk graph H_ϕ from G_n

- G_n depends **only** on the **number** of variables in ϕ
- For every **XOR-clause** $(x_i \oplus x_k)$, where $i < k$:
 - **locally perturb** the disk centers on the intersection of $T_{i,0}$ and $T_{k,1}$
 - similarly for the intersection of $T_{i,1}$ and $T_{k,0}$



Construction of the unit disk graph H_ϕ from G_n

- G_n depends **only** on the **number** of variables in ϕ
- For every **XOR-clause** $(x_i \oplus x_k)$, where $i < k$:
 - **locally perturb** the disk centers on the intersection of $T_{i,0}$ and $T_{k,1}$
 - similarly for the intersection of $T_{i,1}$ and $T_{k,0}$

\Rightarrow the tracks $T_{i,j}$ and $T_{k,2-j}$ have **one more edge** among them in H_ϕ

Construction of the unit disk graph H_ϕ from G_n

- G_n depends **only** on the **number** of variables in ϕ
- For every **XOR-clause** $(x_i \oplus x_k)$, where $i < k$:
 - **locally perturb** the disk centers on the intersection of $T_{i,0}$ and $T_{k,1}$
 - similarly for the intersection of $T_{i,1}$ and $T_{k,0}$

\Rightarrow the tracks $T_{i,j}$ and $T_{k,2-j}$ have **one more edge** among them in H_ϕ

\Rightarrow in a truth assignment of ϕ :

- for the values $x_i = x_k$ that do **not** XOR-satisfy $(x_i \oplus x_k)$,
- we “pay” **two more** bi-colored edges in the resulting bisection of H_ϕ

MIN-BISECTION on unit disk graphs

Theorem

ϕ a *truth assignment* that *XOR-satisfies* at *least* k clauses

$\Leftrightarrow H_\phi$ has a *bisection* with value at *most* $2n^4(n-1) + 3n - 2k$.

MIN-BISECTION on unit disk graphs

Theorem

ϕ a *truth assignment* that XOR-satisfies at *least* k clauses
 $\Leftrightarrow H_\phi$ has a *bisection* with value at *most* $2n^4(n-1) + 3n - 2k$.

Proof idea: (\Rightarrow) :

- if $x_i = 0$ then assign colors: $T_{i,0}$ and $T_{i,1}$

MIN-BISECTION on unit disk graphs

Theorem

ϕ a *truth assignment* that XOR-satisfies at *least* k clauses
 $\Leftrightarrow H_\phi$ has a *bisection* with value at *most* $2n^4(n-1) + 3n - 2k$.

Proof idea: (\Rightarrow):

- if $x_i = 0$ then assign colors: $T_{i,0}$ and $T_{i,1}$
- if $x_i = 1$ then assign colors: $T_{i,0}$ and $T_{i,1}$


MIN-BISECTION on unit disk graphs

Theorem

ϕ a *truth assignment* that XOR-satisfies at *least* k clauses
 $\Leftrightarrow H_\phi$ has a *bisection* with value at *most* $2n^4(n-1) + 3n - 2k$.

Proof idea: (\Rightarrow) :

- if $x_i = 0$ then assign colors: $T_{i,0}$ and $T_{i,1}$
- if $x_i = 1$ then assign colors: $T_{i,0}$ and $T_{i,1}$
- If $(x_i \oplus x_k)$ is *not* a clause of ϕ :
 - we pay exactly $2n^3 + 2n^3 = 4n^3$ edges in the bisection




MIN-BISECTION on unit disk graphs

Theorem

ϕ a *truth assignment* that XOR-satisfies at *least* k clauses
 $\Leftrightarrow H_\phi$ has a *bisection* with value at *most* $2n^4(n-1) + 3n - 2k$.

Proof idea: (\Rightarrow) :

- if $x_i = 0$ then assign colors: $T_{i,0}$ and $T_{i,1}$
- if $x_i = 1$ then assign colors: $T_{i,0}$ and $T_{i,1}$
- If $(x_i \oplus x_k)$ is *not* a clause of ϕ :
 - we pay exactly $2n^3 + 2n^3 = 4n^3$ edges in the bisection
- If $(x_i \oplus x_k)$ is an XOR-satisfied clause of ϕ (i.e. $x_i \neq x_k$):
 - we pay exactly $2n^3 + 2n^3 = 4n^3$ edges




MIN-BISECTION on unit disk graphs

Theorem

ϕ a truth assignment that XOR-satisfies at least k clauses
 $\Leftrightarrow H_\phi$ has a bisection with value at most $2n^4(n-1) + 3n - 2k$.

Proof idea: (\Rightarrow):

- if $x_i = 0$ then assign colors: $T_{i,0}$ and $T_{i,1}$
- if $x_i = 1$ then assign colors: $T_{i,0}$ and $T_{i,1}$
- If $(x_i \oplus x_k)$ is not a clause of ϕ :
 - we pay exactly $2n^3 + 2n^3 = 4n^3$ edges in the bisection
- If $(x_i \oplus x_k)$ is an XOR-satisfied clause of ϕ (i.e. $x_i \neq x_k$):
 - we pay exactly $2n^3 + 2n^3 = 4n^3$ edges
- If $(x_i \oplus x_k)$ is not an XOR-satisfied clause of ϕ (i.e. $x_i = x_k$):
 - we pay exactly $(2n^3 + 1) + (2n^3 + 1) = 4n^3 + 2$ edges



MIN-BISECTION on unit disk graphs

Theorem

ϕ a *truth assignment* that XOR-satisfies at *least* k clauses
 $\Leftrightarrow H_\phi$ has a *bisection* with value at *most* $2n^4(n-1) + 3n - 2k$.

Proof idea: (\Rightarrow) :

- We have $m = \frac{3n}{2}$ clauses
- k clauses are XOR-satisfied
- $\binom{n}{2} - m$ pairs $\{x_i, x_k\}$ do *not* form a clause

MIN-BISECTION on unit disk graphs

Theorem

ϕ a *truth assignment* that XOR-satisfies at *least* k clauses
 $\Leftrightarrow H_\phi$ has a *bisection* with value at *most* $2n^4(n-1) + 3n - 2k$.

Proof idea: (\Rightarrow) :

- We have $m = \frac{3n}{2}$ clauses
- k clauses are XOR-satisfied
- $\binom{n}{2} - m$ pairs $\{x_i, x_k\}$ do *not* form a clause

\Rightarrow we pay:

$$\left(\binom{n}{2} - m \right) \cdot 4n^3 + k \cdot 4n^3 + (m - k) \cdot (4n^3 + 2) = 2n^4(n-1) + 3n - 2k$$

edges in the bisection

MIN-BISECTION on unit disk graphs

Theorem

ϕ a *truth assignment* that XOR-satisfies at *least* k clauses
 $\Leftrightarrow H_\phi$ has a *bisection* with value at *most* $2n^4(n-1) + 3n - 2k$.

Proof idea: (\Leftarrow): similarly to G_n , we can prove:

Lemma

Let \mathcal{B} be a *minimum bisection* of H_ϕ with *size less than* n^6 . Then, for every $1 \leq i \leq n$, the tracks $T_{i,0}$ and $T_{i,1}$ have *different colors* in \mathcal{B} .

MIN-BISECTION on unit disk graphs

Theorem

ϕ a *truth assignment* that XOR-satisfies at *least* k clauses
 $\Leftrightarrow H_\phi$ has a *bisection* with value at *most* $2n^4(n-1) + 3n - 2k$.

Proof idea: (\Leftarrow): similarly to G_n , we can prove:

Lemma

Let \mathcal{B} be a *minimum bisection* of H_ϕ with *size less than* n^6 . Then, for every $1 \leq i \leq n$, the tracks $T_{i,0}$ and $T_{i,1}$ have *different colors* in \mathcal{B} .

- if $T_{i,0}$ and $T_{i,1}$, then set $x_i = 0$

MIN-BISECTION on unit disk graphs

Theorem

ϕ a *truth assignment* that XOR-satisfies at *least* k clauses
 $\Leftrightarrow H_\phi$ has a *bisection* with value at *most* $2n^4(n-1) + 3n - 2k$.

Proof idea: (\Leftarrow): similarly to G_n , we can prove:

Lemma

Let \mathcal{B} be a *minimum bisection* of H_ϕ with *size less than* n^6 . Then, for every $1 \leq i \leq n$, the tracks $T_{i,0}$ and $T_{i,1}$ have *different colors* in \mathcal{B} .

- if $T_{i,0}$ and $T_{i,1}$, then set $x_i = 0$
- if $T_{i,0}$ and $T_{i,1}$, then set $x_i = 1$

MIN-BISECTION on unit disk graphs

Theorem

ϕ a *truth assignment* that XOR-satisfies at *least* k clauses
 $\Leftrightarrow H_\phi$ has a *bisection* with value at *most* $2n^4(n-1) + 3n - 2k$.

Proof idea: (\Leftarrow): similarly to G_n , we can prove:

Lemma

Let \mathcal{B} be a *minimum bisection* of H_ϕ with *size less than* n^6 . Then, for every $1 \leq i \leq n$, the tracks $T_{i,0}$ and $T_{i,1}$ have *different colors* in \mathcal{B} .

- if $T_{i,0}$ and $T_{i,1}$, then set $x_i = 0$
- if $T_{i,0}$ and $T_{i,1}$, then set $x_i = 1$
- count the number of intersections that contribute $4n^3$ (resp. $4n^3 + 2$)
 \Rightarrow at least k clauses of ϕ are XOR-satisfied □

- ① Is MIN-BISECTION tractable on **planar** graphs?
 - the above approach for unit disk graphs is based on **large cliques**
 - ⇒ it is not clear whether it can be extended to planar graphs

Open problems

- ① Is MIN-BISECTION tractable on **planar** graphs?
 - the above approach for unit disk graphs is based on **large cliques**
⇒ it is not clear whether it can be extended to planar graphs
- ② Does MIN-BISECTION have a **constant approximation ratio** on general graphs?
 - or on **planar / unit disk** graphs?
 - it is known: **no PTAS unless $\text{NP} \not\subseteq \cap_{\epsilon>0} \text{BPTIME}(2^{n^\epsilon})$**
(i.e. NP does not have randomized algorithms that run in sub-exponential time) [**Khot, FOCS, 2004**]
 - Can we show **“no PTAS unless $P=NP$ ”** ?

Thank you for your attention!