



Blume Shipment Services - API Documentation

Contents

1. Change Control	3
2. Shipment Services API Integration Guide	4
2.1. Booking RESTful API	4
2.2. Where to Start	4
3. Introduction	5
3.1. API Guidelines	5
3.2. Rate Limit	5
3.3. External URL	6
4. List of the Services	7
4.1. Create Shipment Leg	7
4.1.1. Sample Request to Create Shipment Leg	7
4.1.2. Sample Response to Create Shipment Leg	16
4.2. Cancel Shipment Leg	17
4.3. Update Shipment Leg All	17
4.3.1. Sample Request to Update Shipment Leg (All)	17
4.3.2. Sample Response to Update Shipment Leg (All)	26
4.4. Get Shipment Leg Details	27
5. Field Description	32
5.1. Shipment Leg	32
5.2. Shipment Stops	48
5.3. Shipment Equipments	59
5.4. Shipment Notes/Comments	71
5.5. Shipment Parties	73
5.6. Shipment References	77
5.7. Shipment Charges	78
5.8. Freight Line Items	82
5.9. Master Data	84
6. Error Codes	86





7. Appendix	8	7
-------------	---	---





1. Change Control

This section of the document contains the change control updates made to the content.

Table 1. Change Control Table

Ver sion	Date	Author	Changes	Change Status
1.0	09/09/2 022	Techni cal Docume ntation Team	Migrated Shipment Services API Documentation.	Publis hed
1.1	20/04/2 023	Techni cal Docume ntation Team	Updated: • Create Shipment Leg (on page 7) • Update Shipment Leg All (on page 17) Added: • Freight Line Items (on page 82)	Draft

Table 2. Distribution

Name	Title	Review/Approval		
PSG Team Members	Implementation Analysts, Business Analyst	Review		

The latest version of this document can be found on the Blume Global Documentation Central Repository.





2. Shipment Services API Integration Guide

The latest version is: v1.0

This document outlines the Application Programming Interfaces (APIs) connected to the Blume Shipment Services. The API in this document is the Shipment Services API. The Shipment Services API provides a set of methods or functions that can be called by the requesting application to perform specific actions, such as create, update, cancel Shipment Leg, and get shipment leg details by Shipment number and originator code, Shipment leg number and originator code.

2.1. Booking RESTful API

The document contains the following sections

Introduction (on page 5)	List of the Services (on page):
The primary audience for this document includes internal developers and partner developers who will integrate Shipment Services with their systems. Additionally, the supply chain manager may refer to this document for integration context. A basic understanding of APIs, Hyper Text Transfer Protocol (HTTP), and Representational State Transfer (REST)may be required to understand the concepts described in this document.	 Create Shipment Leg (on page 7) Cancel Shipment Leg (on page 17) Update Shipment Leg All (on page 17) Get Shipment Leg Details (on page 27)
Field Description (on page 32) This section provides a list of attributes that	Error Codes (on page 86) This section provides a list of common error
appear with the documentation.	codes that appear with the documentation.

2.2. Where to Start

We strongly recommend you start with the Introduction (on page 5) to learn the structure of the Booking RESTful API.





3. Introduction

Blume provides an extensive list of APIs to manage the shipments on our platform.

The APIs provide create, update, cancel Shipment; Shipment Leg, get Shipment, and shipment leg details by Shipment number and originator code, Shipment leg number and originator code.

3.1. API Guidelines

The following are the API Guidelines:

- All requests must include base URL
- Each request must be called with one of the HTTP verbs GET, POST, PUT, PATCH
- User must substitute valid values for mandatory and optional fields as and when required.
- All the request and request parameters are case sensitive
- Data is returned in JSON format
- API attempts to conform to the design principles of Representational State Transfer (REST) and relevant W3C HTTP/1.1 standards
- Only use UTF-8 characters encoding. Parameter values should be converted to UTF-8 and URL encoded according to W3C standards

3.2. Rate Limit

- All requests are subject to a rate limit
- Rate limiting restricts the number of times user can request resources from the API within a certain time window
- The default rate limit is 2000 requests per hour.
- If request exceed than defined rate limit, then HTTP "429 Too Many Requests" response will persist until the next hour begins.





3.3. External URL

To be whitelisted during implementation.





4. List of the Services

The description of each field has been provided in the following table along with all the APIs' expect or return, complete or partial shipment object details.

Service Name	URI	Туре	Description	Input	Output
Create Shipment Leg	/mbe/v1.0/cr eateShipmen tLeg	POST	Create a Shipment Leg	Shipment Json	Shipment leg business identifier with status of Success or Failure
Cancel Shipment Leg	/mbe/v1.0/ca ncelShipmen tLeg	POST	Cancel Shipment Leg	Shipment Json	Shipment leg business identifier with status of Success or Failure
Update Shipment Leg All	/mbe/v1.0/u pdateShipm entLegAll	POST	Update Existing Shipment Leg	Shipment Json	Shipment leg business identifier with status of Success or Failure
Get Shipment Leg Details	/mbe/v1.0/ge tShipmentLe gDetails?ide ntifier=1234	GET	Get Shipment Leg details via Shipment Number and Originator Code	Search Criteria	Get shipment leg details for provided shipment leg business identifier

4.1. Create Shipment Leg

4.1.1. Sample Request to Create Shipment Leg

Sample request (in JSON format) to Create Shipment Leg:







```
"shipmentLegs": [
  "id": null,
  "createdBy": "ABC CDE",
  "createDttm": null,
  "lastUpdateDttm": null,
  "version": null,
  "uniqueIdentifier": null,
  "originatorCode": "ABCD-EDP",
  "originatorName": "Name of the Originator",
  "shipmentNumber": null,
  "shipmentLegNumber": null,
  "legSequence": 1,
  "status": "Unassigned",
  "mode": "DRAY",
   "modeName": "DRAY",
   "assignedEquipmentType": "UCU",
   "customerCode": "ACDF",
   "customerName": "Customer",
   "creditCheckStatus": "None",
  "plannedPickupDttmLocal": null,
   "plannedDeliveryDttmLocal": "04-26-2023 07:02",
   "plannedPickupDttmUTC": null,
   "plannedDeliveryDttmUTC": "04-26-2023 11:02",
  "sourceType": "API",
   "shipmentType": "Domestic",
  "tripType": "RoundTrip",
   "totalDistance": 8087.06,
  "totalDistanceUOM": "MILES",
  "totalDurationInMin": 8822,
  "totalDurationUOM": "MINUTES",
  "customAttributes": "{\"abcd\":\"\",\"Color\":
\"\",\"test4\":\"\",\"test5\":\"\",\"test6\":\"\",\"test7\":\"\",\"test8
\":\"\",\"Haul class\":\"\",\"vehicleType\":\"\"}",
   "isVisibilityOnly": false,
  "estimatedArrival": "04-26-2023 07:02",
  "estimatedDeparture": "04-20-2023 00:00",
  "hasAttachment": true,
   "category": null,
  "isCOVisibilityOnly": true,
   "shipmentLegPipelineStatus": null,
  "isCriticalChangeTriggered": false,
   "isStatusChanged": false,
  "isAmendmentActionChanged": false,
  "isWorkOrderOrCarrierChanged": false,
```







```
"isTransactedEntity": false,
"shipmentAttachments": null,
"shipmentEquipment": {
"id": null,
"createdBy": "ABC CDE",
 "updatedBy": "ABC CDE",
 "createDttm": "04-20-2023 07:36",
 "lastUpdateDttm": "04-20-2023 07:36",
"version": null,
 "uniqueIdentifier": null,
"equipmentType": "UCU",
"equipmentNumber": null
"shipmentStops": [
{
  "id": null,
 "createdBy": "ABC CDE",
  "updatedBy": "ABC CDE",
  "createDttm": null,
  "lastUpdateDttm": null,
  "version": null,
  "uniqueIdentifier": null,
  "address": {
  "id": null,
  "createdBy": "ABC CDE",
   "updatedBy": "ABC CDE",
   "createDttm": null,
   "lastUpdateDttm": null,
   "version": null,
   "uniqueIdentifier": null,
   "addressLine1": "jorge wilstermann international airport",
   "city": "Cochabamba",
   "country": "BO",
   "countryLong": "Bolivia",
   "postalCode": "00000",
   "state": "C",
   "stateLong": "Cochabamba Department",
   "latitude": -17.41705,
   "longitude": -66.17871,
   "timeZone": "America/La_Paz",
   "plusCode": "57JMHRMC+5G",
   "locationName": "Jorge Wilstermann International Airport",
   "locationUUID": "8d037a63-6999-48e8-a39e-881620f7bb4e",
   "unlocode": "BOCBB",
  "locationType": "AIRPORT"
  "stopNumber": 1,
```







```
"stopAction": "Pickup",
"stopType": "O",
"mode": "DRAY",
"plannedArrivalStartDttmLocal": "04-21-2023 00:00",
"plannedArrivalEndDttmLocal": null,
"plannedDepartureStartDttmLocal": null,
"plannedDepartureEndDttmLocal": null,
"isLoaded": true,
"carrierEstimatedArrivalDttmLocal": "04-20-2023 00:00",
"carrierEstimatedDepartureDttmLocal": "04-20-2023 01:00",
"blumeEstimatedArrivalDttmLocal": null,
"blumeEstimatedDepartureDttmLocal": null,
"isVisibilityOnly": false,
"transitTimeSource": "KFACTOR",
"isInfeasible": false,
"plannedArrivalStartDttmUTC": null,
"plannedArrivalEndDttmUTC": null,
"plannedDepartureStartDtTmUTC": null,
"plannedDepartureEndDttmUTC": null,
"carrierEstimatedArrivalDttmUTC": "04-20-2023 04:00",
"blumeEstimatedArrivalDttmUTC": null,
"blumeEstimatedDepartureDttmUTC": null,
"actualArrivalDttmLocal": null,
"actualArrivalDttmUTC": null,
"appointmentStartDttmLocal": null,
"appointmentStartDttmUTC": null,
"appointmentEndDttmLocal": null,
"appointmentEndDttmUTC": null,
"cutOffDttmLocal": null,
"cutOffDttmUTC": null,
"earlyReceiptDttmLocal": null,
"earlyReceiptDttmUTC": null,
"lastFreeDttmLocal": null,
"lastFreeDttmUTC": null,
"detentionLastFreeDttmLocal": null,
"detentionLastFreeDttmUTC": null,
"demurrageLastFreeDttmLocal": null,
"demurrageLastFreeDttmUTC": null,
"actualDepartureDttmLocal": null,
"actualDepartureDttmUTC": null,
"appointmentWindowType": null
"id": null,
"createdBy": "ABC CDE",
"updatedBy": "ABC CDE",
"createDttm": null,
```







```
"lastUpdateDttm": null,
"version": null,
"uniqueIdentifier": null,
"address": {
"id": null,
 "createdBy": "ABC CDE",
"updatedBy": "ABC CDE",
 "createDttm": null,
 "lastUpdateDttm": null,
 "version": null,
 "uniqueIdentifier": null,
 "addressLine1": "N1",
 "city": "Conakry",
 "country": "GN",
 "countryLong": "Guinea",
 "postalCode": "00000",
 "state": "C",
 "stateLong": "Conakry",
 "latitude": 9.57566,
 "longitude": -13.62017,
 "timeZone": "Africa/Conakry",
 "plusCode": "6CX8H9GH+7W",
 "locationName": "Conakry International Airport",
 "locationUUID": "e77c2133-f87c-4195-9767-1566c46a6678",
 "unlocode": "GNCKY",
 "locationType": "AIRPORT"
},
"stopNumber": 2,
"stopAction": "Delivery",
"stopType": "D",
"mode": "DRAY",
"plannedArrivalStartDttmLocal": null,
"plannedArrivalEndDttmLocal": null,
"plannedDepartureStartDttmLocal": null,
"plannedDepartureEndDttmLocal": null,
"distance": 4043.53,
"distanceUOM": "MILES",
"isLoaded": true.
"carrierEstimatedArrivalDttmLocal": "04-23-2023 06:31",
"carrierEstimatedDepartureDttmLocal": "04-23-2023 08:31",
"blumeEstimatedArrivalDttmLocal": null,
"blumeEstimatedDepartureDttmLocal": null,
"transitTime": 4411,
"transitTimeUOM": "MINUTES",
"isVisibilityOnly": false,
"transitTimeSource": "KFACTOR",
"isInfeasible": false,
```







```
"plannedArrivalStartDttmUTC": null,
"plannedArrivalEndDttmUTC": null,
"plannedDepartureStartDtTmUTC": null,
"plannedDepartureEndDttmUTC": null,
"carrierEstimatedArrivalDttmUTC": "04-23-2023 06:31",
"blumeEstimatedArrivalDttmUTC": null,
"blumeEstimatedDepartureDttmUTC": null,
"actualArrivalDttmLocal": null,
"actualArrivalDttmUTC": null,
"appointmentStartDttmLocal": null,
"appointmentStartDttmUTC": null,
"appointmentEndDttmLocal": null,
"appointmentEndDttmUTC": null,
"cutOffDttmLocal": null,
"cutOffDttmUTC": null,
"earlyReceiptDttmLocal": null,
"earlyReceiptDttmUTC": null,
"lastFreeDttmLocal": null,
"lastFreeDttmUTC": null,
"detentionLastFreeDttmLocal": null,
"detentionLastFreeDttmUTC": null,
"demurrageLastFreeDttmLocal": null,
"demurrageLastFreeDttmUTC": null,
"actualDepartureDttmLocal": null,
"actualDepartureDttmUTC": null,
"appointmentWindowType": null
"id": null,
"createdBy": "ABC CDE",
"updatedBy": "ABC CDE",
"createDttm": null,
"lastUpdateDttm": null,
"version": null,
"uniqueIdentifier": null,
"address": {
 "id": null,
 "createdBy": "ABC CDE",
 "updatedBy": "ABC CDE",
 "createDttm": null,
 "lastUpdateDttm": null,
 "version": null,
 "uniqueIdentifier": null,
 "addressLine1": "jorge wilstermann international airport",
 "city": "Cochabamba",
 "country": "BO",
 "countryLong": "Bolivia",
```







```
"postalCode": "00000",
 "state": "C",
"stateLong": "Cochabamba Department",
 "latitude": -17.41705,
"longitude": -66.17871,
 "timeZone": "America/La Paz",
"plusCode": "57JMHRMC+5G",
 "locationName": "Jorge Wilstermann International Airport",
"locationUUID": "8d037a63-6999-48e8-a39e-881620f7bb4e",
 "unlocode": "BOCBB",
"locationType": "AIRPORT"
"stopNumber": 3,
"stopAction": "Return",
"stopType": "R",
"plannedArrivalStartDttmLocal": null,
"plannedArrivalEndDttmLocal": null,
"plannedDepartureStartDttmLocal": null,
"plannedDepartureEndDttmLocal": null,
"distance": 4043.53,
"distanceUOM": "MILES",
"isLoaded": false,
"carrierEstimatedArrivalDttmLocal": "04-26-2023 06:02",
"carrierEstimatedDepartureDttmLocal": "04-26-2023 07:02",
"blumeEstimatedArrivalDttmLocal": null,
"blumeEstimatedDepartureDttmLocal": null,
"transitTime": 4411,
"transitTimeUOM": "MINUTES",
"isVisibilityOnly": false,
"transitTimeSource": "KFACTOR",
"isInfeasible": false,
"plannedArrivalStartDttmUTC": null,
"plannedArrivalEndDttmUTC": null,
"plannedDepartureStartDtTmUTC": null,
"plannedDepartureEndDttmUTC": null,
"carrierEstimatedArrivalDttmUTC": "04-26-2023 10:02",
"blumeEstimatedArrivalDttmUTC": null,
"blumeEstimatedDepartureDttmUTC": null,
"actualArrivalDttmLocal": null,
"actualArrivalDttmUTC": null,
"appointmentStartDttmLocal": null,
"appointmentStartDttmUTC": null,
"appointmentEndDttmLocal": null,
"appointmentEndDttmUTC": null,
"cutOffDttmLocal": null,
"cutOffDttmUTC": null,
"earlyReceiptDttmLocal": null,
```







```
"earlyReceiptDttmUTC": null,
  "lastFreeDttmLocal": null,
  "lastFreeDttmUTC": null,
  "detentionLastFreeDttmLocal": null,
  "detentionLastFreeDttmUTC": null,
  "demurrageLastFreeDttmLocal": null,
  "demurrageLastFreeDttmUTC": null,
  "actualDepartureDttmLocal": null,
  "actualDepartureDttmUTC": null,
  "appointmentWindowType": null
],
"railAttributes": {
 "id": null,
 "createdBy": "ABC CDE",
 "updatedBy": "ABC CDE",
 "createDttm": "04-20-2023 07:36",
 "lastUpdateDttm": "04-20-2023 07:36",
 "version": null,
 "uniqueIdentifier": null,
 "interModalPlan": null,
 "programCode": null
},
"masterShipmentReference": "SHIP930383903033",
"lastFreeDttmLocal": null,
"detentionLastFreeDttmLocal": null,
"demurrageLastFreeDttmLocal": null,
"bookingNumber": null,
"workOrderNumber": null,
"receiverCode": null,
"receiverName": null,
"amendmentStatus": null,
"designatedCarrierCode": null,
"assignedCarrierCode": null,
"csConfiqId": null,
"shipmentReferences": null,
"completedOnDttmLocal": null,
"completedOnDttmUTC": null,
"criticalChangeVersion": null,
"importExportAttributes": null,
"lastFreeDate": null,
"detentionLastFreeDate": null,
"demurrageLastFreeDate": null,
"updatedOriginatorCode": "",
"operationType": "CREATE",
"updatedBy": "ABC CDE",
"stopOrders": [
```







```
"transportationOrder": {
"operationType": "CREATE",
"sourceType": "UI",
"originatorCode": "RBIN-EDP",
 "originAddress": {
 "id": null,
 "createdBy": "ABC CDE",
 "updatedBy": "ABC CDE",
 "createDttm": null,
 "lastUpdateDttm": null,
 "version": null,
 "uniqueIdentifier": null,
 "addressLine1": "jorge wilstermann international airport",
 "city": "Cochabamba",
 "country": "BO",
 "countryLong": "Bolivia",
 "postalCode": "00000",
 "state": "C",
 "stateLong": "Cochabamba Department",
 "latitude": -17.41705,
 "longitude": -66.17871,
 "timeZone": "America/La Paz",
 "plusCode": "57JMHRMC+5G",
  "locationName": "Jorge Wilstermann International Airport",
 "locationUUID": "8d037a63-6999-48e8-a39e-881620f7bb4e",
 "unlocode": "BOCBB",
 "locationType": "AIRPORT"
 },
 "destinationAddress": {
 "id": null,
 "createdBy": "ABC CDE",
 "updatedBy": "ABC CDE",
 "createDttm": null,
 "lastUpdateDttm": null,
 "version": null,
 "uniqueIdentifier": null,
 "addressLine1": "jorge wilstermann international airport",
  "city": "Cochabamba",
 "country": "BO",
 "countryLong": "Bolivia",
  "postalCode": "00000",
  "state": "C",
 "stateLong": "Cochabamba Department",
  "latitude": -17.41705,
  "longitude": -66.17871,
 "timeZone": "America/La_Paz",
```



WISETECH GLOBAL GROUP



```
"plusCode": "57JMHRMC+5G",
      "locationName": "Jorge Wilstermann International Airport",
      "locationUUID": "8d037a63-6999-48e8-a39e-881620f7bb4e",
      "unlocode": "BOCBB",
      "locationType": "AIRPORT"
     "transportationOrderNumber": "ORD345",
     "transportationOrderTypeName": "Purchase Order",
     "transportationOrderType": "PurchaseOrder",
     "originLocationName": "Jorge Wilstermann International Airport",
     "transportationOrderDescription": "ORD DESC",
     "destinationLocationName": "Jorge Wilstermann International
Airport",
     "expanded": true,
     "transportationOrderLines": [
       "skuItemNumber": "SKU5768",
       "skuDescription": "SKU DESC",
       "packageType": "Box",
       "barCodeId": "2345",
       "protectionLevelName": "Frozen",
       "productClassName": "Cheese",
       "sequenceNumber": 0
  1
"correlationId": 111,
"entityTransactionIndicator": "SHIPMENT_LEG"
```

4.1.2. Sample Response to Create Shipment Leg

Sample response (in JSON format) to Create Shipment Leg:

```
{
  "correlationId": "123ABC",
  "identifier": "689979036649894",
  "status": "SUCCESS",
  "errorDetails": [
  {
    "errorCode": "p2FOHN4AAh",
    "errorMessage": "XdrxL7Un9s",
    "errorType": "Error"
```





```
}
1
}
```

View the Field Description (on page 32) section for additional information on the attributes that are present in the JSON.

4.2. Cancel Shipment Leg

Sample request (in JSON format) to Cancel Shipment Leg:

```
{
   "correlationId": "123ABC",
   "payload": {
      "identifier": "829174991234661",
      "updatedBy": "Arvind88"
   }
}
```

View the Field Description (on page 32) section for additional information on the attributes that are present in the JSON.

4.3. Update Shipment Leg All

4.3.1. Sample Request to Update Shipment Leg (All)

Sample request (in JSON format) to Update Shipment Leg (All):



Note: If the update payload contains the comment. It always generates a fresh comment. If the additional comment is not necessary, do not include it in the update payload.

```
{
   "shipmentLegs": [
   {
     "id": null,
     "createdBy": "ABC CDE",
     "createDttm": null,
     "lastUpdateDttm": null,
     "version": null,
     "uniqueIdentifier": null,
     "originatorCode": "ABCD-EDP",
```







```
"originatorName": "Name of the Originator",
   "shipmentNumber": null,
  "shipmentLeqNumber": null,
  "legSequence": 1,
  "status": "Unassigned",
   "mode": "DRAY",
  "modeName": "DRAY",
  "assignedEquipmentType": "UCU",
  "customerCode": "BACD",
   "customerName": "Customer",
  "creditCheckStatus": "None",
   "plannedPickupDttmLocal": null,
  "plannedDeliveryDttmLocal": "04-26-2023 07:02",
   "plannedPickupDttmUTC": null,
   "plannedDeliveryDttmUTC": "04-26-2023 11:02",
   "sourceType": "API",
  "shipmentType": "Domestic",
   "tripType": "RoundTrip",
   "totalDistance": 8087.06,
  "totalDistanceUOM": "MILES",
  "totalDurationInMin": 8822,
   "totalDurationUOM": "MINUTES",
 "customAttributes": "{\"abcd\":\"\",\"Color\":
\"\",\"test4\":\"\",\"test5\":\"\",\"test6\":\"\",\"test7\":\"\",\"test8
\":\"\",\"Haul class\":\"\",\"vehicleType\":\"\"}",
   "isVisibilityOnly": false,
  "estimatedArrival": "04-26-2023 07:02",
  "estimatedDeparture": "04-20-2023 00:00",
  "hasAttachment": true,
  "category": null,
  "isCOVisibilityOnly": true,
  "shipmentLegPipelineStatus": null,
   "isCriticalChangeTriggered": false,
   "isStatusChanged": false,
  "isAmendmentActionChanged": false,
   "isWorkOrderOrCarrierChanged": false,
   "isTransactedEntity": false,
   "shipmentAttachments": null,
  "shipmentEquipment": {
   "id": null,
   "createdBy": "ABC CDE",
    "updatedBy": "ABC CDE",
   "createDttm": "04-20-2023 07:36",
    "lastUpdateDttm": "04-20-2023 07:36",
    "version": null,
   "uniqueIdentifier": null,
```







```
"equipmentType": "UCU",
 "equipmentNumber": null
},
"shipmentStops": [
 "id": null,
 "createdBy": "ABC CDE",
 "updatedBy": "ABC CDE",
 "createDttm": null,
  "lastUpdateDttm": null,
  "version": null,
  "uniqueIdentifier": null,
 "address": {
  "id": null,
  "createdBy": "ABC CDE",
  "updatedBy": "ABC CDE",
  "createDttm": null,
   "lastUpdateDttm": null,
  "version": null,
  "uniqueIdentifier": null,
  "addressLine1": "jorge wilstermann international airport",
   "city": "Cochabamba",
  "country": "BO",
  "countryLong": "Bolivia",
  "postalCode": "00000",
   "state": "C",
  "stateLong": "Cochabamba Department",
   "latitude": -17.41705,
  "longitude": -66.17871,
   "timeZone": "America/La_Paz",
   "plusCode": "57JMHRMC+5G",
   "locationName": "Jorge Wilstermann International Airport",
   "locationUUID": "8d037a63-6999-48e8-a39e-881620f7bb4e",
   "unlocode": "BOCBB",
  "locationType": "AIRPORT"
  "stopNumber": 1,
  "stopAction": "Pickup",
  "stopType": "O",
  "mode": "DRAY",
  "plannedArrivalStartDttmLocal": "04-21-2023 00:00",
  "plannedArrivalEndDttmLocal": null,
  "plannedDepartureStartDttmLocal": null,
  "plannedDepartureEndDttmLocal": null,
  "isLoaded": true,
  "carrierEstimatedArrivalDttmLocal": "04-20-2023 00:00",
  "carrierEstimatedDepartureDttmLocal": "04-20-2023 01:00",
```







```
"blumeEstimatedArrivalDttmLocal": null,
"blumeEstimatedDepartureDttmLocal": null,
"isVisibilityOnly": false,
"transitTimeSource": "KFACTOR",
"isInfeasible": false,
"plannedArrivalStartDttmUTC": null,
"plannedArrivalEndDttmUTC": null,
"plannedDepartureStartDtTmUTC": null,
"plannedDepartureEndDttmUTC": null,
"carrierEstimatedArrivalDttmUTC": "04-20-2023 04:00",
"blumeEstimatedArrivalDttmUTC": null,
"blumeEstimatedDepartureDttmUTC": null,
"actualArrivalDttmLocal": null,
"actualArrivalDttmUTC": null,
"appointmentStartDttmLocal": null,
"appointmentStartDttmUTC": null,
"appointmentEndDttmLocal": null,
"appointmentEndDttmUTC": null,
"cutOffDttmLocal": null,
"cutOffDttmUTC": null,
"earlyReceiptDttmLocal": null,
"earlyReceiptDttmUTC": null,
"lastFreeDttmLocal": null,
"lastFreeDttmUTC": null,
"detentionLastFreeDttmLocal": null,
"detentionLastFreeDttmUTC": null,
"demurrageLastFreeDttmLocal": null,
"demurrageLastFreeDttmUTC": null,
"actualDepartureDttmLocal": null,
"actualDepartureDttmUTC": null,
"appointmentWindowType": null
"id": null,
"createdBy": "ABC CDE",
"updatedBy": "ABC CDE",
"createDttm": null,
"lastUpdateDttm": null,
"version": null,
"uniqueIdentifier": null,
"address": {
"id": null,
 "createdBy": "ABC CDE",
 "updatedBy": "ABC CDE",
 "createDttm": null,
 "lastUpdateDttm": null,
 "version": null,
```







```
"uniqueIdentifier": null,
 "addressLine1": "N1",
"city": "Conakry",
 "country": "GN",
"countryLong": "Guinea",
 "postalCode": "00000",
"state": "C",
 "stateLong": "Conakry",
"latitude": 9.57566,
 "longitude": -13.62017,
"timeZone": "Africa/Conakry",
"plusCode": "6CX8H9GH+7W",
 "locationName": "Conakry International Airport",
 "locationUUID": "e77c2133-f87c-4195-9767-1566c46a6678",
"unlocode": "GNCKY",
"locationType": "AIRPORT"
"stopNumber": 2,
"stopAction": "Delivery",
"stopType": "D",
"mode": "DRAY",
"plannedArrivalStartDttmLocal": null,
"plannedArrivalEndDttmLocal": null,
"plannedDepartureStartDttmLocal": null,
"plannedDepartureEndDttmLocal": null,
"distance": 4043.53,
"distanceUOM": "MILES",
"isLoaded": true,
"carrierEstimatedArrivalDttmLocal": "04-23-2023 06:31",
"carrierEstimatedDepartureDttmLocal": "04-23-2023 08:31",
"blumeEstimatedArrivalDttmLocal": null,
"blumeEstimatedDepartureDttmLocal": null,
"transitTime": 4411,
"transitTimeUOM": "MINUTES",
"isVisibilityOnly": false,
"transitTimeSource": "KFACTOR",
"isInfeasible": false,
"plannedArrivalStartDttmUTC": null,
"plannedArrivalEndDttmUTC": null,
"plannedDepartureStartDtTmUTC": null,
"plannedDepartureEndDttmUTC": null,
"carrierEstimatedArrivalDttmUTC": "04-23-2023 06:31",
"blumeEstimatedArrivalDttmUTC": null,
"blumeEstimatedDepartureDttmUTC": null,
"actualArrivalDttmLocal": null,
"actualArrivalDttmUTC": null,
"appointmentStartDttmLocal": null,
```







```
"appointmentStartDttmUTC": null,
"appointmentEndDttmLocal": null,
"appointmentEndDttmUTC": null,
"cutOffDttmLocal": null,
"cutOffDttmUTC": null,
"earlyReceiptDttmLocal": null,
"earlyReceiptDttmUTC": null,
"lastFreeDttmLocal": null,
"lastFreeDttmUTC": null,
"detentionLastFreeDttmLocal": null,
"detentionLastFreeDttmUTC": null,
"demurrageLastFreeDttmLocal": null,
"demurrageLastFreeDttmUTC": null,
"actualDepartureDttmLocal": null,
"actualDepartureDttmUTC": null,
"appointmentWindowType": null
"id": null,
"createdBy": "ABC CDE",
"updatedBy": "ABC CDE",
"createDttm": null,
"lastUpdateDttm": null,
"version": null,
"uniqueIdentifier": null,
"address": {
"id": null,
 "createdBy": "ABC CDE",
 "updatedBy": "ABC CDE",
 "createDttm": null,
 "lastUpdateDttm": null,
 "version": null,
 "uniqueIdentifier": null,
 "addressLine1": "jorge wilstermann international airport",
 "city": "Cochabamba",
 "country": "BO",
 "countryLong": "Bolivia",
 "postalCode": "00000",
 "state": "C",
 "stateLong": "Cochabamba Department",
 "latitude": -17.41705,
 "longitude": -66.17871,
 "timeZone": "America/La_Paz",
 "plusCode": "57JMHRMC+5G",
 "locationName": "Jorge Wilstermann International Airport",
 "locationUUID": "8d037a63-6999-48e8-a39e-881620f7bb4e",
 "unlocode": "BOCBB",
```



WISETECH GLOBAL GROUP



```
"locationType": "AIRPORT"
},
"stopNumber": 3,
"stopAction": "Return",
"stopType": "R",
"plannedArrivalStartDttmLocal": null,
"plannedArrivalEndDttmLocal": null,
"plannedDepartureStartDttmLocal": null,
"plannedDepartureEndDttmLocal": null,
"distance": 4043.53,
"distanceUOM": "MILES",
"isLoaded": false,
"carrierEstimatedArrivalDttmLocal": "04-26-2023 06:02",
"carrierEstimatedDepartureDttmLocal": "04-26-2023 07:02",
"blumeEstimatedArrivalDttmLocal": null,
"blumeEstimatedDepartureDttmLocal": null,
"transitTime": 4411,
"transitTimeUOM": "MINUTES",
"isVisibilityOnly": false,
"transitTimeSource": "KFACTOR",
"isInfeasible": false,
"plannedArrivalStartDttmUTC": null,
"plannedArrivalEndDttmUTC": null,
"plannedDepartureStartDtTmUTC": null,
"plannedDepartureEndDttmUTC": null,
"carrierEstimatedArrivalDttmUTC": "04-26-2023 10:02",
"blumeEstimatedArrivalDttmUTC": null,
"blumeEstimatedDepartureDttmUTC": null,
"actualArrivalDttmLocal": null,
"actualArrivalDttmUTC": null,
"appointmentStartDttmLocal": null,
"appointmentStartDttmUTC": null,
"appointmentEndDttmLocal": null,
"appointmentEndDttmUTC": null,
"cutOffDttmLocal": null,
"cutOffDttmUTC": null,
"earlyReceiptDttmLocal": null,
"earlyReceiptDttmUTC": null,
"lastFreeDttmLocal": null,
"lastFreeDttmUTC": null,
"detentionLastFreeDttmLocal": null,
"detentionLastFreeDttmUTC": null,
"demurrageLastFreeDttmLocal": null,
"demurrageLastFreeDttmUTC": null,
"actualDepartureDttmLocal": null,
"actualDepartureDttmUTC": null,
"appointmentWindowType": null
```







```
],
"railAttributes": {
"id": null,
"createdBy": "ABC CDE",
 "updatedBy": "ABC CDE",
 "createDttm": "04-20-2023 07:36",
 "lastUpdateDttm": "04-20-2023 07:36",
"version": null,
 "uniqueIdentifier": null,
"interModalPlan": null,
"programCode": null
"masterShipmentReference": "SHIP930383903033",
"lastFreeDttmLocal": null,
"detentionLastFreeDttmLocal": null,
"demurrageLastFreeDttmLocal": null,
"bookingNumber": null,
"workOrderNumber": null,
"receiverCode": null,
"receiverName": null,
"amendmentStatus": null,
"designatedCarrierCode": null,
"assignedCarrierCode": null,
"csConfigId": null,
"shipmentReferences": null,
"completedOnDttmLocal": null,
"completedOnDttmUTC": null,
"criticalChangeVersion": null,
"importExportAttributes": null,
"lastFreeDate": null,
"detentionLastFreeDate": null,
"demurrageLastFreeDate": null,
"updatedOriginatorCode": "",
"operationType": "PATCH",
"updatedBy": "ABC CDE",
"stopOrders": [
  "transportationOrder": {
  "operationType": "PATCH",
  "sourceType": "UI",
   "originatorCode": "RBIN-EDP",
   "originAddress": {
   "id": null,
    "createdBy": "ABC CDE",
    "updatedBy": "ABC CDE",
   "createDttm": null,
```







```
"lastUpdateDttm": null,
 "version": null,
"uniqueIdentifier": null,
 "addressLine1": "jorge wilstermann international airport",
"city": "Cochabamba",
"country": "BO",
"countryLong": "Bolivia",
"postalCode": "00000",
"state": "C",
 "stateLong": "Cochabamba Department",
"latitude": -17.41705,
"longitude": -66.17871,
"timeZone": "America/La Paz",
 "plusCode": "57JMHRMC+5G",
 "locationName": "Jorge Wilstermann International Airport",
"locationUUID": "8d037a63-6999-48e8-a39e-881620f7bb4e",
"unlocode": "BOCBB",
"locationType": "AIRPORT"
},
"destinationAddress": {
"id": null,
"createdBy": "ABC CDE",
"updatedBy": "ABC CDE",
"createDttm": null,
"lastUpdateDttm": null,
 "version": null,
 "uniqueIdentifier": null,
"addressLine1": "jorge wilstermann international airport",
"city": "Cochabamba",
 "country": "BO",
 "countryLong": "Bolivia",
"postalCode": "00000",
"state": "C",
 "stateLong": "Cochabamba Department",
 "latitude": -17.41705,
"longitude": -66.17871,
 "timeZone": "America/La_Paz",
 "plusCode": "57JMHRMC+5G",
 "locationName": "Jorge Wilstermann International Airport",
"locationUUID": "8d037a63-6999-48e8-a39e-881620f7bb4e",
"unlocode": "BOCBB",
"locationType": "AIRPORT"
"transportationOrderNumber": "ORD345",
"transportationOrderTypeName": "Purchase Order",
"transportationOrderType": "PurchaseOrder",
"originLocationName": "Jorge Wilstermann International Airport",
```







```
"transportationOrderDescription": "ORD DESC",
     "destinationLocationName": "Jorge Wilstermann International
Airport",
     "expanded": true,
     "transportationOrderLines": [
       "skuItemNumber": "SKU5768",
       "skuDescription": "SKU DESC",
       "packageType": "Box",
       "barCodeId": "2345",
       "protectionLevelName": "Frozen",
       "productClassName": "Cheese",
       "sequenceNumber": 0
     ]
  ]
],
"correlationId": 111,
"entityTransactionIndicator": "SHIPMENT_LEG"
```

4.3.2. Sample Response to Update Shipment Leg (All)

View the Field Description (on page 32) section for additional information on the attributes that are present in the JSON.





4.4. Get Shipment Leg Details

Sample request (in JSON format) to get Shipment Leg details by Shipment Leg Number and **Originator Code**:

```
"correlationId": "123ABC",
"payload": {
  "identifier": "689979036649894",
  "createdBy": "DFGGGGG",
  "updatedBy": "ZXCCXCXC",
  "originatorCode": "XXXXXX",
  "shipmentLegNumber": "AB090822-04",
  "mode": "DRAY",
  "freightDescription": "2 PK NATURAL TRAY TABLE -",
  "shipmentType": "Import",
  "tripType": "OneWay",
  "status": "Accepted",
  "amendmentStatus": "AmendedByMotorCarrier",
  "receiverCode": "3455",
  "receiverName": "FGHJJJ",
  "legSequence": 1,
  "lastFreeDttmLocal": "09-06-2022 22:10",
  "workOrderCreatedDttmLocal": "09-06-2022 22:10",
  "totalDistance": 344,
  "totalDistanceUOM": "DDD",
  "totalDurationInMin": 455,
  "completed_on_dttm_local": "09-06-2022 22:10",
  "hasAttachment": false,
  "shipmentEquipment": {
    "identifier": "78978890899890",
    "equipmentType": "40HC",
    "equipmentNumber": "CKIU4802731"
  "shipmentStops": [
    {
      "address": {
        "addressLine1": "6000 DR. LUKE GLENN GARRETT, JR.",
        "addressLine2": "MEMORIAL HIGHWAY",
        "city": "AUSTELL",
        "countryShort": "US",
        "postalCode": "30106",
        "stateShort": "GA",
        "locationName": "N/S RAMP - AUSTELL"
      "stopNumber": 1,
      "stopAction": "Pickup",
```







```
"plannedPickupStartDateLocal": "09-06-2022 21:10",
  "plannedPickupEndDateLocal": "09-06-2022 22:10",
  "plannedPickupWindowType": "Between",
  "distance": 38709586212,
  "distanceUOM": "uLxf5z3bc5",
  "durationInMinutes": 412669318751,
  "actualArrivalDttmLocal": "09-06-2022 21:10",
  "actualDepartureDttmLocal": "09-06-2022 21:10",
  "carrierCode": "t9ORy5XKWJ",
  "carrierName": "EAxGvHunai",
  "stopStatus": "rjhpnYwRi1",
  "isLoaded": true,
  "dockId": "S6WikOw8rU",
  "appointmentRequired": true,
  "appointmentStartDttmLocal": "09-06-2022 21:10",
  "appointmentEndDttmLocal": "09-06-2022 21:10",
  "appointmentWindowType": "dFh8GzjE8a",
  "scheduledGateOutWindowType": "iNoQWlaOQm",
  "zoneCode": "ZgIXKlf1Ga",
  "geoRegion": "2NQ9pMbx32",
  "podNumber": "XWTbJDSB4f",
  "podReceivedDttmLocal": "09-06-2022 21:10",
  "spellName": "XnbeJlrryC",
  "transitTime": 422051328579,
  "transitTimeUOM": "tiQbSSZK_a",
  "inboundVesselName": "YkHrbhZg12",
  "inboundVoyageNumber": "aTbnHXCdOS",
  "inboundFlightNumber": "ybByTBbmbP",
  "inboundTrainNumber": "FZCZxZUhm1",
  "inboundTruckNumber": "VZSsLzbAKo",
  "outboundVesselName": "WL17NGXNn2",
  "outboundVoyageNumber": "Bmqd6ZpJSY",
  "outboundFlightNumber": "07sWcn7pNU",
  "outboundTrainNumber": " iHYSB5951",
  "outboundTruckNumber": "wOhOq7gqsF",
  "cutOffDttmLocal": "09-06-2022 21:10",
  "earlyReceiptDttmLocal": "09-06-2022 21:10",
  "stopReferenceNumber": "refNum",
  "blumeEstimatedArrivalDttmLocal": "09-06-2022 21:10",
  "blumeEstimatedDepartureDttmLocal": "09-06-2022 21:10",
  "carrierEstimatedArrivalDttmLocal": "09-06-2022 21:10",
  "carrierEstimatedDepartureDttmLocal": "09-06-2022 21:10",
 "identifier": "67879889896888",
},
  "address": {
   "addressLine1": "2855 SELMA HIGHWAY",
```







```
"city": "MONTGOMERY",
 "country": "US",
 "countryLong": "US",
 "postalCode": "36108",
 "state": "AL",
 "locationName": "CSC DISTRIBUTION"
},
"stopNumber": 2,
"stopAction": "Delivery",
"plannedDeliveryStartDateLocal": "09-06-2022 21:10",
"plannedDeliveryEndDateLocal": "09-06-2022 22:10",
"plannedDeliveryWindowType": "Between",
"distance": 38709586212,
"distanceUOM": "uLxf5z3bc5",
"durationInMinutes": 412669318751,
"actualArrivalDttmLocal": "09-06-2022 21:10",
"actualDepartureDttmLocal": "09-06-2022 21:10",
"carrierCode": "t9ORy5XKWJ",
"carrierName": "EAxGvHunai",
"stopStatus": "rjhpnYwRi1",
"isLoaded": true,
"dockId": "S6WikOw8rU",
"appointmentRequired": true,
"appointmentStartDttmLocal": "09-06-2022 21:10",
"appointmentEndDttmLocal": "09-06-2022 21:10",
"appointmentWindowType": "dFh8GzjE8a",
"scheduledGateOutWindowType": "iNoQWla0Qm",
"zoneCode": "ZgIXKlf1Ga",
"geoRegion": "2NQ9pMbx32",
"podNumber": "XWTbJDSB4f",
"podReceivedDttmLocal": "09-06-2022 21:10",
"spellName": "XnbeJlrryC",
"transitTime": 422051328579,
"transitTimeUOM": "tiQbSSZK a",
"inboundVesselName": "YkHrbhZg12",
"inboundVoyageNumber": "aTbnHXCdOS",
"inboundFlightNumber": "ybByTBbmbP",
"inboundTrainNumber": "FZCZxZUhm1",
"inboundTruckNumber": "VZSsLzbAKo",
"outboundVesselName": "WL17NGXNn2",
"outboundVoyageNumber": "Bmqd6ZpJSY",
"outboundFlightNumber": "O7sWcn7pNU",
"outboundTrainNumber": "_iHYSB5951",
"outboundTruckNumber": "wOhOq7gqsF",
"cutOffDttmLocal": "09-06-2022 21:10",
"earlyReceiptDttmLocal": "09-06-2022 21:10",
"stopReferenceNumber": "refNum",
```







```
"blumeEstimatedArrivalDttmLocal": "09-06-2022 21:10",
    "blumeEstimatedDepartureDttmLocal": "09-06-2022 21:10",
    "carrierEstimatedArrivalDttmLocal": "09-06-2022 21:10",
    "carrierEstimatedDepartureDttmLocal": "09-06-2022 21:10",
   "identifier": "234579036649894",
],
"shipmentReferences": [
   "identifier": "645679036649894",
   "shipmentReferenceType": "MASTERSHIPMENTREFNUM",
   "shipmentReferenceValue": "76272468-0002"
],
"shipmentParties": [
     "identifier": "9877678888899899",
    "partyType": "Bill-to",
   "address": {
     "addressLine1": "5515 SPALDING DRIVE",
     "city": "PEACHTREE CORNERS",
      "countryShort": "US",
     "postalCode": "30092",
     "stateShort": "GA"
    },
    "partyName": "CHR LLC",
   "partyCode": "2714351"
 }
],
"shipmentNotes": [
   "identifier": "987679036649894",
   "comments": "ri13F20eU0"
],
"shipmentCharges": [
    "identifier": "689945676649894",
    "createdBy": "L3LIzGI9ri",
    "updatedBy": "vKrJo9Fzvy",
    "chargeCode": "DMyBIFeV3I",
    "chargeName": "IJz5BbBEKa",
    "amount": 285086458186,
    "currencyCode": "kTeAfuTCgw",
    "billTo": "6eWDTeOIdl",
    "comments": "ktwpUDighO",
    "isBillable": true,
```







```
"isInvoiced": true,
    "isChargeDeleted": false,
    "invoiceNumber": "W0dtl6bo2A",
    "isModifiable": true,
    "stopId": 1
    }
}
```

View the Field Description (on page 32) section for additional information on the attributes that are present in the JSON.





5. Field Description

Attribute Names pertaining to date and time for example "createDttm" is represented as "MM-dd-yyyy HH:mm".



Attention: The field descriptions are for the reference purposes only.

The field descriptions for the attributes listed in the JSON code block are provided below:

Table 3. Header API Tables

Attribute Name		Require Optiona Conditi Read Only	Max	Conc	: Values	Description	Additional Notes
correlationId	String	gRequire	d2O		any value,	Correlation id is for debugging and log analysis	internal

5.1. Shipment Leg

Attribute Name	Туре	Require Optiona Conditi Read Only	Max	Values	Description	Additio nal Notes
actualArrival	times	s apti ona	I		Actual arrival/Gate in of carrier	Format: MM-dd- yyyy HH:mm
						Example: 09-29-2 022 12:34





Attribute Name	Туре	Require Optiona Conditi Read Only	May	Con dit ion	Values	Description	Additio nal Notes
actualDeparture	times	Optiona				Actual arrival/Gate in of carrier	Format: MM-dd- yyyy HH:mm
							Example: 09-29-2 022
							12:37
agentCode	Strin	gOptiona	120			Code of the Agent	
agentName	Strin	Optiona	20			Name of the Agent	
amendmentStatus	String	gOptiona	150		Amended by Motor Carrier	Internally calculated amendment	
					Amended by Origina tor	status, if any critical fields are updated by Motor Carrier or Shipper. Not to be used in Create/Update APIs.	
assetReservationExpi rationDate	Date	t iOps tiona	I			Expiry date for asset reservation in Local Time zone	Format: MM-dd- yyyy HH:mm
							Example: 08-23-2 022





Attribute Name	Туре	Require Optiona Conditi Read Only	May	Con dit ion	Values	Description	Additio nal Notes
							15:05
assignedCarrierCode	String	Optiona	50			Carrier assigned to a shipment	
assignedEquipmentT ype	Strin	gOptiona	120			Equipment type assigned to a carrier	
assignedServiceLe vel	String	Optiona	20			Service level assigned to a carrier	
assignedServiceLeve IName	String	gOptiona	120			Service level Name assigned to a carrier	
billOfLadingNumber	Strin	Optiona Required		For Imp ort ship m ent t ype it is Req ui red attri bu te.		Bill of lading number	
billType	String	gOptiona	120			Bill type of a shipment	House Waybill, Master Waybill





Attribute Name	Туре	Require Optiona Conditi Read Only	May	Con dit ion	Values	Description	Additio nal Notes
bondedMove	Boole	Optiona			true/false	Bonded Move, Yes/No	
bookingNumber	String	gOptiona Require		For Exp ort ship m ent t ype it is Req ui red attri bu te.	Genera ted from Booking	Booking number of Ocean/Air Shipment	
chargeableWeight UOM	Strin	Optiona	20		KG,LB	Weight UOM	1000 LB
cogsAmount	Decir	n@ btiona	l12.2			Amount for Cost of goods sold	Example: 2345.10 USD
cogsCurrencyCode	String	Optiona	20		Dollar, Pound, Euro	Currency	
completedOnDttmL ocal	Date	t iOps tiona	I				Format: MM-dd- yyyy HH:mm Example: 10-01-2 022





Attribute Name	Туре	Require Options Conditi Read Only	May	Con dit ion	Values	Description	Additio nal Notes
							03:05
containerProgramC ode	Strin	Optiona	50			Program code of container - Mode = Rail	
createdDate	times	s @ptij ona				Audit field, system uses it to populate all the audit tables across various services.	Format: MM-dd- yyyy HH:mm Example: 10-01-2 022 03:05
createdBy	Strin	Require	50			Audit field, system uses it to populate all the audit tables across various services.	
customAttributes	JSON	IOptiona	1		These additional attributes will be configu red by implemen tation team and string will be provided during	Array of Name, Value pairs of pre-configured custom attributes	





Attribute Name	Туре	Require Optiona Conditi Read Only	May	Con dit ion	Values	Description	Additio nal Notes
					the implemen tation phase.		
customerCode	Strin	Optiona	50			This field is used to create the customer and LSP partnership and provide the access to customer portal.	
customerName	String	gOptiona	1255			Name of the customer	
designatedCarrierCode	Strin	Optiona	255			User preferred carrier code to the shipment	Designa ted Carrier Code tells system, to not look at contract managem ent while tendering the shipment. Source system already has identified the carrier.





Attribute Name	Туре	Require Optiona Conditi Read Only	May	Values	Description	Additio nal Notes
designatedEquipmen tType	String	gOptiona	120		User preferred Equipment Type code to the shipment	
designatedMode	String	Optiona	255		User preferred Mode to the shipment	
designatedServiceLe vel	String	gOptiona	I255	Ex: FX_4day	User preferred service level on the shipment	
designatedServiceLe velName		Optiona		Ex: Fed Ex 4Day	User preferred service level name on the shipment	
destinationGeoReg ion	String	gOptiona	I255		Geo region of destination location	
destinationZoneC ode	String	Optiona	20		Zone code of destionation Location	
estimatedArrival	Time	s Captip na	I		Estimated arrival of carrier	Format: MM-dd- yyyy HH:mm Example: 12-14-2 022 15:20
estimatedDeparture	Time	Optiona			Estimated departure of carrier	Format: MM-dd- yyyy





Attribute Name	Туре	Require Optiona Conditi Read Only	Max	Con dit ion	Values	Description	Additio nal Notes
							HH:mm Example: 12-14-2 022 15:20
expirationDate	Date	t iOps tiona	_			Expiry date and time of shipment in local time zone	Format: MM-dd- yyyy HH:mm Example: 12-14-2 022 15:20
freightDescription	Strin	Optiona	2000			Description of freight	
houseWayBillNumber	Strin	gOptiona	150			House Way bill number of Ocean/Air shipment	
incoTermCode	Strin	Optiona	20			Incoterm code for International shipment.	Incoterm drives some planning and routing decisions based on incoterm.





Attribute Name	Туре	Require Optiona Conditi Read Only	Max		Values	Description	Additio nal Notes
incoTermDesc	Strin	gOptiona	150		CIF - Cost Insurance and Freight (insert named port of destinati on)		
isBliResubmitted	Boole	Optiona	1	Tr ue/F alse		Flag to enable resubmit bill of lading button	
isDestinationTransit	Boole	O ptiona	I 1	Tr ue/F alse		Flag to set destination location is a transit location	
isGoodsStackable	Boole	Optiona	1	Tr ue/F alse		Flag to set goods can be stackable or not	
isHazmat	Boole	வி ptiona	l1	Tr ue/F alse		Flag to set shipment is hazmat or no	
isInsuranceRequired	Boole	Optiona	1	Tr ue/F alse		Flag to set if insurance is required for a shipment	
isOriginTransit	Boole	O ptiona	I 1	Tr ue/F alse		Flag to set origin location is a transit location	





Attribute Name	Туре	Require Optiona Conditi Read Only	May	Con dit ion	Values	Description	Additio nal Notes
isRailBillTriggered	Boole	Optiona	1	Tr ue/F alse		Flag to indicate if Rail bill is triggered	
lastFreeDate	Date	t iOqu etiona	I			Last free date of a shipment in Local time zone	Format: MM-dd- yyyy HH:mm Example: 10-01-2 022 03:05
updatedTimestamp	times	Optiona				Last updated shipment date and time for Audit	Format: MM-dd- yyyy HH:mm Example: 12-14-2 022 15:20
legSequence	bigin	tOptiona	I	Ex: 1,2,3		Leg sequence of a shipment	
loadType	String	Optiona	20			Load type of a shipment	FCL, LCL, LTL, FTL
masterShipmentNum ber	Strin	gOptiona	150			Master Shipment number (E2E shipment number)	





Attribute Name	Туре	Require Optiona Conditi Read Only	May	Con dit ion	Values	Description	Additio nal Notes
masterWayBillNum ber	Strin	Optiona	100			Master way bill number of a shipment	
mode	Strin	gRequire	d5O			Assigned mode of a shipment	AIR, DRAY, RAIL, BARGE, FCL, LCL,LTL,P ARCEL, RAIL, TL
modeName	String	Optiona	50			Description of Mode	
moveType	String	gOptiona	120			Type of move	Cross Town, Destinat ion Dray, Origin Dray
numOfPackages	bigin	Optiona	10			'Number of packages being shipped on the shipment	
numOfPackagesUOM	Strin	gOptiona	1100		Each, Case, Pallet, Box	Package UOM	10 Case
originGeoRegion	String	Optiona	50			Geo region of Origin location	
originZoneCode	Strin	gOptiona	120			Zone code of Origin Location	
originatorCode	String	Require	50			Shipper Office code	





Attribute Name	Туре	Require Optiona Conditi Read Only	Max	Con dit ion	Values	Description	Additio nal Notes
originatorName	String	gOptiona	1100			Shipper Office Name	
packageType	String	Optiona	20			Type of Package	BAG, CASE, DRUM,PIE CES, ROLLs, SACK
paymentNumber	String	gOptiona	1200			Payment Type	
paymentTerm	Strin	Optiona	20		Example: Prepaid, Collect and Third Party'	Payment Terms between the originator and carrier	
plannedDeliveryDate	Date	t iOps tiona	I			Planned Delivery Date and time of a carrier in Local time zone (Calculated by Time feasibility)	Format: MM-dd- yyyy HH:mm Example: 12-14-2 022 15:20
plannedPickupDate	Date	Optiona				Planned Pick up Date and time of a carrier in Local time zone (Calculated by Time feasibility)	Format: MM-dd- yyyy HH:mm Example: 12-14-2 022





Attribute Name	Туре	Require Optiona Conditi Read Only	Max	Con dit ion	Values	Description	Additio nal Notes
							15:20
portOfDischarge	Strin	gOptiona	150			Name of Port of Discharge	
portOfLoading	Strin	Optiona	50			Name of Port of Arrival	
primaryCarrier	Strin	gOptiona	1100			Primary Carrier of transportation that is associated to the master shipment	
primaryMode	Strin	Optiona	50			Primary Mode of transportation that is associated to the master shipment	
proNumber	Strin	gOptiona	150			Pro Number , used for LTL mode	
productClass	Strin	Optiona	50			Product class of goods being shipped	
protectionLevel	Strin	gOptiona	150			'Protection Level of the goods being shipped	
quantity	Decir	Optiona	12,2			'Quantity of the goods on the shipment'	





Attribute Name	Туре	Require Optiona Conditi Read Only	May	Con dit ion	Values	Description	Additio nal Notes
quantityUOM	String	gOptiona	120		Example, Units, cases	ok.	BOX, CARTON, PIECES
receiverCode	Strin	Optiona	20			Code of receiver of goods	
receiverName	String	gOptiona	I25O			Name of receiver of goods	
representativeCarrie rCode	String	Optiona	255			Representative carrier set in contract management	
shipmentLegNumber	Strin	gRequire	diOO			Shipment number of leg, if not provided system will generate	
shipmentNumber	String	Optiona	100			Shipment number of master shipment / Parent shipment	
shipmentType	String	gRequire	d2O		Domestic ,lmport,Ex port	Shipment type	Domest ic, Export, Import
status	String	Optiona	100			Status of Shipment	Tender ed, Unassign ed, Active





Attribute Name	Туре	Require Optiona Conditi Read Only	May	Con dit ion	Values	Description	Additio nal Notes
totalDistance	Decir	Y@ btiona	l12,2			'Total distance travelled by the shipment'	100 MILES
totalDistanceUOM	String	Optiona	20				MILES
totalDurationInMin	Decir	n@ btiona	120,2			Total duration of the shipment	
trainNumber	String	Optiona	50			Train # if the mode is RAIL	
tripType	Strin	gRequire	d50		OneWay, RoundT rip	'Indicates whether the trip is a one way or round trip	OneWay, RoundT rip
updatedBy	Strin	Optiona Require		Cre ate - Opt io nal Upd ate - Req ui red		Last Updated By	
vendorCode	Strin	gOptiona	120			'Code of the Supplier who is shipping the products on the shipment'	





Attribute Name	Туре	Require Optiona Conditi Read Only	Max	Con dit ion	Values	Description	Additio nal Notes
vendorName	String	Optiona	255			Name of the Supplier who is shipping the products on the shipment	
volume	Decir	Y@ ptiona	l12,2			Volume of the goods on the shipment	
volumeUOM	String	Optiona	20			Unit of measurement for volume	CBC, CBF, CBI, CBM, CF, MTQ
volumetricWeight	Decir	m a ptiona	l12,2			Theoretical weight computed by dividing actual weight with the dimensional factor	
volumetricWeight UOM	String	Optiona	20			Unit of measurement for volumetric weight	CBC, CBF, CBI, CBM, CF, MTQ
weight	Decir	Ƴ @ btiona	l12,2			Weight of the Shipment	
weightUOM	String	Optiona	20		KG, LB	Weight UOM	KG, LB
workOrderCreatedD ate	Date ⁻	t iOps tiona	I			Work order create date time in Local time zone (When tendered)	Format: MM-dd- yyyy HH:mm Example: 12-14-2 022





Attribute Name	Туре	Require Optiona Conditi Read Only	Max	Values	Description	Additio nal Notes
						15:20
workOrderNumber	String	Optiona	50		Work Order number (Generated when tender to carrier	
workOrderStatus	Strin	gOptiona	l		Status of work order	

5.2. Shipment Stops

Attribute Name	Туре	Require Optiona Conditi Read Only	Max	Con dit ion	Values	Description	Additio nal Notes
actualArrivalDate	date	i Ope tiona				Actual Arrival Local Date and Time of the shipment.	Format: MM-dd- yyyy HH:mm Example: 12-14-2 022 15:20
actualDepartureDate	date	Optiona				Actual Departure Local Date and Time of the Shipment.	Format: MM-dd- yyyy HH:mm





Attribute Name	Туре	Require Optiona Conditi Read Only	May	Con dit ion	Values	Description	Additio nal Notes
							Example: 12-14-2 022 15:20
addressLine1	string	gRequire	200			Address Line 1 of shipment stop	
addressLine2	string	Optiona	100			Address Line 2 of shipment stop	
city	string	gRequire	d5O			City of shipment stop	
contactName	string	Optiona	50			Contact Name of shipment stop	
countryShort	string	gRequire	d2O			Country Name of shipment stop	
countryLong	string	Optiona	100			Long country of shipment stop	
createdTimestamp	times	: apti pona	13		yy yy-MM- dd'T'HH:m m:ss.SSS 'Z'	Shipment creation date and time .	Format: MM-dd- yyyy HH:mm Example: 12-14-2 022 15:20





Attribute Name	Туре	Require Optiona Conditi Read Only	Max	Con dit ion	Values	Description	Additio nal Notes
createdBy	string	Optiona	100			Created By Name	
fax	string	Optiona	120			fax number of shipment	
updatedTimestamp	times	Optiona	3		yy yy-MM- dd'T'HH:m m:ss.SSS 'Z'	Date and time for the last shipment details update.	Format: MM-dd- yyyy HH:mm Example: 12-14-2 022 15:20
latitude	decir	m a þtiona	120,5			Latitude coordinates of location	
locationCode	string	Optiona	50			Location Code of Shipment	
locationName	string	gOptiona	1200			Location Name of Shipment	
locationType	string	Optiona	50			Location Type	AIRPORT, AIR CARGO FACILITY, CROSS DOCK, DC, LTL TERMINA L,PORT
longitude	decir	r @ þtiona	120,5			Longitude coordinates of location	





Attribute Name	Туре	Require Optiona Conditi Read Only	May	Con dit ion	Values	Description	Additio nal Notes
plusCode	string	Optiona	20			Plus Code of location	
postalCode	string	gRequire	d2O			Postal code of location	
stateShort	string	Require	20			State name of shipment party	
stateLong	string	gOptiona	180			Long state name of shipment party	
telephone	string	Optiona	20			Telephone number of shipment party	
timeZone	string	gOptiona	1100			Time Zone of the location	
unlocode	string	Optiona	50			United Nations Code for Trade and Transport Locations of location .	
updatedBy	string	Optiona	1100			Last Updated By Name	
appointmentEndD ate	date	Optiona				Local Appointment End Date and Time	Format: MM-dd- yyyy HH:mm Example: 12-14-2 022 15:20





Attribute Name	Туре	Require Optiona Conditi Read Only	May	Con dit ion	Values	Description	Additio nal Notes
appointmentRequi red	Boole	ைptiona	l1		T/Y	Is the Appointment required	
appointmentStartD ate	date	Optiona				Local Appointment Start Date and Time	Format: MM-dd- yyyy HH:mm Example: 12-14-2 022 15:20
appointmentWindow Type	string	Optiona	I2O		At,Betwe en,After, Before.	Type of Appointment Window	
blumeEstimatedArriv alDate	date	Optiona				Blume Platform's Local Estimated Arrival Date and Time.	Format: MM-dd- yyyy HH:mm Example: 12-14-2 022 15:20
blumeEstimatedDep artureDate	datet	i Ope tiona	I			Blume Platform's Local Estimated Departure Date and Time	Format: MM-dd- yyyy HH:mm





Attribute Name	Туре	Require Optiona Conditi Read Only	May	Con dit ion	Values	Description	Additio nal Notes
							Example: 12-14-2 022 15:20
carrierCode	string	Optiona	50			Carrier Code of the Carrier associated with the Shipment.	
carrierEstimatedArriv alDate	datet	i © pe tiona	I			Carrier's Local Estimated Arrival Date and Time.	Format: MM-dd- yyyy HH:mm Example: 12-14-2 022 15:20
carrierName	string	Optiona	50			Name of the Carrier	
comments	string	gOptiona	14000)		Any additional information related to the shipment.	
distance	decir	Optiona	25,15			Distance of the shipment legs	
distanceUOM	string	Optiona	120			Distance Unit of Measure	250 KM
dockld	string	Optiona	50			Docking Port ID	





Attribute Name	Туре	Require Optiona Conditi Read Only	May	Con dit ion	Values	Description	Additio nal Notes
durationInMinutes	decir	m a þtiona	125,15			Total Duration in minutes	
expectedDeliveryEn dDate	date	Optiona				Local Expected Delivery End Date and Time	Format: MM-dd- yyyy HH:mm Example: 12-14-2 022 15:20
expectedDeliverySta rtDate	date	:i O petiona	1			Local Expected Delivery Start Date and Time	Format: MM-dd- yyyy HH:mm Example: 12-14-2 022 15:20
expectedPickupEnd Date	date	Optiona				Local Expected Pickup End Date and Time	Format: MM-dd- yyyy HH:mm Example: 12-14-2 022 15:20





Attribute Name	Туре	Require Options Conditi Read Only	May	Con dit ion	Values	Description	Additio nal Notes
expectedPickupStart Date	date	t iOpe tiona	I			Local Expected Pickup Start Date and Time	Format: MM-dd- yyyy HH:mm Example: 12-14-2 O22
gateInActualReason Code	string	Optiona	20			Gate In Actual Reason Code	15:20
gateInActualReasonD escription	string	Optiona	150			Gate In Actual Reason Description	
gateOutActualReaso nCode	string	Optiona	20			Gate Out Actual Reason Code	
gateOutActualReaso nDescription	string	gOptiona	150			Gate Out Actual Reason Description	
geoRegion	string	Optiona	50			Geographical Region	
isLoaded	Boole	O ptiona	I		Y/N	Loaded Move or Empty Move of the shipment leg.	
mode	string	Optiona				Type of Mode for the Shipment	
originatorCode	string	Optiona	150			An identifier for the Originator	





Attribute Name	Туре	Require Optiona Conditi Read Only	May	Con dit ion	Values	Description	Additio nal Notes
						office that is managing the shipment	
plannedArrivalEndD ate	date	Optiona				Local Planned Arrival Date and Time	Format: MM-dd- yyyy HH:mm Example: 12-14-2 022 15:20
plannedArrivalStartD ate	date	: iRe equire	d			Local Planned Arrival Start Date and Time	Format: MM-dd- yyyy HH:mm Example: 12-14-2 022 15:20
plannedArrivalWindo wType	string	Optiona	20		At, Between, After, Before	Type of Planned Arrival Window	After, At, Before, Between
plannedDepartureEn dDate	datet	i Ope tiona	I			Local Planned Departure End Date and Time	Format: MM-dd- yyyy HH:mm





Attribute Name	Туре	Require Options Conditi Read Only	May	Con dit ion	Values	Description	Additio nal Notes
							Example: 12-14-2 022 15:20
plannedDepartureSt artDate	datet	Optiona				Local Planned Departure Start Date and TimeplannedD epartureStartD ttmLocal	Format: MM-dd- yyyy HH:mm Example: 12-14-2 022 15:20
plannedDepartureWi ndowType	string	gOptiona	120		At, Between, After, Before	Type of Planned Departure Windowplanne dDepartureWin dowType	After, At, Before, Between
podNumber	string	Optiona	50			Proof of delivery number	
podReceivedDate	datet	i Ope tiona	I			Local Proof of delivery received date and time	Format: MM-dd- yyyy HH:mm Example: 12-14-2 022





Attribute Name	Туре	Require Optiona Conditi Read Only	May	Con dit ion	Values	Description	Additio nal Notes
							15:20
spellName	string	Optiona	50			Terminal name for Rail shipments	
stopAction	string	gRequire	± 50		LiveLoad, LiveUnlo ad, Drop and Pick, Pickup, Delivery, Return, Customs, Departu re, Arrival	Stop the activity happening on the shipment	
stopNumber	bigin	Require	2			Number of stops on the shipment leg	
stopReferenceNum ber	string	gOptiona	150			Reference Number for the Stop	
stopStatus	string	Optiona	20			Stop Status of the shipment	
updatedBy	string	gOptiona	150			Last Updated By Name	
zoneCode	string	Optiona	20			Zone Code of the Location	





5.3. Shipment Equipments

Attribute Name	Туре	Require Optiona Conditi Read Only	May	Values	Description	Additio nal Notes
altitude	Decir	1@ btiona	l12,2		Altitude the container can be moved.	
altitudeUOM	String	Optiona	20	CM,FT,I N,M	UOM of Altitude	CM,FT,I N,M
certifiedWeight	Decir	1@ ptiona	120,2		Certified weight of the container.	
certifiedWeightUOM	String	Optiona	20	KG,LB	Sets weight UOM	KG,LB
chassisColor	String	gOptiona	120		Informational field, to indicate the chassis colour.	
chassisNumber	String	Optiona	50		Chassis number attached to a container.	
chassisProvider	String	gOptiona	150		Chassis Provider, pre configured as a partner in Blume Organization	
co2	Decir	Optiona	20,2		Carbon Dioxide level of a container.	
comments	Strin	gOptiona	1500		Any comments to be associated to container.	





Attribute Name	Туре	Require Optiona Conditi Read Only	May	Con dit ion	Values	Description	Additio nal Notes
commodity	String	Optiona	50			Commodity description of a container	
commodityGoodsNu mber	Strin	gOptiona	150			same commodity code need to be provided on the contract management, if the rating is commodity specific.	
createdTimestamp	times	Optiona				Date and Time container was created.	Format: MM-dd- yyyy HH:mm Example: 12-14-2 022 15:20
createdBy	Strin	gOptiona	150			container created source	
createdSourceType	String	Optiona	20			container created source Type	
dimensionUOM	Strin	gOptiona	120		CM,FT,I N,M	UOM of height, weight, width	CM,FT,I N,M
dimensionUOMName	Strin	Optiona	20		CM,FT,I N,M	Description of dimension UOM	CM,FT,I N,M





Attribute Name	Туре	Require Optiona Conditi Read Only	May	Con dit ion	Values	Description	Additi nal No	
equipmentClass	Strin	gOptiona	I5O		Trailer, Chassis, Freight Container	Class container belongs to		
equipmentHeight	Deci	Optiona	20,2			Height of the container.		Note: Only two decimals are all owed.
equipmentLength	Decii	ma btiona	I2O,2			Length of the container		N o te: O nly two d e ci m





Attribute Name	Туре	Require Options Conditi Read Only	May	Con dit ion	Values	Description	Additio nal Notes
							als are all o w ed.
equipmentNumber	Strin	Require	50	Req ui red for Y ard Visi bil ity	Assigned by Street Turn or Motor Carrier during empty pickup	Sets container number	
equipmentType	Strin	gRequire	±20		Specify UCU (Unspecified container unit) if unknown.	Sets standard container code like 40ST etc.	22UP-20' Hardtop, 2528-Ge nset Underslu ng, 25GP-H IGH CUBE CONT
equipmentTypeCode Desc	String	Optiona	50			Code of container Type	
equipmentTypeN ame	String	gOptiona	120			Description of container Type.	
equipmentWidth	Decir	Optiona	20,2			Width of the container.	23.55 FT N o te:





Attribute Name	Туре	Require Optiona Conditi Read Only	Max	Con dit ion	Values	Description	Addit nal No	
								nly two d e ci m als are all o w ed.
gensetNumber	String	gOptiona	150			Sets genset number of the container.		
grossVolume	Decir	Optiona	20,2			Sets gross volume of the container.	23.55 MTQ	
								N o te: O nly two d e ci m als are all o





Attribute Name	Туре	Require Optiona Conditi Read Only	May	Con dit ion	Values	Description	Additi nal No	
								w ed.
grossVolumeUOM	Strin	gOptiona	120		CR,MTQ,C F,FTQ	Sets volume UOM of the container.	CR,MT F,FTQ	Q,C
grossWeight	Decir	Optiona	20,2			Sets gross weight of the container.		Note: Only two decimals are all owed.
grossWeightUOM	Strin	gOptiona	120		KG,LB	Sets weight UOM	KG,LB	
humidity	Decir	Optiona	20,2			Humidity of the container.		N o te: O nly





Attribute Name	Туре	Require Options Conditi Read Only	May	Con dit ion	Values	Description	Additio nal Notes
							two d e ci m als are all o w ed.
isChassisLeased	Boole	e an ptiona	I		true/false	indicates if the chassis is self leased.	
isEmpty	Boole	Optiona			true/false	indicates if the container can be stacked.	
isEquipmentStacka ble	Boole	O ptiona	_		true/false	indicates if the container is empty.	
isOverWeight	Boole	Optiona			true/false	indicates if the container is overweight.	
isRefrigerated	Boole	O ptiona			true/false	indicates if the container is refrigerated.	
updatedTimestamp	times	Optiona				Last updated date and time.	
maxAltitude	Decir	m a þtiona	120,2			Maximum Altitude a container can be moved.	23.55 M N o te:





Attribute Name	Туре	Require Optiona Conditi Read Only	May	Con dit ion	Values	Description	Additio nal Notes
							O nly two d e ci m als are all o w ed.
maxAltitudeUOM	Strin	Optiona	20		CM,FT,I N,M	Attitude UOM	CM,FT,I N,M
maxPackages	Bigin	tOptiona	l1O			Maximum packages in an container.	
maxPackagesUOM	Strin	Optiona	20			packages UOM	10 Case
maxTemperature	Decir	m a ptiona	120,2			Maximum temp a container can be moved.	23.55 C N o te: O nly two d e ci m als are all





Attribute Name	Туре	Require Optiona Conditi Read Only	May	Con dit ion	Values	Description	Additio nal Notes
							o w ed.
maxTemperature UOM	Strin	Optiona	20		C, F	Temp UOM	C, F
maxVolume	Decir	Y@ btiona	120,2			Maximum volume of a container.	
maxVolumeUOM	Strin	Optiona	20		Cubic feet, cubic meter	Volume UOM	Cubic feet, cubic meter
maxWeight	Decir	n@ btiona	120,2			Maximum weight of a container.	Note: Only two decimals are all owed.
maxWeightUOM	Strin	Optiona	20		KG,LB	Weight UOM	KG,LB





Attribute Name	Туре	Require Optiona Conditi Read Only	May	Con dit ion	Values	Description	Addit nal No	
minTemperature	Decir	Ma btiona	I2O,2			Minimum temp a container can be moved.	23.55	Note: Only two decimals are all owed.
minTemperature UOM	String	Optiona	20		C, F	Temp UOM	C, F	
o2	Decir	r@ btiona	120,2			Oxygen Level of Container	23.55	N o te: O nly two d e ci m als are





Attribute Name	Туре	Require Optiona Conditi Read Only	May	Con dit ion	Values	Description	Addit nal No	
								all o w ed.
originatorCode	String	Optiona	20			Shipper Office Code		
packageType	Strin	gOptiona	1100			Sets type of the package.		
packages	Bigin	Optiona	10			Number of packages		
releaseNumber	String	gOptiona	150			Release number of a container.		
reservationNumber	String	Optiona	50			Reservation number of a container		
sealNumber	String	gOptiona	150			Seal Number of a container		
setPointTemperature	Decir	Optiona	20,2			Set Point temp a container can be moved.	23.55	Note: Only two decimals are





Attribute Name	Туре	Require Optiona Conditi Read Only	May	Con dit ion	Values	Description	Addit nal No	
								o w ed.
setPointTemperature UOM	String	gOptiona	120		C, F	Temp UOM	C, F	
tareWeight	Decir	Optiona	20,2			Weight of empty container.	23.55	Note: Only two decimals are all owed.
tareWeightUOM	String	gOptiona	120		KG,LB	Weight UOM	KG,LB	
updatedBy	Strin	Optiona	50			Last updated by source		
vgmMethod	String	gOptiona	120			Method to verify gross mass.		
vgmWeight	Decir	Optiona	20,2			Weight after gross mass if verified.	23.55	LB





Attribute Name	Type	Require Optiona Conditi Read Only	Max	Con dit ion	Values	Description	Additio nal Note	
							N o te O nll tv d e ci m al ar al o w ec	i i ls re
vgmWeightUOM	String	gOptiona	120		KG,LB	Weight UOM	KG,LB	

5.4. Shipment Notes/Comments

Attribute Name	Туре	Require Optiona Conditi Read Only	May	Con dit ion	Values	Description	Additio nal Notes
comments	Strin	gOptiona	14000)		Comments provided on the shipment.	
createdTimestamp	times	Optiona	3			Created Date and Time	Format: MM-dd- yyyy





Attribute Name	Туре	Require Optiona Conditi Read Only	Max	Values	Description	Additio nal Notes
						HH:mm Example: 12-14-2 022 15:20
createdBy	Strin	gOptiona	150		Shipment Created by Name	
updatedTimeStamp	times	Optiona	3		Last Updated Date and Time	Format: MM-dd- yyyy HH:mm Example: 12-14-2 022 15:20
originatorCode	Strin	gOptiona	120		An identifier for the Originator office that is managing the shipment.	
party	Strin	Optiona	50		Shipment Party Name	
shipmentType	Strin	gOptiona	150	Domest ic, Import, Ex	Type of shipment	Domest ic, Import, Ex





Attribute Name	Туре	Require Optiona Conditi Read Only	May	Con dit ion	Values	Description	Additio nal Notes
					port		port
updatedBy	Strin	Optiona	50			Shipment last updated by name.	

5.5. Shipment Parties

Attribute Name	Туре	Require Optiona Conditi Read Only	Max	Con dit ion	Values	Description	Additio nal Notes
address	Strin	gOptiona	1200			Address of shipment party.	
addressLine1	Strin	Require	200			Address Line 1 of shipment party.	
addressLine2	Strin	gOptiona	1100			Address Line 2 of shipment party.	
city	Strin	Require	50			City of shipment party.	
contactName	Strin	gOptiona	1250			Contact Name of shipment party.	
countryShort	Strin	Require	50		Ex: US	Country Name of shipment party.	
countryLong	Strin	gOptiona	1250		United States	Full Country Name	





Attribute Name	Туре	Require Optiona Conditi Read Only	May	Con dit ion	Values	Description	Additio nal Notes
createdDate	Time	Require	3			Created Date and Time	Format: MM-dd- yyyy HH:mm Example: 12-14-2 022 15:20
createdBy	Strin	gRequire	d 50			Created By Name	
fax	Strin	Optiona	20			Fax number of shipment party	
lastUpdatedDate	times	s apti pona	13			Last Updated Date and Time	Format: MM-dd- yyyy HH:mm Example: 12-14-2 022 15:20
latitude	decir	Optiona	20, 5			Latitude coordinates of location	
locationCode	Strin	gOptiona	I5O			Location Code of shipment	
locationName	String	Optiona	200			Location Code of shipment	





Attribute Name	Туре	Require Optiona Conditi Read Only	May	Con dit ion	Values	Description	Additio nal Notes
locationType	String	gOptiona	150			Location Type of shipment	
locationUUID	Strin	Optiona	50			Location Universally Unique Identifier Number	
longitude	decir	r@ þtiona	I2O, 5			Longitude coordinates of location	
plusCode	Strin	Optiona	20			Plus Code of location	
postalCode	Strin	gRequire	20			Postal code of location	
stateShort	Strin	Require	20			State name of shipment party	
stateLong	Strin	gOptiona	180			Long state name of shipment party	
telephone	Strin	Optiona	20			Telephone number of shipment party	
timeZone	Strin	gOptiona	1100			Time Zone of the location	
unlocode	Strin	Optiona	50			United Nations Code for Trade and Transport Locations of location.	
updatedBy	Strin	gOptiona	150			Last Updated By Name	





Attribute Name	Туре	Require Optiona Conditi Read Only	May	Con dit ion	Values	Description	Additio nal Notes
dunsNumber	Strin	Optiona	50			Data Universal Numbering System Number of shipment party.	
email	Strin	gOptiona	I8O			Email address of shipment party.	
orgUUID	Strin	Optiona	20			Organization Universally Unique Identifier number.	
orgUUIDStatus	Strin	gOptiona	120			Organization Universally Unique Identifier number Status.	
originatorCode	Strin	Optiona	20			An identifier for the Originator office that is managing the shipment.	
partyCode	Strin	gOptiona	I5O			Shipment Party Code	
partyName	Strin	Optiona	100			Shipment Party Name	
partyType	String	gOptiona	150			Shipment Party Type	





Attribute Name	Туре	Require Optiona Conditi Read Only	May	Con dit ion	Values	Description	Additio nal Notes
phoneExtension	String	Optiona	20			Extension number of shipment party.	
phoneNumber	String	gOptiona	120			Phone number of shipment party.	

5.6. Shipment References

Attribute Name	Туре	Require Optiona Conditi Read Only	Max	Con dit ion	Values	Description	Additio nal Notes
createdDate	Time	s Reнqu oire	c3		yy yy-MM- dd'T'HH:m m:ss.SSS 'Z'	Shipment creation date and time	Format: MM-dd- yyyy HH:mm Example: 12-14-2 022 15:20
createdBy	Strin	Require	50			Name or Id of the person who added the comments.	
lastUpdatedDate	Time	s ©apntip na	13			Date and time for the last shipment details update.	Format: MM-dd- yyyy HH:mm





Attribute Name	Туре	Require Optiona Conditi Read Only	May	Con dit ion	Values	Description	Additio nal Notes
							Example: 12-14-2 022 15:20
orignatorCode	String	Optiona	20			An identifier for the Originator office that is managing the shipment.	
receiverCode	Strin	gOptiona	120			Designated Carrier Code.	
shipmentReferenceT ype	String	Optiona	50		SHIPMEN TREFN UM, PICKUPRE FERENCE NUMBER	Reference type of a shipment.	
shipmentReferenceV alue	String	gOptiona	1600		CUSTOM ERREF NUM	The Reference value for a Shipment.	

5.7. Shipment Charges

Attribute Name	Туре	Require Optiona Conditi Read Only	Max	Con dit ion	Values	Description	Additio nal Notes
amount	decir	m a þtiona	l12,2			Base charge amount	





Attribute Name	Туре	Require Optiona Conditi Read Only	Max	Con dit ion	Values	Description	Additio nal Notes
approvalStatus	string	Optiona	20			Sets status of the charge.	
billTo	string	gOptiona	1250		Ex. Carrier, LSP, Supplier	Bill to Party Value	
chargeBasis	string	Optiona	20		'Flat Charge, Per UOM, Percenta ge'	Charge Basis of the Shipment.	
chargeBasisUOM	string	gOptiona	120		'Mile, KM, Pound, Base Charge',	Charge Basis of the Shipment in Unit of measure.	'Mile, KM, Pound, Base Charge',
chargeBasisValue	decir	Optiona	12,2		'1000, 12000'	Charge Basis value of the shipment.	
chargeCode	Strinį	gRequire	d2O		'Base Dray, Demurra ge, Toll Cost, Fuel Surchar ge.	Charge Code of the shipment.	
chargeGroup	Strin	Optiona	20		'Base Charge, Accessori al, Fuel Surchar ge, Asset Charge.	Charge Group of the shipment	
chargeName	Strin	gOptiona	150			Name of the Charge	





Attribute Name	Туре	Require Optiona Conditi Read Only	May	Con dit ion	Values	Description	Additio nal Notes
chargeStatus	Strin	Optiona	20			Status of the Charge	
comments	Strin	gOptiona	12000)		Comments regarding the Charge .	
createdTimestamp	times	Optiona				Created Date and Time	Format: MM-dd- yyyy HH:mm Example: 12-14-2 022 15:20
createdBy	Strin	gOptiona	I5O			Name or ID charge was created by	
currencyCode	String	Optiona	20			Currency Code of the charge.	
invoiceNumber	String	gOptiona	150			Number of the Invoice.	
invoiceableDate	date	Optiona				The Invoiceable date.	Format: MM-dd- yyyy HH:mm Example: 12-14-2 022 15:20





Attribute Name	Туре	Require Optiona Conditi Read Only	Max	Con dit ion	Values	Description	Additio nal Notes
isBillable	Boole	வ ptiona	I		true/false	Charge can be billable or not	
isInvoiced	Boole	Optiona			true/false	Charge can be invoiced or not	
isModifiable	Boole	வ ptiona	I		true/false	Charge can be modified or not	
updatedTimestamp	times	Require				Last updated date and time	
originatorCode	String	gOptiona	120			Originator Code	
partnerCode	String	Optiona	50			For Carrier related charges, it will be carrier code. For charges related to other service providers, it will the respective code of the service provider. If the charges are related to Customer, it will be the customer code.	
payableInvoiceNum ber	String	gOptiona	150			Payable Invoice Number	
ratePerUnitBasisVa lue	decir	Optiona	12,2			Rate per Unit Basis Value	





Attribute Name	Туре	Require Optiona Conditi Read Only	Max	Con dit ion	Values	Description	Additio nal Notes
revenue	decir	r@ þtiona	l12,2			Revenue incurred from charge.	
updatedBy	Strin	Optiona	50			Name or ID the charge	
woChargeld	String	gOptiona	I5O			Work Order Charge ID	

5.8. Freight Line Items

Attri bute Name	Туре	Requir ed/Opti onal/Co ndition al/Read Only	Max Le ngth	Cond ition	Values	Descri ption	Addit ional Notes
commod ity	String	Optional	100			Commod ity descript ion of shipme nt.	
create dBy	String	Required	50			Freight created by	
itemN ame	String	Optional	50			Name of the Freight item	
itemNum ber	bigint	Optional	10			Number of the Freight item.	





Attri bute Name	Type	Requir ed/Opti onal/Co ndition al/Read Only	Max Le ngth	Cond ition	Values	Descri ption	Addit ional Notes
lastUpda teDttm	timest amp	Optional	3		yy yy-MM- dd'T'HH: mm:ss.SS S'Z'	Date and time for the last freight line item updated.	
originator Code	String	Optional	20			An identifier for the Origina tor office that is manag ing the shipme nt.	
purchase OrderNu mber	String	Optional	50			Number of the Purchase Order.	
quantity	Decimal	Optional	12,2			Quantity of Freight line items.	
quantity UOM	String	Optional	20			The unit of freight line item that is manag ed.	
uniqueld enfier	bigint	Optional	50			Unique identifica tion number	





Attri bute Name	Туре	Requir ed/Opti onal/Co ndition al/Read Only	Max Le ngth	Cond ition	Values	Descri ption	Addit ional Notes
						of the freight line item.	
updat eBy	String	Optional	50			Freight line item updated by.	

5.9. Master Data

Attribute Name	Туре	Require Optiona Conditi Read Only	Max	Values	Description	Additio nal Notes
equipmentType	string	gRequire(2 0	Specify UCU (Unspecified containerunit) if unknown.	Sets standard container code like 40ST etc.	22UP-20' Hardtop, 2528-Ge nset Underslu ng, 25GP-H IGH CUBE CONT
mode	strinį	Optiona	50		Assigned mode of a shipment	AIR, DRAY, RAIL, BARGE, FCL, LCL,LTL, PARCEL, RAIL, TL





Attribute Name	Туре	Require Optiona Conditi Read Only	May	Con dit ion	Values	Description	Additio nal Notes
shipmentType	string	Require	d2O		Domestic ,lmport, Export	Shipment Type	Domestic ,lmport, Export
party	string	Optiona	50			Shipment Party Name	
address	string	Optiona	1200			Address of shipment party.	
tripType	decir	Require	50		OneWay, RoundT rip	Indicates whether the trip is a one way or round trip	OneWay, RoundT rip
stopAction	Strin	gRequire	d50		LiveLoad, Live, Unload, Drop and Pick, Pickup, Delivery, Return,Cu stoms, Departu re, Arrival	Stop the activity happening on the shipment	





6. Error Codes



Note: Please email support@blumeglobal.com to speak with Blume Global Support if you require more information on specific error codes.

Table 4. Error Codes

Error Code	Error Description
BO312O21	Content Errors : Invalid originator code supplied.
BO313OO1	Missing Data Errors: Shipment leg number and originator code are required.
B0304002	Logic Errors : No records found for supplied input.
BO309001	Internal Errors: There is a problem processing your request. Please retry later or contact support.
BO312O41	Content Errors: Country code cannot be more than two characters and in upper case. Example: US, CA.
BO312O42	Content Errors: Minimum 2 stops are required.
BO312O52	Content Errors: Origin and Destination is not covered under the contract.
BO312O79	Content Error: Stop Number cannot be Zero.





7. Appendix

Refer to your customer specific data requirements to ensure you are entering all information requested by your customer.

If you need a copy of your customer data requirements please contact Blume Global Support at support@blumeglobal.com.