



How to build a basic CRUD app with Node.js and ReactJS ?

- Read
- Discuss
- Courses

In this article, we will create a basic Student app from scratch.

App functionality:

- Create a new student
- Update an existing student
- Show students list
- Delete a student

REST API in this project:

REST API	URL
GET	http://localhost:4000/students



GET	/students/update-student/id
POST	/students/create-student
PUT	/students/update-student/id
DELETE	/students/delete-student/id

First of all, we will work on the frontend part of our application using React.js.

Create React Application and installing modules

Step 1: Let's start building the Front-end part with React. To create a new React App, enter the following code into terminal and hit enter.

```
npx create-react-app mern-stack-crud
```

Step 2: Move into the React project folder.

```
cd mern-stack-crud
```

Step 3: To run the React App, run the following command:

```
npm start
```

This command opens the React App to the browser on the following URL: <http://localhost:3000/>

Step 4: To build the React App we need to install some external modules.

NPM	Detail
React-Bootstrap	React-Bootstrap has evolved and grown alongside React, making it an excellent choice for your UI.

React-Router-Dom	React Router DOM enables you to implement routing in a React App.
Axios	It is a promise base HTTP Client and use for network request.
Formik	A great library to build form in React.
Yup	Yup is a JavaScript schema builder for form validation.

To install, run the following code on the terminal.


```
npm i react-bootstrap@next bootstrap@5.1.0 react-router-dom  
axios formik yup
```

Step 5: Creating Simple React Components – In this step we will create some React Components to manage student data.

Head over to **src** folder, make a folder and name it **Components** and within that directory create the following components.

- **StudentForm.js** – Reusable Student form
- **create-student.component.js** – Responsible for create new student
- **edit-student.component.js** – Responsible for update student data
- **student-list.component.js** – Responsible for display all student
- **StudentTableRow.js** – Responsible for display a single student

Project Structure: It will look like the following



front-end project structure

Step 6: Create student form – In this step, we will build a reusable student form with Formik and React-Bootstrap. This form has all the necessary fields to enter student details. We have also made client-side form validation with Yup. In the future, we will use this component for creating and update a student. Go to ***src/Components/StudentForm.js*** and write the following code.

StudentForm.js

```
import React from "react";
import * as Yup from "yup";
import { Formik, Form, Field, ErrorMessage } from "formik";
import { FormGroup, FormControl, Button } from "react-bootstrap";

const StudentForm = (props) => {
  const validationSchema = Yup.object().shape({
```

```
name: Yup.string().required("Required"),
email: Yup.string()
  .email("You have enter an invalid email address")
  .required("Required"),
rollno: Yup.number()
  .positive("Invalid roll number")
  .integer("Invalid roll number")
  .required("Required"),
});
console.log(props);
return (
  <div className="form-wrapper">
    <Formik {...props} validationSchema={validationSchema}>
      <Form>
        <FormGroup>
          <Field name="name" type="text"
            className="form-control" />
          <ErrorMessage
            name="name"
            className="d-block invalid-feedback"
            component="span"
          />
        </FormGroup>
        <FormGroup>
          <Field name="email" type="text"
            className="form-control" />
          <ErrorMessage
            name="email"
            className="d-block invalid-feedback"
            component="span"
          />
        </FormGroup>
        <FormGroup>
          <Field name="rollno" type="number"
            className="form-control" />
          <ErrorMessage
            name="rollno"
            className="d-block invalid-feedback"
            component="span"
          />
        </FormGroup>
        <Button variant="danger" size="lg"
          block="block" type="submit">
          {props.children}
        </Button>
      </Form>
    </Formik>
  </div>
);
```

```
};
```

```
export default StudentForm;
```

Step 7: Create a new student: In this step, we will create a component to add a new student. We have already created a ***StudentForm*** component to enter student details. Now, it's time to use this component. Go to ***src/Components/create-student.component.js*** and write the following code.

create-student.component.js

```
// CreateStudent Component for add new student

// Import Modules
import React, { useState, useEffect } from "react";
import axios from 'axios';
import StudentForm from "../StudentForm";

// CreateStudent Component
const CreateStudent = () => {
  const [formValues, setFormValues] =
    useState({ name: '', email: '', rollno: '' })
  // onSubmit handler
  const onSubmit = studentObject => {
    axios.post(
      'http://localhost:4000/students/create-student',
      studentObject)
      .then(res => {
        if (res.status === 200)
          alert('Student successfully created')
        else
          Promise.reject()
      })
      .catch(err => alert('Something went wrong'))
  }

  // Return student form
  return(
    <StudentForm initialValues={formValues}
      onSubmit={onSubmit}
      enableReinitialize>
      Create Student
    </StudentForm>
  )
}
```

```
// Export CreateStudent Component
export default CreateStudent
```

Step 8: Update student's details: In this section, we will create a component to update details. We have reusable *StudentForm* component, let's use it again. We will fetch student details to reinitialise form. Go to *src/Components/edit-student.component.js* and write the following code.

edit-student.component.js

```
// EditStudent Component for update student data

// Import Modules
import React, { useState, useEffect } from "react";
import axios from "axios";
import StudentForm from "../StudentForm";

// EditStudent Component
const EditStudent = (props) => {
  const [formValues, setFormValues] = useState({
    name: "",
    email: "",
    rollno: "",
  });

  //onSubmit handler
  const onSubmit = (studentObject) => {
    axios
      .put(
        "http://localhost:4000/students/update-student/" +
        props.match.params.id,
        studentObject
      )
      .then((res) => {
        if (res.status === 200) {
          alert("Student successfully updated");
          props.history.push("/student-list");
        } else Promise.reject();
      })
      .catch((err) => alert("Something went wrong"));
  };

  // Load data from server and reinitialize student form
  useEffect(() => {
```

```

    axios
      .get(
        "http://localhost:4000/students/update-student/"
        + props.match.params.id
      )
      .then((res) => {
        const { name, email, rollno } = res.data;
        setFormValues({ name, email, rollno });
      })
      .catch((err) => console.log(err));
  }, []);

  // Return student form
  return (
    <StudentForm
      initialValues={formValues}
      onSubmit={onSubmit}
      enableReinitialize
    >
      Update Student
    </StudentForm>
  );
};

// Export EditStudent Component
export default EditStudent;

```

Step 9: Display list of students: In this step, we will build a component to display the student details in a table. We will fetch student's data and iterate over it to create table row for every student. Go to *src/Components/student-list.component.js* and write the following code.

student-list.component.js

```

import React, { useState, useEffect } from "react";
import axios from "axios";
import { Table } from "react-bootstrap";
import StudentTableRow from "./StudentTableRow";

const StudentList = () => {
  const [students, setStudents] = useState([]);

  useEffect(() => {
    axios
      .get("http://localhost:4000/students/")

```



```

        .then(({ data }) => {
            setStudents(data);
        })
        .catch((error) => {
            console.log(error);
        });
    }, []);

const DataTable = () => {
    return students.map((res, i) => {
        return <StudentTableRow obj={res} key={i} />;
    });
};

return (
    <div className="table-wrapper">
        <Table striped bordered hover>
            <thead>
                <tr>
                    <th>Name</th>
                    <th>Email</th>
                    <th>Roll No</th>
                    <th>Action</th>
                </tr>
            </thead>
            <tbody>{DataTable()}</tbody>
        </Table>
    </div>
);
};

export default StudentList;

```

Step 10: Display a single student: In this step, we will return table row which is responsible to display student data. Go to *src/Components/StudentTableRow.js* and write the following code.

StudentTableRow.js

```

import React from "react";
import { Button } from "react-bootstrap";
import { Link } from "react-router-dom";
import axios from "axios";

const StudentTableRow = (props) => {
    const { _id, name, email, rollno } = props.obj;

```

```

const deleteStudent = () => {
  axios
    .delete(
      "http://localhost:4000/students/delete-student/" + _id
    )
    .then((res) => {
      if (res.status === 200) {
        alert("Student successfully deleted");
        window.location.reload();
      } else Promise.reject();
    })
    .catch((err) => alert("Something went wrong"));
};

return (
  <tr>
    <td>{name}</td>
    <td>{email}</td>
    <td>{rollno}</td>
    <td>
      <Link className="edit-link"
        to={"/edit-student/" + _id}>
        Edit
      </Link>
      <Button onClick={deleteStudent}
        size="sm" variant="danger">
        Delete
      </Button>
    </td>
  </tr>
);
};

export default StudentTableRow;

```

Step 11: Edit App.js: Finally, include the menu to make routing in our MERN Stack CRUD app. Go to *src/App.js* and write the following code.

App.js

```

// Import React
import React from "react";

// Import Bootstrap
import { Nav, Navbar, Container, Row, Col }
  from "react-bootstrap";
import "bootstrap/dist/css/bootstrap.css";

```

```
// Import Custom CSS
import "./App.css";

// Import from react-router-dom
import { BrowserRouter as Router, Switch,
  Route, Link } from "react-router-dom";

// Import other React Component
import CreateStudent from
  "./Components/create-student.component";
import EditStudent from
  "./Components/edit-student.component";
import StudentList from
  "./Components/student-list.component";

// App Component
const App = () => {
  return (
    <Router>
      <div className="App">
        <header className="App-header">
          <Navbar bg="dark" variant="dark">
            <Container>
              <Navbar.Brand>
                <Link to={"/create-student"}
                  className="nav-link">
                  React MERN Stack App
                </Link>
              </Navbar.Brand>

              <Nav className="justify-content-end">
                <Nav>
                  <Link to={"/create-student"}
                    className="nav-link">
                    Create Student
                  </Link>
                </Nav>

                <Nav>
                  <Link to={"/student-list"}
                    className="nav-link">
                    Student List
                  </Link>
                </Nav>
              </Nav>
            </Container>
          </Navbar>
        </header>
```

```

    <Container>
      <Row>
        <Col md={12}>
          <div className="wrapper">
            <Switch>
              <Route exact path="/"
                component={CreateStudent} />
              <Route path="/create-student"
                component={CreateStudent} />
              <Route path="/edit-student/:id"
                component={EditStudent} />
              <Route path="/student-list"
                component={StudentList} />
            </Switch>
          </div>
        </Col>
      </Row>
    </Container>
  </div>
</Router>
);
};

export default App;

```

Step 12: Add style – Go to *src/App.css* and write the following code.

App.css

```

.wrapper {
  padding-top: 30px;
}

body h3 {
  margin-bottom: 25px;
}

.navbar-brand a {
  color: #ffffff;
}

.form-wrapper,
.table-wrapper {
  max-width: 500px;
  margin: 0 auto;
}

```

```
.table-wrapper {
  max-width: 700px;
}

.edit-link {
  padding: 7px 10px;
  font-size: 0.875rem;
  line-height: normal;
  border-radius: 0.2rem;
  color: #fff;
  background-color: #28a745;
  border-color: #28a745;
  margin-right: 10px;
  position: relative;
  top: 1px;
}

.edit-link:hover {
  text-decoration: none;
  color: #ffffff;
}

/* Chrome, Safari, Edge, Opera */
input::-webkit-outer-spin-button,
input::-webkit-inner-spin-button {
  -webkit-appearance: none;
  margin: 0;
}


/* Firefox */
input[type=number] {
  -moz-appearance: textfield;
}
```

Now, we have successfully created the frontend for our ***mern-stack-app***. Let's build the backend part. Before, jumping to next section take a look how the frontend part working without backend.

Step to run the application: Open the terminal and type the following command.

```
npm start
```

Output:



Now we will work on the backend part of our application. We will create a folder inside our ***mern-stack-crud*** to manage the server services such as database, models, schema, routes and APIs, name this folder ***backend***.

Step 1: Run command to create ***backend*** folder for server and get inside of it.

```
mkdir backend && cd backend
```

Step 2: Create package.json – Next, we need to create a separate ***package.json*** file for managing the server of our ***mern-stack-crud*** app.

```
npm init -y
```

Go to ***backend/package.json*** file will look like the following. Replace the ***test*** property like:

```
"test": "echo \"Error: no test specified\" && exit 1"
"start": "nodemon server.js"
```

Step 3: Install Node Dependencies – Install the following Node dependencies.

NPM	Detail
Express	Node.js framework that helps in creating powerful REST APIs.
body-parser	Extracts the entire body portion of a request stream and exposes it on req.body.
cors	It's a Node.js package that helps in enabling Access-Control-Allow-Origin CORS header.
mongoose	It's a NoSQL database for creating a robust web application.


To install the above dependencies, run the following code on the terminal.

```
npm install express body-parser cors mongoose
```

You may install *nodemon* as dev dependency to automate the server restarting process.

```
npm i -D nodemon
```

Back-end project structure



Step 4: Setting up MongoDB Database – In this step, we will set up a MongoDB database for our app. Before, starting make sure you have latest version of MongoDB is installed on your system. Create folder inside the **backend** folder and name it **database**. Create a file by the name of **db.js** inside the **database** folder. Go to **backend/database/db.js** and write the following code.

db.js

```
module.exports = {  
  db: 'mongodb://localhost:27017/reactdb'  
};
```

We have declared the MongoDB database and name it **reactdb**.

Step 5: Define Mongoose Schema – Now, create MongoDB schema for interacting with MongoDB database. Create a folder called **models** inside **backend** folder to keep schema related files and create a file **Student.js** inside of it to define MongoDB schema. Go to **backend/models/Student.js** and write the following code.

Student.js

```
const mongoose = require('mongoose');  
const Schema = mongoose.Schema;  
  
let studentSchema = new Schema({  
  name: {  
    type: String  
  },  
  email: {  
    type: String  
  },  
  rollno: {  
    type: Number  
  }  
}, {  
  collection: 'students'  
})
```



```
module.exports = mongoose.model('Student', studentSchema)
```

We declared name, email, and rollno fields along with their respective data types in student Schema.

Step 6: Create Routes Using ExpressJS – In this step, we are set up some routes (REST APIs) for CREATE, READ, UPDATE and DELETE using Express and Node.js. These routes will help us to manage the data in our *mern-stack-crud* app. Create a folder and name it routes inside backend folder. Here we will keep all the routes related files. Also, create a file and name it *student.routes.js* inside *routes* folder, in this file we will define our routes.

```
mkdir routes && cd routes && touch student.route.js
```

Then, go to *backend/routes/student.route.js* file and write the following code.

student.route.js

```
let mongoose = require("mongoose"),
    express = require("express"),
    router = express.Router();

// Student Model
let studentSchema = require("../models/Student");

// CREATE Student
router.post("/create-student", (req, res, next) => {
  studentSchema.create(req.body, (error, data) => {
    if (error) {
      return next(error);
    } else {
      console.log(data);
      res.json(data);
    }
  });
});

// READ Students
router.get("/", (req, res) => {
  studentSchema.find((error, data) => {
    if (error) {
      return next(error);
    }
  });
});
```

```
    } else {
      res.json(data);
    }
  });
});

// UPDATE student
router
  .route("/update-student/:id")
  // Get Single Student
  .get((req, res) => {
    studentSchema.findById(
      req.params.id, (error, data) => {
        if (error) {
          return next(error);
        } else {
          res.json(data);
        }
      }
    );
  })

  // Update Student Data
  .put((req, res, next) => {
    studentSchema.findByIdAndUpdate(
      req.params.id,
      {
        $set: req.body,
      },
      (error, data) => {
        if (error) {
          return next(error);
          console.log(error);
        } else {
          res.json(data);
          console.log("Student updated successfully !");
        }
      }
    );
  });

// Delete Student
router.delete("/delete-student/:id",
  (req, res, next) => {
    studentSchema.findByIdAndRemove(
      req.params.id, (error, data) => {
        if (error) {
          return next(error);
        } else {
          res.status(200).json({
```

```
        msg: data,
      });
    }
  });
});

module.exports = router;
```

Step 7: Configure server.js – We have almost created everything for our *mern-stack-crud* app. Now, create the *server.js* file in the root of the *backend* folder. Go to *backend/server.js* and write the following code.

server.js

```
let express = require('express');
let mongoose = require('mongoose');
let cors = require('cors');
let bodyParser = require('body-parser');
let dbConfig = require('./database/db');

// Express Route
const studentRoute = require('../backend/routes/student.route')

// Configure MongoDB Database
mongoose.set('useNewUrlParser', true);
mongoose.set('useFindAndModify', false);
mongoose.set('useCreateIndex', true);
mongoose.set('useUnifiedTopology', true);

// Connecting MongoDB Database
mongoose.Promise = global.Promise;
mongoose.connect(dbConfig.db).then(() => {
  console.log('Database successfully connected!')
},
error => {
  console.log('Could not connect to database : ' + error)
}
)

const app = express();
app.use(bodyParser.json());
app.use(bodyParser.urlencoded({
  extended: true
}));
app.use(cors());
```

```
app.use('/students', studentRoute)

// PORT
const port = process.env.PORT || 4000;
const server = app.listen(port, () => {
  console.log('Connected to port ' + port)
})

// 404 Error
app.use((req, res, next) => {
  res.status(404).send('Error 404!')
});

app.use(function (err, req, res, next) {
  console.error(err.message);
  if (!err.statusCode) err.statusCode = 500;
  res.status(err.statusCode).send(err.message);
});
```

Now, we have successfully created the backend for our *mern-stack-app*.

Our final project directory structure:

```

✓ MERN-STACK-APP
  ✓ backend
    ✓ database
      JS db.js
    ✓ models
      JS Student.js
    > node_modules
  ✓ routes
    JS student.route.js
  {} package-lock.json
  {} package.json
  JS server.js
  > node_modules
  > public
  ✓ src
    ✓ Components
      JS create-student.component.js
      JS edit-student.component.js
      JS student-list.component.js
      JS StudentForm.js
      JS StudentTableRow.js
    # App.css
    JS App.js
    JS App.test.js
    # index.css
    JS index.js
    logo.svg
    JS serviceWorker.js
  .gitignore
  {} package-lock.json
  {} package.json
```

project-directory-structure

Now, start the MongoDB database server to run the server.

Step to run the application: Open a terminal and run the following command to start the Nodemon server by staying in the **backend** folder.


```
npm start
```

If everything is working well you will see the following output on the terminal screen.

```
[nodemon] 1.19.4
[nodemon] to restart at any time, enter `rs`
[nodemon] watching dir(s): *.*
[nodemon] watching extensions: js,mjs,json
[nodemon] starting `node server.js`
Connected to port 4000
Database successfully connected!
```

mern-stack-crud server-running

Final output:



mern-stack-crud-app

Whether you're preparing for your first job interview or aiming to upskill in this ever-evolving tech landscape, [GeeksforGeeks Courses](#) are your key to success. We provide top-quality content at affordable prices, all geared towards accelerating your growth in a time-bound manner. Join the millions we've already empowered, and we're here to do the same for you. Don't miss out - [check it out now!](#)

Last Updated : 10 Apr, 2022

30

[Previous](#)

[Next](#)

Creating a Vertical Stepper in React

Largest Rectangle Area under Histogram using JavaScript | Without using Stacks

Similar Reads

Build a Basic React App that Display "Hello World!"

How to do CRUD operations in ReactJS ?

CRUD Operations and File Upload using Node.js and MongoDB

Build a simple Song Lyrics Finder app using ReactJS

Build a Anagram Checker App Using ReactJS

Build a Random User Generator App Using ReactJS

Build a Simple Tip Calculator App with ReactJS

Node.js CRUD Operations Using Mongoose and MongoDB Atlas

Build a Simple Beginner App with Node.js Bootstrap and MongoDB

Build a Node.js-powered Chatroom Web App

Complete Tutorials

SAP - Systems Applications and Products | A Complete Learning Hub

Spring MVC Tutorial

Spring Boot Tutorial

Java 8 Features - Complete Tutorial

React Material UI

B **braktim99**

Article Tags : [Blogathon-2021](#) , [MongoDB-method](#) , [NodeJS-Questions](#) , [Picked](#) , [React-Questions](#) , [Blogathon](#) , [MongoDB](#) , [Node.js](#) , [ReactJS](#)

Additional Information



A-143, 9th Floor, Sovereign Corporate Tower, Sector-136, Noida, Uttar Pradesh - 201305



Company

[About Us](#)

[Legal](#)

[Careers](#)

[In Media](#)

[Contact Us](#)

[Advertise with us](#)

[GFG Corporate Solution](#)

[Placement Training Program](#)

[Apply for Mentor](#)

Explore

[Job-A-Thon Hiring Challenge](#)

[Hack-A-Thon](#)

[GfG Weekly Contest](#)

[Offline Classes \(Delhi/NCR\)](#)

[DSA in JAVA/C++](#)

[Master System Design](#)

[Master CP](#)

[GeeksforGeeks Videos](#)

Languages

Python
Java
C++
PHP
GoLang
SQL
R Language
Android Tutorial

Data Science & ML

Data Science With Python
Data Science For Beginner
Machine Learning Tutorial
ML Maths
Data Visualisation Tutorial
Pandas Tutorial
NumPy Tutorial
NLP Tutorial
Deep Learning Tutorial

Python

Python Programming Examples
Django Tutorial
Python Projects
Python Tkinter
Web Scraping
OpenCV Python Tutorial
Python Interview Question

DevOps

Git
AWS
Docker

DSA

Data Structures
Algorithms
DSA for Beginners
Basic DSA Problems
DSA Roadmap
Top 100 DSA Interview Problems
DSA Roadmap by Sandeep Jain
All Cheat Sheets

HTML & CSS

HTML
CSS
Bootstrap
Tailwind CSS
SASS
LESS
Web Design

Computer Science

GATE CS Notes
Operating Systems
Computer Network
Database Management System
Software Engineering
Digital Logic Design
Engineering Maths

Competitive Programming

Top DS or Algo for CP
Top 50 Tree
Top 50 Graph

[Kubernetes](#)[Top 50 Array](#)[Azure](#)[Top 50 String](#)[GCP](#)[Top 50 DP](#)[DevOps Roadmap](#)[Top 15 Websites for CP](#)

System Design

[What is System Design](#)[Monolithic and Distributed SD](#)[High Level Design or HLD](#)[Low Level Design or LLD](#)[Crack System Design Round](#)[System Design Interview Questions](#)[Grokking Modern System Design](#)

JavaScript

[TypeScript](#)[ReactJS](#)[NextJS](#)[AngularJS](#)[NodeJS](#)[Express.js](#)[Lodash](#)[Web Browser](#)

NCERT Solutions

[Class 12](#)[Class 11](#)[Class 10](#)[Class 9](#)[Class 8](#)[Complete Study Material](#)

School Subjects

[Mathematics](#)[Physics](#)[Chemistry](#)[Biology](#)[Social Science](#)[English Grammar](#)

Commerce

[Accountancy](#)[Business Studies](#)[Indian Economics](#)[Macroeconomics](#)[Microeconomics](#)[Statistics for Economics](#)

Management & Finance

[Management](#)[HR Management](#)[Income Tax](#)[Finance](#)[Economics](#)

UPSC Study Material

[Polity Notes](#)[Geography Notes](#)[History Notes](#)

SSC/ BANKING

[SSC CGL Syllabus](#)[SBI PO Syllabus](#)[SBI Clerk Syllabus](#)

[Science and Technology Notes](#)[IBPS PO Syllabus](#)[Economy Notes](#)[IBPS Clerk Syllabus](#)[Ethics Notes](#)[SSC CGL Practice Papers](#)[Previous Year Papers](#)

Colleges

[Indian Colleges Admission & Campus Experiences](#)[Top Engineering Colleges](#)[Top BCA Colleges](#)[Top MBA Colleges](#)[Top Architecture College](#)[Choose College For Graduation](#)

Companies

[IT Companies](#)[Software Development Companies](#)[Artificial Intelligence\(AI\) Companies](#)[CyberSecurity Companies](#)[Service Based Companies](#)[Product Based Companies](#)[PSUs for CS Engineers](#)

Preparation Corner

[Company Wise Preparation](#)[Preparation for SDE](#)[Experienced Interviews](#)[Internship Interviews](#)[Competitive Programming](#)[Aptitude Preparation](#)[Puzzles](#)

Exams

[JEE Mains](#)[JEE Advanced](#)[GATE CS](#)[NEET](#)[UGC NET](#)

More Tutorials

[Software Development](#)[Software Testing](#)[Product Management](#)[SAP](#)[SEO](#)[Linux](#)[Excel](#)

Write & Earn

[Write an Article](#)[Improve an Article](#)[Pick Topics to Write](#)[Share your Experiences](#)[Internships](#)

@GeeksforGeeks, Sanchhaya Education Private Limited, All rights reserved