Modelling Software-based Systems

Correctness by Contruction of sequential algorithms using Event-B Refinement by fusion

Master Informatique

Dominique Méry
Telecom Nancy,Université de Lorraine

29 octobre 2026

dominique.mery@loria.fr

Summary

1. CM5
2. Overview
3. Programming by contract
   - Short view
   - The call-as-event idea
   - Main idea
4. Short Summary on Event-B
5. Internalizing events by merging
6. Analysis and then Synthesis
   - Analysis using Refinement
   - Synthesis by Merging
7. Summing a list of integer values

Current Section Summary

1. CM5
2. Overview
3. Programming by contract
   - Short view
   - The call-as-event idea
   - Main idea
4. Short Summary on Event-B
5. Internalizing events by merging
6. Analysis and then Synthesis
   - Analysis using Refinement
   - Synthesis by Merging
7. Summing a list of integer values

Current Section Summary

1. CM5
2. Overview
3. Programming by contract
   - Short view
   - The call-as-event idea
   - Main idea
4. Short Summary on Event-B
5. Internalizing events by merging
6. Analysis and then Synthesis
   - Analysis using Refinement
   - Synthesis by Merging
7. Summing a list of integer values

Introduction

Introduction

- Guidelines for using the transformations proposed b y J.-R. Abrial and used for generating sequential algorithms.

Introduction

- Guidelines for using the transformations proposed b y J.-R. Abrial and used for generating sequential algorithms.
- Possibility to combine with others provers as TLAPS, Frama-c

Introduction

- Guidelines for using the transformations proposed b y J.-R. Abrial and used for generating sequential algorithms.
- Possibility to combine with others provers as TLAPS, Frama-c
- Illustrating the merging of events and the step to code.


Introduction

- Guidelines for using the transformations proposed b y J.-R. Abrial and used for generating sequential algorithms.
- Possibility to combine with others provers as TLAPS, Frama-c
- Illustrating the merging of events and the step to code.
- Relationship to PlusCal and TLA$^+$ proof tools

Big steps versus Small steps

Frpm pre/post to algorithm(s)

Refining a pre/post specification into a sequential algorithm



Current Section Summary

1. CM5
2. Overview
3. Programming by contract
   - Short view
   - The call-as-event idea
   - Main idea
4. Short Summary on Event-B
5. Internalizing events by merging
6. Analysis and then Synthesis
   - Analysis using Refinement
   - Synthesis by Merging
7. Summing a list of integer values

Current Sub Section Summary

1 CM5

2 Overview

3 Programming by contract
- Short view
- The call-as-event idea
- Main idea

4 Short Summary on Event-B

5 Internalizing events by merging

6 Analysis and then Synthesis

7 Summing a list of integer values

Verification of contract (I)

A program P *satisfies* a contract (pre,post) :

- P transforms a variable x from an initial value x_0 and produces a final value x_f : $x_0 \xrightarrow{P} x_f$
- x_0 satisfait pre : pre(x_0) and x_f satisfait post : post(x_0, x_f)
- pre$(x_0) \wedge x_0 \xrightarrow{P} x_f \Rightarrow$ post(x_0, x_f)

requires $pre(x_0)$
ensures $post(x_0, x_f)$
variables X

begin
$0 : P_0(x_0, x)$
instruction$_0$
...
$i : P_i(x_0, x)$
...
instruction$_{f-1}$
$f : P_f(x_0, x)$
end

Floyd style

- $pre(x_0) \wedge x = x_0 \Rightarrow P_0(x_0, x)$
- $pre(x_0) \wedge P_f(x_0, x) \Rightarrow post(x_0, x)$
- For each pair ℓ, ℓ' such that $\ell \longrightarrow \ell'$, one checks that foa any value $x, x' \in \text{MEMORY}$

$$\left(\begin{array}{l} \left(\begin{array}{l} pre(x_0) \wedge P_\ell(x_0, x)) \\ \wedge cond_{\ell,\ell'}(x) \wedge x' = f_{\ell,\ell'}(x) \end{array} \right) \\ \Rightarrow P_{\ell'}(x_0, x') \end{array} \right),$$

Verification du contract (II)

A program P *satisfies* a contract (pre,post) :

- P transforms a variable x from an initial value x_0 and produces a final value x_f : $x_0 \xrightarrow{P} x_f$
- x_0 satisfait pre : pre(x_0) and x_f satisfait post : post(x_0, x_f)
- pre$(x_0) \wedge x_0 \xrightarrow{P} x_f \Rightarrow$ post(x_0, x_f)

Hoare style

requires $pre(x_0)$
ensures $post(x_0, x_f)$
variables X

begin
$0 : P_0(x_0, x)$
$\texttt{instruction}_0$
...
$i : P_i(x_0, x)$
...
$\texttt{instruction}_{f-1}$
$f : P_f(x_0, x)$
end

Verification du contract (II)

A program P *satisfies* a contract (pre,post) :

- P transforms a variable x from an initial value x_0 and produces a final value x_f : $x_0 \xrightarrow{P} x_f$
- x_0 satisfait pre : pre(x_0) and x_f satisfait post : post(x_0, x_f)
- pre$(x_0) \wedge x_0 \xrightarrow{P} x_f \Rightarrow$ post(x_0, x_f)

requires $pre(x_0)$
ensures $post(x_0, x_f)$
variables X
begin
$0 : P_0(x_0, x)$
$\texttt{instruction}_0$
...
$i : P_i(x_0, x)$
...
$\texttt{instruction}_{f-1}$
$f : P_f(x_0, x)$
end

Hoare style

- $\forall x_f, x_0.$pre$(x_0) \wedge x_0 \xrightarrow{P} x_f \Rightarrow$ post(x_0, x_f)

Verification du contract (II)

A program P *satisfies* a contract (pre,post) :

- P transforms a variable x from an initial value x_0 and produces a final value x_f : $x_0 \xrightarrow{P} x_f$
- x_0 satisfait pre : pre(x_0) and x_f satisfait post : post(x_0, x_f)
- pre$(x_0) \wedge x_0 \xrightarrow{P} x_f \Rightarrow$ post(x_0, x_f)

requires $pre(x_0)$
ensures $post(x_0, x_f)$
variables X
begin
$0 : P_0(x_0, x)$
`instruction`$_0$
...
$i : P_i(x_0, x)$
...
`instruction`$_{f-1}$
$f : P_f(x_0, x)$
end

Hoare style

- $\forall x_f, x_0.$pre$(x_0) \wedge x_0 \xrightarrow{P} x_f \Rightarrow$ post(x_0, x_f)
- $\forall x_f, x_0.$pre$(x_0) \Rightarrow (x_0 \xrightarrow{P} x_f \Rightarrow$ post$(x_0, x_f))$

Verification du contract (II)

A program P *satisfies* a contract (pre,post) :

- P transforms a variable x from an initial value x_0 and produces a final value x_f : $x_0 \xrightarrow{P} x_f$
- x_0 satisfait pre : pre(x_0) and x_f satisfait post : post(x_0, x_f)
- pre$(x_0) \wedge x_0 \xrightarrow{P} x_f \Rightarrow$ post(x_0, x_f)

requires $pre(x_0)$
ensures $post(x_0, x_f)$
variables X
begin
$0 : P_0(x_0, x)$
$\texttt{instruction}_0$
...
$i : P_i(x_0, x)$
...
$\texttt{instruction}_{f-1}$
$f : P_f(x_0, x)$
end

Hoare style

- $\forall x_f, x_0.$pre$(x_0) \wedge x_0 \xrightarrow{P} x_f \Rightarrow$ post(x_0, x_f)
- $\forall x_f, x_0.$pre$(x_0) \Rightarrow (x_0 \xrightarrow{P} x_f \Rightarrow$ post$(x_0, x_f))$
- $\forall x_0.$pre$(x_0) \Rightarrow \forall x_f.(x_0 \xrightarrow{P} x_f \Rightarrow$ post$(x_0, x_f))$

Verification du contract (II)

A program P *satisfies* a contract (pre,post) :

- P transforms a variable x from an initial value x_0 and produces a final value x_f : $x_0 \xrightarrow{P} x_f$
- x_0 satisfait pre : pre(x_0) and x_f satisfait post : post(x_0, x_f)
- pre$(x_0) \wedge x_0 \xrightarrow{P} x_f \Rightarrow$ post(x_0, x_f)

requires $pre(x_0)$
ensures $post(x_0, x_f)$
variables X
begin
$0 : P_0(x_0, x)$
$\texttt{instruction}_0$
...
$i : P_i(x_0, x)$
...
$\texttt{instruction}_{f-1}$
$f : P_f(x_0, x)$
end

Hoare style

- $\forall x_f, x_0.$pre$(x_0) \wedge x_0 \xrightarrow{P} x_f \Rightarrow$ post(x_0, x_f)
- $\forall x_f, x_0.$pre$(x_0) \Rightarrow (x_0 \xrightarrow{P} x_f \Rightarrow$ post$(x_0, x_f))$
- $\forall x_0.$pre$(x_0) \Rightarrow \forall x_f.(x_0 \xrightarrow{P} x_f \Rightarrow$ post$(x_0, x_f))$
- $\forall x_0.$pre$(x_0) \Rightarrow \forall x.(x_0 \xrightarrow{P} x \Rightarrow$ post$(x_0, x))$

Verification du contract (II)

A program P *satisfies* a contract (pre,post) :

- P transforms a variable x from an initial value x_0 and produces a final value x_f : $x_0 \xrightarrow{P} x_f$
- x_0 satisfait pre : pre(x_0) and x_f satisfait post : post(x_0, x_f)
- pre$(x_0) \wedge x_0 \xrightarrow{P} x_f \Rightarrow$ post(x_0, x_f)

requires $pre(x_0)$
ensures $post(x_0, x_f)$
variables X
begin
$0 : P_0(x_0, x)$
$\texttt{instruction}_0$
...
$i : P_i(x_0, x)$
...
$\texttt{instruction}_{f-1}$
$f : P_f(x_0, x)$
end

Hoare style

- $\forall x_f, x_0.$pre$(x_0) \wedge x_0 \xrightarrow{P} x_f \Rightarrow$ post(x_0, x_f)
- $\forall x_f, x_0.$pre$(x_0) \Rightarrow (x_0 \xrightarrow{P} x_f \Rightarrow$ post$(x_0, x_f))$
- $\forall x_0.$pre$(x_0) \Rightarrow \forall x_f.(x_0 \xrightarrow{P} x_f \Rightarrow$ post$(x_0, x_f))$
- $\forall x_0.$pre$(x_0) \Rightarrow \forall x.(x_0 \xrightarrow{P} x \Rightarrow$ post$(x_0, x))$
- $\forall x_0.$pre$(x_0) \Rightarrow WLP(P)($post$(x_0, x))$

A Simple C Function

Listing 1 – Simple contract

```
#ifndef _A_H
#define _A_H
// Definition of the  mathematical function mathpower2
/*@ axiomatic auxmath {
  @ lemma rule1: \forall int n; n >0 ==> n*n == (n-1)*(n-1)+2*(n-1)+1;
  @ } */
/*@  requires  0 <= x;
  @ requires x*x <= INT_MAX;
     assigns \nothing;
     ensures \result == x*x;
*/
int power2(int x);
#endif
```

A Simple C Function

Listing 2 – Simple contract

```
#include <limits.h>
#include "power2.h"

int power2(int x)
{int r,k,cv,cw,or,ok,ocv,ocw;
  r=0;k=0;cv=0;cw=0;or=0;ok=k;ocv=cv;ocw=cw;
     /*@ loop invariant 0 <= cv && 0 <= cw && 0 <= k;
       @ loop invariant cv == k*k;
        @ loop invariant k <= x;
        @ loop invariant cw == 2*k;
        @ loop invariant 4*cv == cw*cw;
        @ loop assigns k,cv,cw,or,ok,ocv,ocw;
       @ loop variant x-k;
*/
  while (k<x)
    {
    ok=k;ocv=cv;ocw=cw;
      k=ok+1;
      cv=ocv+ocw+1;
      cw=ocw+2;

    }
  r=cv;
  return(r);
}
```

A Simple C Function

Listing 3 – Simple contract

```
frama-c -wp -rte power2.c
[kernel] Parsing power2.c (with preprocessing)
[rte:annot] annotating function power2
[wp] 30 goals scheduled
[wp] Proved goals:    32 / 32
  Terminating:         1
  Unreachable:         1
  Qed:                22 (5ms-1ms-7ms)
  Alt-Ergo 2.6.0:      8 (13ms-15ms-18ms)
```

Correct by Construction

- Finding or computing annotations is difficult and even undecidable !

Correct by Construction

- Finding or computing annotations is difficult and even undecidable !
- Given

Contract EX
Variables $X(int)$
Requires $pre(x_0)$
Ensures $post(x_0, x_f)$

Correct by Construction

- Finding or computing annotations is difficult and even undecidable !
- Given

  Contract EX
  Variables $X(int)$
  Requires $pre(x_0)$
  Ensures $post(x_0, x_f)$

- Design of the algorithm ALG fulfiling the contract

Correct by Construction

- Finding or computing annotations is difficult and even undecidable !
- Given

Contract EX
Variables $X(int)$
Requires $pre(x_0)$
Ensures $post(x_0, x_f)$

- Design of the algorithm ALG fulfiling the contract
- HOARE triple :

$$\{\mathbf{pre(x_0)} \wedge \mathbf{x} = \mathbf{x_0}\}\text{ALG}\{\mathbf{post(x_0, x)}\}$$

Correct by Construction

- Finding or computing annotations is difficult and even undecidable !
- Given

Contract EX
Variables $X(int)$
Requires $pre(x_0)$
Ensures $post(x_0, x_f)$

- Design of the algorithm ALG fulfiling the contract
- HOARE triple :

$$\{\mathbf{pre(x_0)} \wedge \mathbf{x} = \mathbf{x_0}\}\text{ALG}\{\mathbf{post(x_0, x)}\}$$

Idea ?

From Contract EX, using a step by step approach to find an algorithm ALG satisfying it using refinement and Event-B models.
Applying the CLEANROOM model but with tool support


Current Sub Section Summary

1. CM5
2. Overview
3. Programming by contract
   - Short view
   - The call-as-event idea
   - Main idea
4. Short Summary on Event-B
5. Internalizing events by merging
6. Analysis and then Synthesis
7. Summing a list of integer values

Topics

- Providing patterns for helping the use of refinement.
- Making proofs as simple as possible.
- Simplifying the discovery of invariants
- we focus on the transformation of the final concrete specification into a PlusCal algorithm :
  1. transforming an EVENT B specification into a PlusCal algorithm
  2. using the merging of events to get only one event corresponding to the call of the algroithm
  3. double checking the resulting algorithm by using TLA$^+$ and its proof system.

The call as event idea



- `call_procedure` is simulated by the event call_procedure :

EVENT CALL_PROCEDURE
WHEN
$P(d)$
THEN
$r :| Q(d, r')$
END

- $P(d)$ is specifying the inputs of the procedure.
- $Q(d, r)$ is expressing the relation between the inputs d and the results r.

Current Sub Section Summary

1. CM5
2. Overview
3. Programming by contract
   - Short view
   - The call-as-event idea
   - Main idea
4. Short Summary on Event-B
5. Internalizing events by merging
6. Analysis and then Synthesis
7. Summing a list of integer values

Call as event

- A pre/post specification is a pair of assertions $(pre, post)$
- $(pre, post)$ is defining a *transformation* over variables that is correct with respect to *HOARE* triples :

$$\{pre\}transformation\{post\}$$

- **Problem** : Design of a program PROG simulating the *transformation* with respect to $(pre, post)$:

$$\{pre\}\text{PROG}\{post\}$$


- **Idea** : Writing a *one-shot* relation simulating the relation over *flexible* variables :

$$\forall x, y.pre(x) \wedge R(x, y) \Rightarrow post(x, y)$$


- **event** : Expressing the relation :

EVENT PROG
WHEN
$pre(x)$
THEN
$y :| post(x, y')$
END


The sequential pattern




The sequential pattern




The sequential pattern




The sequential pattern




The sequential pattern




The sequential pattern




The sequential pattern




The sequential pattern




The sequential pattern



The sequential pattern



Global Picture



Current Section Summary

1. CM5
2. Overview
3. Programming by contract
   - Short view
   - The call-as-event idea
   - Main idea
4. Short Summary on Event-B
5. Internalizing events by merging
6. Analysis and then Synthesis
   - Analysis using Refinement
   - Synthesis by Merging
7. Summing a list of integer values

Short Summary on Event-B (context)

- Context : static properties of Event-B models
  - Sets : user-defined types
  - Constants : static object in development
  - Axioms : presumed properties about sets and constants
  - Theorems : derived properties about sets and constants

SETS
A
CONSTANTS
B, C, f
AXIOMS
$ax1 : B \subseteq A$
$ax2 : C \subseteq A$
$ax3 : g \in B \pfun C$
$ax4 : \forall A.A \subseteq \mathbb{N} \land 0 \in A \land suc[A] \subseteq A \Rightarrow \mathbb{N} \subseteq A$
...

Short Summary on Event-B (discrete)

- Machine : behavioral properties of Event-B models
  - Variables : states
  - Invariants : properties of variables that always need to hold
  - Theorems : derived properties about variables
  - Events : possible state changes

EVENT e
  ANY t
  WHERE
    $G(c, s, t, x)$
  THEN
    $x :\mid (P(c, s, t, x, x'))$
  END

- c et s are constantes and visible sets by e
- x is a state variable or a list of variabless
- $G(c, s, t, x)$ is the condition for observing e.
- $P(c, s, t, x, x')$ is the assertion for the relation over x and x'.
- $BA(e)(c, s, x, x')$ is the *before-after* relationship for e and is defined by $\exists t.G(c, s, t, x) \ \wedge \ P(c, s, t, x, x')$.

Short Summary on Event-B (refinement)

- Given an abstract and a corresponding concrete event

EVENT ae $\widehat{=}$
ANY v **WHERE**
$G(x, v)$
THEN
$x := E(x, v)$
END

EVENT ce $\widehat{=}$
ANY w **WHERE**
$H(y, w)$
THEN
$y := F(y, w)$
END

$$I(x) \ \wedge \ J(x, y) \ \wedge \ H(y, w)$$
$$\Longrightarrow$$
$$\exists v \cdot (G(x, v) \ \wedge \ J(E(x, v), F(y, w)))$$

- $BA(ae)(x, x') \ \widehat{=} \ \exists v.G(x, v) \wedge x' = E(x)$
- $BA(ce)(y, y') \ \widehat{=} \ \exists w.H(y, w) \wedge y' = F(y)$

Modelling systems in Event-B

Modelling systems in Event-B

MACHINE
m
SEES
c
VARIABLES
x
INVARIANT
$I(x)$
THEOREMS
$Q(x)$
INITIALISATION
$Init(x)$
EVENTS
$\ldots e$
END

Modelling systems in Event-B

MACHINE
m
SEES
c
VARIABLES
x
INVARIANT
$I(x)$
THEOREMS
$Q(x)$
INITIALISATION
$Init(x)$
EVENTS
$\ldots e$
END

c defines the static environment for the proofs related to m : sets, constants, axioms, theorems $\Gamma(m)$.

Modelling systems in Event-B

MACHINE
m
SEES
c
VARIABLES
x
INVARIANT
$I(x)$
THEOREMS
$Q(x)$
INITIALISATION
$Init(x)$
EVENTS
$\ldots e$
END

c defines the static environment for the proofs related to m : sets, constants, axioms, theorems $\Gamma(m)$.

$\Gamma(m) \vdash \forall x \in Values : \textsc{Init}(x) \Rightarrow \mathrm{I}(x)$

Modelling systems in Event-B

MACHINE
m
SEES
c
VARIABLES
x
INVARIANT
$I(x)$
THEOREMS
$Q(x)$
INITIALISATION
$Init(x)$
EVENTS
$\ldots e$
END

c defines the static environment for the proofs related to m : sets, constants, axioms, theorems $\Gamma(m)$.

$\Gamma(m) \vdash \forall x \in Values : \textsc{Init}(x) \Rightarrow \mathrm{I}(x)$

$\forall e :$
$\Gamma(m) \vdash \forall x, x', u \in Values : \mathrm{I}(x) \wedge R(u, x, x') \Rightarrow \mathrm{I}(x')$

Modelling systems in Event-B

MACHINE
m
SEES
c
VARIABLES
x
INVARIANT
$I(x)$
THEOREMS
$Q(x)$
INITIALISATION
$Init(x)$
EVENTS
$\ldots e$
END

c defines the static environment for the proofs related to m : sets, constants, axioms, theorems $\Gamma(m)$.

$\Gamma(m) \vdash \forall x \in Values : \textsc{Init}(x) \Rightarrow \mathrm{I}(x)$

$\forall e :$
$\Gamma(m) \vdash \forall x, x', u \in Values : \mathrm{I}(x) \wedge R(u, x, x') \Rightarrow \mathrm{I}(x')$

$\Gamma(m) \vdash \forall x \in Values : \mathrm{I}(x) \Rightarrow \mathrm{Q}(x)$

Modelling systems in Event-B

MACHINE
m
SEES
c
VARIABLES
x
INVARIANT
$I(x)$
THEOREMS
$Q(x)$
INITIALISATION
$Init(x)$
EVENTS
$\ldots e$
END

c defines the static environment for the proofs related to m : sets, constants, axioms, theorems $\Gamma(m)$.

$\Gamma(m) \vdash \forall x \in Values : \text{INIT}(x) \Rightarrow \text{I}(x)$


$\forall e :$
$\Gamma(m) \vdash \forall x, x', u \in Values : \text{I}(x) \wedge R(u, x, x') \Rightarrow \text{I}(x')$

$\Gamma(m) \vdash \forall x \in Values : \text{I}(x) \Rightarrow \text{Q}(x)$

e
ANY
u
WHERE
$G(x, u)$
THEN
$x :| (R(u, x, x'))$
END

or e is **observed** $x \xrightarrow{e} x'$


Refinement between two machines




Current Section Summary

1. CM5
2. Overview
3. Programming by contract
   - Short view
   - The call-as-event idea
   - Main idea
4. Short Summary on Event-B
5. Internalizing events by merging
6. Analysis and then Synthesis
   - Analysis using Refinement
   - Synthesis by Merging
7. Summing a list of integer values

Merging two events



Merging two events




$AX(s, c), I(s, c, x), H(v, s, c, y) \vdash G_1(s, c, x) \vee G_2(s, c, x).$


Applying the fusion of events

Strategy for merging events

Let be two events ae1 and ae2 such that the two guards are complementary (ie g(ae1) $\Leftrightarrow \neg$g(ae2) or g(ae2) $\Leftrightarrow \neg$g(ae1)).

- Let cei be the event with the guard g(aei) and with the action $(g(ae1) \Rightarrow a(ae1)) \wedge (g(ae2 \Rightarrow a(ae2))$.
  Then cei refines aei.
- Let ce be the event with the guard g(ae1) $\vee$ g(ae2).
  Then ce refines cei by fusion.





Current Section Summary

1. CM5
2. Overview
3. Programming by contract
   - Short view
   - The call-as-event idea
   - Main idea
4. Short Summary on Event-B
5. Internalizing events by merging
6. Analysis and then Synthesis
   - Analysis using Refinement
   - Synthesis by Merging
7. Summing a list of integer values

Current Sub Section Summary

1. CM5
2. Overview
3. Programming by contract
4. Short Summary on Event-B
5. Internalizing events by merging
6. Analysis and then Synthesis
   - Analysis using Refinement
   - Synthesis by Merging
7. Summing a list of integer values

Computing two sums

First n numbers and first odd/even numbers

- First the **pre/post specification** . . .
- Possibility to use a programming language with contracts too

Computing two sums

First n numbers and first odd/even numbers


- First the **pre/post specification** ...
- Possibility to use a programming language with contracts too

requires $input_0 \geq 0 \wedge rs_0, re_0 \in \mathbb{Z}$

ensures $\begin{cases} rs_f = s(input_0) \\ re_f = es(input_0) \\ input_f = input_0 \end{cases}$

variables input, re, rs

- Find two sequences s and es computing the sum of first n natural numbers and first even numbers smaller than n
- Prove that :
  - $\forall n.n \in \mathbb{N} \Rightarrow s(n) = \sum_{i=0}^{i=n} i.$
  - $\forall n.n \in \mathbb{N} \Rightarrow es(n) = \sum_{i=0}^{i=n/2} 2 * i.$


final
skip
PREPOST
refines
refines
refines
computing1
step+
step-
COMPUTING
refines
computingn
step+n
step-n
PCALGO(M14)
computingn
step+n
step-n
M15
refines
refines (merging)
refines (merging)
compitingn
step+-n
M16
refines
refines
compitingn
step+-n
M19
refines
refines
(Init,Next)
M20

First n numbers and first odd/even numbers

$axm1 : n \in \mathbb{N}$

$axm2 : s \in \mathbb{N} \to \mathbb{N} \land os \in \mathbb{N} \to \mathbb{N} \land es \in \mathbb{N} \to \mathbb{N}$

$axm3 : es(0) = 0 \land os(0) = 0 \land s(0) = 0$

$axm4 : \forall i, l \cdot i \in \mathbb{N} \land l \in \mathbb{N} \land i = 2 * l \Rightarrow s(i+1) = s(i) + i + 1 \land es(i+1) =$

$axm5 : \forall i, l \cdot i \in \mathbb{N} \land l \in \mathbb{N} \land i = 2 * l + 1 \Rightarrow s(i+1) = s(i) + i + 1 \land es(i +$

$axm6 : suc \in \mathbb{N} \to \mathbb{N} \land (\forall i \cdot i \in \mathbb{N} \Rightarrow suc(i) = i + 1)$

$axm7 : \forall A \cdot A \subseteq \mathbb{N} \land 0 \in A \land suc[A] \subseteq A \Rightarrow \mathbb{N} \subseteq A$

$th1 : \forall i \cdot i \in \mathbb{N} \Rightarrow s(i+1) = s(i) + i + 1$

$th2 : \forall u, v \cdot u \in \mathbb{N} \land v \in \mathbb{N} \land 2 * u = v \Rightarrow u = v/2$

$th3 : \forall k \cdot k \in \mathbb{N} \Rightarrow 2 * s(k) = k * k + k$

$th4 : \forall k \cdot k \in \mathbb{N} \Rightarrow s(k) = (k * k + k)/2$

$th5 : \forall k \cdot k \in \mathbb{N} \Rightarrow es(2 * k) = 2 * s(k)$

$th6 : \forall k \cdot k \in \mathbb{N} \Rightarrow es(2 * k + 1) = 2 * s(k)$

$th7 : \forall k \cdot k \in \mathbb{N} \land k \neq 0 \Rightarrow os(2 * k) = k * k$

$th8 : \forall k \cdot k \in \mathbb{N} \Rightarrow os(2 * k + 1) = (k + 1) * (k + 1)$

Stating the pre/post specification in Event-B

INVARIANTS

$inv1 : input \in \mathbb{Z}$

$inv6 : input = n$

$inv2 : rs \in \mathbb{Z} \land re \in \mathbb{Z}$

$inv3 : ok \in BOOL$

$inv4 : ok = TRUE \Rightarrow rs = s(input) \land re = es(input)$

END

Stating the pre/post specification in Event-B

Refining for computing (1)

INVARIANTS

$inv1 : cur \in 0 \,..\, n$

$inv2 : ee \in 0 \,..\, n \pfun \mathbb{N}$

$inv3 : ss \in 0 \,..\, n \pfun \mathbb{N}$

$inv5 : dom(ss) = 0 \,..\, cur \land dom(ee) = dom(ss) \land dom(ss) \subseteq \mathbb{N}$

$inv6 : \forall i \cdot i \in 0 \,..\, cur \Rightarrow ee(i) = es(i) \land ss(i) = s(i)$

VARIANT

THEN

$act1 : ok := FALSE$

$act2 : rs :\in \mathbb{Z}$

$act3 : re :\in \mathbb{Z}$

$act4 : input := n$

$act5 : ee := \{0 \mapsto 0\}$

$act6 : ss := \{0 \mapsto 0\}$

$act7 : cur := 0$


END

Refining for computing (2)

Refining for computing (3)

Refining for computing (4)

Diagram of events



Completing the analysis

MACHINE $M1$ **SEES** $C0$
VARIABLES
$input, rs, re, ok,$
INVARIANTS
$inv1 : input \in \mathbb{Z}$
$inv6 : input = n$
$inv2 : rs \in \mathbb{Z} \land re \in \mathbb{Z}$
$inv3 : ok \in BOOL$
$inv4 : ok = TRUE \Rightarrow rs = s(input) \land re = es(input)$

Completing the analysis

MACHINE $M11$ **SEES** $C0$
VARIABLES
$input, rs, re, ok, ee, ss, cur,$
INVARIANTS
$inv1 : cur \in 0 \,..\, n$
$inv2 : ee \in 0 \,..\, n \pfun \mathbb{N}$
$inv3 : ss \in 0 \,..\, n \pfun \mathbb{N}$
$inv5 : dom(ss) = 0 \,..\, cur \land dom(ee) = dom(ss) \land dom(ss) \subseteq \mathbb{N}$
$inv6 : \forall i \cdot i \in 0 \,..\, cur \Rightarrow ee(i) = es(i) \land ss(i) = s(i)$

Completing the analysis


MACHINE $M12$ **SEES** $C0$
VARIABLES
$input, rs, re, ok, ee, ss, cur, cs, ce,$
INVARIANTS
$inv1 : cs = ss(cur)$
$inv2 : ce = ee(cur)$

Completing the analysis

MACHINE $M13$ **SEES** $C0$
VARIABLES
$input, rs, re, ok, ee, ss, cur, cs, ce,$
INVARIANTS
$inv1 : cs = ss(cur)$
$inv2 : ce = ee(cur)$
$inv4 : ce = es(cur)$
$inv3 : cs = s(cur)$

Completing the analysis

MACHINE $M14$ **SEES** $C0, C1$
VARIABLES
$input, rs, re, cur, cs, ce, l,$
INVARIANTS
$inv1 : cs = s(cur)$
$inv5 : l = start \Leftrightarrow ok = FALSE$
$inv6 : l = end \Leftrightarrow ok = TRUE$
$inv2 : cs = s(cur)$
$inv3 : l \in L$
$inv4 : l = end \Rightarrow re = es(n) \wedge rs = s(n)$


final
skip
PREPOST
refines
refines
refines
computing1
step+
step-
COMPUTING
refines
computingn
step+n
step-n
PCALGO(M14)
computingn
step+n
step-n
M15
refines
refines (merging)
refines (merging)
compitingn
step+-n
M16
refines
refines
compitingn
step+-n
M19
refines
refines
(Init,Next)
M20

Generation of an algorithm from M14

Translation from Evenrts

```
struct sums  codesum(int n)
{int  k,ce,cs; struct sums r;
  r.s=0;r.se=0;k=0;ce=0;cs=0;
  while (k<n)
    {
      if ( k % 2 != 0)
        { ce = ce + k + 1;cs = cs +k+1;        k = k +1;}
      else
        { ce = ce ;cs = cs +k+1;        k = k +1;}
       }
  r.s=cs;r.se=ce;
  return(r);
}
```

Generation of an algorithm from M14

Improving and checking with Frama-c

```
#include "structure.h"
#include "trans-even.h"
struct sums  codesum(int n)
{int  k,ce,cs; struct sums r;
  r.s=0;r.se=0;k=0;ce=0;cs=0;
  /*@ loop invariant k >= 0 && k <= n && mathsum(k) == cs;
    @ loop invariant  ( (k % 2 == 0) ==> (mathse(k) == ce));
    @ loop invariant  ( (k % 2 != 0) ==> (mathse(k) == ce));
    loop assigns k, ce,cs;
    loop variant n-k;
   */
  while (k<n)
    {
      if ( k % 2 != 0)
        { ce = ce + k + 1;cs = cs +k+1;        k = k +1;}
      else
        { ce = ce ;cs = cs +k+1;        k = k +1;}
       }
  r.s=cs;r.se=ce;
  return(r);
```

Generation of an algorithm from M14

Improving and checking with Frama-c

```
#include "structure.h"
#include "trans-even.h"
struct sums  codesum(int n)
{int  k,ce,cs; struct sums r;
  r.s=0;r.se=0;k=0;ce=0;cs=0;
  /*@ loop invariant k >= 0 && k <= n && mathsum(k) == cs;
    @ loop invariant  ( (k % 2 == 0) ==> (mathse(k) == ce));
    @ loop invariant  ( (k % 2 != 0) ==> (mathse(k) == ce));
    loop assigns k, ce,cs;
    loop variant n-k;
   */
  while (k<n)
    {
      if ( k % 2 != 0)
        { ce = ce + k + 1;}
      cs = cs +k+1;        k = k +1;
 cp trabs-e*          }
  r.s=cs;r.se=ce;
  return(r);
}
```

Generation of an algorithm from M14

Using the Plugin EB2Algo

```
rs :∈ ℤ ||
re :∈ ℤ ||
input = n ||
cur = 0 ||
ce = 0 ||
cs = 0

while cur≠n do
    if cur mod 2≠0 then
        cur = cur+1 ||
        cs = cs+cur+1 ||
        ce = ce+cur+1
    else
        cur = cur+1 ||
        cs = cs+cur+1 ||
        ce = ce
    od;
```

Current Sub Section Summary

1. CM5
2. Overview
3. Programming by contract
4. Short Summary on Event-B
5. Internalizing events by merging
6. Analysis and then Synthesis
   - Analysis using Refinement
   - Synthesis by Merging
7. Summing a list of integer values

Merging events

EVENT e1
ANY
x
WHERE
$G1(s, c, x, u)$
THEN
$u :\mid (R(s, c, x, u, u'))$
END

EVENT e2
ANY
x
WHERE
$G2(s, c, x, u)$
THEN
$u :\mid (R(s, c, x, u, u'))$
END

Merging events

EVENT e1
ANY
x
WHERE
$G1(s, c, x, u)$
THEN
$u :| (R(s, c, x, u, u'))$
END

EVENT e2
ANY
x
WHERE
$G2(s, c, x, u)$
THEN
$u :| (R(s, c, x, u, u'))$
END

EVENT e $refines$ $e1, e2$
ANY
x
WHERE
$H(s, c, x, u)$
THEN
$u :| (R(s, c, x, u, u'))$
END

Merging events

EVENT e1
ANY
x
WHERE
$G1(s, c, x, u)$
THEN
$u :| (R(s, c, x, u, u'))$
END

EVENT e2
ANY
x
WHERE
$G2(s, c, x, u)$
THEN
$u :| (R(s, c, x, u, u'))$
END

EVENT e $refines$ $e1, e2$
ANY
x
WHERE
$H(s, c, x, u)$
THEN
$u :| (R(s, c, x, u, u'))$
END

Checking the Proof Obligation :

$$Ax(s, c), I(s, c, u), H(s, c, x, u) \vdash G1(s, c, x, u) \vee G2(s, c, x, u)$$

Synthesis Phase

- Preparing merging by transforming actions.

EVENT e
ANY
x
WHERE
$G(s, c, x, u)$
THEN
$u :| (R(s, c, x, u, u'))$
END

EVENT f refines e
ANY
x
WHERE
$G(s, c, x, u)$
THEN
$u :| (G(s, c, x, u) \Rightarrow R(s, c, x, u, u'))$
END

- Internalizing the action as a before after relation
- $G(s, c, x, u) \wedge (G(s, c, x, u) \Rightarrow R(s, c, x, u, u')) \Leftrightarrow$
  $G(s, c, x, u) \wedge R(s, c, x, u, u')$

Synthesis Phase

- Preparing merging by transforming actions.

EVENT e
ANY
x
WHERE
$G(s, c, x, u)$
THEN
$u :| (R(s, c, x, u, u'))$
END

EVENT f refines e
ANY
x
WHERE
$G(s, c, x, u)$
THEN
$u :| (G(s, c, x, u) \Rightarrow R(s, c, x, u, u'))$
END

- $G(s, c, x, u) \wedge (G(s, c, x, u) \Rightarrow R(s, c, x, u, u')) \Leftrightarrow$
$G(s, c, x, u) \wedge R(s, c, x, u, u')$
- $A(s, c, u) \wedge I(s, c, u) \wedge BA(f)(s, c, u, u') \Rightarrow$
$I(s, c, u') \wedge BA(e)(s, c, u, u')$

Synthesis Phase

- Preparing merging by transforming actions.

EVENT e
ANY
x
WHERE
$G(s, c, x, u)$
THEN
$u :| (R(s, c, x, u, u'))$
END

EVENT f refines e
ANY
x
WHERE
$G(s, c, x, u)$
THEN
$u :| (G(s, c, x, u) \Rightarrow R(s, c, x, u, u'))$
END

- $G(s, c, x, u) \wedge (G(s, c, x, u) \Rightarrow R(s, c, x, u, u')) \Leftrightarrow$
  $G(s, c, x, u) \wedge R(s, c, x, u, u')$
- $A(s, c, u) \wedge I(s, c, u) \wedge BA(f)(s, c, u, u') \Rightarrow$
  $I(s, c, u') \wedge BA(e)(s, c, u, u')$
- $A(s, c, u) \wedge I(s, c, u) \wedge G(s, c, x, u) \wedge (G(s, c, x, u) \Rightarrow$
  $R(s, c, x, u, u')) \Rightarrow I(s, c, u') \wedge G(s, c, x, u) \wedge R(s, c, x, u, u')$

Synthesis Phase : review of machines from M15-M20

MACHINE $M15$ **SEES** $C0, C1$
VARIABLES
$input, rs, re, cur, cs, ce, l,$

Synthesis Phase : review of machines from M15-M20

MACHINE $M16$ **SEES** $C0, C1$
VARIABLES
$input, rs, re, cur, cs, ce, l,$

Synthesis Phase : review of machines from M15-M20

MACHINE $M17$ **SEES** $C0, C1$
VARIABLES
$input, rs, re, cur, cs, ce, l,$

Synthesis Phase : review of machines from M15-M20

MACHINE $M18$ **SEES** $C0, C1$
VARIABLES
$input, rs, re, cur, cs, ce, l,$

Synthesis Phase : review of machines from M15-M20

MACHINE $M19$ **SEES** $C0, C1$
VARIABLES
$input, rs, re, cur, cs, ce, l,$

Synthesis Phase : review of machines from M15-M20

MACHINE $M20$ **SEES** $C0, C1$
VARIABLES
$input, rs, re, cur, cs, ce, l,$


Generating a TLA specification

```
----------------------------
next1 ==
      (l="start" /\   cur < n  /\ ( cur % 2 = 0))
      /\   (cur'=cur+1 /\  ce'=ce /\  l'=l
      /\  cs'=cs+cur+1 /\  re'=re /\  rs'=rs)
o
delsnext2 ==
      (l="start" /\   cur < n  /\ ( cur % 2 # 0))
      /\ (cur'=cur+1 /\  ce'=ce+cur+1 /\  l'=l
      /\  cs'=cs+cur+1 /\  re'=re /\ rs'=rs)

next3 ==
 (l="start" /\  cur=n) /\   (rs'=cs /\  re'=ce
 /\  l'="end" /\  cur'=cur /\ cs'=cs/\ ce'=ce)

Next ==
      (next1 \/ next2 \/ next3)

Init == l="start" /\   cur=0 /\ rs=0 /\ cs=0 /\ re=0 /\ ce =0
============================================================
```


final
skip
PREPOST
refines
refines
refines
computing1
step+
step-
COMPUTING
refines
computingn
step+n
step-n
PCALGO(M14)
computingn
step+n
step-n
M15
refines
refines (merging)
refines (merging)
compitingn
step+-n
M16
refines
refines
compitingn
step+-n
M19
refines
refines
(Init,Next)
M20

Current Section Summary

1. CM5
2. Overview
3. Programming by contract
   - Short view
   - The call-as-event idea
   - Main idea
4. Short Summary on Event-B
5. Internalizing events by merging
6. Analysis and then Synthesis
   - Analysis using Refinement
   - Synthesis by Merging
7. Summing a list of integer values

Contract for the problem Summing a list of integer values

Contract for the problem Summing a list of integer values

VARIABLES $n, v, r, done$

REQUIRES
$$\begin{cases} n_0 \in \mathbb{N} \\ n_0 \neq 0 \\ v_0 \in 1..n_0 \rightarrow \mathbb{Z} \\ r_0 \in \mathbb{Z} \\ done_0 \in \mathbb{BOOL} \end{cases}$$

ENSURES
$$\begin{pmatrix} r_f = \sum_{k=1}^{n_0} v_0(k) \\ done_f = TRUE \end{pmatrix}$$

Contract for the problem Summing a list of integer values

Contract for the problem Summing a list of integer values

VARIABLES $n, v, r, done$

REQUIRES
$$\begin{cases} n_0 \in \mathbb{N} \\ n_0 \neq 0 \\ v_0 \in 1..n_0 \rightarrow \mathbb{Z} \\ r_0 \in \mathbb{Z} \\ done_0 \in \mathbb{BOOL} \end{cases}$$

ENSURES
$$\begin{pmatrix} r_f = \sum_{k=1}^{n_0} v_0(k) \\ done_f = TRUE \end{pmatrix}$$

- the initial values of n, v and done, denoted n_0, v_0, $done_0$ and the final value of r denoted r_f.
- the final value of the variable r denoted r_f is the sum $\sum_{k=1}^{n_0} v_0(k)$.

Contract for the problem Summing a list of integer values

Contract for the problem Summing a list of integer values

VARIABLES $n, v, r, done$

REQUIRES
$$\begin{cases} n_0 \in \mathbb{N} \\ n_0 \neq 0 \\ v_0 \in 1..n_0 \rightarrow \mathbb{Z} \\ r_0 \in \mathbb{Z} \\ done_0 \in \mathbb{BOOL} \end{cases}$$

ENSURES
$$\begin{pmatrix} r_f = \sum_{k=1}^{n_0} v_0(k) \\ done_f = TRUE \end{pmatrix}$$

- the initial values of n, v and done, denoted n_0, v_0, $done_0$ and the final value of r denoted r_f.
- the final value of the variable r denoted r_f is the sum $\sum_{k=1}^{n_0} v_0(k)$.

computation method

Defining the computation process by defining a sequence u in the context S0

computation method = inductive process

CONTEXT $S0$
CONSTANTS $n0\ v0\ u$
AXIOMS
$@pre1\ n0 \in \mathbb{N}$
$@pre2\ n0 \neq 0$
$@pre5\ v0 \in 1..n0 \to \mathbb{Z}$
$@axm1\ u \in 0..n0 \to \mathbb{Z}$
$@axm2\ u(0) = 0$
$@axm3\ \forall k.\ k \in 1..n0$
$\Rightarrow\ u(k) = u(k-1) + v0(k)$
end

computation method = inductive process

CONTEXT $S0$
CONSTANTS $n0\ v0\ u$
AXIOMS
$@pre1\ n0 \in \mathbb{N}$
$@pre2\ n0 \neq 0$
$@pre5\ v0 \in 1..n0 \to \mathbb{Z}$
$@axm1\ u \in 0..n0 \to \mathbb{Z}$
$@axm2\ u(0) = 0$
$@axm3\ \forall k.\ k \in 1..n0 \Rightarrow u(k) = u(k-1) + v0(k)$
end

- The context S0 defines the sequence u supporting the computation method by definition of the summation expression.

computation method = inductive process

CONTEXT $S0$
CONSTANTS $n0\ v0\ u$
AXIOMS
$@pre1\ n0 \in \mathbb{N}$
$@pre2\ n0 \neq 0$
$@pre5\ v0 \in 1..n0 \to \mathbb{Z}$
$@axm1\ u \in 0..n0 \to \mathbb{Z}$
$@axm2\ u(0) = 0$
$@axm3\ \forall k.\ k \in 1..n0 \Rightarrow u(k) = u(k-1) + v0(k)$
end

- The context S0 defines the sequence u supporting the computation method by definition of the summation expression.
- The refinement process starts by the specification namely S1 and leads to the machine S7 which is containing the event final internalizing the computation of the sum.

Expressing pre/post in a machine S1 (I)

MACHINE $S1$ SEES $S0$
VARIABLES $r\ v\ n\ done$
INVARIANTS
$@inv1\ r \in \mathbb{Z}$
$@inv2\ n \in \mathbb{Z}$
$@inv3\ v \in 1..n \rightarrow \mathbb{Z}$
$@inv4\ done \in BOOL$
$@read-values\ n = n0 \wedge v = v0$
$@post\ done = TRUE \Rightarrow r = u(n0)$
EVENT $INITIALISATION$
then
$@act1\ r :\in \mathbb{Z}$
$@act2\ n := n0$
$@act3\ v := v0$
$@act4\ done := FALSE$
end

- v and n are variables getting the input values as $v0$ and $n0$: *read-values* lebel.
- r is getting the result of the computing process under the control of *done* : post label.
- *post* : expression of the partial correctness.

Expressing pre/post in a machine S1 (II)


- The final1 event expresses the relationship between intial and final values of variables.
- The keep event expresses the *hidden* loop preparing the final resylt.

EVENT $final1$
  where
  $@grd1\ done = FALSE$
  then
  $@act1\ r := u(n)$
  $@act2\ done := TRUE$
end

$anticipated$ EVENT $keep$
  then
  $@act1\ r, n, v, done :|$
  $(r' \in \mathbb{Z} \land n' \in \mathbb{Z}$
  $\land\ v' \in 1..n' \to \mathbb{Z}$
  $\land\ done' \in BOOL$
  $\land\ n' = n0 \land v' = v0$
  $\land\ (done' = TRUE$
  $\Rightarrow\ r' = u(n0)))$
end


Summary of the refinement steps

Refinement from S1 till S7.



Summary of the refinement steps


Refinement from S1
till S7.



- Identifying the final1 event as simulating the pre/post contract in S1.

Summary of the refinement steps


Refinement from S1 till S7.



- Identifying the final1 event as simulating the pre/post contract in S1.
- Refining by using u and introducing events simulating computing steps in S4.

Summary of the refinement steps

Refinement from S1 till S7.



- Identifying the final1 event as simulating the pre/post contract in S1.
- Refining by using u and introducing events simulating computing steps in S4.
- Merging events of S4 into one event in S7.

From S1 to S4 via S2 and S3

From S1 to S4 via S2 and S3

MACHINE $S2$ REFINES $S1$ SEES $S0$
VARIABLES $r\ i\ uu\ n\ v\ done$
INVARIANTS
$@inv1\ i \in 0..n$
$@inv2\ uu \in 0..n \pfun \mathbb{Z} \land dom(uu) = 0..i$
$@inv3\ \forall k.\ k \in dom(uu) \Rightarrow uu(k) = u(k)$
$@inv4\ done = FALSE \Rightarrow i \in 0..n$
$@inv6\ done = TRUE \Rightarrow i = n$
$@inv7\ i \in 0..n-1 \Rightarrow done = FALSE$
$theorem\ @datath\ v = v0 \land n = n0$
VARIANT $n - i$

- The variable uu is recording the sequence u by computing until i is n0.
- The new event step is refining the event keep and decreases the variant.

From S1 to S4 via S2 and S3

MACHINE $S2$ REFINES $S1$ SEES $S0$
VARIABLES $r\ i\ uu\ n\ v\ done$
INVARIANTS
$@inv1\ i \in 0..n$
$@inv2\ uu \in 0..n \pfun \mathbb{Z} \land dom(uu) = 0..i$
$@inv3\ \forall k.\ k \in dom(uu) \Rightarrow uu(k) = u(k)$
$@inv4\ done = FALSE \Rightarrow i \in 0..n$
$@inv6\ done = TRUE \Rightarrow i = n$
$@inv7\ i \in 0..n-1 \Rightarrow done = FALSE$
$theorem\ @datath\ v = v0 \land n = n0$
VARIANT $n - i$

MACHINE $S3$ REFINES $S2$ SEES $S0$
VARIABLES $r\ i\ uu\ cu\ n\ v\ done$
INVARIANTS
$@inv1\ cu \in \mathbb{Z}$
$@inv2\ cu = u(i)$

- The variable uu is recording the sequence u by computing until i is n0.
- The new event step is refining the event keep and decreases the variant.
- The new variable cu is recoring the last computed valuye of uu.
- Proofs of the invariants are made easier.

The machine S4 in the middle (I)

MACHINE $S4$ REFINES $S3$ SEES $S0$
VARIABLES $r\ i\ cu\ n\ v\ done$
INVARIANTS
$theorem\ @inv1\ cu = u(i)$
EVENTS
EVENT $INITIALISATION$
then
$@act1\ r :\in \mathbb{Z}$
$@act2\ i := 0$
$@act4\ cu := 0$
$@act5\ v := v0$
$@act6\ n := n0$
$@act7\ done := FALSE$
end

The machine S4 in the middle (I)

MACHINE $S4$ REFINES $S3$ SEES $S0$
VARIABLES $r\ i\ cu\ n\ v\ done$
INVARIANTS
$theorem\ @inv1\ cu = u(i)$
EVENTS
EVENT $INITIALISATION$
then
$@act1\ r :\in \mathbb{Z}$
$@act2\ i := 0$
$@act4\ cu := 0$
$@act5\ v := v0$
$@act6\ n := n0$
$@act7\ done := FALSE$
end

- The variable uu helps in the proof process but is expensive.
- The variable uu is hidden in the abstractions.

The machine S4 in the middle (II)

EVENT $final$ REFINES $final$
where
$@grd1\ i = n$
$@grd2\ done = FALSE$
then
$@act1\ r := cu$
$@act2\ done := TRUE$
end

EVENT $step000$ REFINES $step$
where
$@grd1\ i < n$
$@grd2\ done = FALSE$
then
$@act1\ i := i + 1$
$@act3\ cu := cu + v(i + 1)$
end

The machine S4 in the middle (II)

EVENT $final$ REFINES $final$
where
$@grd1\ i = n$
$@grd2\ done = FALSE$
then
$@act1\ r := cu$
$@act2\ done := TRUE$
end

EVENT $step000$ REFINES $step$
where
$@grd1\ i < n$
$@grd2\ done = FALSE$
then
$@act1\ i := i + 1$
$@act3\ cu := cu + v(i + 1)$
end

- Events are made simpler and uu is hidden.
- Events are guarded by evaluable conditions as $i < n$ which is implying $i \notin dom(uu)$
- Using EB2ALGO, one gets an algorithm but no proof is given of the transformations.

The machine S7 with one event

MACHINE $S7$ REFINES $S6$ SEES $S0$
VARIABLES $r\ i\ cu\ n\ v\ done$
INVARIANTS
$theorem\ @inv1\ done = FALSE \Rightarrow i \in 0..n$
$theorem\ @inv2\ done = TRUE \Rightarrow i = n$
$theorem\ @inv3\ i \in 0..n-1 \Rightarrow done = FALSE$
$theorem\ @inv4\ i \in 0..n$
EVENT $final$ REFINES $final$
where
$@grd2\ done = FALSE$
then
$@act1\ r, i, cu, n, v, done :| ($
$(i = n$
$\Rightarrow (r' = cu \wedge cu' = cu \wedge i' = i \wedge n' = n$
$\wedge\ v' = v \wedge done' = TRUE))$
$\wedge\ (i < n$
$\Rightarrow (\ r' = r \wedge cu' = cu + v(i+1) \wedge i' = i+1$
$\wedge\ n' = n \wedge v' = v \wedge done' = done))$
$)$
end

Defining an algorithm by a set of actions

Defining an algorithm by a set of actions

$$guard(r, i, cu, n, v, done) \equiv done = FALSE$$

$$action \equiv \left[\begin{array}{ll} i = n \Rightarrow & \left[\begin{array}{l} (r' = cu \wedge cu' = cu \wedge i' = i \wedge n' = n \\ \wedge v' = v \wedge done' = TRUE) \end{array} \right. \\ i < n \Rightarrow & \left[\begin{array}{l} r' = r \wedge cu' = cu + v(i+1) \wedge i' = i + 1 \wedge n' = n \\ \wedge v' = v \wedge done' = done \end{array} \right. \end{array} \right.$$

Defining an algorithm by a set of actions

$$guard(r, i, cu, n, v, done) \equiv done = FALSE$$

$$action \equiv \left[\begin{array}{ll} i = n \Rightarrow & \left[\begin{array}{l} (r' = cu \wedge cu' = cu \wedge i' = i \wedge n' = n \\ \wedge v' = v \wedge done' = TRUE) \end{array} \right. \\ i < n \Rightarrow & \left[\begin{array}{l} r' = r \wedge cu' = cu + v(i+1) \wedge i' = i + 1 \wedge n' = n \\ \wedge v' = v \wedge done' = done \end{array} \right. \end{array} \right.$$

- The machine S7 contains an event Initialisation and a next relation
-

Defining an algorithm by a set of actions

$$guard(r, i, cu, n, v, done) \equiv done = FALSE$$

$$action \equiv \left[\begin{array}{ll} i = n \Rightarrow & \left[\begin{array}{l} (r' = cu \wedge cu' = cu \wedge i' = i \wedge n' = n \\ \wedge v' = v \wedge done' = TRUE) \end{array} \right. \\ i < n \Rightarrow & \left[\begin{array}{l} r' = r \wedge cu' = cu + v(i+1) \wedge i' = i + 1 \wedge n' = n \\ \wedge v' = v \wedge done' = done \end{array} \right. \end{array} \right.$$

- The machine S7 contains an event Initialisation and a next relation
-

Definition

(mapping of a binary relation)
A binary relation R on $State$ can be mapped to a GKAT term e for the interpretation i, if $\mathcal{R}_i(e) = R$ and we write $map_i(R) = e$

Defining an algorithm by a set of actions (I)

Guarded Kleene Algebra with Tests

Summing a list of integer values is now considering the iteration property and we obtain

$$init.a^{(c)}b$$

where


- $sat(init) = \{(n0, v0, FALSE, 0, 0, ?)\}$
- $\mathcal{R}_i(A)(s, s') \triangleq cu' = cu + v(i+1) \wedge i' = i+1 \wedge r' = r$, $a \triangleq cu := cu + v(i+1); i := i+1$ and $map_i(A) = a$
- $\mathcal{R}_i(B)(s, s') \triangleq r' = cu \wedge done' = TRUE \wedge cu' = cu \wedge i' = i$ and $b \triangleq r := cu; done := TRUE$
- $eval(c) = \{(s, s) | s(i) < s(n)\}$.

Defining an algorithm by a set of actions (II)

Listing 4 – PlusCal algorithm for summing a vector

```
  --algorithm sumvect {
variables n=n0, v=v0, i=0, cu=0, r;
{
w1: while (i # n) {
   w2: cu:=cu+v[i+1]; i:=i+1;
};
w3: r:=cu; Gu
}}
```

Global View


EB1
CO1
translates
contract(pre,post)
analysis
refines
implements
implements
EB2
translates
EB2ALGO
algorithm A
implements
algorithm C
merging
refines
translates
eb⇝pluscal
eb⇝pluscal
EB3
translates
eb⇝tla
algorithm B
tla(eb3)
(PlusCal)
eb⇝tla
tla(eb3)
(init,next)

Global View

- Algorithm A is generated using EB2Algo
-

$$
\begin{array}{l}
r :\in \mathbb{Z} \parallel i := 0 \parallel cu := 0 \parallel v := v0 \parallel n := n0 \\
while\ i < n\ do \\
\quad i := i + 1 \parallel cu := cu + v(i+1) \\
od;
\end{array}
$$

Global View

- Algorithm B is simply defined by

$$guard(r,i,cu,n,v,done) \equiv done = FALSE$$

$$action \equiv \left[\begin{array}{ll} i = n \Rightarrow & \left[\begin{array}{l} (r' = cu \wedge cu' = cu \wedge i' = i \wedge n' = n \\ \wedge v' = v \wedge done' = TRUE) \end{array}\right. \\ i < n \Rightarrow & \left[\begin{array}{l} r' = r \wedge cu' = cu + v(i+1) \wedge i' = i+1 \wedge n' = n \\ \wedge v' = v \wedge done' = done \end{array}\right. \end{array}\right.$$

Global View

Algorithm C is generated using our transformations based on GKAT algebra

```
      --algorithm sumvect  {
variables  n=n0,v=v0,i=0,cu=0,r;
{
w1:while (i # n) {
  w2:cu:=cu+v[i+1]; i:=i+1;
};
w3:r:=cu;
}}
```