

Current Summary

- ## 9 Examples of Event B models

- Event B : <http://www.event-b.org/>
- Atelier B : <http://www.atelierb.eu/>
- RODIN Platform : <http://www.event-b.org/platform.html>
- EB2ALL Toolset : <http://eb2all.loria.fr>
- RIMEL project : <http://rimel.loria.fr>
- **Using the Arche platform of UL and accessing the course MOSOS with password mery**

Current Summary

- 1 Documentation
- 2 Introduction by a Problem
- 3 Dependability and security assurance
- 4 Overview of formal techniques and formal methods
- 5 Modelling Language
- 6 A Simple Example
- 7 Modelling state-based systems
- 8 The Event B modelling language
- 9 Examples of Event B models

```
#include <stdio.h>
#include <stdlib.h>
#include <time.h>

int main() {
    int x, y;
    // Seed the random number generator with the current time
    srand(time(NULL));
    // Generate a random number between 1 and 100
    x = rand() % 100 + 1;
    // Perform some calculations
    y = x / (100 - x);
    printf("Result: -%d\n", y);
    return 0;
}
```

```
[kernel] Parsing bug0.c (with preprocessing)
[rte:annot] annotating function main
[wp] Running WP plugin...
[kernel:annot:missing-spec] FRAMAC_SHARE/libc/stdlib.h:299: Warning:
  Neither code nor explicit exits and terminates for function rand
  generating default clauses. See —generated-spec—* options for n
[kernel:annot:missing-spec] FRAMAC_SHARE/libc/stdlib.h:302: Warning:
  Neither code nor explicit exits and terminates for function srand
  generating default clauses. See —generated-spec—* options for n
[kernel:annot:missing-spec] FRAMAC_SHARE/libc/time.h:126: Warning:
  Neither code nor explicit exits and terminates for function time
  generating default clauses. See —generated-spec—* options for n
[kernel:annot:missing-spec] FRAMAC_SHARE/libc/stdio.h:211: Warning:
  Neither code nor explicit exits and terminates for function prin
  generating default clauses. See —generated-spec—* options for n
[wp] 8 goals scheduled
[wp] [Timeout] typed_main_call_printf_va_1_requires (Alt-Ergo)
[wp] [Timeout] typed_main_assert_rte_division_by_zero (Alt-Ergo)
[wp] Proved goals:      6 / 8
    Qed:                3
    Alt-Ergo 2.6.0:      3 (17ms–20ms–27ms)
    Timeout:             2
```

Function main

```
// Heisenbug
#include <stdio.h>
#include <stdlib.h>
#include <time.h>
//
int main() {
    int x, y, i=0;
    for (i = 0; i <= 1000000; i++) {
        // Seed the random number generator with the current time
        srand(time(NULL));
        // Generate a random number between 1 and 100
        x = rand() % 100 + 1;
        printf("Result: -x=-%d\n", x);
        // Perform some calculations
        y = x / (100 - x);
        printf("Result: -i=%d--and-y=%d\n", i, y);
    }
    return 0;
}
```


Our aim is to analyze what is implicit and what is explicit in formal modelling...

- **Semantics in modelling :**

- ▶ Semantics expressed by a *theory* (e.g. Event-B) used to formalize hardware and/or software systems
- ▶ Same theory is used for wide variety of heterogeneous systems

- **Semantics in domain :**

- ▶ Environment within which system evolve : application domain/context
- ▶ Information provided by domain is often associated while in operation
- ▶ Either assumed and omitted while formalising systems **or** hardcoded in formal models
- ▶ Same context is used for wide variety of heterogeneous systems



A case study for studying these properties

Nose Gear Velocity



- Estimated ground velocity of the aircraft should be available only if it is within 3 km/hr of the true velocity at some moment within past 3 seconds

Characterization of a System (I)

- NG velocity system :
 - ▶ **Hardware :**
 - *Electro-mechanical sensor* : detects rotations
 - *Two 16-bit counters* : Rotation counter, Milliseconds counter
 - *Interrupt service routine* : updates rotation counter and stores current time.
 - ▶ **Software :**
 - *Real-time operating system* : invokes update function every 500 ms
 - *16-bit global variable* : for recording rotation counter update time
 - *An update function* : estimates ground velocity of the aircraft.
- Input data available to the system :
 - ▶ *time* : in milliseconds
 - ▶ *distance* : in inches
 - ▶ *rotation angle* : in degrees
- Specified system performs velocity estimations in *imperial* unit system
- **Note** : expressed functional requirement is in *SI* unit system (km/hr).


What are the main properties to consider for formalization ?

- Two different types of data :
 - ▶ counters with modulo semantics
 - ▶ non-negative values for time, distance, and velocity
- Two dimensions : *distance* and *time*
- Many units : distance (inches, kilometers, miles), time (milliseconds, hours), velocity (kph, mph)
- And interaction among components

How should we model ?

- Designer needs to consider units and conversions between them to manipulate the model
- One approach : Model units as *sets*, and conversions as constructed types – *projections*.
- Example :
 - 1 $estimateVelocity \in \text{MILES} \times \text{HOURS} \rightarrow \text{MPH}$
 - 2 $mphTokph \in \text{MPH} \rightarrow \text{KPH}$

Sample Velocity Estimation



Listing 1 – Bug bug0

```
#include <stdio.h>
#include <stdlib.h>
#include <time.h>

int main() {
    int x, y;
    // Seed the random number generator with the current time
    srand(time(NULL));
    // Generate a random number between 1 and 100
    x = rand() % 100 + 1;
    // Perform some calculations
    y = x / (100 - x);
    printf("Result: -%d\n", y);
    return 0;
}
```

Listing 2 – Bug bug00

```
// Heisenbug
#include <stdio.h>
#include <stdlib.h>
#include <time.h>
//
int main() {
    int x, y, i=0;
    for (i = 0; i <= 1000000; i++) {
        // Seed the random number generator with the current time
        srand(time(NULL));
        // Generate a random number between 1 and 100
        x = rand() % 100 + 1;
        printf("Result: -x=-%d\n", x);
        // Perform some calculations
        y = x / (100 - x);
        printf("Result: -i=%d--and-y=%d\n", i, y);
    }
    return 0;
}
```


Listing 3 – Bug bug000

```
// Heisenbug
#include <stdio.h>
#include <stdlib.h>
#include <time.h>
#include <limits.h>

int main() {
    int x, y, i=0;

    for (i = 0; i <= INT_MAX; i++) {
        // Seed the random number generator with the current time
        srand(time(NULL)+i);

        // Generate a random number between 1 and 100
        x = rand() % 100 + 1;

        printf("Result: -x=-%d\n", x);
        // Perform some calculations
        y = x / (100 - x);

        printf("Result: -i=%d--%d\n", i, y);
    }

    return 0;
}
```


Critical System

Critical systems are systems in which defects could have a dramatic impact on human life or the environment.


System failure

Software failure or fault of complex systems is the major cause in the software crisis. For example,

- **Therac-25 (1985-1987)** : six people overexposed through radiation.
- **Cardiac Pacemaker (1990-2002)** : 8834 pacemakers were explanted.
- **Insulin Infusion Pump (IIP) (2010)** : 5000 adverse events.

Traditional System Engineering Approach

Spiral Model, Waterfall Model, V-Shaped Model, etc.




The Cleanroom Method

The Cleanroom method, then, uses a number of techniques to develop software carefully, in a well-controlled way, so as to avoid or eliminate as many defects as possible before the software is ever executed. Elements of the method are :

- specification of all components of the software at all levels ;
- stepwise refinement using constructs called "box structures" ;
- verification of all components by the development team ;
- statistical quality control by independent certification testing ;
- no unit testing, no execution at all prior to certification testing.

The Cleanroom approach to software development is based on five key strategies :

- Formal specification : The software to be developed is formally specified. A state-transition model which shows system responses to stimuli is used to express the specification.
- Incremental development : The software is partitioned into increments which are developed and validated separately using the Cleanroom process. These increments are specified, with customer input, at an early stage in the process.
- Structured programming : Only a limited number of control and data abstraction constructs are used. The program development process is a process of stepwise refinement of the specification. A limited number of constructs are used and the aim is to apply correctness-preserving transformations to the specification to create the program code.
- Static verification : The developed software is statically verified using rigorous software inspections. There is no unit or module testing process for code components.
- Statistical testing of the system : The integrated software increment is tested statistically (see Chapter XX), to determine its reliability. These statistical tests are based on an operational profile which is developed in parallel with the system specification.



MACHINE

m

SEES

c

VARIABLES

x

INVARIANT

$I(x)$

THEOREMS

$Q(x)$

INITIALISATION

$Init(x)$

EVENTS

$\dots e$

END

- c defines the static environment $\Gamma(m)$ for the proofs related to m : sets, constants, axioms, theorems.
- $\Gamma(m) \vdash \forall x, x' \in Values : INIT(x) \Rightarrow I(x)$
- $\forall e :$
 $\Gamma(m) \vdash \forall x, x' \in Values :$
 $I(x) \wedge G(x, u) \wedge R(u, x, x') \Rightarrow I(x')$
- $\Gamma(m) \vdash \forall x, x' \in Values : I(x) \Rightarrow Q(x)$

e

ANY

u

WHERE

$G(x, u)$

THEN



$x : |(R(u, x, x'))$

END



or $x \xrightarrow{e} x'$

Refinement of a model by another one (I)

i



Refinement of a model by another one (II)




Context

Developing a life-cycle methodology combining the refinement approach with various tools including verification tool, model checker tool, real-time animator and finally, producing the source code into many languages using automatic code generation tools.


Objectives

- To establish a unified theory for the critical system development.
- To build a set of tools for supporting new development life-cycle methodology.
- To develop a closed-loop system for verification purpose.
- Graphical based refinement technique to handle the complexity of the system.
- To satisfy requirements and metrics for certifiable assurance and safety.
- To support evidence-based certification.

Critical System Development Life-Cycle Methodology



Critical System Development Life-Cycle Methodology




What is Real-time Animator ?

- Visual representation of formal model using real time data set.


Why should we use Formal Model Animator ?

- To validate system behavior according to the stakeholders
- To express formal models for non-mathematical domain experts
- To discover the error in the early stage of system development (Traceability)

Proposed Architecture



System : Heart $\oplus$ Pacemaker





Bradycardia Operating Modes


Operating Modes

Category	Chambers Paced	Chambers Sensed	Response to Sensing	Rate Modulation
Letters	O -None A -Atrium V -Ventricle D -Dual(A+V)	O -None A -Atrium V -Ventricle D -Dual(A+V)	O -None T -Triggered I -Inhibited D -Dual(T+I)	R -Rate Modulation


i.e. AOO, VOO, AAI, AAT, VVI, VVT, AATR, VVTR, AOOR etc. . .




One and Two-Electrode Pacemaker



DDD Pacing Modes




DDD Pacing Modes



$axm1 : LRL \in 30 \dots 175$
 $axm2 : URL \in 50 \dots 175$
 $axm3 : URI \in \mathbb{N}_1 \wedge URI = 60000/URL$
 $axm4 : LRI \in \mathbb{N}_1 \wedge LRI = 60000/LRL$
 $axm5 : status = \{ON, OFF\}$
 $axm6 : FixedAV \in 70 \dots 300$
 $axm7 : ARP \in 150 \dots 500$
 $axm8 : VRP \in 150 \dots 500$
 $axm9 : PVARP \in 150 \dots 500$
 $axm10 : V_Blank \in 30 \dots 60$
...

DDD Pacing Modes



$axm1 : LRL \in 30 \dots 175$
 $axm2 : URL \in 50 \dots 175$
 $axm3 : URI \in \mathbb{N}_1 \wedge URI = 60000/URL$
 $axm4 : LRI \in \mathbb{N}_1 \wedge LRI = 60000/LRL$
 $axm5 : status = \{ON, OFF\}$
 $axm6 : FixedAV \in 70 \dots 300$
 $axm7 : ARP \in 150 \dots 500$
 $axm8 : VRP \in 150 \dots 500$
 $axm9 : PVARP \in 150 \dots 500$
 $axm10 : V_Blank \in 30 \dots 60$
 $\dots$

$inv1 : PM_Actuator_A \in status$
 $inv2 : PM_Sensor_A \in status$
 $inv5 : Pace_Int \in URI \dots LRI$
 $inv6 : sp \in 1 \dots Pace_Int$
 $inv7 : last_sp \geq PVARP \wedge last_sp \leq Pace_Int$
 $inv11 : sp < VRP \wedge AV_Count_STATE = FALSE \Rightarrow$
 $PM_Actuator_V = OFF \wedge PM_Sensor_A = OFF$
 $PM_Sensor_V = OFF \wedge PM_Actuator_A = OFF$
 $inv12 : Pace_Int_flag = FALSE \wedge PM_Actuator_V =$
 $sp = Pace_Int \vee (sp < Pace_Int \wedge$
 $AV_Count > V_Blank \wedge AV_Count \geq FixedAV)$
 $inv13 : Pace_Int_flag = FALSE \wedge PM_Actuator_A =$
 $(sp \geq Pace_Int - FixedAV)$
 $\dots$

DDD Pacing Modes

EVENT Actuator_ON_V

WHEN

grd1 : $PM_Actuator_V = OFF$

grd2 : $(sp = Pace_Int)$

$\vee$
 $(sp < Pace_Int \wedge AV_Count > V_Blank \wedge$
 $AV_Count \geq FixedAV)$

grd3 : $sp \geq VRP \wedge sp \geq PVARP$

THEN

act1 : $PM_Actuator_V := ON$

act2 : $last_sp := sp$

END

EVENT Actuator_OFF_V

WHEN

grd1 : $PM_Actuator_V = ON$

grd2 : $(sp = Pace_Int)$

$\vee$
 $(sp < Pace_Int \wedge AV_Count > V_Blank$
 $AV_Count \geq FixedAV$

grd3 : $AV_Count_STATE = TRUE$

grd4 : $PM_Actuator_A = OFF$

grd5 : $PM_Sensor_A = OFF$

THEN

act1 : $PM_Actuator_V := OFF$

act2 : $AV_Count := 0$

act3 : $AV_Count_STATE := FALSE$

act4 : $PM_Sensor_V := OFF$

act5 : $sp := 1$

END

EVENT tic

WHEN

grd1 : $(sp < VRP)$

$\vee$


$(sp \geq VRP \wedge sp < Pace_Int - FixedAV \wedge$
 $PM_Sensor_A = ON \wedge PM_Sensor_V = ON)$

THEN


act1 : $sp := sp + 1$

END

First Refinement (Threshold) : Sensor Activity in DDD



First Refinement (Threshold) : Sensor Activity in DDD



$inv1 : Thr_A \in \mathbb{N}_1 \wedge Thr_V \in \mathbb{N}_1$

$inv2 : Pace_Int_flag = FALSE \wedge sp > VRP \wedge sp < Pace_Int - FixedAV \Rightarrow PM_Sensor_V$

$inv3 : Pace_Int_flag = FALSE \wedge sp > Pace_Int - FixedAV \wedge sp < Pace_Int \wedge AV_Count_$
 $PM_Sensor_A = OFF \wedge PM_Sensor_V = ON \wedge PM_Actuator_A = OFF$

Second and Third Refinements

Second Refinement : Hysteresis

EVENT Hyt_Pace_Updating Refines Change_Pace_Int

ANY

Hyt_Pace_Int

WHERE

grd1 : *Pace_Int_flag* = *TRUE*

grd2 : *Hyt_Pace_Int_flag* = *TRUE*

grd3 : *Hyt_Pace_Int* ∈ *Pace_Int* .. *LRI*

THEN

act1 : *Pace_Int* := *Hyt_Pace_Int*

act2 : *Hyt_Pace_Int_flag* := *FALSE*

act3 : *HYT_State* := *TRUE*

END

Second and Third Refinements

Second Refinement : Hysteresis

```
EVENT Hyt_Pace_Updating Refines Change_Pace_Int
ANY
    Hyt_Pace_Int
WHERE
    grd1 : Pace_Int_flag = TRUE
    grd2 : Hyt_Pace_Int_flag = TRUE
    grd3 : Hyt_Pace_Int  $\in$  Pace_Int .. LRI

THEN
    act1 : Pace_Int := Hyt_Pace_Int
    act2 : Hyt_Pace_Int_flag := FALSE
    act3 : HYT_State := TRUE

END
```

Third Refinement : Rate Modulation

```
EVENT Increase_Interval Refines Change_Pace_Int
WHEN
    grd1 : Pace_Int_flag = TRUE
    grd1 : acler_sensed  $\geq$  threshold
    grd1 : HYT_State = FALSE

THEN
    act1 : Pace_Int := 60000/MSR
    act1 : acler_sensed_flag := TRUE

END
```


ProB

Model Checker is used to verify the Event-B model and correctness of operating modes.

Proof Statistics

Model	Total number of POs	Automatic Proof	Interactive Proof
One-electrode pacemaker			
Abstract Model	203	199(98%)	4(2%)
First Refinement	48	44(91%)	4(9%)
Second Refinement	12	8(66%)	4(34%)
Third Refinement	105	99(94%)	6(6%)
Two-electrode pacemaker			
Abstract Model	204	195(95%)	9(5%)
First Refinement	234	223(95%)	11(5%)
Second Refinement	3	3(100%)	0(0%)
Third Refinement	83	74(89%)	9(11%)
Total	892	845(94%)	47(6%)

Code Generation



EVENT Actuator_ON_V

WHEN

Actuator_ON_V.Guard1 : $PM_Actuator_ON_V$

Actuator_ON_V.Guard2 : $(sp = Pace_Int)$

$\vee$

$(sp < Pace_Int \wedge$

$AV_Count > V_Blank \wedge$

$AV_Count \geq FixedAV)$

Actuator_ON_V.Guard3 : $sp \geq VRP \wedge s$

THEN

Actuator_ON_V.Action1 : $PM_Actuator_ON_V$

Actuator_ON_V.Action2 : $last_sp := sp$


END

```


...
BOOL Actuator_ON_V(void)
{
    /* Guards No. 1*/
    if(PM_Actuator_V == OFF){
        /* Guards No. 2*/
        if((sp == Pace_Int) || ((sp < Pace_Int) &&
            (AV_Count > V_Blank) && (AV_Count >= FixedAV))){
            /* Guards No. 3*/
            if((sp >= VRP) && (sp >= PVARP) && (sp >= URI)){
                /* Actions */
                PM_Actuator_V = ON;
                last_sp = sp;
                return TRUE;
            }
        }
        return FALSE;
    }
    ...
}

```

Electrical Conduction Model



Closed-loop Model



- Applying the complete cycle for a real pacemaker or a new challenge. . .
- System engineering : developing a pump, managing insulin, . . .
- Questions on dependability
- Questions on proving and testing : relationship with physicians.
- Questions on modelling biological environment

Current Summary


- ① Documentation
- ② Introduction by a Problem
- ③ Dependability and security assurance
- ④ Overview of formal techniques and formal methods
- ⑤ Modelling Language
- ⑥ A Simple Example
- ⑦ Modelling state-based systems
- ⑧ The Event B modelling language
- ⑨ Examples of Event B models

Examples of modelling languages

- Z : set theory, predicate calculus, schemas.
- VDM : types, pre/post specification, invariant, operations
- B : set theory, predicate calculus, generalized substitution, abstract machines, refinement, implementation.
- RAISE : abstract data types, functions,
- TLA⁺ : set theory, modules, temporal logic of actions.
- UNITY : temporal logic, actions systems, superposition.
- UML
- JML and Spec# : programming by contract


- Mathematical foundations of Models : syntax, semantics, pragmatics, theory, soundness.
- Mathematical reasoning is based on sound proof rules
- Common language for facilitating the communication.

Observing the safe system



- The context defines the possible values
- Safety requirement means that *something bad will never happen*.
- Invariant defines the set of effective possible values
- Transitions modify state variables and maintains the invariant.

Observing the unsafe system



- Transitions modify state variables and **may not maintain** the invariant.
- ... and **may not guarantee** safety properties.

Second step : definition of state variables

- The system model should be able to record the lecturing teachers and the attending students.
- The system model should be enough expressive to state when a given student is attending a lecture given by whom.
- Variable **attending** records students which attended some lecture with a given teacher.
- Variable **islecturing** records teachers who are lecturing.
- Variable **pause** records students are not attending a lecture but are somewhere not in a lecture.

Third step : properties of state variables

Expression of the invariant

$$\begin{aligned} \text{inv1} &: \text{attending} \in \text{STUDENTS} \leftrightarrow \text{TEACHERS} \\ \text{inv2} &: \text{islecturing} \subseteq \text{TEACHERS} \\ \text{inv3} &: \forall e. e \in \text{STUDENTS} \wedge e \in \text{dom}(\text{attending}) \\ &\quad \Rightarrow \text{attending}(e) \in \text{islecturing} \\ \text{inv4} &: \text{pause} \subseteq \text{STUDENTS} \\ \text{inv5} &: \text{pause} \cap \text{dom}(\text{attending}) = \emptyset \\ \text{inv6} &: \text{pause} \cup \text{dom}(\text{attending}) = \text{STUDENTS} \end{aligned}$$

Checking proof obligations!

Fourth step : Updating state variables

EVENT INITIALISATION

BEGIN

act1 : *attending* := $\emptyset$

act2 : *islecturing* := $\emptyset$

act3 : *pause* := *STUDENTS*

END

Fourth step : Updating state variables

```
EVENT startingattending
ANY
  e e is a student
  p p is a teacher
WHERE
  grd1 :  $e \in STUDENTS$ 
  grd3 :  $p \in TEACHERS$ 
  grd4 :  $p \in islecturing$ 
  grd2 :  $e \notin dom(attending)$ 
THEN
  act1 :  $attending(e) := p$ 
  act2 :  $pause := pause \setminus \{e\}$ 
END
```

Fourth step : Updating state variables

```
EVENT teachergivinglecture
  ANY
   $p$ 
  WHERE
     $grd2 : p \in TEACHERS$ 
     $grd1 : p \notin islecturing$ 
  THEN
     $act1\ islecturing := islecturing \cup \{p\}$ 
  END
```

Fourth step : Updating state variables

```
EVENT teacherendinglecture
ANY
  p
WHERE
  grd1 :  $p \in TEACHERS$ 
  grd2 :  $p \in islecturing$ 
THEN
  act1 :  $islecturing := islecturing \setminus \{p\}$ 

  act3 :  $attending := attending \setminus \{f \mapsto q \mid \left( \begin{array}{l} f \in STUDENTS \\ \wedge q \in TEACHERS \\ \wedge f \mapsto q \in attending \\ \wedge q = p \end{array} \right)\}$ 

  act2 :  $pause := pause \cup \{f \mid f \in STUDENTS \wedge f \in attending^{-1}[\{p\}]\}$ 
END
```

Fourth step : Updating state variables

```
EVENT studentleavinglecture
  ANY
    ge
  WHERE
    grd1 : ge  $\subseteq$  dom(attending)
    grd2 : ge  $\neq \emptyset$ 
  THEN
    act1 : attending := ge  $\triangleleft$  attending
    act2 : pause := pause  $\cup$  ge
  END
```


Mathematical tools for modelling systems

- **set theory : sets, relations, functions . . .**
- **transition systems**
- **predicate calculus**
- **decision procedures**
- **interactive theorem prover**

Current Summary

- ① Documentation
- ② Introduction by a Problem
- ③ Dependability and security assurance
- ④ Overview of formal techniques and formal methods
- ⑤ Modelling Language
- ⑥ A Simple Example
- ⑦ Modelling state-based systems**
- ⑧ The Event B modelling language
- ⑨ Examples of Event B models

Changing state of system

A **flexible variable** x is observed at different instants :

$$x_0 \xrightarrow{\tau} x_1 \xrightarrow{\tau} x_2 \xrightarrow{\tau} x_3 \xrightarrow{\tau} \dots \xrightarrow{\tau} x_i \xrightarrow{\tau} x_{i+1} \xrightarrow{\tau} \dots$$

τ hides effectives changes of state or actions or events

$$x_0 \xrightarrow{\alpha_1} x_1 \xrightarrow{\alpha_2} x_2 \xrightarrow{\alpha_3} x_3 \xrightarrow{\alpha_4} \dots \xrightarrow{\alpha_i} x_i \xrightarrow{\alpha_{i+1}} x_{i+1} \xrightarrow{\alpha_{i+2}} \dots$$

Occurences of e τ can be added between two instants ie stuttering steps :

$$x_0 \xrightarrow{\alpha_1} x_1 \xrightarrow{\alpha_2} x_2 \xrightarrow{\tau} x_2 \xrightarrow{\alpha_3} x_3 \xrightarrow{\alpha_4} \dots \xrightarrow{\alpha_i} x_i \xrightarrow{\tau} x_i \xrightarrow{\alpha_{i+1}} x_{i+1} \xrightarrow{\alpha_{i+2}} \dots$$

Changing state of system

A **flexible variable** x is observed at different instants :

$$x_0 \xrightarrow{\tau} x_1 \xrightarrow{\tau} x_2 \xrightarrow{\tau} x_3 \xrightarrow{\tau} \dots \xrightarrow{\tau} x_i \xrightarrow{\tau} x_{i+1} \xrightarrow{\tau} \dots$$

τ hides effective changes of state or actions or events

$$x_0 \xrightarrow{\alpha_1} x_1 \xrightarrow{\alpha_2} x_2 \xrightarrow{\alpha_3} x_3 \xrightarrow{\alpha_4} \dots \xrightarrow{\alpha_i} x_i \xrightarrow{\alpha_{i+1}} x_{i+1} \xrightarrow{\alpha_{i+2}} \dots$$

Occurrences of τ can be added between two instants ie stuttering steps :

$$x_0 \xrightarrow{\alpha_1} x_1 \xrightarrow{\alpha_2} x_2 \xrightarrow{\tau} x_2 \xrightarrow{\alpha_3} x_3 \xrightarrow{\alpha_4} \dots \xrightarrow{\alpha_i} x_i \xrightarrow{\tau} x_i \xrightarrow{\alpha_{i+1}} x_{i+1} \xrightarrow{\alpha_{i+2}} \dots$$

Changing state of system

A **flexible variable** x is observed at different instants :

$$x_0 \xrightarrow{\tau} x_1 \xrightarrow{\tau} x_2 \xrightarrow{\tau} x_3 \xrightarrow{\tau} \dots \xrightarrow{\tau} x_i \xrightarrow{\tau} x_{i+1} \xrightarrow{\tau} \dots$$

τ hides effective changes of state or actions or events

$$x_0 \xrightarrow{\alpha_1} x_1 \xrightarrow{\alpha_2} x_2 \xrightarrow{\alpha_3} x_3 \xrightarrow{\alpha_4} \dots \xrightarrow{\alpha_i} x_i \xrightarrow{\alpha_{i+1}} x_{i+1} \xrightarrow{\alpha_{i+2}} \dots$$

Occurrences of τ can be added between two instants ie stuttering steps :

$$x_0 \xrightarrow{\alpha_1} x_1 \xrightarrow{\alpha_2} x_2 \xrightarrow{\tau} x_2 \xrightarrow{\alpha_3} x_3 \xrightarrow{\alpha_4} \dots \xrightarrow{\alpha_i} x_i \xrightarrow{\tau} x_i \xrightarrow{\alpha_{i+1}} x_{i+1} \xrightarrow{\alpha_{i+2}} \dots$$

Changing state of system

A **flexible variable** x is observed at different instants :

$$x_0 \xrightarrow{\tau} x_1 \xrightarrow{\tau} x_2 \xrightarrow{\tau} x_3 \xrightarrow{\tau} \dots \xrightarrow{\tau} x_i \xrightarrow{\tau} x_{i+1} \xrightarrow{\tau} \dots$$

τ hides effective changes of state or actions or events

$$x_0 \xrightarrow{\alpha_1} x_1 \xrightarrow{\alpha_2} x_2 \xrightarrow{\alpha_3} x_3 \xrightarrow{\alpha_4} \dots \xrightarrow{\alpha_i} x_i \xrightarrow{\alpha_{i+1}} x_{i+1} \xrightarrow{\alpha_{i+2}} \dots$$

Occurrences of τ can be added between two instants ie **stuttering steps** :

$$x_0 \xrightarrow{\alpha_1} x_1 \xrightarrow{\alpha_2} x_2 \xrightarrow{\tau} x_2 \xrightarrow{\alpha_3} x_3 \xrightarrow{\alpha_4} \dots \xrightarrow{\alpha_i} x_i \xrightarrow{\tau} x_i \xrightarrow{\alpha_{i+1}} x_{i+1} \xrightarrow{\alpha_{i+2}} \dots$$

Changing state of system

A **flexible variable** x is observed at different instants :

$$x_0 \xrightarrow{\tau} x_1 \xrightarrow{\tau} x_2 \xrightarrow{\tau} x_3 \xrightarrow{\tau} \dots \xrightarrow{\tau} x_i \xrightarrow{\tau} x_{i+1} \xrightarrow{\tau} \dots$$

τ hides effective changes of state or actions or events

$$x_0 \xrightarrow{\alpha_1} x_1 \xrightarrow{\alpha_2} x_2 \xrightarrow{\alpha_3} x_3 \xrightarrow{\alpha_4} \dots \xrightarrow{\alpha_i} x_i \xrightarrow{\alpha_{i+1}} x_{i+1} \xrightarrow{\alpha_{i+2}} \dots$$

Occurrences of τ can be added between two instants ie **stuttering steps** :

$$x_0 \xrightarrow{\alpha_1} x_1 \xrightarrow{\alpha_2} x_2 \xrightarrow{\tau} x_2 \xrightarrow{\alpha_3} x_3 \xrightarrow{\alpha_4} \dots \xrightarrow{\alpha_i} x_i \xrightarrow{\tau} x_i \xrightarrow{\alpha_{i+1}} x_{i+1} \xrightarrow{\alpha_{i+2}} \dots$$

A **safety** property S over x states that something will not happen : $S(x)$ means that S holds for x

An **invariant** property I over x states a strong safety property

$$\begin{aligned} x_0 &\xrightarrow{\alpha_1} x_1 \xrightarrow{\alpha_2} x_2 \xrightarrow{\tau} x_2 \xrightarrow{\alpha_3} x_3 \xrightarrow{\alpha_4} \dots \xrightarrow{\alpha_i} x_i \xrightarrow{\tau} x_i \xrightarrow{\alpha_{i+1}} x_{i+1} \xrightarrow{\alpha_{i+2}} \dots \\ (S(x_0) &\xrightarrow{\alpha_1} S(x_1) \xrightarrow{\alpha_2} S(x_2) \xrightarrow{\tau} S(x_2) \xrightarrow{\alpha_3} S(x_3) \xrightarrow{\alpha_4} \dots \xrightarrow{\alpha_i} S(x_i) \xrightarrow{\tau} \\ S(x_i) &\xrightarrow{\alpha_{i+1}} S(x_{i+1}) \xrightarrow{\alpha_{i+2}} \dots \end{aligned}$$

or equivalently $\forall i \in \mathbb{N} : S(x_i)$

Checking the relation

- You can check for every i in $\mathbb{N}$ that $S(x_i)$ is true but it can be long if states are different
- You can compute an abstraction of the set of states
- You can try to prove and for instance the induction principle may be usefull
- So be carefull and improve your modelling before to run the checker
- Use the induction

State properties of a system

- A state property namely $P(x)$ is a first order predicate with free variables x , where x is a flexible variable.
- A flexible variable x has a current value x , a next value x' , an initial value x_0 and possibly a final value x_f .
- A predicate $P(x)$ is considered as a set of values v such that $P(v)$ holds : set-theoretical interpretation

Examples of state properties

- Mutual exclusion : a set of processes share common resources, a printer is shared by users, ...
- Deadlock freedom : the system is never blocked, there is always at least one next state, ...
- Partial correctness : a component is correct with respect to a precondition and a postcondition.
- Safety properties : nothing bad can happen

- An action α over states is a relation between values of state variables **before** and values of variables **after**

$$\alpha(x, x') \text{ or } x \xrightarrow{\alpha} x'$$

- Flexible variable x has two values x and x' .
- Priming flexible variables is borrowed from TLA
- **Hypothesis 1** : **Values of x belongs to a set of values called VALUES** and defines the context of the system.
- **Hypothesis 2** : **Relations over x and x' belong to a set of relations $\{r_0, \dots, r_n\}$**

Operational model of a system

- A system $\mathcal{S}$ is observed with respect to flexible variables x .
- Flexible variables x of $\mathcal{S}$ are modified according to a finite set of relations over the set of values $\text{VALUES} : \{r_0, \dots, r_n\}$
- $\text{INIT}(x)$ denotes the set of possible initial values for x .

$$\mathcal{OMS} = (x, \mathbf{Values}, \mathbf{Init}(x), \{r_0, \dots, r_n\})$$

Safety and invariance of system

- **Hypothesis 3** : $\mathcal{O}MS = (x, \text{VALUES}, \text{INIT}(x), \{r_0, \dots, r_n\})$
- **Hypothesis 4** : $x \longrightarrow x' \triangleq (x \ r_0 \ x') \vee \dots \vee (x \ r_n \ x')$
- $I(x)$ is inductively invariant for a system called $\mathcal{S}$, if

$$\begin{cases} \forall x \in \text{VALUES} : \text{INIT}(x) \Rightarrow I(x) \\ \forall x, x' \in \text{VALUES} : I(x) \wedge x \longrightarrow x' \Rightarrow I(x') \end{cases}$$
 $I(x)$ is called an invariant in $\mathcal{B}$
- $Q(x)$ is a safety property for a system called $\mathcal{S}$, if

$$\forall x, y \in \text{VALUES} : \text{INIT}(x) \wedge x \xrightarrow{\star} y \Rightarrow Q(y)$$
 $Q(x)$ is called a theorem in $\mathcal{B}$

Modelling systems : first attempt

MODEL

m

...

...

...

VARIABLES

x

INVARIANT

$I(x)$

THEOREMS

$Q(x)$

INITIALISATION

$Init(x)$

EVENTS

$\{r_0, \dots, r_n\}$

END

- A model has a name m
- Flexible variables x are declared
- $I(x)$ provides information over x
- $Q(x)$ provides information over x

Defining an induction principle for an operational model

$$(I) \forall x, y \in \mathbf{Values} : \mathbf{Init}(x) \wedge x \xrightarrow{\star} y \Rightarrow \mathbf{Q}(y)$$

if, and only if,

(II) there exists a state property $I(x)$ such that :

$$\forall x, x' \in \mathbf{Values} : \begin{cases} (1) \mathbf{Init}(x) \Rightarrow I(x) \\ (2) I(x) \Rightarrow \mathbf{Q}(x) \\ (3) I(x) \wedge x \longrightarrow x' \Rightarrow I(x') \end{cases}$$

if, and only if,

(III) there exists a state property $I(x)$ such that :

$$\forall x, x' \in \mathbf{Values} : \begin{cases} (1) \mathbf{Init}(x) \Rightarrow I(x) \\ (2) I(x) \Rightarrow \mathbf{Q}(x) \\ (3) \forall i \in \{0, \dots, n\} : I(x) \wedge x \ r_i \ x' \Rightarrow I(x') \end{cases}$$

Modelling systems : second attempt

MODEL

m

...

...

...

VARIABLES

x

INVARIANT

$I(x)$

THEOREMS

$Q(x)$

INITIALISATION

$Init(x)$

EVENTS

$\{r_0, \dots, r_n\}$

END

- $\forall x \in \text{VALUES} : \text{INIT}(x) \Rightarrow I(x)$
- $\forall x, x' \in \text{VALUES} : \forall i \in \{0, \dots, n\} :$
 $I(x) \wedge x \ r_i \ x' \Rightarrow I(x')$
- $\forall x \in \text{VALUES} : I(x) \Rightarrow Q(x)$

Modelling systems : last attempt !

MODEL

m

$\Gamma(m)$

VARIABLES

x

INVARIANT

$I(x)$

THEOREMS

$Q(x)$

INITIALISATION

$Init(x)$

EVENTS

$\{r_0, \dots, r_n\}$

END

- $\Gamma(m)$ defines the static environment for the proofs related to m .
- $\Gamma(m) \vdash \forall x \in \text{VALUES} : \text{INIT}(x) \Rightarrow I(x)$
- $\forall i \in \{0, \dots, n\} :$
 $\Gamma(m) \vdash \forall x, x' \in \text{VALUES} : I(x) \wedge x \ r_i \ x' \Rightarrow I(x')$
- $\Gamma(m) \vdash \forall x \in \text{VALUES} : I(x) \Rightarrow Q(x)$

Modelling systems : Hello world !

MODEL FACTORIAL_EVENTS

Static Part *context*

CONSTANTS

factorial, m

AXIOMS

$$\begin{aligned} & m \in \mathbb{N} \wedge \text{factorial} \in \mathbb{N} \leftrightarrow \mathbb{N} \wedge 0 \mapsto 1 \in \text{factorial} \wedge \\ & \forall(n, fn). (n \mapsto fn \in \text{factorial} \Rightarrow n + 1 \mapsto (n + 1) * fn \in \text{factorial}) \wedge \\ & \forall f \cdot \left(\begin{array}{l} f \in \mathbb{N} \leftrightarrow \mathbb{N} \wedge \\ 0 \mapsto 1 \in f \wedge \\ \forall(n, fn). (n \mapsto fn \in f \Rightarrow n + 1 \mapsto (n + 1) \times fn \in f) \\ \Rightarrow \\ \text{factorial} \subseteq f \end{array} \right) \end{aligned}$$

Dynamic Part *machine*

VARIABLES

result, ok

INVARIANT

result $\in \mathbb{N}$

ok $\in \mathbb{B}$

ok = TRUE $\Rightarrow$ *result* = *factorial*(*n*)

THEOREMS

factorial $\in \mathbb{N} \longrightarrow \mathbb{N}$;

factorial(0) = 1 ;

$\forall n. (n \in \mathbb{N} \Rightarrow \text{factorial}(n + 1) = (n + 1) \times \text{factorial}(n))$

INITIALISATION

result := $\in \mathbb{N}$

ok := FALSE

EVENTS

computation = ANY *ok* = FALSE THEN *result, ok* := *factorial*(*m*), TRUE END

END

Modelling systems relations as events

MODEL

m

Static Part *context*

SETS

s

CONSTANTS

c

AXIOMS

$P(s, c)$

THEOREMS

$Q(s, c)$

Dynamic Part *machine*

VARIABLES

x

INVARIANT

$I(s, c, x)$

THEOREMS

$S(s, c, x)$

INITIALISATION

$Init(s, c, x)$

EVENTS

$\{r_1, \dots, r_n\}$

END

- $\Gamma(m)$ defines the static environment for the proofs related to m from s , c and $P(s, c)$ and $\Gamma(m)$ is defined from the static part.
- $\Gamma(m) \vdash Q(s, c)$
- $\Gamma(m) \vdash \forall x, x' \in \text{VALUES} : \text{INIT}(s, c, x) \Rightarrow I(s, c, x)$
- $\forall i \in \{1, \dots, n\} :$
 $\Gamma(m) \vdash \forall x, x' \in \text{VALUES} :$
 $I(s, c, x) \wedge x r_i x' \Rightarrow I(s, c, x')$
- $\Gamma(m) \vdash \forall x, x' \in \text{VALUES} : I(s, c, x) \Rightarrow S(s, c, x)$

step 1 : Understanding the **problem** to solve

step 2 : Organizing requirements and extracting properties

step 3 : Writing a first very **abstract** system model

step 4 : Consulting the requirements and **adding** a new detail in the current model by **refinement**

step 5 : Either the model is enough detailed and the process stops, or the model is not yet enough concrete and the step 4 is repeated.

Current Summary

- 1 Documentation
- 2 Introduction by a Problem
- 3 Dependability and security assurance
- 4 Overview of formal techniques and formal methods
- 5 Modelling Language
- 6 A Simple Example
- 7 Modelling state-based systems
- 8 The Event B modelling language

- ## 9 Examples of Event B models

Expressing models in the event B notation

- Models are defined in two ways :
 - ▶ an abstract machine
 - ▶ a refinement of an existing model
- Models use **constants** which are defined in structures called **contexts**
- B structures are related by the three possible relations :
 - ▶ the **sees** relationship for expressing the use of constants, sets satisfying axioms and theorems.
 - ▶ the **extends** relationship for expressing the extension of contexts by adding new constants and new sets
 - ▶ the **refines** relationship stating that a B model is refined by another one.

Machines

- **REFINES**
- **SEES** a context
- **VARIABLES** of the model
- **INVARIANTS** satisfied by the variables
- **THEOREMS** satisfied by the variables
- **EVENTS** modifying the variables
- **VARIANT**

Contexts

- **EXTENDS** another context
- **SETS** declares new sets
- **CONSTANTS** define a list of constants
- **AXIOMS** define the properties of constants and sets
- **THEOREMS** list the theorems which should be derived from axioms

MACHINE
 m
 REFINES
 am
 SEES
 c
 VARIABLES
 u
 INVARIANTS
 $I(u)$
 THEOREMS
 $Q(u)$
 VARIANT
 $\langle variant \rangle$
 EVENTS
 $\langle event \rangle$
 END

- $\Gamma(m)$: environment for the machine m defined by the context c
- $\Gamma(m) \vdash \forall u \in \text{VALUES} : \text{INIT}(u) \Rightarrow \text{I}(u)$
- For each event e in E :
 $\Gamma(m) \vdash \forall u, u' \in \text{VALUES} : \text{I}(u) \wedge \text{BA}(e)(u, u') \Rightarrow \text{I}(u')$
- $\Gamma(m) \vdash \forall u \in \text{VALUES} : \text{I}(u) \Rightarrow \text{Q}(u)$

Contexts in Event B

CONTEXTS

C
EXTENDS

ac
SETS

^sCONSTANTS

k AXIOMS

$ax1 : \dots$
THEOREMS

```

    th1 : ...
END

```

- ac : c is extending ac and add new features
- s : sets are defined either by intension or by extension
- k : constants are defined and
- axioms characterize constants and sets
- theorems are derived from axioms in the current context

before-after relation for e

For each event e, a before-after relation is defined over (flexible) variables.
Three events are possible

- $e \triangleq \text{BEGIN } x : |P(x, x') \text{ END} : \text{BA}(e)(x, x') \triangleq P(x; x')$
- $e \triangleq \text{WHEN } G(x) \text{ THEN } x : |P(x, x') \text{ END} : \text{BA}(e)(x, x') \triangleq G(x) \wedge P(x; x')$
- $e \triangleq \text{ANY } p \text{ WHEN } G(p, x) \text{ THEN } x : |P(p, x, x') \text{ END} : \text{BA}(e)(x, x') \triangleq \exists p. G(p, x) \wedge P(x; x')$

guard for e

For each event e, a guard is defined over (flexible) variables.
Three events are possible

- $e \triangleq \text{BEGIN } x : |P(x, x') \text{ END} : \text{grd}(x) \triangleq \text{TRUE}$
- $e \triangleq \text{WHEN } G(x) \text{ THEN } x : |P(x, x') \text{ END} : \text{grd}(e)(x) \triangleq G(x)$
- $e \triangleq \text{ANY } p \text{ WHEN } G(p, x) \text{ THEN } x : |P(p, x, x') \text{ END} : \text{grd}(e)(x) \triangleq \exists p. G(p, x)$

Proof obligations for a B model

$$\text{inv1} \quad \Gamma(s, c) \vdash \text{Init}(x) \Rightarrow I(x)$$

$$\text{inv2} \quad \Gamma(s, c) \vdash I(x) \wedge BA(e)(x, x') \Rightarrow I(x')$$

$$\text{fis} \quad \Gamma(s, c) \vdash I(x) \wedge \text{grd}(E) \Rightarrow \exists x' \cdot P(x, x')$$

$$\text{safe} \quad \Gamma(s, c) \vdash I(x) \Rightarrow A(x)$$

$$\text{dead} \quad \Gamma(s, c) \vdash I(x) \Rightarrow (\text{grd}(e_1) \vee \dots \vee \text{grd}(e_n))$$

The factorial model

CONTEXT

fonctions

CONSTANTS

factorial, n

AXIOMS

$ax1 : n \in \mathbb{N}$

$ax2 : factorial \in \mathbb{N} \leftrightarrow \mathbb{N}$

$ax3 : 0 \mapsto 1 \in factorial$

$ax4 : \forall(i, fn).(i \mapsto fn \in factorial \Rightarrow i + 1 \mapsto (i + 1) * fi \in factorial) \wedge$

$$\forall f \cdot \left(\begin{array}{l} f \in \mathbb{N} \leftrightarrow \mathbb{N} \wedge \\ 0 \mapsto 1 \in f \wedge \\ \forall(n, fn).(n \mapsto fn \in f \Rightarrow n + 1 \mapsto (n + 1) \times fn \in f) \\ \Rightarrow \\ factorial \subseteq f \end{array} \right)$$

END

Current Summary

9 Examples of Event B models

The factorial model

MACHINE

specification

SEES *fonctions*

VARIABLES

resultat

INVARIANT

resultat $\in \mathbb{N}$

THEOREMS

th1 : *factorial* $\in \mathbb{N} \rightarrow \mathbb{N}$;

th2 : *factorial*(0) = 1 ;

th3 : $\forall n. (n \in \mathbb{N} \Rightarrow \text{factorial}(n + 1) = (n + 1) \times \text{factorial}(n))$

INITIALISATION

resultat : $\in \mathbb{N}$

EVENTS

computing1 = BEGIN *resultat* := *factorial*(*n*) END

END

Communications between agents

MACHINE *agents*

SEES *data*

VARIABLES

sent

got

lost

INVARIANTS

inv1 : $sent \subseteq AGENTS \times AGENTS$

inv2 : $got \subseteq AGENTS \times AGENTS$

inv4 : $(got \cup lost) \subseteq sent$

inv6 : $lost \subseteq AGENTS \times AGENTS$

inv7 : $got \cap lost = \emptyset$

INITIALISATION

BEGIN

act1 : $sent := \emptyset$

act2 : $got := \emptyset$

act4 : $lost := \emptyset$

END

Communications between agents

EVENT sending a message

ANY

a, b

WHERE

$grd11 : a \in AGENTS$

$grd12 : b \in AGENTS$

$grd1 : a \mapsto b \notin sent$

THEN

$act11 : sent := sent \cup \{a \mapsto b\}$

END

EVENT getting a message

ANY

a, b

WHERE

$grd11 : a \in AGENTS$

$grd12 : b \in AGENTS$

$grd13 : a \mapsto b \in sent \setminus (got \cup lost)$

THEN

$act11 : got := got \cup \{a \mapsto b\}$

END

Communications between agents

```
EVENT losing a message
ANY
  a
  b
WHERE   $grd1 : a \in AGENTS$ 
        $grd2 : b \in AGENTS$ 
        $grd3 : a \mapsto b \in sent \setminus (got \cup lost)$ 
THEN
   $act1 : lost := lost \cup \{a \mapsto b\}$ 
END
```

CONTEXTS

data

SETS

MESSAGES

AGENTS

DATA

CONSTANTS

n

infile

AXIOMS

$axm1 : n \in \mathbb{N}$

$axm2 : n \neq 0$

$axm3 : infile \in 1 .. n \rightarrow DATA$

END

Current Summary

- ## 9 Examples of Event B models

General form of an event

```
EVENT e
  ANY t
  WHERE
     $G(c, s, t, x)$ 
  THEN
     $x : |(P(c, s, t, x, x'))|$ 
  END
```

- c et s are constantes and visible sets by e
- x is a state variable or a list of variables
- $G(c, s, t, x)$ is the condition for observing e .
- $P(c, s, t, x, x')$ is the assertion for the relation over x and x' .
- $BA(e)(c, s, x, x')$ is the *before-after* relationship for e and is defined by $\exists t. G(c, s, t, x) \wedge P(c, s, t, x, x')$.

General form of proof obligations for an event e

Proofs obligations are simplified when they are generated by the module called POG and goals in sequents as $\Gamma \vdash G$:

- ① $\Gamma \vdash G_1 \wedge G_2$ is decomposed into the two sequents $(1) \Gamma \vdash G_1$
 $(2) \Gamma \vdash G_2$
- ② $\Gamma \vdash G_1 \Rightarrow G_2$ is transformed into the sequent $\Gamma, G_1 \vdash G_2$

Proof obligations in Rodin

- $INIT/I/INV : C(s, c), INIT(c, s, x) \vdash I(c, s, x)$
- $e/I/INV : C(s, c), I(c, s, x), G(c, s, t, x), P(c, s, t, x, x') \vdash I(c, s, x')$
- $e/act/FIS : C(s, c), I(c, s, x), G(c, s, t, x) \vdash \exists x'. P(c, s, t, x, x')$

