Cours MALG & MOVEX

Vérification mécanisée de contrats (II) (The ANSI/ISO C Specification Language (ACSL))

Dominique Méry
Telecom Nancy, Université de Lorraine

Année universitaire 2025-2026 (12 mars 2026 9:25 A.M.)

Plan

1. Programs as Predicate Transformers
2. Annotations
3. Contracts
   - Extending C programming language by contracts
4. Stop MOVEX6
   - Playing with variables
   - Ghost Variables

Sommaire

1. Programs as Predicate Transformers
2. Annotations
3. Contracts
   - Extending C programming language by contracts
4. Stop MOVEX6
   - Playing with variables
   - Ghost Variables

Sommaire

1. Programs as Predicate Transformers
2. Annotations
3. Contracts
   - Extending C programming language by contracts
4. Stop MOVEX6
   - Playing with variables
   - Ghost Variables

Current Summary

1. Programs as Predicate Transformers
2. Annotations
3. Contracts
   - Extending C programming language by contracts
4. Stop MOVEX6
   - Playing with variables
   - Ghost Variables

Asserted Program {P} S {Q}



Asserted Program {P} S {Q}



Asserted Program {P} S {Q}

{P} S {Q}



$$P \Rightarrow WLP(S)(\mathsf{Q})$$

Asserted Program {P} S {Q}

{P} S {Q}



$$P \Rightarrow WLP(S)(\mathsf{Q})$$

Computing WLP(S)(Q) ?

Current Summary

1. Programs as Predicate Transformers
2. Annotations
3. Contracts
   - Extending C programming language by contracts
4. Stop MOVEX6
   - Playing with variables
   - Ghost Variables

Writing a simple contract

variables x

requires $x0 >= 0 \wedge x0 <= 10;$

ensures $\begin{cases} x0\%2 = 0 \;\Rightarrow\; 2\cdot\backslash\text{result} = x0; \\ x0\%2 \neq 0 \;\Rightarrow\; 2\cdot\backslash\text{result} = x0-1; \\ x = x0 \end{cases}$

$\left[\begin{array}{l} \text{begin} \\ int\ y; \\ y = x/2; \\ return(y); \\ \text{end} \end{array}\right.$

- \result is the value returned by the command `return(y)`.
- `return(y)` is equivalent to \result:= `y`.

(Writing a simple contract.)

Listing 1 – project-divers/annotation.c

```
/*@ requires x >= 0 && x <= 10;
  @ assigns \nothing;
  @ ensures x % 2 == 0 ==> 2*\result == x;
 @ ensures x % 2 != 0 ==> 2*\result == x-1;
*/
int f(int x)
{
int y;
y = x/2 ;
return(y);
}
```

Writing a simple contract

(Writing a simple contract.)

Listing 2 – project-divers/annotationwp.c

```
/*@ requires 0 <= x  && x <=  10;
  @ assigns \nothing;
  @ ensures  x % 2 == 0 ==> 2*\result == x;
  @ ensures  x % 2 != 0 ==> 2*\result == x-1;
  @*/

int f(int x)
{
/*@ assert x % 2 == 0 ==> 2* (x / 2) == x; */
/*@ assert   x % 2 != 0 ==> 2* (x / 2) == x-1; */
  int y;
/*@ assert x % 2 == 0 ==> 2* (x / 2) == x; */
/*@ assert   x % 2 != 0 ==> 2* (x / 2) == x-1; */
  y  = x / 2;
/*@ assert x % 2 == 0 ==> 2*y == x; */
/*@ assert   x % 2 != 0 ==> 2*y == x-1; */
  return(y);
/*@ assert x % 2 == 0 ==> 2*y == x; */
/*@ assert   x % 2 != 0 ==> 2*y == x-1; */

  }
```

Property to check

$$x \geq 0 \wedge x \leq 10 \Rightarrow \begin{cases} x\%2 \neq 0 \;\Rightarrow\; 2\cdot(x/2) = x-1 \\ x\%2 = 0 \;\Rightarrow\; 2\cdot(x/2) = x \end{cases}$$

Writing a simple contract

(Checking the precondition.)

Listing 3 – project-divers/annotation0.c

```
/*@ requires x >= 0 && x <  0;
  @ assigns \nothing;
  @ ensures \result == 0;
  @*/
int annotation0(int x)
{
  int y;
  y  =  y / (x-x);
  return(y);
  }
```

Writing a simple contract

(Checking the precondition.)

Listing 4 – project-divers/annotation0wp.c

```
/*@ requires x >= 0 && x <  0;
  @ assigns \nothing;
  @ ensures \result == 0;
  @*/
int annotation(int x)
{
  /*@ assert y / (x-x) == 0; */
  int y;
  /*@ assert y / (x-x) == 0; */
  y  =  y / (x-x);
  /*@ assert y == 0; */
  return(y);
  /*@ assert y == 0; */
  }
```

Property to check

$x \geq 0 \wedge < 0 \Rightarrow y/(x-x) = 0$

Transformations of annotated programs (1)

$//@$ assert $P(v0, v)$:
$S1; S2$
$//@$ assert $Q(v0, v)$:

- Applying the property : $wp(S1; S2)(A) = wp(S1)(wp(S2)(A))$
-

$//@$ assert $P(v0, v)$:
$S1;$
$//@$ assert $wp(S2)(Q(v0, v))$:
$S2;$
$//@$ assert $Q(v0, v)$:

$//@$ assert $P(v0, v)$:
$//@$ assert $xp(S1)(wp(S2)(Q(v0, v)))$:
$S1;$
$//@$ assert $wp(S2)(Q(v0, v))$:
$S2;$
$//@$ assert $Q(v0, v)$:

Transformations of annotated programs (2)

//@ assert $P(v0, v)$:
IF B THEN
  $S1$
ELSE
  $S2$
FI
//@ assert $Q(v0, v)$:

- Applying the property : $wp(if(B, S1, S2)(A) = b \wedge wp(S1)(A) \vee \neg B \wedge wp(S2)(A)$.
-

//@ assert $P(v0, v)$:
IF B THEN
  $S1$
ELSE
  $S2$
FI
//@ assert $Q(v0, v)$:

//@ assert $P(v0, v)$:
IF B THEN
  $S1$
//@ assert $Q(v0, v)$:
ELSE
  $S2$
//@ assert $Q(v0, v)$:
FI
//@ assert $Q(v0, v)$:

Transformations of annotated programs (2)

$//@$ assert $P(v0, v)$:
IF B THEN
  $S1$
$//@$ assert $Q(v0, v)$:
ELSE
  $S2$
$//@$ assert $Q(v0, v)$:
FI
$//@$ assert $Q(v0, v)$:

Transformations of annotated programs (2)

$//@$ assert $P(v0, v)$:
IF B THEN
  $S1$
$//@$ assert $Q(v0, v)$:
ELSE
  $S2$
$//@$ assert $Q(v0, v)$:
FI
$//@$ assert $Q(v0, v)$:

$//@$ assert $P(v0, v)$:
IF B THEN
$//@$ assert $B \wedge wp(S2)(Q(v0, v))$:
  $S1$
$//@$ assert $Q(v0, v)$:
ELSE
$//@$ assert $\neg B \wedge wp(S2)(Q(v0, v))$:
  $S2$
$//@$ assert $Q(v0, v)$:
FI

Transformations of annotated programs (2)

//@ assert $P(v0, v)$:
IF B THEN
  $S1$
//@ assert $Q(v0, v)$:
ELSE
  $S2$
//@ assert $Q(v0, v)$:
FI
//@ assert $Q(v0, v)$:

//@ assert $P(v0, v)$:
IF B THEN
//@ assert $B \wedge wp(S2)(Q(v0, v))$:
  $S1$
//@ assert $Q(v0, v)$:
ELSE
//@ assert $\neg B \wedge wp(S2)(Q(v0, v))$:
  $S2$
//@ assert $Q(v0, v)$:
FI

//@ assert $P(v0, v)$:
IF B THEN
//@ assert $b \wedge wp(S1)(Q(v0, v))$:
  $S1$
//@ assert $Q(v0, v)$:
ELSE
//@ assert $\neg b \wedge wp(S2)(Q(v0, v))$:
  $S2$
//@ assert $Q(v0, v)$:
FI
//@ assert $Q(v0, v)$:

Transformations of annotated programs (2)

//@ assert $P(v0, v)$:
IF B THEN
  $S1$
//@ assert $Q(v0, v)$:
ELSE
  $S2$
//@ assert $Q(v0, v)$:
FI
//@ assert $Q(v0, v)$:

//@ assert $P(v0, v)$:
IF B THEN
//@ assert $B \wedge wp(S2)(Q(v0, v))$:
  $S1$
//@ assert $Q(v0, v)$:
ELSE
//@ assert $\neg B \wedge wp(S2)(Q(v0, v))$:
  $S2$
//@ assert $Q(v0, v)$:
FI

//@ assert $P(v0, v)$:
IF B THEN
//@ assert $b \wedge wp(S1)(Q(v0, v))$:
  $S1$
//@ assert $Q(v0, v)$:
ELSE
//@ assert $\neg b \wedge wp(S2)(Q(v0, v))$:
  $S2$
//@ assert $Q(v0, v)$:
FI
//@ assert $Q(v0, v)$:

- $b \wedge P(v0, v) \Rightarrow$
  $b \wedge wp(S1)(Q(v0, v))$
- $\neg b \wedge P(v0, v) \Rightarrow$
  $\neg b \wedge wp(S2)(Q(v0, v))$

Transformations of annotated programs (3)

$//@$ assert $P(v0, v)$:
$//@$ loop invariant $I(v0, v)$:
WHILE B THEN
  S
OD
$//@$ assert $Q(v0, v)$:

- Applying the iteration rule of Hoare Logic :

Transformations of annotated programs (3)

$//@$ assert $P(v0, v)$:
$//@$ loop invariant $I(v0, v)$:
WHILE B THEN
  S
OD
$//@$ assert $Q(v0, v)$:

- Applying the iteration rule of Hoare Logic :

$//@$ assert $P(v0, v)$:
$//@$ loop invariant $I(v0, v)$:
$//@$ assert $I(v0, v)$:
WHILE B THEN
$//@$ assert $b \wedge I(v0, v)$:
  S
$//@$ assert $I(v0, v)$:
OD
$//@$ assert $Q(v0, v)$:

Transformations of annotated programs (3)

//@ assert $P(v0, v)$:
//@ loop invariant $I(v0, v)$:
WHILE B THEN
  S
OD
//@ assert $Q(v0, v)$:

- Applying the iteration rule of Hoare Logic :

//@ assert $P(v0, v)$:
//@ loop invariant $I(v0, v)$:
//@ assert $I(v0, v)$:
WHILE B THEN
//@ assert $b \wedge I(v0, v)$:
  S
//@ assert $I(v0, v)$:
OD
//@ assert $Q(v0, v)$:

- $b \wedge I(v0, v) \Rightarrow wp(S)(I(v0, v))$
- $P(v0, v) \Rightarrow I(v0, v))$
- $\neg b \wedge I(v0, v) \Rightarrow Q(v0, v)$

Summary of transformations

- Checking the preservation of invariant.
- Applying the wps on assertions according to startements.

Assertions

- Assertions at a control point of the program

```
/*@  assert pred; */

//@  assert pred;
```

- Assertions at a control point of the program components.

```
/*@  for id1,id2, ..., idn: assert pred; */
```

Verification using WLP

(Incrementing a number)

Listing 5 – project-divers/compwp0.c

```
#define x0 5
/*@ assigns \nothing;*/
int exemple() {
  int x=x0;
  //@ assert x == x0;
  x = x + 1;
//@ assert x== x0+1;
return x;
}
```

(Incrementing a number)

Listing 6 – project-divers/compwp0wp.c

```
#define x0 5
/*@ assigns \nothing; */
int exemple() {
  //@ assert x0 == x0;
//@ assert x0+1 == x0+1;
  int x=x0;
  //@ assert x == x0;
//@ assert x+1 == x0+1;
  x = x + 1;
//@ assert x== x0+1;
return x;
}
```

Summary on annotations and assertions

- requires
- assigns
- ensures
- decreases
- predicate
- logic
- lemma

Current Summary

1. Programs as Predicate Transformers
2. Annotations
3. Contracts
   - Extending C programming language by contracts
4. Stop MOVEX6
   - Playing with variables
   - Ghost Variables

Current Subsection Summary

1. Programs as Predicate Transformers
2. Annotations
3. Contracts
   - Extending C programming language by contracts
4. Stop MOVEX6
   - Playing with variables
   - Ghost Variables

Programming by contract

- The calling function should garantee the required condition or precondition introduced by the clauses requires $P1 \wedge \ldots \wedge Pn$ at the calling point.
- The called function returns results that are ensured by the clause ensures $E1 \wedge \ldots \wedge Em$; ensures clause exporess a relatrionship between the initial values of variables and the final values.
- initial values of a variable v is denoted $\backslash old(v)$
- The variables which are not in the set $L1 \cup \ldots \cup Lp$ are not modified.

Listing 7 – contrat

```
/*@ requires P1;...;requires Pn;
  @ assigns L1;...;assigns Lm;
  @ ensures E1;...;ensures Ep;
  @*/
```

Examples of contract (1)

(Division)

Listing 8 – project-divers/annotation.c

```
/*@ requires x >= 0 && x <= 10;
  @ assigns \nothing;
  @ ensures x % 2 == 0 ==> 2*\result == x;
 @ ensures x % 2 != 0 ==> 2*\result == x-1;
*/
int f(int x)
{
int y;
y = x/2 ;
return(y);
}
```

Examples of contract (1)

(Division)

Listing 9 – project-divers/annotationwp.c

```
/*@ requires 0 <= x  && x <=  10;
  @ assigns \nothing;
  @ ensures  x % 2 == 0 ==> 2*\result == x;
  @ ensures  x % 2 != 0 ==> 2*\result == x-1;
  @*/

int f(int x)
{
/*@ assert x % 2 == 0 ==> 2* (x / 2) == x; */
/*@ assert   x % 2 != 0 ==> 2* (x / 2) == x-1; */
  int y;
/*@ assert x % 2 == 0 ==> 2* (x / 2) == x; */
/*@ assert   x % 2 != 0 ==> 2* (x / 2) == x-1; */
  y  = x / 2;
/*@ assert x % 2 == 0 ==> 2*y == x; */
/*@ assert   x % 2 != 0 ==> 2*y == x-1; */
  return(y);
/*@ assert x % 2 == 0 ==> 2*y == x; */
/*@ assert   x % 2 != 0 ==> 2*y == x-1; */

  }
```

Examples of contract (1)

Property to check
x is the value of the variable x when calling the function $x \geq 0 \wedge x < 10; \Rightarrow \left(\begin{array}{lcl} x \ \% \ 2 & = & 0 \Rightarrow 2 \cdot (x/2) = x \\ x \ \% \ 2 & \neq & 0 \Rightarrow 2 \cdot (x/2) = x - 1 \end{array} \right)$

Proof Obligations from Frama-c

```
  Goal Post-condition (file annotation.c, line 3) in 'annotation':
Let x_1 = x / 2.
Assume {
  Type: is_sint32(x) /\ is_sint32(x_1).
  (* Goal *)
  When: (x % 2) = 0.
  (* Pre-condition *)
  Have: (0 <= x) /\ (x <= 10).
}
Prove: (2 * x_1) = x.
Prover Alt-Ergo 2.6.0 returns Valid (Qed:0.71ms) (13ms) (29)


Goal Post-condition (file annotation.c, line 4) in 'annotation':
Let x_1 = x / 2.
Assume {
  Type: is_sint32(x) /\ is_sint32(x_1).
  (* Goal *)
  When: (x % 2) != 0.
  (* Pre-condition *)
  Have: (0 <= x) /\ (x <= 10).
}
Prove: (1 + (2 * x_1)) = x.
Prover Alt-Ergo 2.6.0 returns Valid (Qed:0.55ms) (14ms) (37)
}
```

Verification of a contract

A programme P *fulfils* a contract (pre,post) :

- P transforms a variable v à partir d'une valeur initiale v_0 and producing a final value v_f : $x_0 \xrightarrow{P} v_f$
- x_0 satisfait pre : pre(v_0) and v_f satisfait post : post(v_0, v_f)
- pre$(v_0) \wedge v_0 \xrightarrow{P} v_f \Rightarrow$ post(v_0, v_f)

requires $pre(in_0)$
ensures $post(in_0, out_f)$
variables in, out
$type1 \quad f(type2\ in_0)$
local variables x
  begin
    $S(f)$
  $return(out);$
  end

- $v = (in, out, x)$: in (input parameters), out (results), x (local variables)
- pre$(in_0) \wedge (in_0, out_0, v_0) \xrightarrow{P} (in_0, out_f, v_f) \Rightarrow$ post(in_0, out_f)
- pre$(in_0) \wedge in = in_0 \wedge out = out_0 \Rightarrow [S(f)](post(in_0, out))$

Verification Condition for Assignment

Listing 10 – an1.c

```
//@ assert l1: P(x);
  x = e(x);
//@ assert l2: Q(x);
```

Verification Condition for Assignment

Listing 11 – an1.c

```
//@ assert l1: P(x);
  x = e(x);
//@ assert l2: Q(x);
```

- $P(x) \Rightarrow WP(x := e(x))(Q(x))$

Verification Condition for Assignment

Listing 12 – an1.c

```
//@ assert l1: P(x);
  x = e(x);
//@ assert l2: Q(x);
```

- $P(x) \Rightarrow WP(x := e(x))(Q(x))$
- $P(x) \Rightarrow Q[x \mapsto e(x))]$

Verification Condition for Assignment

Listing 13 – an1.c

```
//@ assert l1: P(x);
  x = e(x);
//@ assert l2: Q(x);
```

- $P(x) \Rightarrow WP(x := e(x))(Q(x))$
- $P(x) \Rightarrow Q[x \mapsto e(x))]$
- $P(x1) \Rightarrow Q[x \mapsto e(x1))]$ (renaming of free occurences of x by x1)

Verification Condition for Assignment

Listing 14 – an1.c

```
//@ assert l1: P(x);
  x = e(x);
//@ assert l2: Q(x);
```

- $P(x) \Rightarrow WP(x := e(x))(Q(x))$
- $P(x) \Rightarrow Q[x \mapsto e(x))]$
- $P(x1) \Rightarrow Q[x \mapsto e(x1))]$ (renaming of free occurences of x by x1)
- $P(x1) \wedge x = e(x1) \Rightarrow Q(x)$

Verification Condition for Assignment

Listing 15 – an1.c

```
//@ assert l1: P(x);
  x = e(x);
//@ assert l2: Q(x);
```

- $P(x) \Rightarrow WP(x := e(x))(Q(x))$
- $P(x) \Rightarrow Q[x \mapsto e(x))]$
- $P(x1) \Rightarrow Q[x \mapsto e(x1))]$ (renaming of free occurences of x by x1)
- $P(x1) \wedge x = e(x1) \Rightarrow Q(x)$
- $P(x1) \wedge x = e(x1) \Rightarrow Q(x)$

Verification Condition for Assignment

Listing 16 – an1.c

```
//@ assert l1: P(x);
  x = e(x);
//@ assert l2: Q(x);
```

- $P(x) \Rightarrow WP(x := e(x))(Q(x))$
- $P(x) \Rightarrow Q[x \mapsto e(x))]$
- $P(x1) \Rightarrow Q[x \mapsto e(x1))]$ (renaming of free occurences of x by x1)
- $P(x1) \wedge x = e(x1) \Rightarrow Q(x)$
- $P(x1) \wedge x = e(x1) \Rightarrow Q(x)$
- $\vdash P(x1) \wedge x = e(x1) \Rightarrow Q(x)$

Verification Condition for Assignment

Listing 17 – an1.c

```
//@ assert l1: P(x);
  x = e(x);
//@ assert l2: Q(x);
```

- $P(x) \Rightarrow WP(x := e(x))(Q(x))$
- $P(x) \Rightarrow Q[x \mapsto e(x))]$
- $P(x1) \Rightarrow Q[x \mapsto e(x1))]$ (renaming of free occurences of x by x1)
- $P(x1) \wedge x = e(x1) \Rightarrow Q(x)$
- $P(x1) \wedge x = e(x1) \Rightarrow Q(x)$
- $\vdash P(x1) \wedge x = e(x1) \Rightarrow Q(x)$
- $P(x1) \wedge x = e(x1) \vdash Q(x)$

Verification Condition for Assignment

Listing 18 – an1.c

```
//@ assert l1: P(x);
  x = e(x);
//@ assert l2: Q(x);
```

- $P(x) \Rightarrow WP(x := e(x))(Q(x))$
- $P(x) \Rightarrow Q[x \mapsto e(x))]$
- $P(x1) \Rightarrow Q[x \mapsto e(x1))]$ (renaming of free occurences of x by x1)
- $P(x1) \wedge x = e(x1) \Rightarrow Q(x)$
- $P(x1) \wedge x = e(x1) \Rightarrow Q(x)$
- $\vdash P(x1) \wedge x = e(x1) \Rightarrow Q(x)$
- $P(x1) \wedge x = e(x1) \vdash Q(x)$

  Assume $\{$
  $P(x1)$
- $x = e(x1)$
  $\}$
  Prove:$Q(x)$
-

Verification conditions

Verification conditions

```
  Goal Assertion
  (file annotations14.c, line 5):
Assume {
  Type: is_sint32(x) /\ is_sint32(x_1).
  Have: x_1 = 1.
  Have: (1 + x_1) = x.
}
Prove: x = 2.
Prover Qed returns Valid
```

Verification conditions

```
  Goal Assertion
  (file annotations14.c, line 5):
Assume {
  Type: is_sint32(x) /\ is_sint32(x_1).
  Have: x_1 = 1.
  Have: (1 + x_1) = x.
}
Prove: x = 2.
Prover Qed returns Valid
```

```
void main(void){
  int x;
  x = 1;
  x = x + 1;
  /*@  assert x == 2; */
}
```

Verification conditions

```
  Goal Assertion
  (file annotations14.c, line 5):
Assume {
  Type: is_sint32(x) /\ is_sint32(x_1).
  Have: x_1 = 1.
  Have: (1 + x_1) = x.
}
Prove: x = 2.
Prover Qed returns Valid
```

```
void main(void){
  int x;
  x = 1;
  x = x + 1;
  /*@  assert x == 2; */

  }
```

```
        Goal Assertion
        (file annotations15.c, line 7):
  Assume {
    Type: is_sint32(x) /\ is_sint32(x_1)
         /\ is_sint32(x_2) /\ is_sint32(y).
    Have: x_2 = 1.
    Have: (1 + x_2) = x_1.
    Have: (2 * x_1) = y.
    Have: (x_1 + y) = x.
  }
  Prove: x = 6.
  Prover Qed returns Valid
```

Verification conditions

```
  Goal Assertion
  (file annotations14.c, line 5):
Assume {
  Type: is_sint32(x) /\ is_sint32(x_1).
  Have: x_1 = 1.
  Have: (1 + x_1) = x.
}
Prove: x = 2.
Prover Qed returns Valid
```

```
void main(void){
  int x;
  x = 1;
  x = x + 1;
  /*@  assert x == 2; */

  }
```

```
        Goal Assertion
        (file annotations15.c, line 7):
  Assume {
    Type: is_sint32(x) /\ is_sint32(x_1)
          /\ is_sint32(x_2) /\ is_sint32(y).
    Have: x_2 = 1.
    Have: (1 + x_2) = x_1.
    Have: (2 * x_1) = y.
    Have: (x_1 + y) = x.
  }
  Prove: x = 6.
  Prover Qed returns Valid
```

```
void main(void){
  int x,y;
  x = 1;
  x = x + 1;
  y = 2*x;
  x = x+y;
  /*@  assert x == 6; */

  }
```

Examples of contract (2)

(Precondition)

Listing 19 – project-divers/annotation0.c

```
/*@ requires x >= 0 && x <  0;
  @ assigns \nothing;
  @ ensures \result == 0;
  @*/
int annotation0(int x)
{
  int y;
  y  =  y / (x-x);
  return(y);
  }
```

Examples of contract (2)

(Precondition)

Listing 20 – project-divers/annotation0wp.c

```
/*@ requires x >= 0 && x <  0;
  @ assigns \nothing;
  @ ensures \result == 0;
  @*/
int annotation(int x)
{
  /*@ assert y / (x-x) == 0; */
  int y;
  /*@ assert y / (x-x) == 0; */
  y  =  y / (x-x);
  /*@ assert y == 0; */
  return(y);
  /*@ assert y == 0; */
  }
```

Examples of contract (2)

Property to check

$0 \leq x \wedge x \leq 10 \Rightarrow y/(x-x) = 0$

Definition of a contract (specification)

- Define the mathematical fucntion to compute (what to compute ?)
- Define an inductive method for computing the mathematical function and using axioms.

(facctorial what)

Listing 21 – project-factorial/factorial.h

```
#ifndef _A_H
#define _A_H
/*@ axiomatic mathfact {
  @ logic integer mathfact(integer n);
  @ axiom mathfact_1: mathfact(1) == 1;
  @ axiom mathfact_rec: \forall integer n; n > 1
  ==> mathfact(n) == n * mathfact(n-1);
  @ } */

/*@ requires n > 0;
  decreases n;
  ensures \result == mathfact(n);
  assigns \nothing;
*/
int codefact(int n);
#endif
```

Definition of a contract (programming)

- Define the program codefact for computing mathfact (How to compute ?)
- Define the algorithm computing the function mathfact

(facctorial how)

Listing 22 – project-factorial/factorial.c

```
#include "factorial.h"

int codefact(int n) {
  int y = 1;
  int x = n;
  /*@ loop invariant x >= 1 && x <= n && mathfact(n) == y * mathfact(x);
    loop assigns x, y;
    loop variant x;
   */
  while (x != 1) {
    y = y * x;
    x = x - 1;
  };
  return y;

}
```

Definition of a contract (approach)

- The specification of a function (mathfact) to compute requires to define it mathematically.
- The definition is stated in an axtiomatic framework and is preferably inductive (mathfact) which is used in assrtions or theorems or lemmas.
- The relationship between the ciomputed value (\result) and the mathematical value (mathfact(n)) is stated in the ensures clause :

$$\backslash\text{result} == \text{mathfact}(n)$$

- The main property to prove is codefact(n)==mathfact(n) : Calling codefact for n returns a value equal to mathfact(n).

Tryptic Pattern



Contracts with named behaviours

Listing 23 – contrat

```
/*@ requires P;
@ behavior b1:
  @ assumes A1;
  @ requires R1 ;
  @ assigns L1;
  @ ensures E1;
@ behavior b2:
  @ assumes A2;
  @ requires R2;
  @ assigns L2;
  @ ensures E2;
@*/
```

Division should not return silly expressions !

(Pairs of integers)

Listing 24 – project-divers/structures.h

```
#ifndef _STRUCTURE_H


struct s {
    int q;
    int r;
};

#endif
```

Division should not return silly expressions !

(Specification)

Listing 25 – project-divers/division.h

```
#ifndef _A_H
#define _A_H
#include "structures.h"
/*@ requires a >= 0 && b >= 0;
 @ requires b != 0;
  @ ensures 0 <= \result.r;
  @ ensures \result.r < b;
  @ ensures  a ==  b * \result.q + \result.r;
*/
struct s  division(int a, int b);
#endif
```

Division should not return silly expressions !

(Algorithm)

Listing 26 – project-divers/division.c

```
#include <stdio.h>
#include <stdlib.h>
#include "division.h"

struct s  division(int a, int b)
{  int rr = a;
   int qq = 0;
   struct s  silly = {-1,-1};
   struct s resu;
   if (b == 0) {
     return silly;
   }
   else
     {
  /*@
    loop invariant
    ( a ==  b*qq + rr) &&
    rr >= 0;
    loop assigns rr,qq;
    loop variant rr;
   */
   while (rr >= b) { rr = rr - b; qq=qq+1;};
   resu.q= qq;
   resu.r = rr;
  return resu;
}
}
```

Iteration Rule for PC

If $\{P \wedge B\}\mathbf{S}\{P\}$, then $\{P\}$**while B do S od**$\{P \wedge \neg B\}$.

- Prove $\{P \wedge B\}\mathbf{S}\{P\}$ or $P \wedge B \Rightarrow \{\mathbf{S}\}(P)$.
- By the iteration rule, we conclude that $\{P\}$**while B do S od**$\{P \wedge \neg B\}$ without using WLP.
- Introduction of LOOP INVARIANTS in the notation.

Listing 27 – loop.c

```
/*@ loop invariant I1;
    loop invariant I2;
    ...
    loop invariant In;
    loop assigns X;
    loop variant E;
  */
```

(Invariant de boucle)

Listing 28 – project-divers/anno6.c

```
/*@ requires a >= 0 && b >= 0;
  ensures 0 <= \result;
  ensures \result < b;
  ensures \exists integer k; a == k * b + \result;
*/
int rem(int a, int b) {
  int r = a;
  /*@
    loop invariant
    (\exists integer i; a == i * b + r) &&
    r >= 0;
    loop assigns r;
   */
  while (r >= b) { r = r - b;};
  return r;
}
```

Current Subsection Summary

1. Programs as Predicate Transformers
2. Annotations
3. Contracts
   - Extending C programming language by contracts
4. Stop MOVEX6
   - Playing with variables
   - Ghost Variables

Initial value of x $\backslash old(x)$

- $\backslash old(x)$ is the value of the variable when the function is called.
- It can be used in the postcondition of the *ensures* clause.

(Modifying variables while calling)

Listing 29 – project-divers/old1.c

```
/*@ requires \valid(a) && \valid(b);
   @ assigns *a,*b;
    @ ensures    *a == \at(*a,Pre) +2;
    @ ensures  *b == \at(*b,Pre)+\at(*a,Pre)+2;

        @ ensures  \result == 0;
*/
int old(int *a, int *b) {
  int x,y;
  x = *a;
  y = *b;
  x=x+2;
   y = y +x;

  *a = x;
  *b = y;
  return 0 ;
}
```

Expression $\backslash at(e, id)$

- $\backslash at(e, id)$ is the value of e at the control point id.
- id should occur before $\backslash at(e, id)$
- id is one of the possible expressions : Pre, Here, Old, Post, LoopEntry, LoopCurrent, Init
- $\backslash old(e)$ is equivalent to $\backslash at(e, Old)$

Exemple pour $\backslash at(e, id)$

(label Pre)

Listing 30 – project-divers/at1.c

```
/*@
  requires \valid(a) && \valid(b);
  assigns *a,*b;
  ensures  *a == \old(*a)+2;
  ensures  *b == \old(*b)+\old(*a)+2;
*/
int at1(int *a, int *b) {
//@ assert *a == \at(*a,Pre);
  *a = *a +1;
//@ assert *a == \at(*a,Pre)+1;
  *a = *a +1;
//@ assert *a == \at(*a,Pre)+2;
  *b = *b +*a;
//@ assert *a == \at(*a,Pre)+2 && *b == \at(*b,Pre)+\at(*a,Pre)+2;
  return 0;
}
```

–

Example for $\backslash at(e, id)$

(autre label)

Listing 31 – project-divers/at2.c

```
void f (int n) {
for (int i = 0; i < n; i++) {
/*@ assert \at(i,LoopEntry) == 0; */
int j=0;
while (j++ < i) {
/*@ assert \at(j,LoopEntry) == 0; */
/*@ assert \at(j,LoopCurrent) + 1 == j; */
} }
}
```

Example for $\backslash at(e, id)$

(otherlabel)

Listing 32 – project-divers/change1.c

```
/*@ requires \valid(a) && *a >= 0;
  @ assigns *a;
  @ ensures   *a == \old(*a)+2 && \result == 0;
*/
int  change1(int *a)
{  int x = *a;
   x = x + 2;
   *a = x;
   return 0;
}
```

Current Subsection Summary

1. Programs as Predicate Transformers
2. Annotations
3. Contracts
   - Extending C programming language by contracts
4. Stop MOVEX6
   - Playing with variables
   - Ghost Variables

Labels in ACSL

In **Frama-C** and the **ACSL** language, the expression :

```
\at(e, L)
```

evaluates an expression `e` in the memory state corresponding to a label `L`.

Main labels

- `Pre` : state at the beginning of the function
- `Post` : state at the end of the function
- `Here` : current state
- `Old` : initial value (often in `ensures`)
- `LoopEntry` : state before the loop
- `LoopCurrent` : start of the current iteration
- `Init` : initial state of the programme

Example with Old

```
void swap(int *a, int *b){

  int tmp;

  /*@
    requires a != \null && b != \null;
    assigns *a, *b;
    ensures *a == \at(*b,Old);
    ensures *b == \at(*a,Old);
  */

  tmp = *a;
  *a = *b;
  *b = tmp;
}
```

Why use \at

In proofs with the **WP** plugin, we must compare :

- the state **before** execution
- the state **after** execution

Example :

$$\cdot a_{final} = b_{initial}$$

We therefore write :

```
*a == \at(*b,Pre)
```

This allows the prover to reason about the **initial values of the programme**.

Example

Listing 33 – contrat

```
/*@ requires x >= 0;
@ ensures \result == \old(x) ;
@*/
int f(int x)
{
  int y;
  y=x;
  x=x+1;
  return(y);
 }
```

Example

Listing 34 – contrat

```
/*@ requires x >= 0;
@ ensures \result == \old(x) && \old(x) == x;
@*/
int f(int x)
{int y;
  y=x;
  x=x+1;
  /*@ assert x == \at(x,Pre)+1; */
  return(y);
}
```

Example

Listing 35 – contrat

```
/*@ requires x >= 0;
@ assigns \nothing;
@ ensures \result == \old(x);
@*/
int f(int x)
{int y;
  y=x;
  x=x+1;
  return(y);
}
```

Current Subsection Summary

1. Programs as Predicate Transformers
2. Annotations
3. Contracts
   - Extending C programming language by contracts
4. Stop MOVEX6
   - Playing with variables
   - Ghost Variables

Ghost variable

- A variable called *ghost* allows to model a computed value useful for stating a model property : the ghost variable is hidden for the computer but not for the model.
- It should not change the semantics of others variables and should not change the effective variables.

Wrong use of ghost variable

(Bug)

Listing 36 – project-divers/ghost2.c

```
int f (int x, int y) {
  //@ghost int z=x+y;
switch (x) {
case 0: return y;
//@ ghost case 1: z=y;
// above statement is correct.
//@ ghost case 2: { z++; break; }
// invalid, would bypass the non-ghost default
default: y++; }
return y; }

int g(int x) { //@ ghost int z=x;
if (x>0){return x;}
//@ ghost else { z++; return x; }
// invalid, would bypass the non-ghost return
return x+1; }
```

(Ghost variable)

Listing 37 – project-divers/ghost1.c

```
/*@ requires a >= 0 && b >= 0;
  ensures 0 <= \result;
  ensures \result < b;
  ensures \exists integer k; a == k * b + \result; */
int rem(int a, int b) {
  int r = a;
 /*@ ghost   int q=0;    */
  /*@
    loop invariant
    a == q * b + r &&
    r >= 0 &&  r <= a;
    loop assigns r;
    loop assigns q;
// loop variant r;
*/
  while (r >= b) {
    r = r - b;
/*@ ghost     q = q+1;    */
  };
  return r;
}
```