# Modelling Software-based Systems

## The Modelling Language Event-B

Telecom Nancy

Dominique Méry
Telecom Nancy,Université de Lorraine

21 avril 2026

dominique.mery@loria.fr

# General Summary


1. Documentation
2. Introduction by Problems
   - Safety Properties of C Programs
   - Importance of Domain
   - Tracking bugs in C codes
3. Modelling Language
4. A Simple Example : Management of Students and Teachers
5. Modelling state-based systems
6. The Event B modelling language
7. Examples of Event B models
8. Summary on Events

# Current Summary


1. Documentation
2. Introduction by Problems
3. Modelling Language
4. A Simple Example : Management of Students and Teachers
5. Modelling state-based systems
6. The Event B modelling language
7. Examples of Event B models
8. Summary on Events

# Tools

- Event B : http ://www.event-b.org/
- Atelier B : http ://www.atelierb.eu/
- RODIN Platform : http ://www.event-b.org/platform.html
- EB2ALL Toolset : http ://eb2all.loria.fr
- RIMEL project : http ://rimel.loria.fr
- The Modelling Language Event-B and related topics as lectures notes, tutorials, models. https ://mery54.github.io/teaching/mosos/
- The Modelling Language Event-B and related topics as lectures notes, tutorials, models. https ://mery54.github.io/teaching/mosos/

# Current Summary


1. Documentation
2. Introduction by Problems
3. Modelling Language
4. A Simple Example : Management of Students and Teachers
5. Modelling state-based systems
6. The Event B modelling language
7. Examples of Event B models
8. Summary on Events

# RTE

```c
#include <stdio.h>
#include <stdlib.h>
#include <time.h>

int main() {
    int x, y;
    // Seed the random number generator with the current time
    srand(time(NULL));
    // Generate a random number between 1 and 100
    x = rand() % 100 + 1;
    // Perform some calculations
    y = x / (100 - x);
    printf("Result:-%d\n", y);
    return 0;
}
```

# RTE with frama-c

```
[kernel] Parsing bug0.c (with preprocessing)
[rte:annot] annotating function main
[wp] Running WP plugin...
[kernel:annot:missing-spec] FRAMAC_SHARE/libc/stdlib.h:299: Warnin
  Neither code nor explicit exits and terminates for function rand
   generating default clauses. See -generated-spec-* options for m
[kernel:annot:missing-spec] FRAMAC_SHARE/libc/stdlib.h:302: Warnin
  Neither code nor explicit exits and terminates for function sran
   generating default clauses. See -generated-spec-* options for m
[kernel:annot:missing-spec] FRAMAC_SHARE/libc/time.h:126: Warning:
  Neither code nor explicit exits and terminates for function time
   generating default clauses. See -generated-spec-* options for m
[kernel:annot:missing-spec] FRAMAC_SHARE/libc/stdio.h:211: Warning
  Neither code nor explicit exits and terminates for function prin
   generating default clauses. See -generated-spec-* options for m
[wp] 8 goals scheduled
[wp] [Timeout] typed_main_call_printf_va_1_requires (Alt-Ergo)
[wp] [Timeout] typed_main_assert_rte_division_by_zero (Alt-Ergo)
[wp] Proved goals:    6 / 8
  Qed:                 3
  Alt-Ergo 2.6.0:      3 (17ms-20ms-27ms)
  Timeout:             2
```

---

```
  Function main
```

# RTE with frama-c

```c
// Heisenbug
#include <stdio.h>
#include <stdlib.h>
#include <time.h>
//
int main() {
  int x, y, i=0;
    for (i = 0; i <= 1000000; i++) {
    // Seed the random number generator with the current time
    srand(time(NULL));
    // Generate a random number between 1 and 100
    x = rand() % 100 + 1;
        printf("Result: x= %d\n",x);
    // Perform some calculations
    y = x / (100 - x);
    printf("Result: i=%d  and y=%d\n",i, y);
    }
    return 0;
}
```

# RTE with frama-c but a modification

```c
// Heisenbug
#include <stdio.h>
#include <stdlib.h>
#include <time.h>
#include <limits.h>



int main() {
  int x, y, i=0;

    for (i = 0; i <= INT_MAX; i++) {
    // Seed the random number generator with the current time
    srand(time(NULL)+i);

    // Generate a random number between 1 and 100
     x = rand() % 100 + 1;

        printf("Result: x=--%d\n",x);
    // Perform some calculations
    y = x / (100 - x);

    printf("Result: i=%d--%d\n",i, y);
    }
```

# Implicit and explicit in formal modelling

**Our aim is to analyze what is implicit and what is explicit in formal modelling...**

- **Semantics in modelling** :
  - Semantics expressed by a *theory* (e.g. Event-B) used to formalize hardware and/or software systems
  - Same theory is used for wide variety of heterogeneous systems
- **Semantics in domain** :
  - Environment within which system evolve : application domain/context
  - Information provided by domain is often associated while in operation
  - Either assumed and omitted while formalising systems or hardcoded in formal models
  - Same context is used for wide variety of heterogeneous systems



**A case study for studying these properties**

# Nose Gear Velocity

- Estimated ground velocity of the aircraft should be available only if it is within 3 `km/hr` of the true velocity at some moment within past 3 seconds

# Characterization of a System (I)

- NG velocity system :
  - **Hardware** :
    - *Electro-mechanical sensor* : detects rotations
    - *Two 16-bit counters* : Rotation counter, Milliseconds counter
    - *Interrupt service routine* : updates rotation counter and stores current time.
  - **Software** :
    - *Real-time operating system* : invokes update function every `500 ms`
    - *16-bit global variable* : for recording rotation counter update time
    - *An update function* : estimates ground velocity of the aircraft.
- Input data available to the system :
  - *time* : in `milliseconds`
  - *distance* : in `inches`
  - *rotation angle* : in `degrees`
- Specified system performs velocity estimations in *imperial* unit system
- Note : expressed functional requirement is in *SI* unit system (km/hr).

# Characterization of a System (II) cont.

What are the main properties to consider for formalization ?

- Two different types of data :
  - counters with modulo semantics
  - non-negative values for time, distance, and velocity
- Two dimensions : *distance* and *time*
- Many units : distance (`inches`, `kilometers`, `miles`), time (`milliseconds`, `hours`), velocity (`kph`, `mph`)
- And interaction among components

How should we model ?

- Designer needs to consider units and conversions between them to manipulate the model
- One approach : Model units as *sets*, and conversions as constructed types – *projections*.
- Example :

1. $estimateVelocity \in \texttt{MILES} \times \texttt{HOURS} \rightarrow \texttt{MPH}$
2. $mphTokph \in \texttt{MPH} \rightarrowtail\!\!\!\!\twoheadrightarrow \texttt{KPH}$

# Sample Velocity Estimation




NGClickTime = 4123 millisecs
NGRotations = 8954

NGClickTime = 4367milli
NGRotations = 8955

WHEEL_DIAMETER = 22 inches
PI = 3.14

12 inches/foot
5280 feet/mile

estimatedGroundVelocity = distance travel/elapsed time
= ((3.14 * 22)/(12*5280))/((4367-4123)/(1000*3600
= 16 mph

# bug0.c

Listing 1 – Bug bug0

```c
#include <stdio.h>
#include <stdlib.h>
#include <time.h>

int main() {
    int x, y;
    // Seed the random number generator with the current time
    srand(time(NULL));
    // Generate a random number between 1 and 100
    x = rand() % 100 + 1;
    // Perform some calculations
    y = x / (100 - x);
    printf("Result: %d\n", y);
    return 0;
}
```

# bug00.c

Listing 2 – Bug bug00

```c
// Heisenbug
#include <stdio.h>
#include <stdlib.h>
#include <time.h>
//
int main() {
  int x, y,i=0;
    for (i = 0; i <= 1000000; i++) {
    // Seed the random number generator with the current time
    srand(time(NULL));
    // Generate a random number between 1 and 100
    x = rand() % 100 + 1;
        printf("Result: x=--%d\n",x);
    // Perform some calculations
    y = x / (100 - x);
    printf("Result: i=%d--and y=%d\n",i, y);
    }
    return 0;
}
```

Listing 3 – Bug bug000

```
// Heisenbug
#include <stdio.h>
#include <stdlib.h>
#include <time.h>
#include <limits.h>



int main() {
  int x, y,i=0;

    for (i = 0; i <= INT_MAX; i++) {
    // Seed the random number generator with the current time
    srand(time(NULL)+i);

    // Generate a random number between 1 and 100
     x = rand() % 100 + 1;

        printf("Result: x= %d\n",x);
    // Perform some calculations
    y = x / (100 - x);

    printf("Result: i=%d - %d\n",i, y);
    }

    return 0;
}
```

# Current Summary


1. Documentation
2. Introduction by Problems
3. Modelling Language
4. A Simple Example : Management of Students and Teachers
5. Modelling state-based systems
6. The Event B modelling language
7. Examples of Event B models
8. Summary on Events

# Observing the safe system




- The context defines the possible values
- Safety requirement means that *something bad will never happen*.
- Invariant defines the set of effective possible values
- Transitions modify state variables and maintains the invariant.

# Observing the unsafe system




- Transitions modify state variables and may not maintain the invariant.
- ... and may not guaranteesafety properties.

# Tools

- Event B : http ://www.event-b.org/
- Atelier B : http ://www.atelierb.eu/
- RODIN Platform : http://www.event-b.org/platform.html

# The Event B Method

- The Event B Method is invented by J.-R. Abrial from 1988 : abstract system, events, refinement, invariant.
- Atelier B and RODIN are supporting the Event B method
- An event is observed and triggered, when a guard is true
- Proof obligations are generated using the weakest-precondition semantics.
- A Event B model intends to model a reactive system.

# Current Summary


1. Documentation
2. Introduction by Problems
3. Modelling Language
4. A Simple Example : Management of Students and Teachers
5. Modelling state-based systems
6. The Event B modelling language
7. Examples of Event B models
8. Summary on Events

# A Simple Example

**Managing teachers, students, lectures and class rooms**

- Modelling the access control of students for lectures given by teachers
- When a student is attending a lecture, he/she can not attend another lecture
- When a teacher is lecturing, he/she is not lecturing another session.
- A student can not be lecturing without a teacher and when he is not attending a lecture, he is outside the classroom.
- When a teacher is ending a lecture, every student which is attending, is leaving the class room.
- When a student is not attending a lecture, he is free.

# First step : identification of sets, constants, properties

- Sets : students, teachers
- **Property 1 :** When a student is attending a lecture, he/she can not attend another lecture
- **Property 2 :** When a teacher is lecturing, he/she is not lecturing another session.
- **Property 3 :**A student can not be lecturing without a teacher and when he is not attending a lecture, he is outside the classroom.
- **Property 4 :** When a teacher is ending a lecture, every student which is attending, is leaving the class room.
- **Property 5 :** When a student is not attending a lecture, he is free.

# Second step : definition of state variables

- **The system model should be able to record the lecturing teachers and the attending students.**
- **The system model should be enough expressive to state when a given student is attending a lecture given by whom.**
- **Variable attending records students which atteding some lecture with a given teacher.**
- **Variable islecturing records teachers who are lecturing.**
- **Variable pause records sudents are not attending a lecture but are somewhere not in a lecture.**

# Third step : properties of state variables

**Expression of the invariant**

$$
\begin{array}{l}
inv1 : attending \in STUDENTS \nrightarrow TEACHERS \\
inv2 : islecturing \subseteq TEACHERS \\
inv3 : \forall e \cdot e \in STUDENTS \wedge e \in dom(attending) \\
\qquad\qquad\qquad \Rightarrow \quad attending(e) \in islecturing \\
inv4 : pause \subseteq STUDENTS \\
inv5 : pause \cap dom(attending) = \varnothing \\
inv6 : pause \cup dom(attending) = STUDENTS
\end{array}
$$

Checking proof obligations !

# Fourth step : Updating state variables

**UseCases**

- **EVENT** INITIALISATION : initializing state variables
- **EVENT** startingattending : a group of students is moving from *pause* to *lecture*
- **EVENT** teachergivinglecture : a teacher is starting a new lecture
- **EVENT** teacherendinglecture : a teacher is halting the lecture
- **EVENT** studentleavinglecture : a group of students is moving from *lecture* to *pause*

# Fourth step : Updating state variables

**EVENT** INITIALISATION
**BEGIN**
$act1 : \ attending := \varnothing$
$act2 : \ islecturing := \varnothing$
$act3 : \ pause := STUDENTS$
**END**

# Fourth step : Updating state variables

**EVENT** startingattending
**ANY**
$e$ e is a student
$p$ p is a teacher
**WHERE**
$grd1: \ e \in STUDENTS$
$grd3: \ p \in TEACHERS$
$grd4: \ p \in islecturing$
$grd2: \ e \notin dom(attending)$
**THEN**
$act1: \ attending(e) := p$
$act2: \ pause := pause \setminus \{e\}$
**END**

# Fourth step : Updating state variables

**EVENT** teachergivinglecture
  **ANY**
    $p$
  **WHERE**
    $grd2: \ p \in TEACHERS$
    $grd1: \ p \notin islecturing$
  **THEN**
    $act1 \ islecturing := islecturing \cup \{p\}$
**END**

# Fourth step : Updating state variables

**EVENT** teacherendinglecture
**ANY**
$p$
**WHERE**
$grd1 : p \in TEACHERS$
$grd2 : p \in islecturing$
**THEN**
$act1 : islecturing := islecturing \setminus \{p\}$

$$act3 : \ attending := attending \setminus \{f \mapsto q | \begin{pmatrix} f \in STUDENTS \\ \wedge q \in TEACHERS \\ \wedge f \mapsto q \in attending \\ \wedge q = p \end{pmatrix}\}$$

$act2 : pause := pause \cup \{f | f \in STUDENTS \wedge f \in attending^{-1}[\{p\}]\}$
**END**

# Fourth step : Updating state variables

**EVENT** studentleavinglecture
  **ANY**
    $ge$
  **WHERE**
    $grd1 : ge \subseteq dom(attending)$
    $grd2 : ge \neq \varnothing$
  **THEN**
    $act1 : attending := ge \lhd attending$
    $act2 : pause := pause \cup ge$
  **END**

# Mathematical tools for modelling systems

- **set theory : sets, relations, functions . . .**
- **transition systems**
- **predicate calculus**
- **decision procedures**
- **interactive theorem prover**

# Current Summary


1. Documentation
2. Introduction by Problems
3. Modelling Language
4. A Simple Example : Management of Students and Teachers
5. Modelling state-based systems
6. The Event B modelling language
7. Examples of Event B models
8. Summary on Events

# Modelling systems

- A **system** is **observed**
- Observation of things which are
  - either changing over the **time** (*variable*)
  - or stuttering over the **time** (*constant*)
- A system is characterized by a **state**
- A state is made up of contextual **constant informations** over the problem theory and of **modifiable flexible informations** over the system.

# Changing state of system

A **flexible variable** $x$ is observed at different instants :

$x_0 \xrightarrow{\tau} x_1 \xrightarrow{\tau} x_2 \xrightarrow{\tau} x_3 \xrightarrow{\tau} \ldots \xrightarrow{\tau} x_i \xrightarrow{\tau} x_{i+1} \xrightarrow{\tau} \ldots$

**$\tau$ hides effectives changes of state or actions or events**

$x_0 \xrightarrow{\alpha_1} x_1 \xrightarrow{\alpha_2} x_2 \xrightarrow{\alpha_3} x_3 \xrightarrow{\alpha_4} \ldots \xrightarrow{\alpha_i} x_i \xrightarrow{\alpha_{i+1}} x_{i+1} \xrightarrow{\alpha_{i+2}} \ldots$

**Occurences of e $\tau$ can be added between two instants ie stuttering steps :**

$x_0 \xrightarrow{\alpha_1} x_1 \xrightarrow{\alpha_2} x_2 \xrightarrow{\tau} x_2 \xrightarrow{\alpha_3} x_3 \xrightarrow{\alpha_4} \ldots \xrightarrow{\alpha_i} x_i \xrightarrow{\tau} x_i \xrightarrow{\alpha_{i+1}} x_{i+1} \xrightarrow{\alpha_{i+2}} \ldots$

# Changing state of system

A **flexible variable** $x$ is observed at different instants :
$x_0 \xrightarrow{\tau} x_1 \xrightarrow{\tau} x_2 \xrightarrow{\tau} x_3 \xrightarrow{\tau} \ldots \xrightarrow{\tau} x_i \xrightarrow{\tau} x_{i+1} \xrightarrow{\tau} \ldots$
$\tau$ hides effectives changes of state or actions or events
$x_0 \xrightarrow{\alpha_1} x_1 \xrightarrow{\alpha_2} x_2 \xrightarrow{\alpha_3} x_3 \xrightarrow{\alpha_4} \ldots \xrightarrow{\alpha_i} x_i \xrightarrow{\alpha_{i+1}} x_{i+1} \xrightarrow{\alpha_{i+2}} \ldots$
**Occurences of e $\tau$ can be added between two instants ie stuttering steps :**
$x_0 \xrightarrow{\alpha_1} x_1 \xrightarrow{\alpha_2} x_2 \xrightarrow{\tau} x_2 \xrightarrow{\alpha_3} x_3 \xrightarrow{\alpha_4} \ldots \xrightarrow{\alpha_i} x_i \xrightarrow{\tau} x_i \xrightarrow{\alpha_{i+1}} x_{i+1} \xrightarrow{\alpha_{i+2}} \ldots$

# Changing state of system

A **flexible variable** $x$ is observed at different instants :

$x_0 \xrightarrow{\tau} x_1 \xrightarrow{\tau} x_2 \xrightarrow{\tau} x_3 \xrightarrow{\tau} \ldots \xrightarrow{\tau} x_i \xrightarrow{\tau} x_{i+1} \xrightarrow{\tau} \ldots$

$\tau$ hides effectives changes of state or actions or events

$x_0 \xrightarrow{\alpha_1} x_1 \xrightarrow{\alpha_2} x_2 \xrightarrow{\alpha_3} x_3 \xrightarrow{\alpha_4} \ldots \xrightarrow{\alpha_i} x_i \xrightarrow{\alpha_{i+1}} x_{i+1} \xrightarrow{\alpha_{i+2}} \ldots$

**Occurences of e $\tau$ can be added between two instants ie stuttering steps :**

$x_0 \xrightarrow{\alpha_1} x_1 \xrightarrow{\alpha_2} x_2 \xrightarrow{\tau} x_2 \xrightarrow{\alpha_3} x_3 \xrightarrow{\alpha_4} \ldots \xrightarrow{\alpha_i} x_i \xrightarrow{\tau} x_i \xrightarrow{\alpha_{i+1}} x_{i+1} \xrightarrow{\alpha_{i+2}} \ldots$

# Changing state of system

A **flexible variable** $x$ is observed at different instants :

$x_0 \xrightarrow{\tau} x_1 \xrightarrow{\tau} x_2 \xrightarrow{\tau} x_3 \xrightarrow{\tau} \ldots \xrightarrow{\tau} x_i \xrightarrow{\tau} x_{i+1} \xrightarrow{\tau} \ldots$

$\tau$ hides effectives changes of state or actions or events

$x_0 \xrightarrow{\alpha_1} x_1 \xrightarrow{\alpha_2} x_2 \xrightarrow{\alpha_3} x_3 \xrightarrow{\alpha_4} \ldots \xrightarrow{\alpha_i} x_i \xrightarrow{\alpha_{i+1}} x_{i+1} \xrightarrow{\alpha_{i+2}} \ldots$

Occurences of e $\tau$ can be added between two instants ie **stuttering steps** :

$x_0 \xrightarrow{\alpha_1} x_1 \xrightarrow{\alpha_2} x_2 \xrightarrow{\tau} x_2 \xrightarrow{\alpha_3} x_3 \xrightarrow{\alpha_4} \ldots \xrightarrow{\alpha_i} x_i \xrightarrow{\tau} x_i \xrightarrow{\alpha_{i+1}} x_{i+1} \xrightarrow{\alpha_{i+2}} \ldots$

# Changing state of system

A **flexible variable** $x$ is observed at different instants :
$x_0 \xrightarrow{\tau} x_1 \xrightarrow{\tau} x_2 \xrightarrow{\tau} x_3 \xrightarrow{\tau} \ldots \xrightarrow{\tau} x_i \xrightarrow{\tau} x_{i+1} \xrightarrow{\tau} \ldots$
$\tau$ hides effectives changes of state or actions or events
$x_0 \xrightarrow{\alpha_1} x_1 \xrightarrow{\alpha_2} x_2 \xrightarrow{\alpha_3} x_3 \xrightarrow{\alpha_4} \ldots \xrightarrow{\alpha_i} x_i \xrightarrow{\alpha_{i+1}} x_{i+1} \xrightarrow{\alpha_{i+2}} \ldots$
Occurences of e $\tau$ can be added between two instants ie **stuttering steps** :
$x_0 \xrightarrow{\alpha_1} x_1 \xrightarrow{\alpha_2} x_2 \xrightarrow{\tau} x_2 \xrightarrow{\alpha_3} x_3 \xrightarrow{\alpha_4} \ldots \xrightarrow{\alpha_i} x_i \xrightarrow{\tau} x_i \xrightarrow{\alpha_{i+1}} x_{i+1} \xrightarrow{\alpha_{i+2}} \ldots$

# Properties of system

A **safety** property S over x states that something will not happen : S(x) means that S holds for x

An **invariant** property I over x states a strong safety property

$x_0 \xrightarrow{\alpha_1} x_1 \xrightarrow{\alpha_2} x_2 \xrightarrow{\tau} x_2 \xrightarrow{\alpha_3} x_3 \xrightarrow{\alpha_4} \ldots \xrightarrow{\alpha_i} x_i \xrightarrow{\tau} x_i \xrightarrow{\alpha_{i+1}} x_{i+1} \xrightarrow{\alpha_{i+2}} \ldots$

$(S(x_0) \xrightarrow{\alpha_1} S(x_1) \xrightarrow{\alpha_2} S(x_2) \xrightarrow{\tau} S(x_2) \xrightarrow{\alpha_3} S(x_3) \xrightarrow{\alpha_4} \ldots \xrightarrow{\alpha_i} S(x_i) \xrightarrow{\tau} S(x_i) \xrightarrow{\alpha_{i+1}} S(x_{i+1}) \xrightarrow{\alpha_{i+2}} \ldots$

or equivalently $\forall i \in \mathbb{N} : S(x_i)$

# Checking the relation

- You can check for every $i$ in $\mathbb{N}$ that $S(x_i)$ is true but it can be long if states are different
- You can compute an abstraction of the set of states
- You can try to prove and for instance the induction principle may be usefull
- So be carefull and improve your modelling before to run the checker
- Use the induction

# State properties of a system

- A state property namely $P(x)$ is a first order predicate with free variables $x$, where $x$ is a flexible variable.
- A flexible variable $x$ has a current value $x$, a next value $x'$, an initial value $x_0$ and possibly a final value $x_f$.
- A predicate $P(x)$ is considered as a set of values $v$ such that $P(v)$ holds : set-theoretical interpretation

# State Properties

## Safety Property

A safety property states that nothing bad can happen.

## Example

Safety Properties

- Partial correctness  a component is correct wit respect to a precondition and a postcondition.
- No Run Time Error any software action or event does not produce a run-time error as overflow, division by zero ...
- Mutual exclusion  a set of processes share common ressources, a printer is shared by users, ...
- Deadlock freedom the system is never blocked, there is always at least one next state, ...

# Relation/action over states

- An action $\alpha$ over states is a relation between values of state variables **before** and values of variables **after**

$$\alpha(x, x') \text{ or } x \xrightarrow{\alpha} x'$$

- Flexible variable $x$ has two values $x$ and $x'$.
- Priming flexible variables is borrowed from TLA
- **Hypothesis 1** : **Values of $x$ belongs to a set of values called** $\textsc{Values}$ and defines the context of the system.
- **Hypothesis 2** : **Relations over $x$ and $x'$ belong to a set of relations** $\{r_0, \ldots, r_n\}$

# Operational model of a system

- A system $\mathcal{S}$ is observed with respect to flexible variables $x$.
- Flexible variables $x$ of $\mathcal{S}$ are modified according to a finite set of relations over the set of values $\textsc{Values}$ : $\{r_0, \ldots, r_n\}$
- $\textsc{Init}(x)$ denotes the set of possible intial values for $x$.

$$\mathcal{OMS} = (x, \textbf{Values}, \textbf{Init}(x), \{r_0, \ldots, r_n\})$$

# Safety and invariance of system

- **Hypothesis 3** : $\mathcal{OMS} = (x, \textsc{Values}, \textsc{Init}(x), \{r_0, \ldots, r_n\})$
- **Hypothesis 4** : $x \longrightarrow x' \triangleq (x\ r_0\ x') \vee \ldots \vee (x\ r_n\ x')$
- $\mathrm{I(x)}$ is inductively invariant for a system called $\mathcal{S}$, if
  $$\begin{cases} \forall x \in \textsc{Values} : \textsc{Init}(x) \Rightarrow \mathrm{I}(x) \\ \forall x, x' \in \textsc{Values} : \mathrm{I}(x) \wedge x \longrightarrow x' \Rightarrow \mathrm{I}(x') \end{cases}$$
  **I(x) is called an invariant in B**
- $\mathrm{Q(x)}$ is a safety property for a system called $\mathcal{S}$, if
  $\forall x, y \in \textsc{Values} : \textsc{Init}(x) \wedge x \xrightarrow{\star} y \Rightarrow \mathrm{Q}(y)$
  **Q(x) is called a theorem in B**

# Modelling systems : first attempt

**MODEL**
  $m$
...
...
...
**VARIABLES**
  $x$
**INVARIANT**
  $I(x)$
**THEOREMS**
  $Q(x)$
**INITIALISATION**
  $Init(x)$
**EVENTS**
  $\{r_0, \ldots, r_n\}$
**END**

- A model has a name $m$
- Flexibles variables $x$ are declared
- $I(x)$ provides informations over $x$
- $Q(x)$ provides informations over $x$

# Checking safety properties of the model

- $\forall x_0, x \in \textsc{Values} : \textsc{Init}(x_0) \wedge x_0 \xrightarrow{\star} x \Rightarrow \mathrm{Q}(x)$
- **Solution 1** Writing a procedure checking $\textsc{Init}(x_0) \wedge x_0 \xrightarrow{\star} x \Rightarrow \mathrm{Q}(x)$ for each pair $x_0, x \in \textsc{Values}$, when $\textsc{Values}$ is finite and small.
- **Solution 2** Writing a procedure checking $\textsc{Init}(x_0) \wedge x_0 \xrightarrow{\star} x \Rightarrow \mathrm{Q}(x)$ for each pair $x_0, x \in \textsc{Values}$, by constructing an abstraction of $\textsc{Values}$.
- **Solution 3** Writing a proof for $\forall x_0, x \in \textsc{Values} : \textsc{Init}(x_0) \wedge x_0 \xrightarrow{\star} x \Rightarrow \mathrm{Q}(x)$.

# Defining an induction principle for an operational model

**(I)** $\forall x_0, x \in \textbf{Values} : \textbf{Init}(x_0) \wedge x_0 \xrightarrow{\star} x \Rightarrow \textbf{Q}(x)$

**if, and only if,**

(II) there exists a state property $\mathrm{I}(x)$ such that :

$$\forall x_0, x, x' \in \textbf{Values} : \begin{cases} (1) & \textbf{Init}(x_0) \Rightarrow \textbf{I}(x_0) \\ (2) & \textbf{I}(x) \Rightarrow \textbf{Q}(x) \\ (3) & \textbf{I}(x) \wedge x \longrightarrow x' \Rightarrow \textbf{I}(x') \end{cases}$$

**if, and only if,**

(III) there exists a state property $\mathrm{I}(x)$ such that :

$$\forall x_0, x, x' \in \textbf{Values} : \begin{cases} (1) & \textbf{Init}(x_0) \Rightarrow \textbf{I}(x_0) \\ (2) & \textbf{I}(x) \Rightarrow \textbf{Q}(x) \\ (3) & \forall i \in \{0, \ldots, n\} : \textbf{I}(x) \wedge x \ r_i \ x' \Rightarrow \textbf{I}(x') \end{cases}$$

# Modelling systems : second attempt

**MODEL**
$m$
...
...
...
**VARIABLES**
$x$
**INVARIANT**
$I(x)$
**THEOREMS**
$Q(x)$
**INITIALISATION**
$Init(x)$
**EVENTS**
$\{r_0, \ldots, r_n\}$
**END**

- $\forall x_0 \in \textsc{Values} : \textsc{Init}(x_0) \Rightarrow \mathrm{I}(x_0)$
- $\forall x, x' \in \textsc{Values} : \forall i \in \{0, \ldots, n\} :$
$$\mathrm{I}(x) \wedge x \; r_i \; x' \Rightarrow \mathrm{I}(x')$$
- $\forall x \in \textsc{Values} : \mathrm{I}(x) \Rightarrow \mathrm{Q}(x)$

# Modelling systems : last attempt ?

**MODEL**
$m$
**?**
**?**
**?**
**VARIABLES**
$x$
**INVARIANT**
$I(x)$
**THEOREMS**
$Q(x)$
**INITIALISATION**
$Init(x)$
**EVENTS**
$\{r_0, \ldots, r_n\}$
**END**

- What are the environment of the proof for properties ?
- What are theories ?
- How are defining the static objects ?

# Modelling systems : last attempt !

**MODEL**
$m$
$\Gamma(m)$
**VARIABLES**
$x$
**INVARIANT**
$I(x)$
**THEOREMS**
$Q(x)$
**INITIALISATION**
$Init(x)$
**EVENTS**
$\{r_0, \ldots, r_n\}$
**END**

- $\Gamma(m)$ defines the static environment for the proofs related to $m$.
- $\Gamma(m) \vdash \forall x \in \textsc{Values} : \textsc{Init}(x) \Rightarrow \mathrm{I}(x)$
- $\forall i \in \{0, \ldots, n\}$ : $\Gamma(m) \vdash \forall x, x' \in \textsc{Values} : \mathrm{I}(x) \wedge x \; r_i \; x' \Rightarrow \mathrm{I}(x')$
- $\Gamma(m) \vdash \forall x \in \textsc{Values} : \mathrm{I}(x) \Rightarrow \mathrm{Q}(x)$

# Events System Models

An **event system model** is made of

State **constants** and state **variables** constrained by a state **invariant**

A finite set of **events**

**Proofs** ensures the consistency between the invariant and the events

An event system model can be **refined**

**Proofs** must ensure the correctness of refinement

# Modelling systems : Hello world !

**MODEL** *FACTORIAL_EVENTS*

`Static Part` *context*

**CONSTANTS**

$factorial, m$

**AXIOMS**

$$m \in \mathbb{N} \wedge factorial \in \mathbb{N} \leftrightarrow \mathbb{N} \wedge 0 \mapsto 1 \in factorial \wedge$$
$$\forall (n, fn).(n \mapsto fn \in factorial \Rightarrow n+1 \mapsto (n+1) * fn \in factorial) \wedge$$
$$\forall f \cdot \left( \begin{array}{l} f \in \mathbb{N} \leftrightarrow \mathbb{N} \wedge \\ 0 \mapsto 1 \in f \wedge \\ \forall (n, fn).(n \mapsto fn \in f \Rightarrow n+1 \mapsto (n+1) \times fn \in f) \\ \Longrightarrow \\ factorial \subseteq f \end{array} \right)$$

`Dynamic Part` *machine*

**VARIABLES**

$result, ok$

**INVARIANT**

$result \in \mathbb{N}$

$ok \in \mathbb{B}$

$ok = TRUE \Rightarrow result = factorial(n)$

**THEOREMS**

$factorial \in \mathbb{N} \longrightarrow \mathbb{N}$ ;

$factorial(0) = 1$ ;

$\forall n.(n \in \mathbb{N} \Rightarrow factorial(n+1) = (n+1) \times factorial(n))$

**INITIALISATION**

$result :\in \mathbb{N}$

$ok := FALSE$

**EVENTS**

$computation =$ **ANY** $ok = FALSE$ **THEN** $result, ok := factorial(m), TRUE$ **END**

**END**

# Modelling systems relations as events

**MODEL**
$m$
Static Part $context$
**SETS**
$s$
**CONSTANTS**
$c$
**AXIOMS**
$P(s,c)$
**THEOREMS**
$Q(s,c)$
Dynamic Part $machine$
**VARIABLES**
$x$
**INVARIANT**
$I(s,c,x)$
**THEOREMS**
$S(s,c,x)$
**INITIALISATION**
$Init(s,c,x)$
**EVENTS**
$\{r_1,\ldots,r_n\}$
**END**

- $\Gamma(m)$ defines the static environment for the proofs related to $m$ from $s$, $c$ and $P(s,c)$ and $\Gamma(m)$ is defined from the static part.
- $\Gamma(m) \vdash Q(s,c)$
- $\Gamma(m) \vdash \forall x, x' \in \textsc{Values} : \textsc{Init}(s,c,x) \Rightarrow \mathrm{I}(s,c,x)$
- $\forall i \in \{1,\ldots,n\} :$ $\Gamma(m) \vdash \forall x, x' \in \textsc{Values} :$ $\mathrm{I}(s,c,x) \wedge x\ r_i\ x' \Rightarrow \mathrm{I}(s,c,x')$
- $\Gamma(m) \vdash \forall x, x' \in \textsc{Values} : \mathrm{I}(s,c,x) \Rightarrow \mathrm{S}(s,c,x)$

# Modelling systems relations as events

**CONTEXT**
$context_name$
**SETS**
$s$
**CONSTANTS**
$c$
**AXIOMS**
$P(s,c)$
**THEOREMS**
$Q(s,c)$

**MACHINE**
$m$
**SEES**
$context_name$
**VARIABLES**
$x$
**INVARIANT**
$I(s,c,x)$
**THEOREMS**
$S(s,c,x)$
**INITIALISATION**
$Init(s,c,x)$
**EVENTS**
$\{e_1,\ldots,e_n\}$
**END**

- $\Gamma(m)$ defines the static environment for the proofs related to $m$ from $s$, $c$ and $P(s,c)$ and $\Gamma(m)$ is defined from the static part.
- $\Gamma(m) \vdash Q(s,c)$
- $\Gamma(m) \vdash \forall x, x' \in \textsc{Values} : \textsc{Init}(s,c,x) \Rightarrow \mathrm{I}(s,c,x)$
- $\forall i \in \{0,\ldots,n\} : r_i(x,x') \triangleq BA(e_i)(s,c,x,x')$
- $\forall i \in \{0,\ldots,n\} :$
  $\Gamma(m) \vdash \forall x, x' \in \textsc{Values} :$
  $\mathrm{I}(x) \wedge BA(e_i)(s,c,x,x') \Rightarrow \mathrm{I}(s,c,x')$
- $\Gamma(m) \vdash \forall x, x' \in \textsc{Values} : \mathrm{I}(x) \Rightarrow \mathrm{S}(s,c,x)$

# Modelling systems

**step 1** : Understanding the **problem** to solve
**step 2** : **Organizing** requirements and extracting properties
**step 3** : Writing a first very **abstract** system model
**step 4** : Consulting the requirements and **adding** a new detail in the current model by **refinement**
**step 5** : Either the model is enough detailed and the process stops, or the model is not yet enough concrete and the step 4 is repeated.

# Current Summary


1. Documentation
2. Introduction by Problems
3. Modelling Language
4. A Simple Example : Management of Students and Teachers
5. Modelling state-based systems
6. The Event B modelling language
7. Examples of Event B models
8. Summary on Events

# Expressing models in the event B notation

- Models are defined in two ways :
  - an abstract machine
  - a refinement of an existing model
- Models use **constants** which are defined in structures called **contexts**
- B structures are related by the three possible relations :
  - the **sees** relationship for expressing the use of constants, sets satisfying axioms and theorems.
  - the **extends** relationship for expressing the extension of contexts by adding new constants and new sets
  - the **refines** relationship stating that a B model is refined by another one.

# Machines and contexts

**Machines**

- **REFINES**
- **SEES** a context
- **VARIABLES** of the model
- **INVARIANTS** satisfied by the variables
- **THEOREMS** satisfied by the variables
- **EVENTS** modifying the variables
- **VARIANT**

**Contexts**

- **EXTENDS** another context
- **SETS** declares new sets
- **CONSTANTS** define a list of constants
- **AXIOMS** define the properties of constants and sets
- **THEOREMS** list the theorems which should be derived from axioms

# Machines en Event B

**MACHINE**
  $m$
**REFINES**
  $am$
**SEES**
  $c$
**VARIABLES**
  $u$
**INVARIANTS**
  $I(u)$
**THEOREMS**
  $Q(u)$
**VARIANT**
  $< variant >$
**EVENTS**
  $< event >$
**END**

- $\Gamma(m)$ : environment for the machine $m$ defined by the context $c$
- $\Gamma(m) \vdash \forall u \in \textsc{Values} : \textsc{Init}(u) \Rightarrow \mathrm{I}(u)$
- For each event $e$ in $E$ :
  $\Gamma(m) \vdash \forall u, u' \in \textsc{Values} : \mathrm{I}(u) \wedge BA(e)(u, u') \Rightarrow \mathrm{I}(u')$
- $\Gamma(m) \vdash \forall u \in \textsc{Values} : \mathrm{I}(u) \Rightarrow \mathrm{Q}(u)$

# Contexts in Event B

**CONTEXTS**
  $c$
**EXTENDS**
  $ac$
**SETS**
  $s$
**CONSTANTS**
  $c$
**AXIOMS**
  $ax1 : \ldots$
**THEOREMS**
  $th1 : \ldots$
**END**

- $ac$ : $c$ is extending $ac$ and add new features
- $s$ : sets are defined either by intension or by extension
- $c$ : constants are defined and
- axioms characterize constants and sets
- theorems are derived from axioms in the current context

# Events

| Event : $E$ | Before-After Predicate |
|---|---|
| **BEGIN** $x : \lvert P(x, x')$ **END** | $P(x, x')$ |
| **WHEN** $G(x)$ **THEN** $x : \lvert P(x, x')$ **END** | $G(x) \quad \wedge \quad P(x, x')$ |
| **ANY** $t$<br>**WHERE** $G(t, x)$<br>**THEN** $x : \lvert P(x, x', t)$ **END** | $\exists\, t \cdot (\, G(t, x) \quad \wedge \quad P(x, x', t)\,)$ |

# Guards of event

| Event : $E$ | Guard : grd(E) |
|---|---|
| **BEGIN** $S$ **END** | $TRUE$ |
| **WHEN** $G(x)$ **THEN** $T$ **END** | $G(x)$ |
| **ANY** $t$ **WHERE** $G(t,x)$ **THEN** $T$ **END** | $\exists\, t \cdot G(t,x)$ |

# Proof obligations for a B model

| | Proof obligation |
|---|---|
| (INV1) | $\Gamma(s,c) \vdash Init(x) \Rightarrow I(x)$ |
| (INV2) | $\Gamma(s,c) \vdash I(x) \wedge BA(e)(x,x') \Rightarrow I(x')$ |
| (DEAD) | $\Gamma(s,c) \vdash I(x) \Rightarrow (\mathsf{grd}(e_1) \vee \ldots \mathsf{grd}(e_n))$ |
| (SAFE) | $\Gamma(s,c) \vdash I(x) \Rightarrow A(x)$ |
| (FIS) | $\Gamma(s,c) \vdash I(x) \wedge \mathsf{grd}\,(E) \Rightarrow \exists x' \cdot P(x,x')$ |

# Current Summary


1. Documentation
2. Introduction by Problems
3. Modelling Language
4. A Simple Example : Management of Students and Teachers
5. Modelling state-based systems
6. The Event B modelling language
7. Examples of Event B models
8. Summary on Events

# The factorial model

**CONTEXT**
$fonctions$
**CONSTANTS**
$factorial, n$
**AXIOMS**

$$
\begin{array}{l}
ax1 : n \in \mathbb{N} \\
ax2 : factorial \in \mathbb{N} \leftrightarrow \mathbb{N} \\
ax3 : 0 \mapsto 1 \in factorial \\
ax4 : \forall (i, fn).(i \mapsto fn \in factorial \Rightarrow i+1 \mapsto (i+1) * fi \in factorial) \wedge \\
\forall f \cdot \left( \begin{array}{l} f \in \mathbb{N} \leftrightarrow \mathbb{N} \wedge \\ 0 \mapsto 1 \in f \wedge \\ \forall (n, fn).(n \mapsto fn \in f \Rightarrow n+1 \mapsto (n+1) \times fn \in f) \\ \Longrightarrow \\ factorial \subseteq f \end{array} \right)
\end{array}
$$

**END**

# The factorial model

**MACHINE**
$specification$
**SEES** $fonctions$
**VARIABLES**
$resultat$
**INVARIANT**
$resultat \in \mathbb{N}$
**THEOREMS**
$th1 : factorial \in \mathbb{N} \longrightarrow \mathbb{N}$ ;
$th2 : factorial(0) = 1$ ;
$th3 : \forall n.(n \in \mathbb{N} \Rightarrow factorial(n+1) = (n+1) \times factorial(n))$
**INITIALISATION**
$resultat :\in \mathbb{N}$
**EVENTS**
$computing1 =$ **BEGIN** $resultat := factorial(n)$ **END**
**END**

# Communications between agents

**MACHINE** $agents$
**SEES** $data$
**VARIABLES**
$sent$
$got$
$lost$
**INVARIANTS**
$inv1 : sent \subseteq AGENTS \times AGENTS$
$inv2 : got \subseteq AGENTS \times AGENTS$
$inv4 : (got \cup lost) \subseteq sent$
$inv6 : lost \subseteq AGENTS \times AGENTS$
$inv7 : got \cap lost = \varnothing$

**INITIALISATION**
**BEGIN**
$act1 : sent := \varnothing$
$act2 : got := \varnothing$
$act4 : lost := \varnothing$
**END**

# Communications between agents

**EVENT** sending a message
**ANY**
$a, b$
**WHERE**
$grd11 : a \in AGENTS$
$grd12 : b \in AGENTS$
$grd1 : a \mapsto b \notin sent$
**THEN**
$act11 : sent := sent \cup \{a \mapsto b\}$
**END**

**EVENT** getting a message
**ANY**
$a, b$
**WHERE**
$grd11 : a \in AGENTS$
$grd12 : b \in AGENTS$
$grd13 : a \mapsto b \in sent \setminus (got \cup lost)$
**THEN**
$act11 : got := got \cup \{a \mapsto b\}$
**END**

# Communications between agents

**EVENT** loosing a messge
**ANY**
$a$
$b$
**WHERE** $grd1 : a \in AGENTS$
$grd2 : b \in AGENTS$
$grd3 : a \mapsto b \in sent \setminus (got \cup lost)$
**THEN**
$act1 : lost := lost \cup \{a \mapsto b\}$
**END**

**CONTEXTS**
$data$
**SETS**
$MESSAGES$
$AGENTS$
$DATA$
**CONSTANTS**
$n$
$infile$
**AXIOMS**
$axm1 : n \in \mathbb{N}$
$axm2 : n \neq 0$
$axm3 : infile \in 1 \,..\, n \rightarrow DATA$
**END**

# Current Summary


1. Documentation
2. Introduction by Problems
3. Modelling Language
4. A Simple Example : Management of Students and Teachers
5. Modelling state-based systems
6. The Event B modelling language
7. Examples of Event B models
8. Summary on Events

# General form of an event

```
EVENT e
  ANY  t
  WHERE
    G(c, s, t, x)
  THEN
    x :|(P(c, s, t, x, x'))
  END
```

- $c$ et $s$ are constantes and visible sets by e
- $x$ is a state variable or a list of variabless
- $G(c, s, t, x)$ is the condition for observing $e$.
- $P(c, s, t, x, x')$ is the assertion for the relation over $x$ and $x'$.
- $BA(e)(c, s, x, x')$ is the *before-after* relationship for $e$ and is defined by $\exists t.G(c, s, t, x) \ \wedge \ P(c, s, t, x, x')$.

# General form of proof obligations for an event e

Proofs obligations are simplified when they are generated by the module called POG and goals in sequents as $\Gamma \vdash G$ :

1. $\Gamma \vdash G_1 \wedge G_2$ is decomposed into the two sequents $\begin{array}{l}(1)\Gamma \vdash G_1 \\ (2)\Gamma \vdash G_2\end{array}$
2. $\Gamma \vdash G_1 \Rightarrow G_2$ is transformed into the sequent $\Gamma, G_1 \vdash G_2$

## Proof obligations in Rodin

- *INIT/I/INV* : $C(s,c), INIT(c,s,x) \vdash I(c,s,x)$
- *e/I/INV* : $C(s,c), I(c,s,x), G(c,s,t,x), P(c,s,t,x,x') \vdash I(c,s,x')$
- *e/act/FIS* : $C(s,c), I(c,s,x), G(c,s,t,x) \vdash \exists x'.P(c,s,t,x,x')$

# notation

- Chapter Event B
- The Event B Modelling Notation Version 1.4
- The Event-B Mathematical Language 2006
- User Manual of the RODIN PLatform