# Modelling Software-based Systems

## Lecture 5 The access control problem in Event-B

Telecom Nancy (3A LE)

Dominique Méry
Telecom Nancy,Université de Lorraine

13 octobre 2026

dominique.mery@loria.fr

# Summary


1. Refinement of models
2. Summary on Event-B
3. Case Study The Access Control (J.-R. Abrial)
4. Conclusion

# Current Section Summary


1. Refinement of models
2. Summary on Event-B
3. Case Study The Access Control (J.-R. Abrial)
4. Conclusion

# Summing up...

- Refinement relates Event-B models
- Problem for starting a refinement-based development
- Problem for finding the best abstract model
- Problem for discharging unproved proof obligations generated for each refinement step
- The Access Control Problem

# Current Section Summary


1. Refinement of models
2. Summary on Event-B
3. Case Study The Access Control (J.-R. Abrial)
4. Conclusion

# Events as Relations over Variables Values

- Each variable $V$ has a current value $v$, a next value $v'$
- Each event e over variables $V$ is defined by a relation over $v$ and $v'$ denoted $BA(e)(v, v')$.
- An event e has local parameters, variables, guards and actions.
- Events *observe* changes over state variables and changes can be related to code execution or to physical phenomena.

# Simple Form of an Event

- An event of the simple form is denoted by :

$< event_name > \widehat{=}$
**WHEN**
$< condition >$
**THEN**
$< action >$
**END**

where
- $< event_name >$ is an identifier
- $< condition >$ is the firing condition of the event
- $< action >$ is a generalized substitution (parallel "assignment")

# Non-deterministic Form of an Event

- An event of the non-deterministic form is denoted by :

$< event_name > \widehat{=}$
**ANY** $< variable >$ **WHERE**
$< condition >$
**THEN**
$< action >$
**END**

where
- $< event_name >$ is an identifier
- $< variable >$ is a (list of) variable(s)
- $< condition >$ is the firing condition of the event
- $< action >$ is a generalized substitution (parallel "assignment")

# Shape of a Generalized Substitution

A generalized substitution can be

- Simple assignment : $x := E$
- Generalized assignment : $x : |P(x, x')$
- Set assignment : $x :\in S$
- Parallel composition : $\begin{array}{l} T \\ \cdots \\ U \end{array}$

,

# Invariant Preservation Verification (0)

$$\text{INVARIANT} \ \wedge \ \text{GUARD}$$
$$\Longrightarrow$$
$$\text{ACTION establishes INVARIANT}$$

# Invariant Preservation Verification (1)

- Given an event of the simple form :

**EVENT** e $\widehat{=}$
**WHEN**
$G(x)$
**THEN**
$x := E(x)$
**END**

and invariant $I(x)$ to be preserved, the statement to prove is :

$$I(x) \quad \wedge \quad G(x) \quad \Longrightarrow \quad I(E(x))$$

# Invariant Preservation Verification (2)

- Given an event of the simple form :

**EVENT** e $\widehat{=}$
**WHEN**
$G(x)$
**THEN**
$x :| P(x, x')$
**END**

and invariant $I(x)$ to be preserved, the statement to prove is :

$$I(x) \quad \wedge \quad G(x) \quad \wedge \quad P(x, x') \quad \Longrightarrow \quad I(x')$$

# Invariant Preservation Verification (3)

- Given an event of the simple form :

**EVENT** e $\widehat{=}$
**WHEN**
$G(x)$
**THEN**
$x :\in S(x)$
**END**

and invariant $I(x)$ to be preserved, the statement to prove is :

$$I(x) \quad \wedge \quad G(x) \quad \wedge \quad x' \in S(x) \quad \Longrightarrow \quad I(x')$$

# Invariant Preservation Verification (4)

- Given an event of the non-deterministic form :

**EVENT** e $\widehat{=}$
  **ANY** $v$ **WHERE**
    $G(x, v)$
  **THEN**
    $x := E(x, v)$
  **END**

and invariant $I(x)$ to be preserved, the statement to prove is :

$$I(x) \quad \wedge \quad G(x, v) \quad \Longrightarrow \quad I(E(x, v))$$

# Refinement Technique (1)

- Abstract models works with variables $x$, and concrete one with $y$
- A gluing invariant $J(x, y)$ links both sets of vrbls
- Each abstract event is refined by concrete one (see below)

# Refinement Technique (2)

- Some new events may appear : they refine “skip”
- Concrete events must not block more often than the abstract ones
- The set of new event alone must always block eventually

# Correct Refinement Verification (1)

- Given an abstract and a corresponding concrete event

**EVENT** ae $\widehat{=}$
**WHEN**
$G(x)$
**THEN**
$x := E(x)$
**END**

**EVENT** ce $\widehat{=}$
**WHEN**
$H(y)$
**THEN**
$y := F(y)$
**END**

and invariants $I(x)$ and $J(x, y)$, the statement to prove is :

$$I(x) \ \wedge \ J(x, y) \ \wedge \ H(y) \implies G(x) \ \wedge \ J(E(x), F(y))$$

# Correct Refinement Verification (1)

- Given an abstract and a corresponding concrete event

**EVENT** ae $\widehat{=}$
**WHEN**
$G(x)$
**THEN**
$x := E(x)$
**END**

**EVENT** ce $\widehat{=}$
**WHEN**
$H(y)$
**THEN**
$y := F(y)$
**END**

and invariants $I(x)$ and $J(x, y)$, the statement to prove is :

$$I(x) \ \wedge \ J(x, y) \ \wedge \ H(y) \implies G(x) \ \wedge \ J(E(x), F(y))$$

- $BA(ae)(x, x') \ \widehat{=} \ G(x) \wedge x' = E(x)$
- $BA(ce)(y, y') \ \widehat{=} \ H(y) \wedge y' = F(y)$

# Correct Refinement Verification (2)

- Given an abstract and a corresponding concrete event

**EVENT** ae $\widehat{=}$
**ANY** $v$ **WHERE**
$G(x, v)$
**THEN**
$x := E(x, v)$
**END**

**EVENT** ce $\widehat{=}$
**ANY** $w$ **WHERE**
$H(y, w)$
**THEN**
$y := F(y, w)$
**END**

$$I(x) \quad \wedge \quad J(x, y) \quad \wedge \quad H(y, w)$$
$$\Longrightarrow$$
$$\exists v \cdot ( G(x, v) \quad \wedge \quad J(E(x, v), F(y, w)) )$$

- $BA(ae)(x, x') \ \widehat{=} \ \exists v.G(x, v) \wedge x' = E(x)$
- $BA(ce)(y, y') \ \widehat{=} \ \exists w.H(y, w) \wedge y' = F(y)$

# Correct Refinement Verification (3)

- Given a NEW event

**EVENT** ne $\widehat{=}$
  **WHEN**
    $H(y)$
  **THEN**
    $y := F(y)$
  **END**

and invariants $I(x)$ and $J(x, y)$, the statement to prove is :

$$I(x) \quad \wedge \quad J(x, y) \quad \wedge \quad H(y) \quad \Longrightarrow \quad J(x, F(y))$$


- $BA(ne)(y, y') \ \widehat{=} \ H(y) \wedge y' = E(y)$

# Current Section Summary


1. Refinement of models
2. Summary on Event-B
3. Case Study The Access Control (J.-R. Abrial)
4. Conclusion

# A Case Study by J.-R. Abrial

- To control accesses into locations.
- People are assigned certain authorizations
- Each person is given a magnetic card
- Doors are “one way” turnstyles
- Each turnstyle is equipped with :
    - a card reader
    - two lights (one green, the other red)


Turnstyle

# Access Protocol (after introducing card in reader)

- If access permitted
  - green light turned on
  - turnstyle unblocked for 30 sec
- Passing, or 30 sec elapsed
  - green light turned off
  - turnstyle blocked again
- If access refused
  - red light turned on for 2 sec
  - turnstyle stays blocked

# Goal of System Study

- Sharing between Control and Equipment
- For this : constructing a closed model
- Defining the physical environment
- Possible generalization of problem
- Studying safety questions
- Studying synchronisation questions
- Studying marginal behaviour

# Basic System Properties

P1 : The model concerns people and locations
P2 : A person is authorized to be in some locations
P3 : A person can only be in one location at a time
D1 : Outside is a location where everybody can be
P4 : A person is always in some location
P5 : A person is always authorized to be in his location

# Example

## Sets

$$\begin{aligned} \text{persons} &= \{\, \text{p1}, \text{p2}, \text{p3} \,\} \\ \text{locations} &= \{\, \text{l1}, \text{l2}, \text{l3}, \text{l4} \,\} \end{aligned}$$

## Authorizations

| | |
|---|---|
| p1 | l2, l4 |
| p2 | l1, l3, l4 |
| p3 | l2, l3, l4 |

## Correct scenario

| | |
|---|---|
| p1 | l4 |
| p2 | l4 |
| p3 | l4 |

$\rightarrow$

| | |
|---|---|
| p1 | l2 |
| p2 | l4 |
| p3 | l4 |

$\rightarrow$

| | |
|---|---|
| p1 | l2 |
| p2 | l1 |
| p3 | l4 |

$\rightarrow$

| | |
|---|---|
| p1 | l4 |
| p2 | l1 |
| p3 | l4 |

$\rightarrow$

| | |
|---|---|
| p1 | l4 |
| p2 | l1 |
| p3 | l3 |

# Model (1)

Basic sets : persons $\mathrm{P}$ and locations $\mathrm{B}$ (prop. P1)
Constant : authorizations $\mathrm{A}$ (prop. P2)
$\mathrm{A}$ is a binary relation between $\mathrm{P}$ and $\mathrm{B}$

$$\mathrm{A} \in \mathrm{P} \leftrightarrow \mathrm{B}$$

# Model (2)

Constant : $outside$ is a location where everybody is authorized to be (decision D1)

$$outside \in \mathrm{B}$$

$$\mathrm{P} \times \{outside\} \subseteq \mathrm{A}$$

# Model (3)

Variable : situations $\mathrm{c}$ (prop. P3 and P4)
$\mathrm{c}$ is a total function between $\mathrm{P}$ and $\mathrm{B}$
A total function is a special case of a binary relation

$$\mathrm{c} \in \mathrm{P} \rightarrow \mathrm{B}$$

Invariant : situations compatible with auth. (prop. P5)
The function $\mathrm{c}$ is included in the relation $\mathrm{A}$

$$\mathrm{c} \subseteq \mathrm{A}$$

# A magic event which can be observed

- GUARD : $\begin{cases} \text{- Given some person } p \text{ and location } l \\ \text{- } p \text{ is authorized to be in } l : p, l \in \mathrm{A} \\ \text{- } p \text{ is not currently in } l : \mathrm{c}(p) \neq l \end{cases}$
- ACTION : - $p$ jumps into $l$

**EVENT** observation1 $\widehat{=}$
  **ANY** $p, l$ **WHERE**
    $p \in \mathrm{P} \quad \wedge$
    $l \in \mathrm{B} \quad \wedge$
    $p \mapsto l \in \mathrm{A} \quad \wedge$
    $\mathrm{c}(p) \neq l$
  **THEN**
    $\mathrm{c}(p) := l$
  **END**

# Relation overriding

Given two relations $a$ and $b$

Overriding $a$ by $b$ yields a new relation $a \lhd\!\!+ b$

$$a \lhd\!\!+ b \quad \widehat{=} \quad (\mathsf{dom}\,(b) \lhd a) \ \cup \ b$$

Abbreviation

$$f(x) := y \quad \widehat{=} \quad f := f \lhd\!\!+ \{x \mapsto y\}$$

# Invariant Preservation Proof

INVARIANT $\wedge$ GUARD

$\Longrightarrow$

ACTION establishes INVARIANT

$$
\begin{array}{l}
\mathrm{C} \subseteq \mathrm{A} \quad \wedge \\
p \in \mathrm{P} \quad \wedge \\
l \in \mathrm{B} \quad \wedge \\
p \mapsto l \in \mathrm{A} \\
\Longrightarrow \\
(\{p\} \lhd \mathrm{C}) \cup \{p \mapsto l\} \subseteq \mathrm{A}
\end{array}
$$

# First Refinement : Introducing Geometry

P6 : The geometry define how locations communicate
P7 : A location does not communicate with itself
P8 : Persons move between communicating locations

# Refined Model

Constant : communication $\mathrm{STRUCTURE}$ (prop. P6 and P7)
$\mathrm{STRUCTURE}$ is a binary relation between $\mathrm{B}$
The intersection of $\mathrm{STRUCTURE}$ with the identity relation on $\mathrm{B}$ is empty

$$\mathrm{STRUCTURE} \in \mathrm{B} \leftrightarrow \mathrm{B}$$

$$\mathrm{STRUCTURE} \cap \mathsf{id}(\mathrm{B}) = \varnothing$$

# Correct Refinement Verification (reminder)

Concrete events do not block more often than abstract ones

$I(x) \quad \wedge \quad J(x,y) \quad \wedge$
disjunction of abstract guards
$\Longrightarrow$
disjunction of concrete guards

New events block eventually (decreasing the same quantity $V(y)$)

$$I(x) \quad \wedge \quad J(x,y) \quad \wedge \quad H(y) \quad \wedge \quad V(y) = n \implies V(F(y)) < n$$

# Refined Event

Event (prop. P8)
The guard is strengthened
The current location of $p$ and the new location $l$ must communicate

**EVENT** observation1 $\widehat{=}$
  **ANY** $p, l$ **WHERE**
    $p \in \mathrm{P} \quad \wedge$
    $l \in \mathrm{B} \quad \wedge$
    $p \mapsto l \in \mathrm{A} \quad \wedge$
    $\mathrm{C}(p) \neq l$
  **THEN**
    $\mathrm{C}(p) := l$
  **END**

**EVENT** observation2 $\widehat{=}$
  **REFINES** $observation1$
  **ANY** $p, l$ **WHERE**
    $p \in \mathrm{P} \quad \wedge$
    $l \in \mathrm{B} \quad \wedge$
    $p \mapsto l \in \mathrm{A} \quad \wedge$
    $\mathrm{C}(p) \mapsto l \in \mathrm{STRUCTURE}$
  **THEN**
    $\mathrm{C}(p) := l$
  **END**

# Proofs

Invariant preservation : Success

Guard strengthening : Success

$$\exists\,(p,l)\cdot(\,p\mapsto l\ \in\ \mathrm{A}\ \wedge\ \mathrm{C}(p)\mapsto l\ \in\ \mathrm{STRUCTURE}\,)$$
$$\Rightarrow$$
$$\exists\,(p,l)\cdot(\,p\mapsto l\ \in\ \mathrm{A}\ \wedge\ \mathrm{C}(p)\neq l\,)$$

Deadlockfreeness : Failure

$$\exists\,(p,l)\cdot(\,p\mapsto l\ \in\ \mathrm{A}\ \wedge\ \mathrm{C}(p)\neq l\,)$$
$$\Rightarrow$$
$$\exists\,(p,l)\cdot(\,p\mapsto l\ \in\ \mathrm{A}\ \wedge\ \mathrm{C}(p)\mapsto l\ \in\ \mathrm{STRUCTURE}\,)$$

# Safety Problem

P9 : No person must remain blocked in a location.

Solution

P10 : Any person authorized to be in a location must also be authorized to go in another location which communicates with the first one.

$$\boxed{\mathrm{A} \subseteq \mathrm{A} ; \textsc{structure}^{-1}}$$

$$p \mapsto l \in \mathrm{A} \implies \exists m \cdot ( p \mapsto m \in \mathrm{A} \ \wedge \ l \mapsto m \in \textsc{structure} )$$

# Example

| | | | |
|---|---|---|---|
| p1 | l2 | p2 | l4 |
| p1 | l4 | p3 | l2 |
| p2 | l1 | p3 | l3 |
| p2 | l3 | p3 | l4 |

A

| | |
|---|---|
| l1 | l3 |
| l1 | l4 |
| l3 | l2 |
| l4 | l1 |
| l4 | l2 |
| l4 | l3 |

STRUCTURE


| | |
|---|---|
| l1 | l4 |
| l2 | l3 |
| l2 | l4 |
| l3 | l1 |
| l3 | l4 |
| l4 | l1 |

$\text{STRUCTURE}^{-1}$

| | |
|---|---|
| p1 | l1 |
| p1 | l3 |
| p1 | l4 |
| p2 | l1 |

A; STRU

- Opening a door between l2 and l4
- Authorizing p2 to go to l2


b2
b3
p1 p3
p2 p3
p2
p1 p2 p3
p2
b4
b1

# Solution

| p1 | l2 | p2 | l4 |
|---|---|---|---|
| p1 | l4 | p3 | l2 |
| p2 | l1 | p3 | l3 |
| p2 | l2 | p3 | l4 |
| p2 | l3 | | |

A

| l1 | l3 |
|---|---|
| l1 | l4 |
| l2 | l4 |
| l3 | l2 |
| l4 | l1 |
| l4 | l2 |
| l4 | l3 |

STRUCTURE

| l1 | l4 |
|---|---|
| l2 | l3 |
| l2 | l4 |
| l3 | l1 |
| l3 | l4 |
| l4 | l1 |
| l4 | l2 |

$\text{STRUCTURE}^{-1}$

| p1 | l1 | |
|---|---|---|
| p1 | l2 | |
| p1 | l3 | |
| p1 | l4 | |
| p2 | l1 | |
| p2 | l2 | |

A; STRUCTU

Decision

D2 : The system that we are going to construct does not guarantee that people can move “outside”.

# A better solution (1)

Constante : $exit$ is a function, included in $com$, with no cycle

$$exit \in \mathrm{B} - \{outside\} \to \mathrm{B}$$

$$exit \subseteq com$$

$$\forall s \cdot ( s \subseteq \mathrm{B} \implies (s \subseteq exit^{-1}[s] \implies s = \varnothing) )$$

$$\forall x \cdot (x \in s \implies \exists y \cdot ( y \in s \ \wedge \ (x, y) \in exit ) )$$
$$\implies$$
$$s = \varnothing$$

$exit$ is a tree spanning the graph represented by $com$

# A better solution (2)

P10' : Every person authorized to be in a location (which is not "outside") must also be authorized to be in another location communicating with the former and leading towards the exit.

$$\boxed{\mathrm{A} \rhd \{outside\} \subseteq \mathrm{A} ; exit^{-1}}$$

$$\begin{array}{l} p \mapsto l \in \mathrm{A} \ \wedge \\ l \neq outside \\ \Longrightarrow \\ p \mapsto exit(l) \in \mathrm{A} \end{array}$$

# For the experts

Show that no cycle implies the possibility to prove property by induction and vice-versa

$$\forall s \cdot ( s \subseteq \mathrm{B} \ \wedge \ s \subseteq exit^{-1}[s] \implies s = \varnothing )$$
$$\Leftrightarrow$$
$$\forall t \cdot ( \ t \subseteq \mathrm{B} \ \wedge \ outside \in t \ \wedge \ exit^{-1}[t] \subseteq t \implies t = \mathrm{B} )$$

$$t \subseteq \mathrm{B}$$
$$outside \in t$$
$$\forall (x, y) \cdot ( (x \mapsto y) \in exit \ \wedge \ y \in t \implies x \in t )$$
$$\implies$$
$$t = \mathrm{B}$$

# Second Refinement : Introducing Doors

P11 : Locations communicate via one-way doors.

P12 : A person get through a door only if accepted.

P13 : A door is acceptable by at most one person at a time.

P14 : A person is accepted for at most one door only.

P15 : A person is accepted if at the origin of the door.

P16 : A person is accepted if authorized at destination.

# Extending the Model (1)

Set : the set $\mathrm{DOORS}$ of doors
Constants : The origin $\mathrm{ORG}$ and destination $\mathrm{DST}$ of a door (prop. P11)

$$\mathrm{ORG} \in \mathrm{DOORS} \to \mathrm{B}$$
$$\mathrm{DST} \in \mathrm{DOORS} \to \mathrm{B}$$
$$\mathrm{STRUCTURE} = (\mathrm{ORG}^{-1} ; \mathrm{DST})$$

# Extending the Model (2)

Variable : the rel. $\mathrm{DAP}$ between persons and doors (prop. P12 to P16)

$$\begin{array}{l} \mathrm{DAP} \in \mathrm{P} \rightarrowtail\!\!\!\!\!\!\rightarrow \mathrm{DOORS} \\ (\mathrm{DAP} ; \mathrm{ORG}) \subseteq \mathrm{C} \\ (\mathrm{DAP} ; \mathrm{DST}) \subseteq \mathrm{A} \end{array}$$

# Second Refinement : More Properties

P17 : Green light of a door is lit when access is accepted.
P18 : When a person has got through, the door blocks.
P19 : After 30 seconds, the door blocks automatically.
P20 : Red light is lit for 2 sec.when access is refused.
P21 : Red and green lights are not lit simultaneously.

# Extending the Model (3)

Definition : GREEN is exactly the range of DAP (prop. P17 to P19)

$$\text{GREEN} \;\widehat{=}\; \text{ran}\,(\text{DAP})$$

# Extending the Model (4)

Variable : The set $red$ of red doors (prop. P20)

$$red \subseteq \text{DOORS}$$

Invariant : GREEN and $red$ are incompatible (prop. P21)

$$\text{GREEN} \cap red = \varnothing$$

# Condition for Admission

P22 : Person $p$ is accepted through door $d$ if

- $p$ is situated within the origin of $d$
- $p$ is authorized to move to the dest. of $d$
- $p$ is not engaged with another door

$$\begin{array}{l}\mathsf{admitted}\,(p,d) \;\widehat{=}\\ \quad \mathrm{ORG}(d) = \mathrm{C}(p) \;\wedge\\ \quad p \mapsto \mathrm{DST}(d) \in \mathrm{A} \;\wedge\\ \quad p \notin \mathsf{dom}\,(dap)\end{array}$$

# A New Event (1)

Accepting a person $p$ - GUARD :

- Given some person $p$ and door $d$
- $d$ is neither green nor red
- $p$ is admissible through $d$

- ACTION : - make $p$ authorized to pass $d$

**EVENT** accept $\widehat{=}$
  **ANY** $p, d$ **WHERE**
    $p \in \mathrm{P} \quad \wedge$
    $d \in \mathrm{DOORS} \quad \wedge$
    $d \notin \mathrm{GREEN} \cup red \quad \wedge$
    admitted $(p, d)$
  **THEN**
    $\mathrm{DAP}(p) := d$
  **END**

# A New Event (2)

Refusing a person $p$

- GUARD :
  - Given some person $p$ and door $d$
  - $d$ is neither green nor red
  - $p$ is not admissible through $d$
- ACTION :
  - lit the red light

**EVENT** refuse $\widehat{=}$
  **ANY** $p, d$ **WHERE**
    $p \in \mathrm{P} \quad \wedge$
    $d \in \mathrm{DOORS} \quad \wedge$
    $d \notin \mathrm{GREEN} \cup red \quad \wedge$
    $\neg$ admitted $(p, d)$
  **THEN**
    $red := red \cup \{d\}$
  **END**

# Refining Event OBSERVATION2

**EVENT** observation2 $\widehat{=}$
  **ANY** $p, l$ **WHERE**
    $p \in \mathrm{P}$
    $l \in \mathrm{B}$
    $p, l \in \mathrm{A}$
    $\mathrm{C}(p) \mapsto l \in \mathrm{STRUCTURE}$
  **THEN**
    $\mathrm{C}(p) := l$
  **END**

**EVENT** observation3 $\widehat{=}$
  **REFINES** observation2
  **ANY** $d$ **WHERE**
    $d \in \mathrm{GREEN}$
  **THEN**
    $\mathrm{C}(\mathrm{DAP}^{-1}(d)) := \mathrm{DST}(d)$
    $\mathrm{DAP} := \mathrm{DAP} \rhd \{d\}$
  **END**


# New Event (3)

## Turning lights off

**EVENT** off_grn $\widehat{=}$
**ANY** $d$ **WHERE**
$d \in \text{GREEN}$
**THEN**
$\text{DAP} := \text{DAP} \rhd \{d\}$
**END**

**EVENT** off_red $\widehat{=}$
**ANY** $d$ **WHERE**
$d \in red$
**THEN**
$red := red - \{d\}$
**END**

# Synchronization



# Proofs

- Event observation is a correct refinement : OK
- Other events refine skip : OK
- Event observation does not deadlock more : OK
- New events do not take control indefinitely : FAILURE

# Permanent Obstruction of Card Readers

DANGER

- People without the required authorizations
  try indefinitely to enter some locations.
- Other people with the authorization
  always change mind at the last moment.

SOLUTIONS

- Make such practice impossible ? ? ?
- Card Readers can “swallow” a card

# Final Decision

D3 : The system we are going to construct will not prevent people from blocking doors indefinitely :

- either by trying indefinitely to enter places into which they are not authorized to enter,
- or by indefinitely abandoning "on the way" their intention to enter the places in which they are in fact authorized to enter¨.

# Third Refinement : Introducing Card Readers

A decision

D4 : Each card reader is supposed to stay blocked between :

- the sending of a card to the system
- the reception of an acknowledgement.

# Third Refinement : Model Extension

The set $BLR$ of blocked Card Readers
The set $mCard$ of messages sent by Card Readers
The set $mAckn$ of acknowledgment messages

$$BLR \subseteq \text{DOORS}$$

$$mCard \in \text{DOORS} \pfun \text{P}$$

$$mAckn \subseteq \text{DOORS}$$

# Third Refinement : Invariant

$\mathsf{dom}\,(mCard)$, GREEN, $red$, $mAckn$ partition $BLR$

$$\mathsf{dom}\,(mCard) \cup \text{GREEN} \cup red \cup mAckn = BLR$$

$$\mathsf{dom}\,(mCard) \cap (\text{GREEN} \cup red \cup mAckn) = \varnothing$$

$$mAckn \cap (\text{GREEN} \cup red) = \varnothing$$

# Events (1)

**EVENT** CARD $\widehat{=}$
  **ANY** $p, d$
  **WHERE**
    $p \in \mathrm{P}$
    $d \in \mathrm{DOORS} - BLR$
  **THEN**
    $BLR := BLR \cup \{d\}$
    $mCard := mCard \cup \{d \mapsto p\}$
  **END**

# Events (2)

**EVENT** accept3 $\widehat{=}$
  **ANY** $p, d$
  **WHERE**
    $p \in \mathrm{P}$
    $d \in \mathrm{DOORS}$
    $d \notin \mathrm{GREEN} \cup red$
    admitted $(p, d)$
  **THEN**
    $\mathrm{DAP}(p) := d$
  **END**

**EVENT** accept4 $\widehat{=}$
  **REFINES** accept3
  **ANY** $p, d$
  **WHERE**
    $d \mapsto p \in mCard$
    admitted $(p, d)$
  **THEN**
    $\mathrm{DAP}(p) := d$
    $mCard := mCard - \{d \mapsto p\}$
  **END**

# Events (3)

**EVENT** refuse4 $\widehat{=}$
  **REFINES** refuse3
  **ANY** $p, d$
  **WHERE**
    $d \mapsto p \in mCard$
    $\neg$ admitted $(p, d)$
  **THEN**
    $red := red \cup \{d\}$
    $mCard := mCard - \{d \mapsto p\}$
  **END**

# Events (4)

**EVENT** observation4 $\widehat{=}$
  **REFINES** observation3
  **ANY** $d$
  **WHERE**
    $d \in \text{GREEN}$
  **THEN**
    $\text{C}(\text{DAP}^{-1}(d)) := \text{DST}(d)$
    $\text{DAP} := \text{DAP} \rhd \{d\}$
    $mAckn := mAckn \cup \{d\}$
  **END**

# Events (5)


**EVENT** off_grn $\widehat{=}$
**ANY** $d$ **WHERE**
$d \in \text{GREEN}$
**THEN**
$\text{DAP} := \text{DAP} \rhd \{d\}$
$mAckn := mAckn \cup \{d\}$
**END**

**EVENT** off_red $\widehat{=}$
**ANY** $d$ **WHERE**
$d \in red$
**THEN**
$red := red - \{d\}$
$mAckn := mAckn \cup \{d\}$
**END**

# Events (6)

**EVENT** ACKN $\widehat{=}$
  **ANY** $d$ **WHERE**
    $d \in mAckn$
  **THEN**
    $BLR := BLR - \{d\}$
    $mAckn := mAckn - \{d\}$
  **END**

# Synchronization



# Fourth Refinement : Physical Doors and Lights

## Decisions

D5 : When a door has been cleared, it blocks itself automatically
without any intervention from the control system.

D6 : Each door incorporates a local clock for
- the extinction of the green light after 30 sec.
- the extinction of the red light after 2 sec.

# Extending the Model : the Green Chain (1)

The set $mAccept$ of acceptance messages (to doors)
The set $GRN$ of physical green doors
The set $mPass$ of passing messages (from doors)
The set $mOff_grn$ of messages (from doors)

$$mAccept \subseteq \text{DOORS}$$

$$GRN \subseteq \text{DOORS}$$

$$mPass \subseteq \text{DOORS}$$

$$mOff_grn \subseteq \text{DOORS}$$

# Extending the Model : the Green Chain (2)

$mAccept, GRN, mPass, mOff_grn$ partition GREEN

$$mAccept \cup GRN \cup mPass \cup mOff_grn = \text{GREEN}$$

$$mAccept \cap (GRN \cup mPass \cup mOff_grn) = \varnothing$$

$$GRN \cap (mPass \cup mOff_grn) = \varnothing$$

$$mPass \cap mOff_grn = \varnothing$$

# Extending the Model : the Red Chain (1)

The set $mRefuse$ of messages (to doors)
The set $RED$ of phyical red doors
The set $mOff_red$ of messages (from doors)

$$mRefuse \subseteq \text{DOORS}$$

$$RED \subseteq \text{DOORS}$$

$$mOff_red \subseteq \text{DOORS}$$

# Extending the Model : the Red Chain (2)

$mRefuse, RED, mOff_red$ partition $red$

$$mRefuse \cup RED \cup mOff_red = red$$

$$mRefuse \cap (RED \cup mOff_red) = \varnothing$$

$$RED \cap mOff_red = \varnothing$$

# Events (1)

**EVENT** accept $\widehat{=}$
  **ANY** $p, d$ **WHERE**
    $d \mapsto p \in mCard \quad \wedge$
    admitted $(p, d)$
  **THEN**
    $\mathrm{DAP}(p) := d$
    $mCard := mCard - \{d \mapsto p\}$
    $mAccept := mAccept \cup \{d\}$
  **END**

# Events (2)

**EVENT** ACCEPT $\widehat{=}$
  **ANY** $d$ **WHERE**
    $d \in mAccept$
  **THEN**
    $GRN := GRN \cup \{d\}$
    $mAccept := mAccept - \{d\}$
  **END**

# Events (3)

**EVENT** PASS $\widehat{=}$
  **ANY** $d$ **WHERE**
    $d \in GRN$
  **THEN**
    $GRN := GRN - \{d\}$
    $mPass := mPass \cup \{d\}$
  **END**

# Events (4)

**EVENT** observation5 $\widehat{=}$
**REFINES** observation4 **ANY** $d$ **WHERE**
$d \in mPass$
**THEN**
$\mathrm{C}(\mathrm{DAP}^{-1}(d)) := \mathrm{DST}(d)$
$\mathrm{DAP} := \mathrm{DAP} \rhd \{d\}$
$mAckn := mAckn \cup \{d\}$
$mPass := mPass - \{d\}$
**END**

# Events (5)

**EVENT** OFF_GRN $\widehat{=}$
  **ANY** $d$ **WHERE**
    $d \in GRN$
  **THEN**
    $GRN := GRN - \{d\}$
    $mOff_grn := mOff_grn \cup \{d\}$
  **END**

# Events (6)

**EVENT** off_grn $\widehat{=}$
  **ANY** $d$ **WHERE**
    $d \in mOff_grn$
  **THEN**
    $\mathrm{DAP} := \mathrm{DAP} \rhd \{d\}$
    $mAckn := mAckn \cup \{d\}$
    $mOff_grn := mOff_grn - \{d\}$
  **END**

# Events (7)

**EVENT** refuse $\widehat{=}$
  **ANY** $p, d$ **WHERE**
    $d \mapsto p \in mCard \quad \wedge$
    $\neg$ admitted $(p, d)$
  **THEN**
    $red := red \cup \{d\}$
    $mCard := mCard - \{d \mapsto p\}$
    $mRefuse := mRefuse \cup \{d\}$
  **END**

# Events (8)

**EVENT** REFUSE $\widehat{=}$
  **ANY** $d$ **WHERE**
    $d \in mRefuse$
  **THEN**
    $RED := RED \cup \{d\}$
    $mRefuse := mRefuse - \{d\}$
  **END**


# Events (9)

**EVENT** OFF_RED $\widehat{=}$
  **ANY** $d$ **WHERE**
    $d \in RED$
  **THEN**
    $RED := RED - \{d\}$
    $mOff_red := mOff_red \cup \{d\}$
  **END**

# Events (10)

**EVENT** off_red $\widehat{=}$
  **ANY** $d$ **WHERE**
    $d \in mOff_red$
  **THEN**
    $red := red - \{d\}$
    $mAckn := mAckn \cup \{d\}$
    $mOff_red := mOff_red - \{d\}$
  **END**

# Synchronization



# Communications

| Hardware | Network | | | Software |
|---|---|---|---|---|
| CARD | $\rightarrow$ | $mCard$ | $\rightarrow$ | $\begin{cases} \text{accept (1)} \\ \text{refuse (2)} \end{cases}$ |
| ACCEPT | $\leftarrow$ | $mAccept$ | $\leftarrow$ | (1) |
| PASS | $\rightarrow$ | $mPass$ | $\rightarrow$ | observation (3) |
| OFF_GRN | $\rightarrow$ | $mOff_grn$ | $\rightarrow$ | off_grn (3) |
| REFUSE | $\leftarrow$ | $mRefuse$ | $\leftarrow$ | (2) |
| OFF_RED | $\rightarrow$ | $mOff_red$ | $\rightarrow$ | off_red (3) |
| ACKN | $\leftarrow$ | $mAckn$ | $\leftarrow$ | (3) |

# Decomposition (1)

Software Data

$$
\begin{array}{l}
aut \in \mathrm{P} \leftrightarrow \mathrm{B} \\
\mathrm{ORG} \in \textsc{doors} \rightarrow \mathrm{B} \\
\mathrm{DST} \in \textsc{doors} \rightarrow \mathrm{B} \\
\mathrm{A} \subseteq \mathrm{A}; \mathrm{DST}^{-1}; \mathrm{ORG} \\
\mathrm{C} \in \mathrm{P} \rightarrow \mathrm{B} \\
\\
dap \in \mathrm{P} \rightarrowtail \textsc{doors} \\
red \subseteq \textsc{doors}
\end{array}
$$

# Decomposition (2)

Network data

$$mCard \in \text{DOORS} \pfun \mathrm{P}$$

$$mAckn \subseteq \text{DOORS}$$

$$mAccept \subseteq \text{DOORS}$$

$$mPass \subseteq \text{DOORS}$$

$$mOff_grn \subseteq \text{DOORS}$$

$$mRefuse \subseteq \text{DOORS}$$

$$mOff_red \subseteq \text{DOORS}$$

# Decomposition (3)

"Physical" Data

$$BLR \subseteq \text{DOORS}$$

$$GRN \subseteq \text{DOORS}$$

$$RED \subseteq \text{DOORS}$$

# Software Operations

**EVENT** test_soft$(p, d)$

**EVENT** accept_soft$(p, d)$

**EVENT** refuse_soft$(d)$

**EVENT** pass_soft$(d)$

**EVENT** off_grn_soft$(d)$

**EVENT** off_red_soft$(d)$

# Physical Operations

$(p, d) \longleftarrow$ CARD_HARD

ACCEPT_HARD$(d)$

REFUSE_HARD$(d)$

$d \longleftarrow$ PASS_HARD

$d \longleftarrow$ OFF_GRN_HARD

$d \longleftarrow$ OFF_RED_HARD

ACKN_HARD$(d)$

# Network Software Operations

$(p, d) \longleftarrow$ read_card

write_accept$(d)$

write_refuse$(d)$

$d \longleftarrow$ read_pass

$d \longleftarrow$ read_off_grn

$d \longleftarrow$ read_off_red

write_ackn$(d)$

# Network Physical Operations

SEND_CARD$(p, d)$

d $\longleftarrow$ RCV_ACCEPT

d $\longleftarrow$ RCV_REFUSE

SEND_PASS$(d)$

SEND_OFF_GRN$(d)$

SEND_OFF_RED$(d)$

d $\longleftarrow$ RCV_ACKN

**EVENT** CARD $\widehat{=}$
  **VAR** $p, d$ **IN**
    $(p, d) \longleftarrow$ READ_HARD;
    SEND_CARD$(p, d)$
  **END**

**EVENT** accept_refuse $\widehat{=}$
  **VAR** $p, d, b$ **IN**
    $(p, d) \longleftarrow$ read_card;
    $b \longleftarrow$ **EVENT** test_soft$(p, d)$;
    **IF** $b =$ true **THEN** **EVENT** accept_soft$(p, d)$; write_accept$(d)$
    **ELSE** **EVENT** refuse_soft$(d)$; write_refuse$(d)$ **END**
  **END**

**EVENT** ACCEPT $\widehat{=}$
  **VAR** $d$ **IN**
    $d \longleftarrow$ RCV_ACCEPT;
    ACCEPT_HARD$(d)$
  **END**

**EVENT** REFUSE $\widehat{=}$
  **VAR** $d$ **IN**
    d $\longleftarrow$ RCV_REFUSE;
    REFUSE_HARD$(q)$
  **END**

**EVENT** PASS $\widehat{=}$
**VAR** $d$ **IN**
$d \longleftarrow$ PASS_HARD;
SEND_PASS($d$)
**END**

**EVENT** OFF_GRN $\widehat{=}$
**VAR** $d$ **IN**
$d \longleftarrow$ OFF_GRN_HARD;
SEND_OFF_GRN($d$)
**END**

**EVENT** OFF_RED $\widehat{=}$
**VAR** $d$ **IN**
$d \longleftarrow$ OFF_RED_HARD;
SEND_OFF_RED($d$)
**END**

**EVENT** observation $\widehat{=}$
**VAR** $d$ **IN**
$d \longleftarrow$ read_pass;
**EVENT** pass_soft($d$);
write_ackn($d$)
**END**

**EVENT** off_grn $\widehat{=}$
**VAR** $d$ **IN**
$d \longleftarrow$ read_off_grn;
**EVENT** off_grn_soft($d$);
write_ackn($d$)
**END**

**EVENT** off_red $\widehat{=}$
**VAR** $d$ **IN**
$d \longleftarrow$ read_off_red;
**EVENT** off_red_soft($d$);
write_ackn($d$)
**END**

**EVENT** ACKN $\widehat{=}$
**VAR** $d$ **IN**
d $\longleftarrow$ RCV_ACKN;
ACKN_HARD($d$)
**END**

# Conclusion

22 Properties et 6 “System” Decisions - One Problem Generalization
- Access between locations
- One Negative Choice :
- Possible Card Readers Obstructions
- Three Physical Decisions
- Automatic Blocking of Doors
- Automatic Blocking of Card Readers
- Setting up of Clocks on Doors
- The overall development required 183 proofs
- 147 automatic (80%)
- 36 interactive

# Current Section Summary


1. Refinement of models
2. Summary on Event-B
3. Case Study The Access Control (J.-R. Abrial)
4. Conclusion

# Conclusion

- Identify an abstract model
- Identify constants and states
- Identify components
- Plan the refinement
- Start as long as the model is not well defined !

# Generalization of the Access Control Problem

- $A$ is a variable which can be modified by events mdeolling the administration of the access control model :
  - adding authorizations to a set of persons
  - removing or deleting authorizations of a set of persons
- Generalizing to other problems :
  - a set of users U has access to a set of resources R.
  - a set of rooms R is managed by a set of keycards K.
  - a set of users U has access to a set of services S.