

## ML Practical : 03

Title: Given a bank customer, build a neural network-based classifier that can determine whether they will leave or not in the next 6 months. Dataset Description: The case study is from an open-source dataset from Kaggle. The dataset contains 10,000 sample points with 14 distinct features such as CustomerId, CreditScore, Geography, Gender, Age, Tenure, Balance, etc. Link to the Kaggle project: <https://www.kaggle.com/barelydedicated/bank-customer-churn-modeling>

Perform following steps:

- Read the dataset.
- Distinguish the feature and target set and divide the data set into training and test sets. Normalize the train and test data.
- Initialize and build the model. Identify the points of improvement and implement the same. Print the accuracy score and confusion matrix (5 points).

```
import numpy as np
np.set_printoptions(threshold=np.inf)
import matplotlib.pyplot as plt
import pandas as pd
```

```
# Importing the dataset
dataset = pd.read_csv('/content/Churn_Modelling.csv')
```

```
dataset.head()
```

	RowNumber	CustomerId	Surname	CreditScore	Geography	Gender	Age	Tenure	Ba
0	1	15634602	Hargrave	619	France	Female	42	2	
1	2	15647311	Hill	608	Spain	Female	41	1	838
2	3	15619304	Onio	502	France	Female	42	8	1596
3	4	15701354	Boni	699	France	Female	39	1	
4	5	15737888	Mitchell	850	Spain	Female	43	2	1255

```
dataset.tail()
```

	RowNumber	CustomerId	Surname	CreditScore	Geography	Gender	Age	Tenure
<b>9995</b>	9996	15606229	Obijiaku	771	France	Male	39	5
<b>9996</b>	9997	15569892	Johnstone	516	France	Male	35	10
<b>9997</b>	9998	15584532	Liu	709	France	Female	36	7
<b>9998</b>	9999	15682355	Sabbatini	772	Germany	Male	42	3
<b>9999</b>	10000	15628319	Walker	792	France	Female	28	4

dataset.info()

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 10000 entries, 0 to 9999
Data columns (total 14 columns):
#   Column                Non-Null Count  Dtype
---  -
0   RowNumber             10000 non-null  int64
1   CustomerId            10000 non-null  int64
2   Surname                10000 non-null  object
3   CreditScore            10000 non-null  int64
4   Geography              10000 non-null  object
5   Gender                 10000 non-null  object
6   Age                    10000 non-null  int64
7   Tenure                 10000 non-null  int64
8   Balance                10000 non-null  float64
9   NumOfProducts          10000 non-null  int64
10  HasCrCard              10000 non-null  int64
11  IsActiveMember         10000 non-null  int64
12  EstimatedSalary         10000 non-null  float64
13  Exited                  10000 non-null  int64
dtypes: float64(2), int64(9), object(3)
memory usage: 1.1+ MB
```

dataset.shape

(10000, 14)

dataset.isnull().sum()

```
RowNumber      0
CustomerId      0
Surname         0
CreditScore     0
Geography       0
Gender          0
Age             0
Tenure          0
Balance         0
NumOfProducts  0
HasCrCard       0
IsActiveMember  0
EstimatedSalary 0
Exited          0
dtype: int64
```

```
dataset.describe()
```

	RowNumber	CustomerId	CreditScore	Age	Tenure	Bala
<b>count</b>	10000.00000	1.000000e+04	10000.000000	10000.000000	10000.000000	10000.000
<b>mean</b>	5000.50000	1.569094e+07	650.528800	38.921800	5.012800	76485.889
<b>std</b>	2886.89568	7.193619e+04	96.653299	10.487806	2.892174	62397.405
<b>min</b>	1.00000	1.556570e+07	350.000000	18.000000	0.000000	0.000
<b>25%</b>	2500.75000	1.562853e+07	584.000000	32.000000	3.000000	0.000
<b>50%</b>	5000.50000	1.569074e+07	652.000000	37.000000	5.000000	97198.540
<b>75%</b>	7500.25000	1.575323e+07	718.000000	44.000000	7.000000	127644.240
<b>max</b>	10000.00000	1.581569e+07	850.000000	92.000000	10.000000	250898.090

```
X = dataset.iloc[:, 3:13].values
y = dataset.iloc[:, 13].values
```

```
print(X[:10,:], '\n')
```

```
print(y[:10])
```

```
[[[619 'France' 'Female' 42 2 0.0 1 1 1 101348.88]
[608 'Spain' 'Female' 41 1 83807.86 1 0 1 112542.58]
[502 'France' 'Female' 42 8 159660.8 3 1 0 113931.57]
[699 'France' 'Female' 39 1 0.0 2 0 0 93826.63]
[850 'Spain' 'Female' 43 2 125510.82 1 1 1 79084.1]
[645 'Spain' 'Male' 44 8 113755.78 2 1 0 149756.71]
[822 'France' 'Male' 50 7 0.0 2 1 1 10062.8]
[376 'Germany' 'Female' 29 4 115046.74 4 1 0 119346.88]
[501 'France' 'Male' 44 4 142051.07 2 0 1 74940.5]
[684 'France' 'Male' 27 2 134603.88 1 1 1 71725.73]]
```

```
[1 0 1 0 0 1 0 1 0 0]
```

```
from sklearn.preprocessing import LabelEncoder, OneHotEncoder
```

```
from sklearn.compose import ColumnTransformer
```

```
# Country
```

```
labelencoder_X = LabelEncoder()
```

```
X[:, 1] = labelencoder_X.fit_transform(X[:, 1])
```

```
# Gender
```

```
labelencoder_X_2 = LabelEncoder()
```

```
X[:, 2] = labelencoder_X_2.fit_transform(X[:, 2])
```

```
# Giving ordinal feature to our variables
```

```
onehotencoder = ColumnTransformer([("Country", OneHotEncoder(), [1])], remainder = 'passth
```

```
X = onehotencoder.fit_transform(X)
```

```
X = X[:, 1:]
```

```
print(X[:10,:], '\n')
print(y[:10])

[[0.0 0.0 619 0 42 2 0.0 1 1 1 101348.88]
 [0.0 1.0 608 0 41 1 83807.86 1 0 1 112542.58]
 [0.0 0.0 502 0 42 8 159660.8 3 1 0 113931.57]
 [0.0 0.0 699 0 39 1 0.0 2 0 0 93826.63]
 [0.0 1.0 850 0 43 2 125510.82 1 1 1 79084.1]
 [0.0 1.0 645 1 44 8 113755.78 2 1 0 149756.71]
 [0.0 0.0 822 1 50 7 0.0 2 1 1 10062.8]
 [1.0 0.0 376 0 29 4 115046.74 4 1 0 119346.88]
 [0.0 0.0 501 1 44 4 142051.07 2 0 1 74940.5]
 [0.0 0.0 684 1 27 2 134603.88 1 1 1 71725.73]]

[1 0 1 0 0 1 0 1 0 0]
```

```
X.shape
```

```
(10000, 11)
```

```
from sklearn.model_selection import train_test_split
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size = 0.2, random_state =
```

```
from sklearn.preprocessing import StandardScaler
sc = StandardScaler()
X_train = sc.fit_transform(X_train)
X_test = sc.transform(X_test)
```

```
import keras
import sys
from keras.models import Sequential #to initialize NN
from keras.layers import Dense #used to create layers in NN
from keras.layers import Dropout
```

```
classifier = Sequential()
```

```
classifier.add(Dense(units = 6, kernel_initializer = 'uniform', activation = 'relu', input
classifier.add(Dropout(rate=0.1))
```

```
classifier.add(Dense(units = 6, kernel_initializer = 'uniform', activation = 'relu'))
classifier.add(Dropout(rate=0.1))
```

```
classifier.add(Dense(units = 1, kernel_initializer = 'uniform', activation = 'sigmoid'))
```

```
classifier.compile(optimizer = 'adam', loss= "binary_crossentropy", metrics=["accuracy"])
```

```
classifier.fit(X_train, y_train, batch_size = 10, epochs = 100 )
```

```
Epoch 1/100
800/800 [=====] - 3s 2ms/step - loss: 0.4854 - accuracy:
Epoch 2/100
800/800 [=====] - 2s 2ms/step - loss: 0.4350 - accuracy:
Epoch 3/100
800/800 [=====] - 2s 2ms/step - loss: 0.4279 - accuracy:
Epoch 4/100
800/800 [=====] - 2s 2ms/step - loss: 0.4274 - accuracy:
Epoch 5/100
800/800 [=====] - 2s 2ms/step - loss: 0.4272 - accuracy:
Epoch 6/100
800/800 [=====] - 2s 2ms/step - loss: 0.4258 - accuracy:
Epoch 7/100
800/800 [=====] - 2s 2ms/step - loss: 0.4244 - accuracy:
Epoch 8/100
800/800 [=====] - 2s 2ms/step - loss: 0.4237 - accuracy:
Epoch 9/100
800/800 [=====] - 2s 2ms/step - loss: 0.4239 - accuracy:
Epoch 10/100
800/800 [=====] - 2s 2ms/step - loss: 0.4224 - accuracy:
Epoch 11/100
800/800 [=====] - 2s 2ms/step - loss: 0.4202 - accuracy:
Epoch 12/100
800/800 [=====] - 2s 2ms/step - loss: 0.4201 - accuracy:
Epoch 13/100
800/800 [=====] - 2s 2ms/step - loss: 0.4207 - accuracy:
Epoch 14/100
800/800 [=====] - 2s 2ms/step - loss: 0.4199 - accuracy:
Epoch 15/100
800/800 [=====] - 2s 2ms/step - loss: 0.4200 - accuracy:
Epoch 16/100
800/800 [=====] - 2s 2ms/step - loss: 0.4216 - accuracy:
Epoch 17/100
800/800 [=====] - 2s 2ms/step - loss: 0.4234 - accuracy:
Epoch 18/100
800/800 [=====] - 2s 2ms/step - loss: 0.4204 - accuracy:
Epoch 19/100
800/800 [=====] - 2s 2ms/step - loss: 0.4194 - accuracy:
Epoch 20/100
800/800 [=====] - 2s 2ms/step - loss: 0.4200 - accuracy:
Epoch 21/100
800/800 [=====] - 2s 2ms/step - loss: 0.4191 - accuracy:
Epoch 22/100
800/800 [=====] - 2s 2ms/step - loss: 0.4174 - accuracy:
Epoch 23/100
800/800 [=====] - 2s 2ms/step - loss: 0.4227 - accuracy:
Epoch 24/100
800/800 [=====] - 2s 2ms/step - loss: 0.4189 - accuracy:
Epoch 25/100
800/800 [=====] - 2s 2ms/step - loss: 0.4190 - accuracy:
Epoch 26/100
800/800 [=====] - 2s 2ms/step - loss: 0.4200 - accuracy:
Epoch 27/100
800/800 [=====] - 2s 2ms/step - loss: 0.4189 - accuracy:
Epoch 28/100
800/800 [=====] - 2s 2ms/step - loss: 0.4198 - accuracy:
Epoch 29/100
```

y\_pred

```
array([[False],
```

[raise],

```
[False],
[False],
[False],
```

```
from sklearn.metrics import confusion_matrix
cm = confusion_matrix(y_test, y_pred)
```

```
cm
```

```
array([[1546,   49],
       [ 274,  131]])
```

```
from sklearn.metrics import confusion_matrix, accuracy_score, precision_score, recall_score
```

```
print("F1 Score: ",f1_score(y_test,y_pred))
```

```
F1 Score:  0.4478632478632479
```

```
print("Accuracy: ",accuracy_score(y_test,y_pred))
```

```
Accuracy:  0.8385
```

```
print("Precision: ",precision_score(y_test,y_pred))
```

```
print("Recall: ",recall_score(y_test,y_pred))
```

```
Precision:  0.7277777777777777
```

```
Recall:  0.3234567901234568
```

```
print("Error Rate: ",1-accuracy_score(y_test,y_pred))
```

```
Error Rate:  0.16149999999999998
```

```
"""Predict if the customer with the following informations will leave the bank:
```

```
Geography: France
```

```
Credit Score: 600
```

```
Gender: Male
```

```
Age: 40
```

```
Tenure: 3
```

```
Balance: 60000
```

```
Number of Products: 2
```

```
Has Credit Card: Yes
```

```
Is Active Member: Yes
```

```
Estimated Salary: 50000"""
```

```
new_prediction = classifier.predict(sc.transform(np.array([[0.0, 0, 600, 1, 40, 3, 60000,
```

```
new_prediction = (new_prediction > 0.5)
```

```
new_prediction
```

```
1/1 [=====] - 0s 19ms/step
```

```
array([[False]])
```

```

import keras
import sys
from keras.models import Sequential #to initialize NN
from keras.layers import Dense #used to create layers in NN

#Evaluating the ANN
from keras.wrappers.scikit_learn import KerasClassifier
from sklearn.model_selection import cross_val_score

def build_classifier():
    classifier = Sequential()
    classifier.add(Dense(units = 6, kernel_initializer = 'uniform', activation = 'relu', i
    classifier.add(Dense(units = 6, kernel_initializer = 'uniform', activation = 'relu'))
    classifier.add(Dense(units = 1, kernel_initializer = 'uniform', activation = 'sigmoid'
    classifier.compile(optimizer = 'adam', loss= "binary_crossentropy", metrics=["accuracy"])

#fit our model to the training data using KerasClassifier
classifier = KerasClassifier(build_fn = build_classifier, batch_size = 10, epochs = 100

#estimator - object to fit the data
#X - data to fit
#y - Target variable to try to predict
#cv - number of train test folds
#n_jobs - number of CPUs to use to do the computation. -1 means 'all CPUs'
accuracies = cross_val_score(estimator = classifier, X = X_train, y = y_train, cv = 10, n_

```

```

/usr/local/lib/python3.7/dist-packages/ipykernel_launcher.py:18: DeprecationWarning:
/usr/local/lib/python3.7/dist-packages/sklearn/model_selection/_validation.py:372: F
10 fits failed out of a total of 10.
The score on these train-test partitions for these parameters will be set to nan.
If these failures are not expected, you can try to debug them by setting error_score

```

Below are more details about the failures:

-----  
10 fits failed with the following error:

Traceback (most recent call last):

```

File "/usr/local/lib/python3.7/dist-packages/sklearn/model_selection/_validation.p
estimator.fit(X_train, y_train, **fit_params)

```

```

File "/usr/local/lib/python3.7/dist-packages/keras/wrappers/scikit_learn.py", line
return super(KerasClassifier, self).fit(x, y, **kwargs)

```

```


File "/usr/local/lib/python3.7/dist-packages/keras/wrappers/scikit_learn.py", line
if (losses.is_categorical_crossentropy(self.model.loss) and
AttributeError: 'NoneType' object has no attribute 'loss'

```

```

warnings.warn(some_fits_failed_message, FitFailedWarning)

```





[Colab paid products](#) - [Cancel contracts here](#)

