

TECHNICAL SPECIFICATIONS**SOLVENT ACETAT DE ETIL**

Parameter	Units	Value	Test Method
Ethyl Acetate	% mass	99.7 min	GC method
Ethanol	% mass	0.01 max	GC method
Water content	% mass	0.03 max	ASTM D 1364 DIN 51777 using suitable Karl Fischer titrator
Appearance		Clear colourless liquid free from matter of suspension	ASTM D 2090
Colour	Hazen units	10 max	ASTM D 1209
Acidity (as Acetic Acid)	% mass	0,002 max	ASTM D 1613
Odour		Characteristic	ASTM D 1296
Density at 20°C	g/ml	0.899 - 0.901	ASTM D 4052
Refractive index at 20°C		1.371 – 1.373	DIN 51423
Residue on evaporation	% mass	0,002 max	DIN 53172 ASTM D 1353
Distillation range (1013 bar)	°C	76.5 min	DIN 53172
Initial boiling point (IBP)	°C	77.0 max	
Dry point (DP)	°C	77.0 max	
Miscibility with water		Complete	BS 6392/5
Permanganate time	Minutes	20 min	BS 6392/9
Density in vacuum	Kg/l at 20°C	0.8251 min 0.8268 max	ASTM D4052

*The technical data are used solely to describe the product and are not subject to constant monitoring.