

## TECHNICAL SPECIFICATIONS

### SOLVENT ETOSSIPROPANOL

|                             |                                                                                                                                                                                                                                                    |                   |        |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|--------|
| <b>Product description:</b> | Colorless liquid solvent. Ethoxypropanol is chemically 1-ethoxy-2-propanol, an ether of 1,2-propylene glycol with ethanol, an ether alcohol. Due to its non-toxic properties, ethylene glycol ethers are an important substitute for solvent inks. |                   |        |
| <b>Use:</b>                 | Paint industry, Rubber and plastic industry, Printing industry, Pharmaceutical industry. Solvent inks, inks and adhesives as a drying retardant solvent.                                                                                           |                   |        |
| <b>Technical data:</b>      | Color:                                                                                                                                                                                                                                             | Colorless         |        |
|                             | Smell:                                                                                                                                                                                                                                             | Characteristic    |        |
|                             | Density :                                                                                                                                                                                                                                          | 0,895-0,900 g/cm3 | ± 0.10 |
| <b>General advice:</b>      | Mixture may charge electrostatically: always use earthing leads when transferring from one container to another.<br>Operators should wear antistatic footwear and clothing and floors should be of the conducting type.                            |                   |        |
| <b>Safety:</b>              | Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.                                                                                |                   |        |
| <b>Storage:</b>             | Never use pressure to empty. Container is not a pressure vessel.<br>Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws..                                                    |                   |        |