PACK NODE (A19): MODULE CURRENT OVER THE DOCK PINS
CHARGER BQ25792 (SHORE_12V, MEZZANINE, JEITA ON THE MODULE THERMISTOR) + DOCK SIGNAL PINS
GAUGE BQ34Z100-G1 (0x55)
RAIL M1: F3 + TPS61288L 5.05 V (LOGIC, HUB, PCB-B M1)
RAIL M2: F4 + TPS61288L 5.05 V (PCB-B M2)
RAIL PI: F5 + TPS61288L 5.1 V 5 A
MAIN POWER CONTROL LTC2954 + HEATING PAD SWITCH
3.3 V BUCK TPS563201 FROM M1, TEST POINTS, FLAGS

MESHSAT-709 / MESHSAT-789. A19 (4 Sep 2026 rulings, appendix 32.13 to 32.25): the kit UPS. BQ2
Phase A2 schematic (A4: 16.3 fixes), generated by tools/gen_sch_a.py. Netlist style: every pin carries
MeshSat
Sheet: /
File: pcb-a-power.kicad_sch

Title: MeshSat Field Kit carrier – PCB-A POWER + I/O

Size: A0 | Date: 2026-09-05 | **Rev: A**
KiCad E.D.A. 9.0.9 | Id: 1/1