POWER INPUT, RAILS, TEST POINTS

USB 2.0 HUB FE1.1s + UPSTREAM PORTS

CH1 SDR BAY: RTL-SDR V4 or LimeSDR Mini 2.0 (0x40)CH2 ZIGBEE (0x41)

CH3 LoRa: XIAO Wio-SX1262 or T-BEAM 1W (0x45, 2A)CH4 ROCKBLOCK 5V (0x42, 2A)

CH5 T-CALL LTE (0x44, 2A)

I2C EXPANDER PCA9555 (0x20): EN + FAULT

PANEL RIBBON (PCB-C CONTROL PANEL)

DCF77 + A-B INTERCONNECT

ROCKBLOCK SITE: UART SELECT, 9704 + 9603 CONNECTORS, On/Off BUFFER

PI 5 GPIO RIBBON

MESHSAT-709, B11: +5V from the PCB-A module-rail boost over J_5V_MOD (VH); the X1202 UPS output is not used. Phase B2 schematic (B12: no X1202, three rails from PCB-A). generated by tools/gen_sch_b.py. Netlist-driven.

Project	MeshSat
Sheet	/
File	pcb-b-compute.kicad_sch
Title	MeshSat Field Kit carrier — PCB-B COMPUTE
Size	A3
Date	2026-05-02
Rev	A
KiCad	10.0.1