PACK NODE (A17): WELDED 1S8P PACK IN PARALLEL WITH STEMMA QT, 5 V MODULE RAIL (TPS61089 BOOST FROM THE CELL NODE, EN FROM THE X1202 5 V SENSE (J_AB1.12), 3V_A RAIL FROM PCB-B, 3.3 V LDO, TEST POINTS, FLAGS

USB 2.0 HUB FE1.1s (upstream over J_AB1)

CH2 GPS (0x47)

CH3 MEZZANINE CODEC (0x48)

CH4 MEZZANINE UART (0x49)

I2C EXPANDER PCA9555 (0x21): EN, LEDs, FAULTS, SPARES

CH1 WIFI (0x46)

MEZZANINE HARNESS + A–B INTERCONNECT + DOCK

MESHSAT-709. A17: 5 V module rail (F3, TPS61089 boost from the cell node, EN from the X1202 5 V sense J_AB1.12, 3V_A rail from PCB-B, 3.3 V LDO, test points, flags). Phase A2 schematic (2A: 16.3 fuses), generated by tools/gen_sch_a.py. Netlist style: every pin carries its net.

MeshSat

Sheet: /

File: pcb-a-power.kicad_sch

Title: MeshSat Field Kit carrier — PCB-A POWER + I/O

Size: A2	Date: 2026-09-02	Rev: A
KiCad 7.0.A, 9.0.9		Id: 1/1