HARNESS, 5 V ENTRY, 3.3 V LDO, EXCITER SUPPLY

USB AUDIO CODEC PCM2912A, HEADPHONE AMPLIFIER, MIC PREAMP, HEADSET LEADS

SA868 EXCITER, UART BRIDGE, T/R RELAY, 10 dB PAD, LPF, PA LEADS, GATE BIAS SWITCH

PTT AND EMCON LOGIC, PTT MIRROR, LEDS, EXPANDER 0x26 WITH LEVEL STAGES, TEST POINTS, FLAGS

USB HUB TUSB2046B, PORT TERMINATIONS, SPARE PORT

Please DB schematic (SA868 exciter, T/R relay and low-pass filter, the 30 W PA on the face plate, USB audio codec PCM2912A, headphone amplifier, mic preamp, headset leads, PTT and EMCON logic, PTT mirror, LEDs, expander 0x26 with level stages, test points, flags, USB hub TUSB2046B, port terminations, spare port, USB-UART bridge (SAU), 3.3 V LDO, harness, 5 V entry, exciter supply

MeshSat	
Sheet: / File: pcb-d-aprs.kicad_sch	
Title: MeshSat Field Kit carrier — PCB-D APRS MEZZANINE	
Size: A0	Date: 2026-05-07
KiCad 10.0.1	Rev: A Id: 1/1