PACK NODE OVER THE DOCK BLOCK (32.56): 9 A PINS, PRE-CHARGE PIN, DOCK SIGNAL PINS

FRONT END: LM5176 FROM THE 9 TO 36 V INPUT TO THE 20 V CHARGE BUS

CHARGER BQ25731: 4S FROM THE 20 V BUS INTO THE PACK NODE, I2C 0x6B

SLOT RAIL S1: AP64500 5.1 V + INA226 0x40

SLOT RAIL S2: AP64500 5.1 V + INA226 0x41

SLOT RAIL S3: AP64500 5.1 V + INA226 0x44

DEVICE RAIL: AP64500 5.1 V + INA226 0x45

3.3 V LOGIC: TPS62933

MESHSAT-709 / MESHSAT-789, A19 (4 Sep 2026 rulings, appendix 32.13 to 32.25): the kit UPS, BQ2
Phase A22 schematic (appendix 32.55 and 32.56: the B8-2590/U node, LM5176 front end and PA an

MeshSat

Sheet: /

File: pcb-a-power.kicad_sch

Title: MeshSat Field Kit carrier — PCB-A POWER + I/O

Size: A0 | Date: 2026-09-07 | Rev: A

KiCad 8.0.4 9.0.9 | Id: 1/1