

Technical drawing of a mechanical part, likely a flange or base plate, showing dimensions and features.

Overall Dimensions:

- Total Width: 344.0
- Total Height: 228.0

Key Features and Dimensions:

- Top Section:** A series of small rectangular features (possibly holes or slots) are arranged along the top edge, with a total width of 15.0.
- Left Side Features:** Four circular features are arranged vertically on the left side, with a total height of 15.0.
- Right Side Features:** A series of rectangular features (possibly holes or slots) are arranged vertically on the right side, with a total width of 15.0.
- Bottom Section:** A series of rectangular features (possibly holes or slots) are arranged along the bottom edge, with a total width of 15.0.
- Internal Features:** The drawing shows internal structural details, including a central rectangular area and various smaller rectangular features.

1st floor plan of the 'J' panel, showing a large rectangular area with dimensions 344.0 by 228.0. The plan includes various rooms and corridors, with dimensions for each. Key features include a large central hall (28.6 x 17.0), a large rectangular room (19.2 x 16.2), and several smaller rooms and corridors. The plan is color-coded: orange for the 'J' panel, green for the 'K' panel, and blue for the 'L' panel. The 'J' panel is labeled 'J. PANEL 9.6'.

HOLES 12 of 12 (drill 2.0 or more), centre in the case frame, mm			
ref	X	Y	drill/what
SW LIGHT	-150.00	-66.00	15.00 LIGHTING DAY/NIGHT/BLACKOUT toggle (APEN 5636ADK-2V, hinged safety cover; ruling 32.13); NKK H2044SD3A01 on the D3 splashproof bushing, its 0-ring (spare AT5166)
LEAD	-150.00	-70.00	15.00 LEAD locking toggle, maintained (APEN 5636ADK-2V, hinged safety cover; ruling 32.13); K front seal in the keyed 6.5 hole; ZEROIZE HW low wipe thru
SW EMCON	-150.00	-15.00	15.00 EMCON lockset toggle, maintained (APEN 5636ADK-2V, hinged safety cover; ruling 32.13); INHIBIT HW low and EMCON HW low; the same sensor; APEN 5636ADK-2V, hinged safety cover
SW S05	-150.00	-60.00	15.00 S05 locking toggle, maintained (APEN 5636ADK-2V, both positions locked, red boot, hinged safety cover part 32.50; ruling 32.13); K front seal in the keyed 6.5 hole
BZ1	-149.00	-97.00	28.60 IP67 panel-mount sounder, 5 V DC continuous, bezel gasket on the face, two flying leads (Floyd Bell MC-69-530-Q class)
J HSJ1	-118.00	-104.00	17.00 U-174/U headset jack 1 (Amphenol Nexus class, drawing owed): 17 mm hole through the backer, bushing nut below; its five leads run to D8 J HSJ1
J HSJ2	-92.00	-104.00	17.00 U-174/U headset jack 2 (Amphenol Nexus class, drawing owed): 17 mm hole through the backer, bushing nut below; its five leads run to D8 J HSJ2
CM HW1	140.00	100.00	2.20 M2 screw of the USB camera module (25 x 25 board, sheet owed) behind the plate's sealed window
SW TEST	-23.00	-104.00	12.50 C&K ATP19-SL1-603-B0SA-03G; white ring (C&K ATP19-SL1-603-B0SA-03G; silicone gasket washer under the bezel)
SW PI	150.00	60.00	19.20 PI 16 mm recessed momentary, amber ring (PI SHDN REQ to the modules through the controller); C&K ATP16-SL1-403-M0SA-04G; silicone gasket washer under the bezel
SW MAIN	150.00	60.00	19.20 MAIN PWR 19 mm momentary, green ring (to A22 J MAINSW); C&K ATP19-SL1-603-B0SA-03G; silicone gasket washer under the bezel
CAM H2	160.00	100.00	2.20 M2 screw of the USB camera module (25 x 25 board, sheet owed) behind the plate's sealed window

Dimensions in mm. Kit parts (this sheet): machined positions and outlines +0.10; the 3.0 face plate +0.13 and the 6.0 entry plates +0.20 (EN 485-4 class, standard not held, INFERRED); the setting leg's pad height +0.10; rebate depth and line +0.10; spot-face floors +0.10.

Pell: the 1450PFF sheet 1453-314-000 rev A states +0.76 on one-decimal and +0.25 on two-decimal mm (VERIFIED); drawing 1451-931 states no tolerance ("typical industry-standard tolerances apply"), so every case allowance is the session's (INFERRED, UNSTATED).

Industry-standard tolerances apply (v2) to ASME Y14.5M section 5.1 Verdict(s): a METRIC size with minimum with every unstated allowance taken twice, a sensitivity reading and not a bound on those allowances; an OPEN row rests on something no hold source gives. Nominal CAD establishes no fit, seal or alignment; checks T1 to T11 (CASE-MARGINS md section 5) do. Prototype: nothing on this sheet has been made, bought or fitted.

Heights are nominal library bodies at the committed placements; a board's plan tolerance is JLC's outline class (+0.2, not held) and the stack's placement +-1.0 by hand (INFERRED).

A3, mm
not to scale for measurement:
dimensions govern; use the
1:1 templates for marking