



**MANIPAL
UNIVERSITY**

School of Computer Science and Engineering
Department of Computer Science and Engineering

*An analytical study of AI-based methods for early detection of
throat cancer, with a proposed conceptual framework*

Submitted By:
MESHWA SUNIL PATEL
2427030282

Supervised By:
Dr. ONKAR SINGH

Problem statement

Throat cancer is caught too late, too often

- Throat cancer presents a significant diagnostic challenge, as its early symptoms are often subtle and non-specific, leading to detection at advanced stages when treatment outcomes are considerably less favorable
- Conventional diagnostic approaches rely on clinical examinations and specialized procedures, frequently associated with delayed detection and limited accessibility due to infrastructural and economic constraints
- With recent advancements in AI, there is growing potential to support early screening through analysis of diverse medical data sources such as voice signals, medical imaging, and clinical parameters
- Existing research remains fragmented, with a lack of structured analysis focused specifically on AI-driven methods for early detection of throat cancer
- To address this gap, the present study undertakes a systematic analysis of existing approaches, identifies key limitations, and proposes a conceptual framework outlining a potential direction for developing accessible and efficient AI-based screening systems

Motivation

The case for AI-driven screening

Survival rates

Early detection significantly improves patient outcomes, turning a late-stage crisis into a treatable condition.

Faster diagnosis

AI delivers faster, more consistent preliminary screening compared to manual review alone.

Scalable access

AI-powered tools can extend screening to underserved and resource-limited regions worldwide.

Objectives

This analytical study examines AI-driven approaches to throat cancer detection. Four objectives guide the scope and direction of the research.

Analyze methods

Review existing AI-based techniques currently applied to throat cancer detection across published studies.

Compare approaches

Evaluate machine learning and deep learning methods side by side, assessing accuracy, data needs, and clinical relevance.

Identify gaps

Pinpoint limitations, missing datasets, and underexplored techniques in the current body of literature.

System design

Understand architectural concepts behind AI-based screening pipelines for potential clinical deployment.

Literature overview

AI is now widely applied in cancer detection across radiology, pathology, and genomics. Its reach extends beyond any single cancer type, with cross-domain models gaining traction. Machine learning and deep learning are the primary analytical tools studied. Convolutional neural networks (CNNs), support vector machines (SVMs), and random forests appear most frequently in published work.

Imaging-based methods remain the dominant approach. CT, MRI, and endoscopic image analysis account for the majority of published datasets and model architectures. High accuracy rates, often above 90%, have been reported across several controlled studies. However, these results rely on curated datasets and may not generalize to clinical settings.

Literature review

STUDY	METHOD	KEY FINDING
2021 AI methods in head and neck cancer	AI-based diagnostic methods Comprehensive review of artificial intelligence techniques applied to head and neck cancer diagnosis	Comprehensive overview of AI-based diagnostic methods showing strong promise in clinical settings
2020 Deep learning for pharyngeal cancer detection	Deep learning on endoscopic images Applied deep learning models to analyze endoscopic imagery for cancer identification	High detection accuracy achieved when applying deep learning to endoscopic images of pharyngeal cancer
2024 Deep learning approaches review	Systematic review Comprehensive survey of deep learning techniques specifically targeting throat cancer detection	Systematic review confirming deep learning as a viable and advancing approach for throat cancer detection
2021 Single Shot MultiBox Detector (SSD)	SSD architecture Detection and localization of pharyngeal cancer using Single Shot MultiBox Detector model	SSD architecture effectively detected and localized pharyngeal cancer regions in medical imaging data

Key methods

Four dominant AI approaches emerge from the research, each addressing different aspects of throat cancer detection.

CNN image analysis

Convolutional Neural Networks extract spatial features from medical images to classify tissue as healthy or cancerous.

Traditional ML models

Support Vector Machines and Random Forests classify structured features with strong interpretability and lower computational cost.

Deep learning

Multi-layer architectures learn complex hierarchical patterns in medical data, improving diagnostic accuracy on large datasets.

Detection models

Object detection frameworks localize and delineate tumor regions within images, enabling precise spatial identification.

Research gap

Four critical gaps limit the clinical readiness of AI-based throat cancer detection.

Limited datasets

Studies rely on small, controlled datasets lacking diverse patient populations. Results may not generalize to real-world clinical conditions.

No standard benchmarks

There are no standardized evaluation benchmarks across studies, making it difficult to compare methods or replicate findings reliably.

Single-modal focus

Most research examines one data type in isolation. Multi-modal integration of voice, imaging, and clinical records remains largely unexplored.

Low interpretability

AI models function as black boxes. Without transparent reasoning, clinicians lack the trust needed to adopt these tools in diagnostic workflows.

01 Input

Raw medical data such as voice recordings or imaging scans enters the system

02 Preprocessing

Noise reduction and normalization prepare data for analysis

03 Feature extraction

Relevant patterns like MFCC coefficients are isolated from the cleaned data

04 Model

Trained classifiers such as SVM, CNN, or ANN analyze the extracted features

05 Output

The system produces a screening result: healthy or at-risk classification

Feature extraction (MFCC)

Audio signals are converted into numerical features using Mel-Frequency Cepstral Coefficients (MFCC). These coefficients capture frequency characteristics relevant to voice-based analysis and are widely used in audio-based AI systems for health screening.

Models in literature

Machine learning

SVM and Random Forest

Classical models suited for structured, tabular datasets.

Best applied when

- 1 . Dataset size is small to moderate
- 2 . Features are hand-crafted (e.g. MFCC vectors)
- 3 . Interpretability and speed are priorities
- 4 . Detection task uses pre-extracted numeric features

Deep learning

Convolutional Neural Networks (CNN)

Learns patterns directly from raw, unstructured inputs.

Best applied when

- 1 . Data is unstructured: images, spectrograms, audio
- 2 . Large labeled datasets are available
- 3 . Automatic feature learning is preferred
- 4 . Detection task requires spatial pattern recognition

MFCC Feature Representation




Figure 1. MFCC representation of audio signal showing variation of frequency components over time

Proof of concept

Raw audio transformed into machine-readable features, demonstrating the extraction process rather than a developed system.

Evaluation metrics

Each metric captures a different dimension of classifier quality. Together, they reveal whether a model is reliable enough for clinical use.

Accuracy

Overall correctness of predictions. Measures the proportion of all cases, both positive and negative, that the model classifies correctly.

Sensitivity

Ability to correctly identify positive cases. Also called recall, it captures how many true cancer cases the model successfully detects.

Specificity

Ability to correctly identify negative cases. Measures how well the model avoids false alarms by ruling out healthy patients accurately.

F1-score

Harmonic mean of precision and recall. Balances both measures into a single score, especially useful when class distributions are uneven.

Limitations

These limitations observed across the reviewed literature highlight key challenges that must be addressed before AI-based throat cancer screening can advance toward clinical deployment.

Limited datasets

Most reviewed studies relied on small, curated datasets that lack diversity, limiting generalizability of reported results.

Population bias

Studies often used homogeneous patient samples, raising concerns about model performance across different demographics and regions.

Black-box models

Many reviewed papers used deep learning models without addressing interpretability, making clinical adoption difficult to justify.

Hard to implement on real-world data

The methods discussed in the literature are difficult to replicate and deploy on real-world clinical data due to lack of standardized pipelines, limited open-source tools, and gaps between research settings and actual clinical

Future work

Research methodology

Develop a detailed methodology for AI-based throat cancer screening, from data collection to model validation.

Multi-modal fusion

Explore approaches that combine voice analysis, medical imaging, and clinical data for higher diagnostic accuracy.

Conceptual framework

Proposal of a conceptual framework in future semesters, outlining the architecture and design for an AI-based throat cancer screening system.

Research paper

Draft a research paper documenting findings and methodology.
Target: Semester 6

Conclusion

AI shows strong potential for early throat cancer detection by analyzing medical images, voice signals, and clinical data. Current methods achieve high accuracy in controlled settings but face significant challenges in real-world deployment.

Key barriers remain: limited datasets, lack of standardized evaluation, and low model interpretability. Multi-modal integration is still underexplored, yet represents one of the most promising research directions.

This study provides a structured understanding of existing AI approaches, identifies critical gaps in the literature, and outlines a conceptual framework for future development. It bridges fragmented research into a cohesive analytical foundation.

The groundwork is set for practical implementation in subsequent research phases.

References

- [1] H. Mahmood, M. Shaban, N. Rajpoot, and S. A. Khurram, "Artificial Intelligence-based methods in head and neck cancer diagnosis: an overview," *British Journal of Cancer*, vol. 124, pp. 1934–1940, 2021.
- [2] A. Tamashiro et al., "Application of deep learning for detection of pharyngeal cancer using endoscopic images," *Scientific Reports*, 2020.
- [3] "Deep learning approaches for throat cancer detection: A review," *IEEE Xplore*, 2024.
- [4] A. Tamashiro et al., "Deep learning-based detection and localization of pharyngeal cancer using Single Shot MultiBox Detector," *Scientific Reports*, 2021.

Thank you