Dependent Category and Subcategory Fields

Making Subcategory options change based on the selected Category

1. Objective

Right now, the Subcategory field shows **all** its options no matter which Category is selected. This milestone creates a **dependency** between the two fields: once a Category is chosen, the Subcategory list shows **only the options that belong to that Category**. This keeps ticket data accurate and prevents wrong combinations such as Category = Network with Subcategory = Projector.

2. Desired result

Category selected	Subcategory options shown
Network	Wi-Fi
Hardware	Projector
Access	Forgot password
Performance	Slow computer

3. Part A: Turn on the dependency

Step	Action
1	Open the **created table's form** and **right click** on the **Subcategory** field label.
2	Click **Configure Dictionary**.
3	Under **Related Links**, click **Advanced view**.
4	Go to the **Dependent Field** section.
5	Enable the checkbox **Use dependent field** (set it to true).
6	In **Dependent on field**, select **Category**.
7	Click **Save** (or Update).

Meaning: Subcategory now **depends on** Category, so its list filters using the Category value.

4. Part B: Link each Subcategory choice to its Category

On the same dictionary entry, scroll down to the **Choices** section. For each Subcategory choice, fill the **Dependent value** with the **backend value of the matching Category choice**.

Subcategory choice	Dependent value (Category backend value)
Wi-Fi	Network
Projector	Hardware

Subcategory choice	Dependent value (Category backend value)
Forgot password	Access
Slow computer	Performance

Then click **Save**.

5. How the dependent value works

- Every choice has a **label** (what the user sees) and a **value** (the backend name stored in the database).
- The **Dependent value** of a Subcategory choice must equal the **value** of a Category choice.
- When the user picks a Category, the form shows only the Subcategory choices whose dependent value matches it.
- If a Subcategory choice has no dependent value, it will not show under any specific Category.

Tip: open the Category field's choices first and copy the exact backend values (for example, *Network*, *Hardware*, *Access*, *Performance*). The Category choices must already exist, and the spelling and letter case must match exactly.

6. Keep it consistent with the Flow

The auto classify flow sets Category and Subcategory by value. So the values in the choice lists must match what the flow writes:

Flow sets	Choice must exist as
Network / Wi-Fi	Category value Network, Subcategory Wi-Fi
Hardware / Projector	Category value Hardware, Subcategory Projector
Access / Forgot Password	Category value Access, Subcategory Forgot Password
Performance / Slow computer	Category value Performance, Subcategory Slow computer

Note: your notes write 'Forgot password' here but 'Forgot Password' in the flow. Use **one spelling** in both places, otherwise the value set by the flow may not appear in the dropdown.

7. Testing

ID	Scenario	Expected result	Status
DF01	Open a new ticket and select Category = Network	Subcategory shows only Wi-Fi	Pass / Fail
DF02	Select Category = Hardware	Subcategory shows only Projector	Pass / Fail
DF03	Select Category = Access	Subcategory shows only Forgot password	Pass / Fail
DF04	Select Category = Performance	Subcategory shows only Slow computer	Pass / Fail

ID	Scenario	Expected result	Status
DF05	Change Category after choosing a Subcategory	Subcategory list updates to the new Category	Pass / Fail
DF06	Create a ticket through the flow (Projector case)	Hardware / Projector shows correctly after reload	Pass / Fail

8. Points to watch

- Refresh or reload the form after saving the dictionary changes, to see the new behavior.
- If the Subcategory list is empty, check that dependent values are filled and spelled exactly like the Category backend values.
- Dictionary changes are recorded in your current **Update Set**, so they get exported with the project during deployment.
- Add new categories the same way: create the Category choice first, then Subcategory choices with the matching dependent value.

Summary: Enable 'Use dependent field' on Subcategory with Category as the parent, then set each Subcategory choice's dependent value to its Category's backend value. After that, the Subcategory dropdown shows only the options that belong to the chosen Category.