

Normalization is the process of minimizing **redundancy** from a relation or set of relations. Redundancy in relation may cause insertion, deletion and updation anomalies. So, it helps to minimize the redundancy in relations. **Normal forms** are used to eliminate or reduce redundancy in database tables.

1. First Normal Form –

If a relation contain composite or multi-valued attribute, it violates first normal form or a relation is in first normal form if it does not contain any composite or multi-valued attribute. A relation is in first normal form if every attribute in that relation is **singled valued attribute**.

Example 1 – Relation STUDENT in table 1 is not in 1NF because of multi-valued attribute STUD_PHONE. Its decomposition into 1NF has been shown in table 2.

STUD_NO	STUD_NAME	STUD_PHONE	STUD_STATE	STUD_COUNTRY
1	RAM	9716271721, 9871717178	HARYANA	INDIA
2	RAM	9898297281	PUNJAB	INDIA
3	SURESH		PUNJAB	INDIA

Table 1

Conversion to first normal form

STUD_NO	STUD_NAME	STUD_PHONE	STUD_STATE	STUD_COUNTRY
1	RAM	9716271721	HARYANA	INDIA
1	RAM	9871717178	HARYANA	INDIA
2	RAM	9898297281	PUNJAB	INDIA
3	SURESH		PUNJAB	INDIA

Table 2

Example 2 –

ID	Name	Courses

1	A	c1, c2
2	E	c3
3	M	C2, c3

In the above table Course is a multi valued attribute so it is not in 1NF.

Below Table is in 1NF as there is no multi valued attribute

ID	Name	Course

1	A	c1
1	A	c2
2	E	c3
3	M	c2
3	M	c3

2. Second Normal Form –

To be in second normal form, a relation must be in first normal form and relation must not contain any partial dependency. A relation is in 2NF if it has **No Partial Dependency**, i.e., no non-prime attribute (attributes which are not part of any candidate key) is dependent on any proper subset of any candidate key of the table.

Partial Dependency – If the proper subset of candidate key determines non-prime attribute, it is called partial dependency.

Example 1 – Consider table-3 as following below.

STUD_NO	COURSE_NO	COURSE_FEE
1	C1	1000
2	C2	1500
1	C4	2000
4	C3	1000
4	C1	1000
2	C5	2000

{Note that, there are many courses having the same course fee. }

Here,

COURSE_FEE cannot alone decide the value of COURSE_NO or STUD_NO;
COURSE_FEE together with STUD_NO cannot decide the value of COURSE_NO;

COURSE_FEE together with COURSE_NO cannot decide the value of STUD_NO;

Hence,

COURSE_FEE would be a non-prime attribute, as it does not belong to the one only candidate key {STUD_NO, COURSE_NO} ;

But, COURSE_NO -> COURSE_FEE , i.e., COURSE_FEE is dependent on COURSE_NO, which is a proper subset of the candidate key. Non-prime attribute COURSE_FEE is dependent on a proper subset of the candidate key, which is a partial dependency and so this relation is not in 2NF.

To convert the above relation to 2NF,
we need to split the table into two tables such as :

Table 1: STUD_NO, COURSE_NO

Table 2: COURSE_NO, COURSE_FEE

Table 1		Table 2	
STUD_NO	COURSE_NO	COURSE_NO	COURSE_FEE
1	C1	C1	1000
2	C2	C2	1500
1	C4	C3	1000
4	C3	C4	2000
4	C1	C5	2000

NOTE: 2NF tries to reduce the redundant data getting stored in memory. For instance, if there are 100 students taking C1 course, we dont need to store its Fee as 1000 for all the 100 records, instead once we can store it in the second table as the course fee for C1 is 1000.

3. Third Normal Form –

A relation is in third normal form, if there is **no transitive dependency** for non-prime attributes as well as it is in second normal form. A relation is in 3NF if **at least one of the following condition holds** in every non-trivial function dependency $X \rightarrow Y$

1. X is a super key.
2. Y is a prime attribute (each element of Y is part of some candidate key).

STUD_NO	STUD_NAME	STUD_STATE	STUD_COUNTRY	STUD_AGE
1	RAM	HARYANA	INDIA	20
2	RAM	PUNJAB	INDIA	19
3	SURESH	PUNJAB	INDIA	21

Table 4

Transitive dependency – If $A \rightarrow B$ and $B \rightarrow C$ are two FDs then $A \rightarrow C$ is called transitive dependency.

4. Boyce-Codd Normal Form (BCNF) –

A relation R is in BCNF if R is in Third Normal Form and for every FD, LHS is super key. A relation is in BCNF iff in every non-trivial functional dependency $X \rightarrow Y$, X is a super key.