

Declare Your Language

Chapter 10: Virtual Machines & Code Generation


Eelco Visser

IN4303 Compiler Construction

TU Delft

November 2017

Virtual Machines & Code Generation



Outline

Linguistic Abstraction

- High-level programming languages abstract from low-level machine mechanics
- Abstractions in imperative and object-oriented languages
- Calling Conventions
- Register machines vs stack machines

Java Virtual Machine

- Architecture
- Operation stack
- Constant pool
- Local variables
- Heap
- Stack frames
- Class files

Code Generation Mechanics

- Printing strings
- String concatenation
- String interpolation
- Transformation

Reading Material

The Java® Virtual Machine Specification

Java SE 8 Edition

Tim Lindholm
Frank Yellin
Gilad Bracha
Alex Buckley

2015-02-13

Literature: VMs & Compilation

Java Virtual Machine

Tim Lindholm, Frank Yellin: The Java Virtual Machine Specification, 2nd edition. Addison-Wesley, 1999.

Bill Venners: Inside the Java 2 Virtual Machine. McGraw-Hill, 2000.

Activation Records

Andrew W. Appel, Jens Palsberg: Modern Compiler Implementation in Java, 2nd edition. 2002

Literature: Semantics of Programming Languages

Imperative Languages

- Carl A. Gunter: Semantics of Programming Languages: Structures and Techniques. MIT Press, 1992
- Kenneth C. Loudon: Programming Languages: Principles and Practice. Course Technology, 2002

Object-Oriented Languages

- Martin Abadi, Luca Cardelli: A Theory of Objects. Springer, 1996.
- Kim B. Bruce: Foundations of Object-Oriented Programming Languages: Types and Semantics. MIT Press, 2002.
- Timothy Budd: An Introduction to Object-Oriented Programming. Addison-Wesley, 2002.

State & Control

State

Machine state

- a pile of data stored in memory
- memory hierarchy: registers, RAM, disk, network, ...

Imperative program

- computation is series of changes to memory
- basic operations on memory (increment register)
- controlling such operations (jump, return address, ...)
- control represented by state (program counter, stack, ...)

Registers: x86 Family

General purpose registers

- accumulator **AX** - arithmetic operations
- counter **CX** - shift/rotate instructions, loops
- data **DX** - arithmetic operations, I/O
- base **BX** - pointer to data
- stack pointer **SP**, base pointer **BP** - top and base of stack
- source **SI**, destination **DI** - stream operations

Special purpose registers

- segments **SS**, **CS**, **DS**, **ES**, **FS**, **GS**
- flags **EFLAGS**

Example: x86 Assembler

mov AX [1]

read memory

mov CX AX

L: dec CX

mul CX

calculation

cmp CX 1

ja L

jump

mov [2] AX

write memory

Example: Java Bytecode

.method static public m(I)I

iload 1

ifne else

jump

iconst_1

ireturn

else:

iload 1

read memory

dup

iconst_1

isub

calculation

invokestatic Math/m(I)I

imul

ireturn

Memory & Control Abstractions

Memory abstractions

- variables: abstract over data storage
- expressions: combine data into new data
- assignment: abstract over storage operations

Control-flow abstractions

- structured control-flow: abstract over unstructured jumps
- ‘go to statement considered harmful’ Edgser Dijkstra, 1968

Example: C

<code>int f = 1</code>	variable
<code>int x = 5</code>	
<code>int s = f + x</code>	expression
<code>while (x > 1) {</code> <code>f = x * f ;</code> <code>x = x - 1</code> <code>}</code>	control flow
	assignment

Example: Tiger

/* factorial function */

let

var f := 1	variable
------------	----------

var x := 5	
------------	--

var s := f + x	expression
----------------	------------

in

while x > 1 do (control flow
------------------	--------------

f := x * f ;	
--------------	--

x := x - 1	assignment
------------	------------

)	
---	--

end

Procedures

Procedural Abstraction

Control-flow abstraction

- Procedure: named unit of computation
- Procedure call: jump to unit of computation and return

Memory abstraction

- Formal parameter: the name of the parameter
- Actual parameter: value that is passed to procedure
- Local variable: temporary memory

Recursion

- Procedure may (indirectly) call itself
- Consequence?

Example: Procedures in C

```
#include <stdio.h>
```

```
/* factorial function */
```

```
int fac(int num) {
```

formal parameter

```
    if (num < 1)
```

```
        return 1;
```

```
    else
```

```
        return num * fac(num - 1);
```

recursive call

```
}
```

```
int main() {
```

```
    int x = 10;
```

local variable

```
    int f = fac(x);
```

```
    printf("%d! = %d\n", x, f);
```

actual parameter

```
    return 0;
```

```
}
```

Procedures in Tiger

```
/* factorial function */
```

```
let
```

```
function fac( n: int ) : int =
```

formal parameter

```
let
```

```
var f := 1
```

local variable

```
in
```

```
if n < 1 then
```

```
  f := 1
```

```
else
```

```
  f := (n * fac(n - 1));
```

recursive call

```
  f
```

```
end
```

```
var f := 0
```

```
var x := 5
```

```
in
```

```
  f := fac(x)
```

actual parameter

```
end
```

Implementing Procedures with Stack and Stack Frames

Stack

- temporary storage
- grows from high to low memory addresses
- starts at **SS**

Stack frames

- return address
- local variables
- parameters
- stack base: **BP**
- stack top: **SP**

Reminder: Registers in x86 Family

General purpose registers

- accumulator **AX** - arithmetic operations
- counter **CX** - shift/rotate instructions, loops
- data **DX** - arithmetic operations, I/O
- base **BX** - pointer to data
- stack pointer **SP**, base pointer **BP** - top and base of stack
- source **SI**, destination **DI** - stream operations

Special purpose registers

- segments **SS**, **CS**, **DS**, **ES**, **FS**, **GS**
- flags **EFLAGS**

Example: Procedures in x86 Assembler

```
push 21
```

pass parameter

```
push 42
```

```
call _f
```

```
add SP 8
```

free parameters

```
push BP
```

new stack frame

```
mov BP SP
```

```
mov AX [BP + 8]
```

```
mov DX [BP + 12]
```

access parameter

```
add AX DX
```

```
pop BP
```

old stack frame

```
ret
```

Calling Conventions: CDECL

Caller

- push parameters right-to-left on the stack
- clean-up stack after call

```
push 21  
push 42  
call _f  
add ESP 8
```

Callee

- save old BP
- initialise new BP
- save registers
- return result in AX
- restore registers
- restore BP

```
push EBP  
mov EBP ESP  
mov EAX [EBP + 8]  
mov EDX [EBP + 12]  
add EAX EDX  
pop EBP  
ret
```

Calling Conventions: STDECL

caller

- push parameters right-to-left on the stack

```
push 21  
push 42  
call _f@8
```

callee

- save old BP
- initialise new BP
- save registers
- return result in AX
- restore registers
- restore BP

```
push EBP  
mov EBP ESP  
mov EAX [EBP + 8]  
mov EDX [EBP + 12]  
add EAX EDX  
pop EBP  
ret 8
```


Calling Conventions: FASTCALL

Caller

- passes parameters in registers
- pushes additional parameters right-to-left on the stack

```
mov    ECX 21  
mov    EDX 42  
call   @f@8
```

Callee

- save old BP, initialise new BP
- save registers
- return result in AX
- restore registers
- restore BP
- cleans up the stack

```
push   EBP  
mov     EBP ESP  
mov     EAX ECX  
add     EAX EDX  
pop     EBP  
ret
```

Calling Conventions

Procedure declarations

- in principle: full freedom
- project constraints
- target platform constraints

Procedure calls

- need to match procedure declarations

Precompiled libraries

- avoid recompilation
- source code not always available

Standardization

- compilers / high-level languages standardize use of calling conventions
- portable code: does not depend on particular calling convention

Object-Oriented Languages (home work)

Modularity: Objects & Messages

Objects

- generalisation of records
- identity
- state
- behaviour

Messages

- objects send and receive messages
- trigger behaviour
- imperative realisation: method calls

Modularity: Classes

Classes

- generalisation of record types
- characteristics of objects: attributes, fields, properties
- behaviour of objects: methods, operations, features

Encapsulation

- interface exposure
- hide attributes & methods
- hide implementation

```
public class C {  
    public int f1;  
    private int f2;  
    public void m1() { return; }  
    private C m2(C c) { return c; }  
}
```

Inheritance vs Interfaces

Inheritance

- inherit attributes & methods
- additional attributes & methods
- override behaviour
- nominative subtyping

Interfaces

- avoid multiple inheritance
- interface: contract for attributes & methods
- class: provide attributes & methods
- nominative subtyping

```
public class C {  
    public int f1;  
    public void m1() {...}  
    public void m2() {...}  
}  
  
public class D extends C {  
    public int f2;  
    public void m2() {...}  
    public void m3() {...}  
}  
  
public interface I {  
    public int f;  
    public void m();  
}  
  
public class E implements I {  
    public int f;  
    public void m() {...}  
    public void m'() {...}  
}
```

Polymorphism

Ad-hoc polymorphism

- overloading
 - same method name, independent classes
 - same method name, same class, different parameter types
- overriding
 - same method name, subclass, compatible types

Universal polymorphism

- subtype polymorphism
 - inheritance, interfaces
- parametric polymorphism

Static vs. Dynamic Dispatch

Dispatch

- link method call to method

Static dispatch

- type information at compile-time

Dynamic dispatch

- type information at run-time
- single dispatch: one parameter
- multiple dispatch: more parameters

Single Dispatch in Java

```
public class A {} public class B extends A {} public class C extends B {}
```

```
public class D {  
    public A m(A a) { System.out.println("D.m(A a)"); return a; }  
    public A m(B b) { System.out.println("D.m(B b)"); return b; }  
}
```

```
public class E extends D {  
    public A m(A a) { System.out.println("E.m(A a)"); return a; }  
    public B m(B b) { System.out.println("E.m(B b)"); return b; }  
}
```

```
A a = new A(); B b = new B(); C c = new C(); D d = new D(); E e = new E();  
    A ab = b;        A ac = c;                D de = e;
```

```
d. m(a); d. m(b); d. m(ab); d. m(c); d. m(ac);  
e. m(a); e. m(b); e. m(ab); e. m(c); e. m(ac);  
de.m(a); de.m(b); de.m(ab); de.m(c); de.m(ac);
```

Overriding

Methods

- parameter types
- return type

Covariance

- method in subclass
- return type: subtype of original return type

Contravariance

- method in subclass
- parameter types: supertypes of original parameter types

Overloading vs Overriding

```
public class F {  
    public A m(B b) { System.out.println("F.m(B b)"); return b; }  
}
```

```
public class G extends F {  
    public A m(A a) { System.out.println("G.m(A a)"); return a; }  
}
```

```
public class H extends F {  
    public B m(B b) { System.out.println("H.m(B b)"); return b; }  
}
```

```
A a = new A(); B b = new B(); F f = new F(); G g = new G(); H h = new H();  
    A ab = b;
```

```
f.m(b);  
g.m(a); g.m(b); g.m(ab);  
h.m(a); h.m(b); h.m(ab);
```

Invariance

```
public class X {  
    public A a;  
    public A    getA()    { return a ; }  
    public void setA(A a) { this.a = a ; }  
}
```

```
public class Y extends X {  
    public B a;  
    public B    getA()    { return a ; }  
    public void setA(B a) { this.a = a ; }  
}
```

```
A a = new A(); B b  = new B(); X y = new Y();
```

```
y.getA(); y.setA(b); y.setA(a);
```

```
String[] s = new String[3] ; Object[] o = s ; o[1] = new A();
```

Summary: Abstractions

Abstractions for Memory and Control

Imperative languages

- subroutines, routines, procedures, functions, methods
- scoping: local variables
- declarations with parameters (formal parameters)
- calls with arguments (actual parameters)
- pass by value, pass by reference

Machine code

- jumps: call and return
- call stack: return address, parameters, private data
- procedure prologue and epilogue

Imperative vs Object-Oriented

Imperative languages


- state & statements
- abstraction over machine code
- control flow & procedures
- types

Object-oriented languages


- objects & messages
- classes
- inheritance
- types

Java Virtual Machine: Architecture


JVM Architecture




JVM Architecture: Threads




JVM Architecture: Thread




JVM Architecture: Stack




JVM Architecture: Heap



JVM Architecture: Method Area



JVM Architecture: JVM Stack



Reverse Engineering the JVM Instruction Set

JVM: Control Flow

Bytecode Instructions: Goto

method area		
pc: 00		
00	A7	goto
01	00	
02	04	04
03	00	nop
04	A7	goto
05	FF	
06	FF	03

Bytecode Instructions: Goto

method area		
pc: 04		
00	A7	goto
01	00	
02	04	04
03	00	nop
04	A7	goto
05	FF	
06	FF	03

Bytecode Instructions: Goto

method area		
pc: 03		
00	A7	goto
01	00	
02	04	04
03	00	nop
04	A7	goto
05	FF	
06	FF	03

Bytecode Instructions: Goto

method area		
pc: 04		
00	A7	goto
01	00	
02	04	04
03	00	nop
04	A7	goto
05	FF	
06	FF	03

JVM: Operand Stack

Operand Stack

method area			stack	
pc: 00			optop: 00	
00	04	iconst_1	00	
01	05	iconst_2	01	
02	10	bipush	02	
03	2A		03	
04	11	sipush	04	
05	43		05	
06	03		06	

Operand Stack

method area			stack		
pc: 01			optop: 01		
00	04	iconst_1	00	0000	0001
01	05	iconst_2	01		
02	10	bipush	02		
03	2A		03		
04	11	sipush	04		
05	43		05		
06	03		06		

Operand Stack

method area			stack		
pc: 02			optop: 02		
00	04	iconst_1	00	0000	0001
01	05	iconst_2	01	0000	0002
02	10	bipush	02		
03	2A		03		
04	11	sipush	04		
05	43		05		
06	03		06		

Operand Stack

method area			stack		
pc: 04			optop: 03		
00	04	iconst_1	00	0000	0001
01	05	iconst_2	01	0000	0002
02	10	bipush	02	0000	002A
03	2A		03		
04	11	sipush	04		
05	43		05		
06	03		06		

Operand Stack

method area			stack		
pc: 07			optop: 04		
00	04	iconst_1	00	0000	0001
01	05	iconst_2	01	0000	0002
02	10	bipush	02	0000	002A
03	2A		03	0000	4303
04	11	sipush	04		
05	43		05		
06	03		06		

Operand Stack

method area			stack		
pc: 07			optop: 04		
07	60	iadd	00	0000	0001
08	68	imul	01	0000	0002
09	5F	swap	02	0000	002A
0A	64	isub	03	0000	4303
0B	9A	ifne	04		
0C	FF		05		
0D	F5	00	06		

Operand Stack

method area		
pc: 08		
07	60	iadd
08	68	imul
09	5F	swap
0A	64	isub
0B	9A	ifne
0C	FF	
0D	F5	00

stack		
optop: 03		
00	0000	0001
01	0000	0002
02	0000	432D
03		
04		
05		
06		

Operand Stack

method area			stack		
pc: 09			optop: 02		
07	60	iadd	00	0000	0001
08	68	imul	01	0000	865A
09	5F	swap	02		
0A	64	isub	03		
0B	9A	ifne	04		
0C	FF		05		
0D	F5	00	06		

Operand Stack

method area			stack		
pc: 0A			optop: 02		
07	60	iadd	00	0000	865A
08	68	imul	01	0000	0001
09	5F	swap	02		
0A	64	isub	03		
0B	9A	ifne	04		
0C	FF		05		
0D	F5	00	06		

Operand Stack

method area			stack		
pc: 0B			optop: 01		
07	60	iadd	00	0000	8659
08	68	imul	01		
09	5F	swap	02		
0A	64	isub	03		
0B	9A	ifne	04		
0C	FF		05		
0D	F5	00	06		

Operand Stack

method area			stack	
pc: 00			optop: 00	
00	04	iconst_1	00	
01	05	iconst_2	01	
02	10	bipush	02	
03	2A		03	
04	11	sipush	04	
05	43		05	
06	03		06	

JVM: Constant Pool

Constant Pool

method area				stack	
pc: 00		constant pool		optop: 00	
00	12	ldc	00 0000 002A	00	
01	00	00	01 0000 4303	01	
02	12	ldc	02 0000 0000	02	
03	01	01	03 0000 002A	03	
04	14	ldc2_w	04	04	
05	00		05	05	
06	02	02	06	06	

Constant Pool

method area				stack		
pc: 02		constant pool		optop: 01		
00	12	ldc	00 0000 002A	00	0000 002A	
01	00	00	01 0000 4303	01		
02	12	ldc	02 0000 0000	02		
03	01	01	03 0000 002A	03		
04	14	ldc2_w	04	04		
05	00		05	05		
06	02	02	06	06		

Constant Pool

method area				stack		
pc: 04		constant pool		optop: 02		
00	12	ldc	00 0000 002A	00	0000	002A
01	00	00	01 0000 4303	01	0000	4303
02	12	ldc	02 0000 0000	02		
03	01	01	03 0000 002A	03		
04	14	ldc2_w	04	04		
05	00		05	05		
06	02	02	06	06		

Constant Pool

method area				stack		
pc: 07		constant pool		optop: 04		
00	12	ldc	00 0000 002A	00	0000	002A
01	00	00	01 0000 4303	01	0000	4303
02	12	ldc	02 0000 0000	02	0000	0000
03	01	01	03 0000 002A	03	0000	002A
04	14	ldc2_w	04	04		
05	00		05	05		
06	02	02	06	06		

JVM: Local Variables

Local Variables

method area			stack	
pc: 00			optop: 00	local variables
00	04	iconst_1	00	00
01	3B	istore_0	01	01
02	1A	iload_0	02	02
03	3C	istore_1	03	03
04	84	iinc	04	04
05	01	01	05	05
06	01	01	06	06

Local Variables

method area			stack	
pc: 01			optop: 01	local variables
00	04	iconst_1	00 0000 0001	00
01	3B	istore_0	01	01
02	1A	iload_0	02	02
03	3C	istore_1	03	03
04	84	iinc	04	04
05	01	01	05	05
06	01	01	06	06

Local Variables

method area			stack	
pc: 02			optop: 00	local variables
00	04	iconst_1	00	00 0000 0001
01	3B	istore_0	01	01
02	1A	iload_0	02	02
03	3C	istore_1	03	03
04	84	iinc	04	04
05	01	01	05	05
06	01	01	06	06

Local Variables

method area			stack		
pc: 03			optop: 01		local variables
00	04	iconst_1	00 0000 0001	00 0000 0001	
01	3B	istore_0	01	01	
02	1A	iload_0	02	02	
03	3C	istore_1	03	03	
04	84	iinc	04	04	
05	01	01	05	05	
06	01	01	06	06	

Local Variables

method area			stack		
pc: 04			optop: 00	local variables	
00	04	iconst_1	00	0000	0001
01	3B	istore_0	01	0000	0001
02	1A	iload_0	02		
03	3C	istore_1	03		
04	84	iinc	04		
05	01	01	05		
06	01	01	06		

Local Variables

method area			stack		
pc: 07			optop: 00	local variables	
00	04	iconst_1	00	0000	0001
01	3B	istore_0	01	0000	0002
02	1A	iload_0	02		
03	3C	istore_1	03		
04	84	iinc	04		
05	01	01	05		
06	01	01	06		

JVM: Heap

Heap

method area				stack			
pc: 00		constant pool		optop: 00		local variables	
00	12	ldc	00 4303 4303	00		00	002A 002A
01	00	00	01 0000 0004	01		01	
02	19	aload	02	02		02	
03	00	00	03	03		03	
04	12	ldc	04	04		04	
05	01	01	05	05		05	
06	2E	iaload	06	06		06	

heap			
4303	4303	"Compilers"	002A 002A [20,01,40,02,42]

Heap

method area			
pc: 02		constant pool	
00	12	ldc	00 4303 4303
01	00	00	01 0000 0004
02	19	aload	02
03	00	00	03
04	12	ldc	04
05	01	01	05
06	2E	iaload	06

stack			
optop: 01		local variables	
00	4303	4303	00 002A 002A
01			01
02			02
03			03
04			04
05			05
06			06

heap			
4303	4303	"Compilers"	
002A	002A	[20,01,40,02,42]	

Heap

method area				stack			
pc: 04		constant pool		optop: 02		local variables	
00	12	ldc	00 4303 4303	00	4303 4303	00	002A 002A
01	00	00	01 0000 0004	01	002A 002A	01	
02	19	aload	02	02		02	
03	00	00	03	03		03	
04	12	ldc	04	04		04	
05	01	01	05	05		05	
06	2E	iaload	06	06		06	

heap			
4303	4303	"Compilers"	
002A	002A	[20,01,40,02,42]	

Heap

method area			
pc: 06		constant pool	
00	12	ldc	00 4303 4303
01	00	00	01 0000 0004
02	19	aload	02
03	00	00	03
04	12	ldc	04
05	01	01	05
06	2E	iaload	06

stack			
optop: 03		local variables	
00	4303	4303	00 002A 002A
01	002A	002A	01
02	0000	0004	02
03			03
04			04
05			05
06			06

heap			
4303	4303	"Compilers"	
002A	002A	[20,01,40,02,42]	

Heap

method area				stack			
pc: 07		constant pool		optop: 02		local variables	
00	12	ldc	00 4303 4303	00	4303 4303	00	002A 002A
01	00	00	01 0000 0004	01	0000 0042	01	
02	19	aload	02	02		02	
03	00	00	03	03		03	
04	12	ldc	04	04		04	
05	01	01	05	05		05	
06	2E	iaload	06	06		06	

heap	
4303 4303 "Compilers"	002A 002A [20,01,40,02,42]

JVM: Stack Frames

Static vs. Dynamic Dispatch

Dispatch

- link method call to method

Static dispatch

- type information at compile-time

Dynamic dispatch

- type information at run-time
- single dispatch: one parameter
- multiple dispatch: more parameters

Example: Static Call

```
function fac(n: int): int=  
  if  
    n = 0  
  then  
    1  
  else  
    n * fac(n - 1)
```

```
.class public Exp  
  
  .method public static fac(I)I  
  
    iload 1  
    ifne else  
  
    iconst_1  
    ireturn  
  
  else: iload 1  
        dup  
        iconst_1  
        isub  
        invokestatic Exp/fac(I)I  
        imul  
        ireturn  
  
  .end method
```

Example: Dynamic Call

```
function fac(n: int): int=  
  if  
    n = 0  
  then  
    1  
  else  
    n * fac(n - 1)
```

```
.class public Exp  
  
  .method public fac(I)I  
  
    iload 1  
    ifne else  
  
    iconst_1  
    ireturn  
  
  else: iload 0  
        iload 1  
        dup  
        iconst_1  
        isub  
        invokevirtual Exp/fac(I)I  
        imul  
        ireturn  
  
  .end method
```

Code Pattern: Dynamic Method Call

Caller

- push object
- push parameters left-to-right
- call method

Virtual machine on call

- allocate space (frame data, operand stack, local variables)
- store frame data (data pointer, return address, exception table)
- store parameters as local variables
- dynamic dispatch
- point pc to method code

Code Pattern: Return from Method Call


Callee

- parameters in local variables
- leave result on operand stack
- return to caller


Virtual machine on return

- push result on caller's operand stack
- point pc to return address
- destroy frame

Implementation: Heap-Based



Implementation: Stack-Based



Stack Frames

method area			stack		
pc: 03			optop: 02		local variables
00	2A	aload_0	00	4303 4303	00 4303 4303
01	10	bipush	01	0000 0040	01
02	40		02		02
03	B6	invokevirtual	03		03
04	00		04		04
05	01	01	05		05
06	AC	ireturn	06		06

heap		

Stack Frames

method area			stack		
pc: 80			optop: 00		local variables
80	2B	iload_1	00	00	4303 4303
81	59	dup	01	01	0000 0040
82	68	imul	02	02	
83	AC	ireturn	03	03	
84	00		04	04	
85	00		05	05	
86	00		06	06	

heap	

Stack Frames

method area			stack		
pc: 81			optop: 01		local variables
80	2B	iload_1	00	0000 0040	00 4303 4303
81	59	dup	01		01 0000 0040
82	68	imul	02		02
83	AC	ireturn	03		03
84	00		04		04
85	00		05		05
86	00		06		06
heap					

Stack Frames

method area			stack		
pc: 81			optop: 02		local variables
80	2B	iload_1	00	0000 0040	00 4303 4303
81	59	dup	01	0000 0040	01 0000 0040
82	68	imul	02		02
83	AC	ireturn	03		03
84	00		04		04
85	00		05		05
86	00		06		06

heap		

Stack Frames

method area			stack		
pc: 82			optop: 01		local variables
80	2B	iload_1	00	0000 1000	00 4303 4303
81	59	dup	01		01 0000 0040
82	68	imul	02		02
83	AC	ireturn	03		03
84	00		04		04
85	00		05		05
86	00		06		06
heap					

Stack Frames

method area			stack		
pc: 06			optop: 01		local variables
00	2A	aload_0	00	0000 1000	00 4303 4303
01	10	bipush	01		01
02	40		02		02
03	B6	invokevirtual	03		03
04	00		04		04
05	01	01	05		05
06	AC	ireturn	06		06

heap	

JVM: Class Files

Java Compiler

```
> ls
```

```
Course.java
```

```
> javac -verbose Course.java
```

```
[parsing started Course.java]
```

```
[parsing completed 8ms]
```

```
[loading java/lang/Object.class(java/lang:Object.class)]
```

```
[checking university.Course]
```

```
[wrote Course.class]
```

```
[total 411ms]
```

```
> ls
```

```
Course.class
```

```
Course.java
```

Class Files: Format

magic number **CAFEBABE**

class file version (minor, major)

constant pool count + constant pool

access flags

this class

super class

interfaces count + interfaces

fields count + fields

methods count + methods

attribute count + attributes

Jasmin Intermediate Language

```
.class public Exp

    .method public static fac(I)I

        iload 1
        ifne else

        iconst_1
        ireturn

    else: iload 1
        dup
        iconst_1
        isub
        invokestatic Exp/fac(I)I
        imul
        ireturn

    .end method
```

Optimization

Optimizations

Reasons

- code overhead
- execution overhead

Inlining

- replace calls by body of the procedure
- source code level

Tail recursion

- replace recursive calls by loops or jumps
- source or machine code level

Code Generation

```
function fac0(n0: int): int=  
  if  
    n0 = 0  
  then  
    1  
  else  
    n0 * fac0(n0 - 1)
```

```
.method public static fac0(I)I  
  
    iload 1  
    ldc 0  
    if_icmpeq label0  
    ldc 0  
    goto label1  
label0: ldc 1  
label1: ifeq else0  
        ldc 1  
        goto end0  
else0:  iload 1  
        iload 1  
        ldc 1  
        isub  
        invokestatic  
            Exp/fac0(I)I  
        imul  
end0:  ireturn  
.end method
```


Optimization

```
.method public static fac0(I)I
```

```
        iload 1
        ldc 0
        if_icmpeq label0
        ldc 0
        goto label1
label0: ldc 1
label1: ifeq else0
        ldc 1
        goto end0
else0:  iload 1
        iload 1
        ldc 1
        isub
        invokestatic
            Exp/fac0(I)I
        imul
end0:   ireturn
.end method
```

```
.method public static fac0(I)I
```

```
        iload_1
        ifne else0

        iconst_1
        ireturn

else0:  iload_1
        dup
        iconst_1
        isub
        invokestatic
            Exp/fac0(I)I
        imul
        ireturn
.end method
```

Optimization

```
.method public static fac0(I)I
```

```
    iload 1
    ldc 0
    if_icmpeq label0
    ldc 0
    goto label1
label0: ldc 1
label1: ifeq else0
    ldc 1
    goto end0
else0: iload 1
    iload 1
    ldc 1
    isub
    invokestatic
        Exp/fac0(I)I
    imul
end0: ireturn
.end method
```

```
.method public static fac0(I)I
```

```
    iload 1
    ifeq label0
    ldc 0
    goto label1
label0: ldc 1
label1: ifeq else0
    ldc 1
    goto end0
else0: iload 1
    iload 1
    ldc 1
    isub
    invokestatic
        Exp/fac0(I)I
    imul
end0: ireturn
.end method
```

Optimization

```
.method public static fac0(I)I
```

```
    iload 1  
    ifeq label0  
    ldc 0
```

```
    goto label1
```

```
label0: ldc 1
```

```
label1: ifeq else0
```

```
    ldc 1
```

```
    goto end0
```

```
else0: iload 1
```

```
    iload 1
```

```
    ldc 1
```

```
    isub
```

```
    invokestatic
```

```
        Exp/fac0(I)I
```

```
    imul
```

```
end0: ireturn
```

```
.end method
```

```
.method public static fac0(I)I
```

```
    iload 1  
    ifeq label0  
    ldc 0
```

```
    ifeq else0
```

```
label0: ldc 1
```

```
label1: ifeq else0
```

```
    ldc 1
```

```
    goto end0
```

```
else0: iload 1
```

```
    iload 1
```

```
    ldc 1
```

```
    isub
```

```
    invokestatic
```

```
        Exp/fac0(I)I
```

```
    imul
```

```
end0: ireturn
```

```
.end method
```

Optimization

```
.method public static fac0(I)I
```

```
    iload 1  
    ifeq label0
```

```
    ldc 0  
    ifeq else0
```

```
label0: ldc 1
```

```
label1: ifeq else0
```

```
    ldc 1  
    goto end0
```

```
else0: iload 1
```

```
    iload 1  
    ldc 1
```

```
    isub  
    invokestatic
```

```
        Exp/fac0(I)I
```

```
    imul
```

```
end0: ireturn
```

```
.end method
```

```
.method public static fac0(I)I
```

```
    iload 1  
    ifeq label0
```

```
    goto else0
```

```
label0: ldc 1
```

```
label1: ifeq else0
```

```
    ldc 1
```

```
    goto end0
```

```
else0: iload 1
```

```
    iload 1
```

```
    ldc 1
```

```
    isub
```

```
    invokestatic
```

```
        Exp/fac0(I)I
```

```
    imul
```

```
end0: ireturn
```

```
.end method
```

Optimization

```
.method public static fac0(I)I
```

```
    iload 1  
    ifeq label0  
    goto else0
```

```
label0: ldc 1
```

```
label1: ifeq else0
```

```
    ldc 1  
    goto end0
```

```
else0: iload 1  
      iload 1  
      ldc 1  
      isub  
      invokestatic  
          Exp/fac0(I)I  
      imul
```

```
end0: ireturn
```

```
.end method
```

```
.method public static fac0(I)I
```

```
    iload 1  
    ifeq label0  
    goto else0
```

```
label0: ldc 1
```

```
    ifeq else0
```

```
    ldc 1  
    goto end0
```

```
else0: iload 1  
      iload 1  
      ldc 1  
      isub  
      invokestatic  
          Exp/fac0(I)I  
      imul
```

```
end0: ireturn
```

```
.end method
```

Optimization

```
.method public static fac0(I)I
```

```
    iload 1  
    ifeq label0  
    goto else0
```

```
label0: ldc 1  
        ifeq else0
```

```
        ldc 1  
        goto end0  
else0:  iload 1  
        iload 1  
        ldc 1  
        isub  
        invokestatic  
            Exp/fac0(I)I  
        imul
```

```
    end0: ireturn  
.end method
```

```
.method public static fac0(I)I
```

```
    iload 1  
    ifeq label0  
    goto else0
```

```
label0: ldc 1  
        goto end0
```

```
else0:  iload 1  
        iload 1  
        ldc 1  
        isub  
        invokestatic  
            Exp/fac0(I)I  
        imul
```

```
    end0: ireturn  
.end method
```

Optimization

```
.method public static fac0(I)I
```

```
    iload 1
```

```
    ifeq label0
```

```
    goto else0
```

```
label0: ldc 1
```

```
    goto end0
```

```
else0: iload 1
```

```
    iload 1
```

```
    ldc 1
```

```
    isub
```

```
    invokestatic
```

```
        Exp/fac0(I)I
```

```
    imul
```

```
end0: ireturn
```

```
.end method
```

```
.method public static fac0(I)I
```

```
    iload 1
```

```
    ifneq else0
```

```
label0: ldc 1
```

```
    goto end0
```

```
else0: iload 1
```

```
    iload 1
```

```
    ldc 1
```

```
    isub
```

```
    invokestatic
```

```
        Exp/fac0(I)I
```

```
    imul
```

```
end0: ireturn
```

```
.end method
```

Optimization

```
.method public static fac0(I)I
```

```
    iload 1  
    ifneq else0
```

```
label0: ldc 1
```

```
    goto end0
```

```
else0: iload 1
```

```
    iload 1
```

```
    ldc 1
```

```
    isub
```

```
    invokestatic
```

```
        Exp/fac0(I)I
```

```
    imul
```

```
end0: ireturn
```

```
.end method
```

```
.method public static fac0(I)I
```

```
    iload 1  
    ifneq else0
```

```
    ldc 1
```

```
    goto end0
```

```
else0: iload 1
```

```
    iload 1
```

```
    ldc 1
```

```
    isub
```

```
    invokestatic
```

```
        Exp/fac0(I)I
```

```
    imul
```

```
end0: ireturn
```

```
.end method
```


Optimization

```
.method public static fac0(I)I
```

```
    iload 1  
    ifneq else0  
    ldc 1
```

```
    goto end0
```

```
else0:  iload 1  
        iload 1  
        ldc 1  
        isub  
        invokestatic  
            Exp/fac0(I)I  
        imul
```

```
end0:  ireturn
```

```
.end method
```

```
.method public static fac0(I)I
```

```
    iload 1  
    ifneq else0  
    ldc 1
```

```
    ireturn
```

```
else0:  iload 1  
        iload 1  
        ldc 1  
        isub  
        invokestatic  
            Exp/fac0(I)I  
        imul
```

```
end0:  ireturn
```

```
.end method
```

Optimization

```
.method public static fac0(I)I
```

```
    iload 1  
    ifneq else0  
    ldc 1  
    ireturn
```

```
else0: iload 1  
       iload 1  
       ldc 1  
       isub  
       invokestatic  
           Exp/fac0(I)I  
       imul
```

```
end0:  ireturn  
.end method
```

```
.method public static fac0(I)I
```

```
    iload 1  
    ifneq else0  
    ldc 1  
    ireturn
```

```
else0: iload 1  
       dup  
       ldc 1  
       isub  
       invokestatic  
           Exp/fac0(I)I  
       imul
```

```
end0:  ireturn  
.end method
```

Optimization

```
.method public static fac0(I)I
```

```
    iload 1
```

```
    ifneq else0
```

```
    ldc 1
```

```
    ireturn
```

```
else0: iload 1
```

```
    dup
```

```
    ldc 1
```

```
    isub
```

```
    invokestatic
```

```
        Exp/fac0(I)I
```

```
    imul
```

```
end0: ireturn
```

```
.end method
```

```
.method public static fac0(I)I
```

```
    iload_1
```

```
    ifneq else0
```

```
    ldc 1
```

```
    ireturn
```

```
else0: iload_1
```

```
    dup
```

```
    ldc 1
```

```
    isub
```

```
    invokestatic
```

```
        Exp/fac0(I)I
```

```
    imul
```

```
end0: ireturn
```

```
.end method
```

Optimization

```
.method public static fac0(I)I
```

```
    iload_1  
    ifneq else0
```

```
    ldc 1
```

```
    ireturn
```

```
else0: iload_1
```

```
    dup
```

```
    ldc 1
```

```
    isub
```

```
    invokestatic
```

```
        Exp/fac0(I)I
```

```
    imul
```

```
end0: ireturn
```

```
.end method
```

```
.method public static fac0(I)I
```

```
    iload_1  
    ifneq else0
```

```
    iconst_1
```

```
    ireturn
```

```
else0: iload_1
```

```
    dup
```

```
    iconst_1
```

```
    isub
```

```
    invokestatic
```

```
        Exp/fac0(I)I
```

```
    imul
```

```
end0: ireturn
```

```
.end method
```

Tail Recursion Elimination

Example: Tail Recursion

```
.class public Exp

  .method public static fac(I)I

    iload 1
    ifne else

    iconst_1
    ireturn

  else: iload 1
        dup
        iconst_1
        isub
        invokestatic Exp/fac(I)I
        imul
        ireturn
  .end method
```

Example: Tail Recursion

```
.class public Exp
  .method public static fac(I)I
    iload 1
    ifne else

    iconst_1
    ireturn

  else: iload 1
        dup
        iconst_1
        isub
        invokestatic Exp/fac(I)I
        imul
        ireturn
  .end method
```

```
.class public Exp
  .method public static fac(II)I
    iload 1
    ifne else

    iload 2
    ireturn

  else: iload 1
        iconst_1
        isub
        iload 1
        iload 2
        imul
        invokestatic Exp/fac(II)I
        ireturn
  .end method
```

Example: Tail Recursion

```
.class public Exp
  .method public static fac(II)I
    iload 1
    ifne else

    iload 2
    ireturn

  else: iload 1
        iconst_1
        isub
        iload 1
        iload 2
        imul
        invokestatic Exp/fac(II)I
        ireturn
  .end method
```

```
.class public Exp
  .method public static fac(II)I
    strt: iload 1
          ifne else

          iload 2
          ireturn

    else: iload 1
          iconst_1
          isub
          iload 1
          iload 2
          imul
          istore 2
          istore 1
          goto strt
```


Code Generation: Strings

Printing Strings

```
to-jbc = ?Nil()    ; <printstring> "aconst_null\n"  
to-jbc = ?NoVal() ; <printstring> "nop\n"  
to-jbc = ?Seq(es) ; <list-loop(to-jbc)> es
```

```
to-jbc =  
    ?Int(i);  
    <printstring> "ldc ";  
    <printstring> i;  
    <printstring> "\n"
```

```
to-jbc = ?Bop(op, e1, e2) ; <to-jbc> e1 ; <to-jbc> e2 ; <to-jbc> op
```

```
to-jbc = ?PLUS()    ; <printstring> "iadd\n"  
to-jbc = ?MINUS()   ; <printstring> "isub\n"  
to-jbc = ?MUL()     ; <printstring> "imul\n"  
to-jbc = ?DIV()     ; <printstring> "idiv\n"
```

String Concatenation

```
to-jbc: Nil()    -> "aconst_null\n"
to-jbc: NoVal()  -> "nop\n"
to-jbc: Seq(es)  -> <concat-strings> <map(to-jbc)> es

to-jbc: Int(i)   -> <concat-strings> ["ldc ", i, "\n"]

to-jbc: Bop(op, e1, e2) -> <concat-strings> [ <to-jbc> e1,
                                              <to-jbc> e2,
                                              <to-jbc> op ]

to-jbc: PLUS()   -> "iadd\n"
to-jbc: MINUS()  -> "isub\n"
to-jbc: MUL()     -> "imul\n"
to-jbc: DIV()     -> "idiv\n"
```

String Interpolation

```
to-jbc: Nil()    -> $[aconst_null]
to-jbc: NoVal()  -> $[nop]
to-jbc: Seq(es)  -> <map-to-jbc> es
```


```
map-to-jbc: [] -> $[]
map-to-jbc: [h|t] ->
    $[[<to-jbc> h]
      [<map-to-jbc> t]]
```

```
to-jbc: Int(i) -> $[ldc [i]]
to-jbc: Bop(op, e1, e2) ->
    $[[<to-jbc> e1]
      [<to-jbc> e2]
      [<to-jbc> op]]
```

```
to-jbc: PLUS()   -> $[iadd]
to-jbc: MINUS()  -> $[isub]
to-jbc: MUL()    -> $[imul]
to-jbc: DIV()    -> $[idiv]
```

Code Generation: Transformation

Compilation by Transformation



Transformation

```
to-jbc: Nil()    -> [ ACONST_NULL() ]  
to-jbc: NoVal() -> [ NOP() ]  
to-jbc: Seq(es) -> <mapconcat(to-jbc)> es
```

```
to-jbc: Int(i)    -> [ LDC(Int(i)) ]  
to-jbc: String(s) -> [ LDC(String(s)) ]
```

```
to-jbc: Bop(op, e1, e2) -> <mapconcat(to-jbc)> [ e1, e2, op ]
```

```
to-jbc: PLUS()    -> [ IADD() ]  
to-jbc: MINUS()   -> [ ISUB() ]  
to-jbc: MUL()     -> [ IMUL() ]  
to-jbc: DIV()     -> [ IDIV() ]
```

```
to-jbc: Assign(lhs, e) -> <concat> [ <to-jbc> e, <lhs-to-jbc> lhs ]
```

```
to-jbc:    Var(x) -> [ ILOAD(x) ] where <type-of> Var(x) => INT()  
to-jbc:    Var(x) -> [ ALOAD(x) ] where <type-of> Var(x) => STRING()  
lhs-to-jbc: Var(x) -> [ ISTORE(x) ] where <type-of> Var(x) => INT()  
lhs-to-jbc: Var(x) -> [ ASTORE(x) ] where <type-of> Var(x) => STRING()
```

Transformation

to-jbc:

```
IfThenElse(e1, e2, e3) -> <concat> [ <to-jbc> e1  
                                   , [ IFEQ(LabelRef(else)) ]  
                                   , <to-jbc> e2  
                                   , [ GOTO(LabelRef(end)), Label(else) ]  
                                   , <to-jbc> e3  
                                   , [ Label(end) ]  
                                   ]
```

where <newname> "else" => else

where <newname> "end" => end

to-jbc:

```
While(e1, e2) -> <concat> [ [ GOTO(LabelRef(check)), Label(body) ]  
                           , <to-jbc> e2  
                           , [ Label(check) ]  
                           , <to-jbc> e1  
                           , [ IFNE(LabelRef(body)) ]  
                           ]
```

where <newname> "test" => check


where <newname> "body" => body

Transformation: Example

```
function fac(n: int): int=  
  if  
    n = 0  
  then  
    1  
  else  
    n * fac(n - 1)
```

```
.method public static fac(I)I  
  
    iload 1  
    ldc 0  
    if_icmpeq label0  
    ldc 0  
    goto label1  
label0: ldc 1  
label1: ifeq else0  
        ldc 1  
        goto end0  
else0:  iload 1  
        iload 1  
        ldc 1  
        isub  
        invokestatic Exp/fac(I)I  
        imul  
end0:   ireturn  
.end method
```

Compiler Infrastructure: LLVM



Next

Next

Back-End

- Lecture 11: Dataflow Analysis (Nov 28)
- Lecture 12: Garbage Collection (Dec 5)
- Lecture 13: Just-in-Time Compilation (Interpreters & Partial Evaluation) (Dec 12)

Parsing

- Lecture 14: LL Parsing (Dec 19)
- Lecture 15: LR Parsing (Jan 9)

Lab

- Lab 6: Testing Type Analysis (Nov 22)
- Lab 7: Type Analysis (Dec 6)
- Lab 8: Compiling Minimal Programs (Dec 13)
- Lab 9: Compiling Expressions and Statements (Dec 22)
- Lab 10: Compiling Fields, Parameters, and Variables (Jan 19)

