cell.v1.InitFabricShard
Id: " " "-<org>
TaskQueue: infra
Child Workflow
temporal.v1.CreateNamespace
temporal.v1.CreateNamespace
Id: TemporalNamespace-<org>
TaskQueue: infra
temporal.v1.RegisterNamespace
Retry until ready
temporal.v1.DescribeNamespace
Child Workflow
cluster.fabric.v1.CreateNamespace
cluster.fabric.v1.CreateNamespace
Id: KubernetesNamespace-<org>
TaskQueue: infra
helm.v1.RenderChartWithTemplate
kube.v1.Apply
Child Workflow
cluster.fabric.v1.CreateServiceAccount
cluster.fabric.v1.CreateServiceAccount
Id:
KubernetesServiceAccount-<org>
TaskQueue: infra
helm.v1.RenderChartWithTemplate
kube.v1.Apply
Child Workflow
vault.v1.CreateAccess
vault.v1.CreateAccess
Id: VaultAccess-<org>
TaskQueue: infra
vault.v1.CreatePolicy
vault.v1.CreateAuthRole
Child Workflow
cluster.fabric.v1.CreateDeployment
cluster.fabric.v1.CreateDeployment
Id:
Deployment-<org>-<deployment>
TaskQueue: infra
helm.v1.RenderChartWithTemplate
kube.v1.Apply
temporal.v1.CreateNexusEndpoint
Blocking Nexus Call
fabric.v1.BootstrapShard.<org>
fabric.v1.BootstrapShard
Id: FabricOrg-<org>
TaskQueue: infra
Child Workflow
fabric.v1.
BootstrapCertificateAuthorities
create all CAs for org, root CAs offline
fabric.v1.
BootstrapCertificateAuthorities
Id: " " "-<org>
TaskQueue: infra
Child Workflow
fabric.v1.DeployCertificateStore
fabric.v1. DeployCertificateStore
Id: " " "-<org>
TaskQueue: infra
Blocking Nexus Call
vault.v1.CreateAccess.<org>
Read only, access for just Postgres
vault.v1.CreateAccess
Id: VaultAccess-<org>
TaskQueue: infra
vault.v1.CreatePolicy
vault.v1.CreateAuthRole
Child Workflow
crypto.v1.CreatePassword
create admin password
crypto.v1.CreatePassword
Id: " " "-<org>-<id>
TaskQueue: infra
crypto.v1.GeneratePassword
vault.v1.StoreSecret
Child Workflow
cluster.fabric.v1.CreateDeployment
deploy 3 node postgress
cluster.fabric.v1.CreateDeployment
Id:
Deployment-<org>-<deployment>
TaskQueue: infra
helm.v1.RenderChartWithTemplate
kube.v1.Apply
For each (tls, org)
Child Workflow
fabric.v1.
DeployRootCertificateAuthority
fabric.v1.
DeployRootCertificateAuthority
Id: " " "-<org>-<type>
TaskQueue: infra
Blocking Nexus Call
vault.v1.CreateAccess.<org>
Read only, access for just Root CA
vault.v1.CreateAccess
Id: VaultAccess-<org>
TaskQueue: infra
vault.v1.CreatePolicy
vault.v1.CreateAuthRole
Child Workflow
fabric.v1.CreateCertificateDatabase
create db in postgres
fabric.v1.CreateCertificateDatabase
Id: " " "-<org>-<id>
TaskQueue: infra
postgres.v1.CreateDatabase
Child Workflow
crypto.v1.CreatePassword
create user password
crypto.v1.CreatePassword
Id: " " "-<org>-<id>
TaskQueue: infra
crypto.v1.GeneratePassword
vault.v1.StoreSecret
postgres.v1.CreateUser
postgres.v1.GrantPrivileges
Child Workflow
crypto.v1.CreateKeyPair
create root key pair
crypto.v1.CreateKeyPair
Id: " " "-<org>-<id>
TaskQueue: infra
crypto.v1.GenerateKeyPair
vault.v1.StoreSecret
Child Workflow
crypto.v1.CreateCertificate
create self-signed root cert
crypto.v1.CreateCertificate
Id: " " "-<org>-<id>
TaskQueue: infra
vault.v1.FetchSecret
crypto.v1.GenerateCertificate
vault.v1.StoreSecret
Child Workflow
cluster.fabric.v1.CreateDeployment
deploy CA, provide key pair & cert, point at postgres
cluster.fabric.v1.CreateDeployment
Id: " " "-<org>-<deployment>
TaskQueue: infra
helm.v1.RenderChartWithTemplate
kube.v1.Apply
Child Workflow
fabric.v1.
BootstrapCertificateAuthorityAdmin
use default admin and then revoke
cluster.fabric.v1.
BootstrapCertificateAuthorityAdmin
Id: " " "-<org>-<admin>
TaskQueue: infra
Blocking Nexus Call
vault.v1.CreateAccess.<org>
Read only, access for just this CA
vault.v1.CreateAccess
Id: VaultAccess-<org>
TaskQueue: infra
Fairly sure we need this, but not certain what needs to have access
vault.v1.CreatePolicy
vault.v1.CreateAuthRole
if "tls": for each (tls)
if "org": for each (tls, org)
Child Workflow
fabric.v1.CreateIdentity
point at relevant CA
fabric.v1.RevokeIdentity
fabric.v1.CreateIdentity
Id: " " "-<org>-<id>
TaskQueue: infra
Child Workflow
crypto.v1.CreateKeyPair
create admin key pair
crypto.v1.CreateKeyPair
Id: " " "-<org>-<id>
TaskQueue: infra
crypto.v1.GenerateKeyPair
vault.v1.StoreSecret
fabric.v1.RegisterIdentitiy
Do we need to generate the CSR outside of these?
fabric.v1.EnrollIdentity
Some how we need to also produce the full chain
vault.v1.StoreSecret
Child Workflow
fabric.v1.DeployCertificateAuthority
fabric.v1.
DeployCertificateAuthority
Id: " " "-<org>-<type>
TaskQueue: infra
Blocking Nexus Call
vault.v1.CreateAccess.<org>
Read only, access for just this CA
vault.v1.CreateAccess
Id: VaultAccess-<org>
TaskQueue: infra
vault.v1.CreatePolicy
vault.v1.CreateAuthRole
Child Workflow
fabric.v1.CreateCertificateDatabase
create db in postgres
fabric.v1.CreateCertificateDatabase
Id: " " "-<org>-<id>
TaskQueue: infra
postgres.v1.CreateDatabase
Child Workflow
crypto.v1.CreatePassword
create user password
crypto.v1.CreatePassword
Id: " " "-<org>-<id>
TaskQueue: infra
crypto.v1.GeneratePassword
vault.v1.StoreSecret
postgres.v1.CreateUser
postgres.v1.GrantPrivileges
Child Workflow
cluster.fabric.v1.ScaleDeployment
ensure root CA online
cluster.fabric.v1.ScaleDeployment
Id: " " "-<org>-<deployment>
TaskQueue: infra
kube.v1.Apply
Is this right? Wait for healthy?
Child Workflow
fabric.v1.CreateIdentity
point at root CA
fabric.v1.CreateIdentity
Id: " " "-<org>-<id>
TaskQueue: infra
Child Workflow
crypto.v1.CreateKeyPair
create root key pair
crypto.v1.CreateKeyPair
Id: " " "-<org>-<id>
TaskQueue: infra
crypto.v1.GenerateKeyPair
vault.v1.StoreSecret
fabric.v1.RegisterIdentitiy
Do we need to generate the CSR outside of these?
fabric.v1.EnrollIdentity
Some how we need to also produce the full chain
vault.v1.StoreSecret
Child Workflow
cluster.fabric.v1.ScaleDeployment
ensure root CA offline
cluster.fabric.v1.ScaleDeployment
Id: " " "-<org>-<deployment>
TaskQueue: infra
kube.v1.Apply
Is this right? Wait for healthy?
Child Workflow
cluster.fabric.v1.CreateDeployment
deploy CA, provide key pair & cert, point at postgres
cluster.fabric.v1.CreateDeployment
Id:
Deployment-<org>-<deployment>
TaskQueue: infra
helm.v1.RenderChartWithTemplate
kube.v1.Apply
Child Workflow
fabric.v1.
BootstrapCertificateAuthorityAdmin
use default admin and then revoke
cluster.fabric.v1.
BootstrapCertificateAuthorityAdmin
Id: " " "-<org>-<admin>
TaskQueue: infra
Does this need to be different than the root? we aren't using default keys
Blocking Nexus Call
vault.v1.CreateAccess.<org>
Read only, access for just this CA
vault.v1.CreateAccess
Id: VaultAccess-<org>
TaskQueue: infra
Fairly sure we need this, but not certain what needs to have access
vault.v1.CreatePolicy
vault.v1.CreateAuthRole
if "tls": for each (tls)
if "org": for each (tls, org)
Child Workflow
fabric.v1.CreateIdentity
point at relevant CA
fabric.v1.RevokeIdentity
fabric.v1.CreateIdentity
Id: " " "-<org>-<id>
TaskQueue: infra
Child Workflow
crypto.v1.CreateKeyPair
create admin key pair
crypto.v1.CreateKeyPair
Id: " " "-<org>-<id>
TaskQueue: infra
crypto.v1.GenerateKeyPair
vault.v1.StoreSecret
fabric.v1.RegisterIdentitiy
Do we need to generate the CSR outside of these?
fabric.v1.EnrollIdentity
Some how we need to also produce the full chain
vault.v1.StoreSecret
For peer count
Child Workflow
fabric.v1.DeployCouchDb
Single instance
fabric.v1.DeployCouchDb
Id: " " "-<org>-<id>
TaskQueue: infra
Blocking Nexus Call
vault.v1.CreateAccess.<org>
Read only, access for just CouchDb
vault.v1.CreateAccess
Id: VaultAccess-<org>
TaskQueue: infra
vault.v1.CreatePolicy
vault.v1.CreateAuthRole
Child Workflow
crypto.v1.CreatePassword
create admin password
crypto.v1.CreatePassword
Id: " " "-<org>-<id>
TaskQueue: infra
crypto.v1.GeneratePassword
vault.v1.StoreSecret
Child Workflow
cluster.fabric.v1.CreateDeployment
create CouchDb deployment
cluster.fabric.v1.CreateDeployment
Id:
Deployment-<org>-<deployment>
TaskQueue: infra
helm.v1.RenderChartWithTemplate
kube.v1.Apply
Child Workflow
fabric.v1.DeployPeer
//
fabric.v1.DeployPeer
Id: " " "-<org>-<id>
TaskQueue: infra
How do we make sure that peer has access to couchDB password?
Blocking Nexus Call
vault.v1.CreateAccess.<org>
Read only, access for just this Peer
vault.v1.CreateAccess
Id: VaultAccess-<org>
TaskQueue: infra
vault.v1.CreatePolicy
vault.v1.CreateAuthRole
for each (tls, org)
Child Workflow
fabric.v1.CreateIdentity
point at relevant CA
fabric.v1.CreateIdentity
Id: " " "-<org>-<id>
TaskQueue: infra
Child Workflow
crypto.v1.CreateKeyPair
create admin key pair
crypto.v1.CreateKeyPair
Id: " " "-<org>-<id>
TaskQueue: infra
crypto.v1.GenerateKeyPair
vault.v1.StoreSecret
fabric.v1.RegisterIdentitiy
Do we need to generate the CSR outside of these?
fabric.v1.EnrollIdentity
Some how we need to also produce the full chain
vault.v1.StoreSecret
Child Workflow
cluster.fabric.v1.CreateDeployment
create Peer deployment
cluster.fabric.v1.CreateDeployment
Id:
Deployment-<org>-<deployment>
TaskQueue: infra
helm.v1.RenderChartWithTemplate
kube.v1.Apply
For orderer count
Child Workflow
fabric.v1.DeployOrder
//
fabric.v1.DeployOrderer
Id: " " "-<org>-<id>
TaskQueue: infra
Blocking Nexus Call
vault.v1.CreateAccess.<org>
Read only, access for just this Orderer
vault.v1.CreateAccess
Id: VaultAccess-<org>
TaskQueue: infra
vault.v1.CreatePolicy
vault.v1.CreateAuthRole
for each (tls, org)
Child Workflow
fabric.v1.CreateIdentity
point at relevant CA
fabric.v1.CreateIdentity
Id: " " "-<org>-<id>
TaskQueue: infra
Child Workflow
crypto.v1.CreateKeyPair
create admin key pair
crypto.v1.CreateKeyPair
Id: " " "-<org>-<id>
TaskQueue: infra
crypto.v1.GenerateKeyPair
vault.v1.StoreSecret
fabric.v1.RegisterIdentitiy
Do we need to generate the CSR outside of these?
fabric.v1.EnrollIdentity
Some how we need to also produce the full chain
vault.v1.StoreSecret
Child Workflow
cluster.fabric.v1.CreateDeployment
create Orderer deployment
cluster.fabric.v1.CreateDeployment
Id:
Deployment-<org>-<deployment>
TaskQueue: infra
helm.v1.RenderChartWithTemplate
kube.v1.Apply
For chainCode count
Child Workflow
fabric.v1.DeployChainCode
//
fabric.v1.DeployPeer
Id: " " "-<org>-<id>
TaskQueue: infra
Blocking Nexus Call
vault.v1.CreateAccess.<org>
Read only, access for just this Peer
vault.v1.CreateAccess
Id: VaultAccess-<org>
TaskQueue: infra
vault.v1.CreatePolicy
vault.v1.CreateAuthRole
for only (org)
Child Workflow
fabric.v1.CreateIdentity
point at intermediate CA
fabric.v1.CreateIdentity
Id: " " "-<org>-<id>
TaskQueue: infra
Child Workflow
crypto.v1.CreateKeyPair
create peer key pair
crypto.v1.CreateKeyPair
Id: " " "-<org>-<id>
TaskQueue: infra
crypto.v1.GenerateKeyPair
vault.v1.StoreSecret
fabric.v1.RegisterIdentitiy
Do we need to generate the CSR outside of these?
fabric.v1.EnrollIdentity
Some how we need to also produce the full chain
vault.v1.StoreSecret
Child Workflow
cluster.fabric.v1.CreateDeployment
create CouchDb deployment
cluster.fabric.v1.CreateDeployment
Id:
Deployment-<org>-<deployment>
TaskQueue: infra
helm.v1.RenderChartWithTemplate
kube.v1.Apply