CEDAR

cedarcli commands

2.9.24

git

```
add-commit-push COMMENT
  --repo REPO --path PATH...
branch
checkout BRANCH
clone all / docker
clone-missing
fetch
list branch / tag
next
pull
remote
status
```

build

```
[--jobs N] [--workers N] <cmd>
all [--skip-tests]
<build_target> [--skip-tests]
this [--skip-tests]
split-frontends
  [--server-payload]
server-frontends
  [--server-payload]
diagnostics [--apply]
  [--days N] [--max-mib N]
maven clean all
maven clean cedar
```

publish

```
all | <build_target> | this
train [--dry-run]
  [--resume TRAIN_ID]
  [--release-version VER]
  [--next-version NEXT_VER]
  [--from-train TRAIN_ID]
  [--cee-version CEE_VER]
  [--accept-main-only REPO]
train-status [TRAIN_ID]
  [--watch]
baselines [--refresh] [--all]
  [--repository REPO]
components [--apply]
  [--component ID]
probe [--upload]
```

release

```
readiness [--full]
  [--version VER]
  [--next-version NEXT_VER]
  [--from-train TRAIN_ID]
  [--cee-version CEE_VER]
  [--model-version MODEL_VER]
  [--skip-packaging]
plan
  --version VER
  --next-version NEXT_VER
  --from-train TRAIN_ID
  --cee-version CEE_VER
  [--accept-red-develop REPO=RUN]
  [--accept-main-only REPO]
start
  --version VER
  --next-version NEXT_VER
  --from-train TRAIN_ID
  --cee-version CEE_VER
  [--accept-red-develop REPO=RUN]
  [--accept-main-only REPO]
  [--jobs N] [--workers N]
  [--maven-threads N] [--verbose]
resume [--dry-run] [--verbose]
status [--watch]
timings [--compare VER]
abandon
  --version VER --reason WHY
```

mode

```
native
  --profile develop|server
hybrid
  --profile develop|server
docker
--clear [--force]
```

native

```
status
start [--refresh-dependencies]
  all | <run_target>
stop all | <run_target>
restart [--refresh-dependencies]
  all | <run_target>
health [--group GROUP]
  all|microservices|frontends
logs ui-<frontend> [-n LINES]
logs <microservice> [-n LINES]
  [--dropwizard]
watch
```

docker

```
status
start
  all [--train TRAIN_ID|--local] [--pull POLICY] [--timeout SEC]
  <run_target> [--detach] [--train TRAIN_ID|--local] [--pull POLICY]
  POLICY=never|missing|always
stop all | <run_target>
build all | <run_target> | <image>
  [--no-deps] [--local] [--train TRAIN_ID]
validate
setup one-time-setup | create-network
  create-certificates-volume | copy-certificates
remove containers | images | network | volumes | all
```

test

```
e2e [--rest-workers N]
  [--split-lanes N]
status
cleanup
```

<build_target>

```
java
project
parent
libraries
clients
frontends [no --skip-tests]
```

<run_target>

```
infra [start/stop only]
backends [native start/stop]
microservices
microservice all
microservice <microservice>
frontends
frontend all
frontend <frontend>
frontend split-frontends
  [native only]
keycloak / kk [start/stop]
admin [docker only]
```

<frontend>

```
main
openview
monitoring
bridging
content
workspace
designer
```

<microservice>

```
artifact
bridge
group
impex
messaging
monitor
openview
  [docker: open]
repo
resource
schema
submission
terminology
user
valuerecommender
worker
```

prod

```
configure-frontends
reset-frontends
provision-artifact-key
```

repo

```
config
```

check

```
repos
versions [--strict] [--by-file]
components [--strict] [--all]
snapshots [--version VER]
  [--grace-hours N] [--nexus URL]
ci [--all]
ci-env [--apply]
openapi [--all]
main [--all]
design-tokens [--repo REPO]
  [--strict] [--all] [--json]
  [--init-baseline]
  [--prune-baseline]
  [--sync-surfaces]
  [--surface-inventory FILE]
artifact-versioning [--apply]
stores
```

env

```
status
list [native|docker]
filter TERM
  [native|docker]
artifact-key
  init|rotate|retire
```

cert

```
ca [--force]
domains [NAME...]
  [--force]
setup
```

dev

```
add-hosts
copy-keycloak-listener
create-directories
generate-api-key USER_ID
```