Announcements & Such

- Administrative Stuff
 - Grade Curve (so far). Take the average of:
 - (1) your average HW score,
 - (2) your in-class mid-term score (on a 100 point scale), and
 - (3) your take-home mid-term score.
 - * The approximate "curve" for the course is as follows: A-ish (\geq 90), B-ish (80–90), C-ish (60–80), D-ish (50-60).
 - HW #4 is to be returned today. Resub due Thursday
 - From now on, my office hours will be 2-4pm Thursdays.
- Today: back to Chapter 5 Monadic Predicate Logic (LMPL)
 - The basic building blocks of LMPL.
 - The existential and universal quantifiers and variables.
 - Symbolizations with quantifiers.

UCB Philosophy Chapter 5 04/06/10

Branden Fitelson Philosophy 12A Notes

2

New Elements of LMPL

- Now, upper-case letters can be used as LSL sentences *or* **predicates**.
 - *E.g.*, the predicate 'is tall' can be symbolized using 'T'.
- Lower-case letters 'a'-'s' will be used as **individual constants** (names).
- This yields **new atomic sentences** with *subject-predicate structure*:
 - *E.g.*, 'Branden is tall' \mapsto 'Tb'.
- We also have two **quantifier phrases**: all (\forall) and some (\exists) .
- Lower-case letters 't'-'z' will be used as **variables**.
- We use variables + quantifiers to symbolize general claims.
 - E.g., 'Someone is wise'
 - \rightarrow 'There exists an x such that x is wise.'
 - \mapsto ' $(\exists x)Wx$ '
- Each general claim quantifies over a **domain/universe of discourse**.

UCB Philosophy Chapter 5 04/06/10

Branden Fitelson

Philosophy 12A Notes

3

Symbolization in LMPL III: The Existential Quantifier

- The quantifier 'some' is captured using the new symbol '∃' of LMPL.
- For instance, 'Someone is wise' gets symbolized as ' $(\exists x)Wx$ ' in LMPL.
- One must be careful about the *scope* of the existential quantifier. For instance, consider the following two (*non*-equivalent!) sentences:
- (1) Someone is happy and someone is wise.
- (2) Someone is happy and wise.
- Sentence (1) is symbolized in LMPL as ' $(\exists x)Hx \& (\exists x)Wx$ '.
- Sentence (2) is symbolized in LMPL as ' $(\exists x)(Hx \& Wx)$ '.
- How would you symbolize the following sentence in LMPL

'Some economists are wealthy and some are not.'

using the following dictionary?

 E_{--} : __ is an economist.

 L_{--} : __ is wealthy.

Branden Fitelson Philosophy 12A Notes 4

Symbolization in LMPL IV: More on ∃

- What, exactly, does '∃' mean?
- When I say 'Someone in this room is wise', I'm asserting the *disjunction* 'Either Branden is wise, or Mike is wise, or ...' (*i.e.*, ' $Wb \lor Wm \lor ...$ ').
- In *finite* domains of discourse, we can always express existentially quantified sentences as disjunctions. But, in *infinite* domains, we cannot, since our language does not permit infinitely long formulas.
- We can use negation, together with the existential quantifier, to express other kinds of quantifiers. For instance, we may symbolize

'No unwise person is happy.'

in LMPL as: $(\neg(\exists x)(\neg Wx \& Hx))$.

How would you symbolize the following sentence?

'If a wealthy economist exists, then so does a famous mathematician.'

UCB Philosophy Chapter 5 04/06/10 UCB Philosophy Chapter 5 04/06/10

Branden Fitelson

Philosophy 12A Notes

Branden Fitelson

5

7

Philosophy 12A Notes

6

Symbolization in LMPL V: Free vs Bound and Open vs Closed

- In 'Wx', the variable 'x' is said to be *free*. But, in ' $(\exists x)Wx$ ', the variable 'x' is said to be *bound* by the existential quantifier.
- Formulas like 'Wx' which contain free variables are called *open sentences*. Formulas with *no* free variables are called *closed sentences*.
- Only closed sentences assert things that can be either true or false of some particular individuals in the domain of discourse (or the domain).
- For instance, 'Wx' says 'x is wise'. But, since the 'x' in 'Wx' does not refer to any particular thing, 'Wx' can be neither true nor false.
- But, when we *existentially quantify* 'Wx', we end-up with ' $(\exists x)Wx$ ', which clearly *does* make an assertion that is either true or false (depending on whether any *particular* person in the domain happens to be wise).
- Which of the following are open/closed? [NOTE: '3' binds like '~'!]

(1) 'Ha' (2) 'Wx' (3) ' $(\exists x)Hx$ '	$(4) '(\exists x) Hx \& Wx'$	$(5) '(\exists x) Hx \& Wb'$
---	------------------------------	------------------------------

CHAPTER 5 UCB Philosophy 04/06/10

Symbolization in LMPL VI: More Examples with ∃

- Let's symbolize the following sentences. Whenever we symbolize in LMPL, we must state our dictionary of monadic predicates, and we must also say what the domain of discourse is over which we are quantifying.
- 1. No smoggy city is unpolluted.
- 2. Vampires do not exist.
- 3. If ghosts and vampires do not exist, then nothing can be a ghost without being a vampire.
- If the dictionary is (where the domain is people in this classroom now):

 S_{--} : __ is standing up at the podium.

 W_{--} : __ is wealthy.

b: Branden

then what do the following two LMPL sentences assert (in English)?

 $\sim Wb$ $\sim (\exists x)(Sx \& Wx)$

CHAPTER 5 UCB Philosophy 04/06/10

Branden Fitelson

Philosophy 12A Notes

Symbolization in LMPL VII: Back to ① and ②

• Now, we are in a position to symbolize in LMPL the argument ① that we saw at the beginning of the previous lecture:

• Since there are only finitely many people, we can see why this argument is valid, by representing its conclusion as a long (but finite!) *disjunction*, in which its only premise is a disjunct:

• We can use a similar trick for argument ②. The premise of ② $['(\forall x)Hx']$ entails a *conjunction* $['Ha \& \cdots \& Hp \& \cdots ']$, and its conclusion ['Hp'] is one of the conjuncts of that conjunction.

Branden Fitelson

Philosophy 12A Notes

04/06/10

Some Symbolizations Involving ∃

E__ : __ is an even number a: the number 2

P__: __ is a prime number Domain: natural numbers (ℕ)

G__: __ is greater than the number 2

(1) There exists a prime number and there exists an even number.

 $(\exists x)Px \& (\exists x)Ex$

- (2) There exists an even prime number. $[(\exists x)(Px \& Ex)]$
- (3) 2 is an even prime number. [Ea & Pa]
- (4) If 2 is prime, then there are some even primes. $[Pa \rightarrow (\exists x)(Px \& Ex)]$
- (5) No number is even if it is prime. $[\sim (\exists x)(Px \& Ex)]$
 - Careful with this one! Why *isn't* this ' $\sim (\exists x)(Px \rightarrow Ex)$ '?
 - Compare: No number is even if it is prime and greater than 2.
 - * In LMPL, this is: $(\neg(\exists x))[(Px \& Gx) \& Ex]'$, which is true. Why?
 - * Note: $\sim (\exists x) [(Px \& Gx) \rightarrow Ex]'$ is false! Why?

UCB Philosophy CHAPTER 5 04/06/10 UCB Philosophy CHAPTER 5

The *Universal* Quantifier ∀

9

11

- To symbolize English sentences like 'Everyone is happy', we will need the *universal* quantifier '∀' (which means 'every' or 'all').
 - (i) We begin with the raw English sentence: 'Everyone is happy'.
- (ii) Then, we move to the *Logish* form: 'For every x, x is happy'.
- (iii) Finally, we have the full LMPL symbolization: $(\forall x)Hx'$.
- As with the existential quantifier, we must be careful with the *scope* of '∀'. How would we symbolize the following two sentences?
- (1) 'Everyone is happy and everyone is wise.'
- (2) 'Everyone is happy and wise.'
- These sentences get symbolized differently, because they have different (syntactic) *structures*. But, do they have different *meanings*? In Chapter 6, we'll *prove* the answer to this question.

UCB Philosophy Chapter 5 04/06/10

Branden Fitelson Philosophy 12A Notes 10

The Universal Quantifier II

- How should one symbolize the following English sentence?
 - (3) 'Everyone who is happy is wise.'
- Note: Unlike (1) and (2) above, (3) does *not* have the consequence that *everyone* is happy. So, what, exactly, *does* (3) say?
- (3) says that *if* a person is happy, *then* that person is wise. This suggests the following *Logish* form (*wrt* the domain of people):

'For every x, if x is happy then x is wise.'

• Now, we are ready for the full LMPL symbolization:

$$(\forall x)(Hx \rightarrow Wx)$$

 We will use this same trick to symbolize sentences like 'Every happy person is a wise person' or 'If someone is happy then he/she is wise', which both assert the same thing as (3).

UCB Philosophy Chapter 5 04/06/10

Branden Fitelson Philosophy 12A Notes

The Universal Quantifier III

- How should one symbolize the following English sentence?

 (4) 'Only happy people are wise.'
- Note: (4) does *not* say that *all* happy people are wise. That is, unlike (3), (4) does *not* say that a person is wise *if* he/she is happy. Rather, (4) says that a person is wise *only if* he/she is happy.
- This suggests the following *Logish* form (domain of people): 'For every *x*, *x* is wise *only if x* is happy.'
- Now, we are ready for the full LMPL symbolization:


$$(\forall x)(Wx \rightarrow Hx)$$

• Here, we have the usual distinction between necessary and sufficient conditions. (3) says that happiness is *sufficient* for wisdom. But, (4) says that happiness is *necessary* for wisdom.

Branden Fitelson Philosophy 12A Notes 12

The Universal Quantifier IV, and Venn Diagrams

- Consider the following English sentence:
 - (5) 'No one who is unhappy is wise.'
- When trying to paraphrase or symbolize sentences like this in LMPL, it is useful to *picture* what they say using a *Venn Diagram*:



• (5) says that region ③ in the Venn Diagram is empty. So, (5) asserts the same thing as the following LMPL sentence:

$$(5.1) (\forall x)(Wx \rightarrow Hx)$$

UCB Philosophy Chapter 5 04/06/10

UCB Philosophy Chapter 5 04/06/10

The Intimate Relationship Between ∃ and ∀

• What we have just shown (informally) is:

 $(\neg(\exists x)(Wx \& \neg Hx))$ is equivalent to $(\forall x)(Wx \to Hx)$

• This is just a *special case* of the following *general equivalences*:

 $\lceil \sim (\exists v) \sim \phi v \rceil$ is equivalent to $\lceil (\forall v) \phi v \rceil$ and $\lceil \sim (\forall v) \sim \phi v \rceil$ is equivalent to $\lceil (\exists v) \phi v \rceil$

- Here, ' ϕ ' is a *metavariable* ranging over formulas of LMPL (thought of as functions of ν), and ' ν ' ranges over variable symbols of LMPL.
- It follows from the second general equivalence above that $\sim (\exists x)(Wx \& \sim Hx)$ is equivalent to $\sim \sim (\forall x) \sim (Wx \& \sim Hx)$. But, this is equivalent to $(\forall x) \sim (Wx \& \sim Hx)$, hence $(\forall x)(Wx \to Hx)$.
- Our formal semantics will make these relationships more precise.

UCB Philosophy Chapter 5 04/06/10

Branden Fitelson Philosophy 12A Notes 15

Further Symbolization Problems

- If someone says "all athletes are not superstars" (another example: "all that glitters is not gold"), they are not to be symbolized exactly as read.
 - Sounds like $(\forall x)(Ax \rightarrow \sim Sx)$, but it's really $\sim (\forall x)(Ax \rightarrow Sx)$.
 - Note: this is equivalent to $(\exists x)(Ax \& \sim Sx)$.
- "The only" gets symbolized like "All". Example:
 - "The only animals in this canyon are skunks" is $(\forall x)((Ax \& Cx) \to Sx)$. Where Ax: x is an animal, Cx: x is in this canyon, and Sx: x is a skunk.
 - Clearly, $(\forall x)(Sx \rightarrow (Ax \& Cx))$ is *not* what's intended. Why?
- "None but", "none except" and "no ... except" are like "Only". Examples:
 - "None but the brave deserve a Purple Heart" is $(\forall x)(Px \rightarrow Bx)$. Where Bx: x is brave, Px: x deserves a Purple Heart.
 - "No birds except peacocks are proud of their tails" is equivalent to
 "Only peacocks are birds that are proud of their tails".

Branden Fitelson Philosophy 12A Notes

- Here's *why* (informally) $\lceil \sim (\exists v) \sim \phi v \rceil$ and $\lceil (\forall v) \phi v \rceil$ are equivalent.
- Next, note that, informally, $(\exists v) \sim \phi v$ asserts a *disjunction*: $\sim \phi a \vee \sim \phi b \vee \dots$
- So, by DeMorgan, its negation ' $\sim (\exists v) \sim \phi v$ ' asserts a *conjunction*: $\sim \sim \phi a \& \sim \sim \phi b \& \dots$
- Then, by Double Negation (DN), we can see this is equivalent to: $\phi a \& \phi b \& \dots$
- But, this just asserts that *every* individual has ϕ . In other words, this says the same thing that the universal claim $(\forall v)\phi v$ says!
- Therefore, $\lceil \sim (\exists v) \sim \phi v \rceil$ is equivalent to $\lceil (\forall v) \phi v \rceil$. QED.
- We can run a parallel argument for $\lceil \sim (\forall v) \sim \phi v \rceil$ and $\lceil (\exists v) \phi v \rceil$.

UCB Philosophy Chapter 5 04/06/10

Branden Fitelson

Philosophy 12A Notes

16

14

LMPL Symbolizations: Summary and Tips

- Some general symbolization forms we've seen so far:
 - All Fs are Gs. LMPL: $(\forall x)(Fx \rightarrow Gx)$.
 - An *F* is a *G*. LMPL: $(\forall x)(Fx \rightarrow Gx)$.
 - *F*s are *G*s. LMPL: (∀x)(Fx → Gx).
 - Only Fs are Gs. LMPL: $(\forall x)(Gx \rightarrow Fx)$.
 - The only *F*s are *G*s. LMPL: $(\forall x)(Fx \rightarrow Gx)$.
 - Some Fs are Gs. LMPL: $(\exists x)(Fx \& Gx)$.
 - No Fs are Gs. LMPL: $\sim (\exists x)(Fx \& Gx)$.
 - Nothing is an F if it's G. $\sim (\exists x)(Gx \& Fx)$. [NOT $\sim (\exists x)(Gx \to Fx)$!]
 - If anything is an F, then Gs are. LMPL: $(\exists x)Fx \to (\forall x)(Gx \to Fx)$.
 - 'All Fs are not Gs' can sometimes really be $\sim (\forall x)(Fx \rightarrow Gx)$.
 - None but Fs are Gs (or None except Fs are Gs). $(\forall x)(Gx \rightarrow Fx)$.
- Remember: $\lceil \sim (\exists v) \sim \phi v \rceil$ is equivalent to $\lceil (\forall v) \phi v \rceil$ and $\lceil \sim (\forall v) \sim \phi v \rceil$ is equivalent to $\lceil (\exists v) \phi v \rceil$. You should be able to use these proficiently.

UCB Philosophy Chapter 5 04/06/10

UCB Philosophy Chapter 5

04/06/10

- Some equivalences:
 - 'All *F*s are *G*s' is equivalent to 'No *F*s are non-*G*s'.
 - * $(\forall x)(Fx \rightarrow Gx)$ is equivalent to $\sim (\exists x)(Fx \& \sim Gx)$.
 - 'All *F*s are *G*s' is equivalent to 'All non-*G*s are non-*F*s'.
 - * $(\forall x)(Fx \rightarrow Gx)$ is equivalent to $(\forall x)(\sim Gx \rightarrow \sim Fx)$.
 - 'Some *F*s are *G*s' is equivalent to 'Some *G*s are *F*s'.
 - * $(\exists x)(Fx \& Gx)$ is equivalent to $(\exists x)(Gx \& Fx)$.
 - 'No Fs are Gs' is equivalent to 'No Gs are Fs'.
 - * $\sim (\exists x)(Fx \& Gx)$ is equivalent to $\sim (\exists x)(Gx \& Fx)$.
- Some *non*-equivalences:
 - 'All *F*s are *G*s' is *not* equivalent to 'All *G*s are *F*s'.
 - * $(\forall x)(Fx \rightarrow Gx)$ is *not* equivalent to $(\forall x)(Gx \rightarrow Fx)$.
 - 'Some *F*s are non-*G*s' is *not* equivalent to 'Some *G*s are non-*F*s'.
 - * $(\exists x)(Fx \& \sim Gx)$ is *not* equivalent to $(\exists x)(Gx \& \sim Fx)$.
- The LSL equivalences + the general quantifier equivalences yield all.

UCB Philosophy Chapter 5 04/06/10

Branden Fitelson Philosophy 12A Notes 18

Further Symbolizations Involving \forall and \exists

- How should we paraphrase and/or symbolize the following sentence? (6) If anyone is wealthy, then economists are.
- At first blush, we might try to paraphrase (6) as follows:
 (6.1) If everyone is wealthy, then all economists are wealthy (which gives the LMPL symbolization: '(∀x)Wx → (∀x)(Ex → Wx)').
- But, (6.1) *cannot* be right. If the antecedent of (6.1) is true, then *everybody* is wealthy (not just the economists!). In this sense, (6.1) is analogous to an LSL *tautology* it's true *in all possible worlds*. Is *that* all (6) asserts?
- In fact, (6) asserts something *much stronger* than (6.1). What (6) says is that all it takes for every economist to be wealthy is for there to exist *one* wealthy person. This leads to the following alternative paraphrase of (6): (6.2) If *someone* is wealthy, then all economists are wealthy (which

gives the LMPL symbolization: $(\exists x)Wx \rightarrow (\forall x)(Ex \rightarrow Wx)'$).

UCB Philosophy

Chapter 5

04/06/10

Branden Fitelson

Philosophy 12A Notes

19

Still More Symbolizations Involving \forall and \exists

- How should we paraphrase and/or symbolize the following sentence?
 - (7) Every wealthy logician is happy.
- It helps to do a *Logish*, intermediate form first:
 - (7.1) For every x, if x is wealthy and x is a logician, then x is happy.
- This leads to the following LMPL symbolization:

$$(7.2) (\forall x)((Wx \& Lx) \rightarrow Hx)$$

- OK, but what about the following sentence?
 - (8) No wealthy economists are happy.
- This time, the *Logish*, intermediate form is:
 - (8.1) Not: there is at least one x such that x is wealthy, and x is an economist, and x is happy.
- Which leads to the following LMPL symbolization:

$$(8.2) \sim (\exists x)((Wx \& Ex) \& Hx)$$

Branden Fitelson

20

One Last Symbolization Involving \forall

Philosophy 12A Notes

- (9) A fetus is a person, but an embryo is not.
 - In this case, the domain of discourse must be wider than the domain of people (since we need to be able to say that some things are not persons).
 And, 'is a person' must then be included as a predicate in our dictionary.

P__ : __ is a person

F__: __ is a fetus

E__ : __ is an embryo

Domain of Discourse : all things

- Now, it helps to do a *Logish*, intermediate form first:
 - (9.1) For every x, if x is a fetus then x is a person, and for every x, if x is an embryo then x not a person.
- This leads to the following LMPL symbolization:

$$(9.2) (\forall x) (Fx \rightarrow Px) & (\forall x) (Ex \rightarrow \sim Px)$$

which is *semantically equivalent* (as we will *prove* in Chapter 6) to:

$$(9.3) (\forall x)((Fx \rightarrow Px) \& (Ex \rightarrow \sim Px))$$

But, (9.2) is preferred over (9.3), since (9.2) is closer to the structure of (9).

UCB Philosophy Chapter 5 04/06/10

UCB Philosophy CHAPTER 5 04/06/10