## Lifting tool instructions



Fiber Preparation Systems

4.3.2008

# Instructions for using of the lifting tool

#### 1. Restrictions

- 1.1. The lifting tool can only be used for lifting the screen basket and the rotor of the ModuScreen screen/RotoWash washer.
- 1.2. Do not use the lifting tool for lifting parts heavier than the maximum load shown on the tool.
- 1.3. Do not use the lifting tool as an extraction tool. All parts to be lifted must be detached before lifting.

## 2. Instructions

- 2.1. Place the lifting tool on top of the part to be lifted in a suitable position for lifting.
- 2.2. Fasten the lifting tool to the lifting holes in the part to be lifted using suitable screws. Before lifting, the screws must be tightened in all lifting points (qty: 2 6) on the lifting tool intended for the lifting of the part.
- 2.3. Fasten the lifting device to the fixed loop in the lifting tool or to a lifting eye screw fastened to the lifting point on the lifting tool, and lift off the part from the screen/washer.

### 3. Service

- 3.1. The lifting tool must be kept clean and stored in a dry place.
- 3.2. If the paint surface has damaged during operation, the damaged places must be patched up.

ANDRITZ OY

Domicile/Kotipaikka Helsinki VAT: FI10453978/Y-tunnus 1045397-8