

HEC MONTRÉAL

Writing with
`\title{LATEX}`

The Basics

BENOIT HAMEL



Benoit Hamel
Library technician, technical support
HEC Montréal Library

Writing with `\title{LATEX}`

Part One : The Basics
HEC Montréal Edition, revised and extended (english version)

© 2016 Vincent Goulet for the [original version](#). A list of sources that have been used for elaborating this training session can be found at the end of this document.

© This work is provided under the [Creative Commons Attribution-ShareAlike 4.0 International \(CC BY-SA 4.0\)](#) license. According to the license, you are free to:

- share – copy and redistribute the material in any medium or format;
- adapt – remix, transform, and build upon the material for any purpose, even commercially.

Under the following terms:

- Attribution – You must give appropriate credit, provide a link to the license, and indicate if changes were made. You may do so in any reasonable manner, but not in any way that suggests the licensor endorses you or your use.
- ShareAlike – If you remix, transform, or build upon the material, you must distribute your contributions under the same license as the original.
- No additional restrictions – You may not apply legal terms or technological measures that legally restrict others from doing anything the license permits.

Training Session Summary

A T_EX and L^AT_EX Presentation

What is T_EX and L^AT_EX?

L^AT_EX Document Creation Process

The Basics

Document Structure

Writing

Document Organization

Parts of a Document

Table of Contents and Referencing

Text Appearance

Fonts

Displaying text

hecthes Document Class


Bibliographie

A $\text{T}_{\text{E}}\text{X}$ and \LaTeX Presentation



What is \LaTeX ?

LESLIE LAMPORT



- A set of markup commands created by Leslie Lamport to facilitate \TeX 's use.
- Doesn't require any knowledge of typography in general and \TeX particularly.
- Typographic and logical markup language used to set the text layout (like HTML).
- Cross-platform language, identical from one operating system to the other and extensible with packages.
- “*author-level program*”



L^AT_EX Document Creation Process



HEC MONTRÉAL


Writing with a new perspective

- You write your document in plain text and you use commands to describe **what the text is** and **not what it should look like**.
- You focus on your **content**.
- You let \LaTeX do its work, that is taking care of the **container**.


\LaTeX Document Creation Process



L^AT_EX Document Creation Process



\LaTeX Document Creation Process



\LaTeX Document Creation Process



visualization with an
external reader

Some Things Done Simply with L^AT_EX...

... and not necessarily with a word processor

- Title page
- Table of contents
- Page numbering
- Figures and tables: display on a page, numbering, reference
- Equations: display, numbering and reference
- Citations and bibliographies
- Hyphenation
- Two-sided documents

Tools you'll need

- A T_EX distribution
 - T_EX Live (Windows and Unix/Linux)
 - MacT_EX, derived from T_EX Live (Mac OS)
 - MiK_TE_X (Windows, Mac OS and Unix/Linux)
- An integrated writing environment
 - Too many to list them all. . .
 - The library uses and recommends T_EXStudio
- A command line terminal

The Basics





Document Structure



HEC MONTRÉAL

Document structure

A \LaTeX document always has two parts:

```
\documentclass[11pt,french]{article}
\usepackage[utf8]{inputenc}
\usepackage[T1]{fontenc}
\usepackage{babel}
\usepackage[autolanguage]{numprint}

\begin{document}

  \section{Primo}

  Ac class dis donec erat facilisis magna mattis
  placerat potenti praesent primis sed tellus turpis
  ut vehicula. Ad amet eleifend eros fames habitant
  imperdiet integer laoreet leo magna magnis neque
  netus senectus taciti torquent.

  \section{Deuxio}

  Cursus dui egestas eget eros et hac magna massa mollis
  natoque penatibus sagittis sed tellus urna velit
  vestibulum vitae vulputate.
\end{document}
```

Document structure

A \LaTeX document always has two parts:

```
\documentclass[11pt,french]{article}  
\usepackage[utf8]{inputenc}  
\usepackage[T1]{fontenc}  
\usepackage{babel}  
\usepackage[autolanguage]{numprint}
```

← Preamble

```
\begin{document}
```

```
\section{Primo}
```

Ac class dis donec erat facilisis magna mattis
placerat potenti praesent primis sed tellus turpis
ut vehicula. Ad amet eleifend eros fames habitant
imperdiet integer laoreet leo magna magnis neque
netus senectus taciti torquent.

```
\section{Deuxio}
```

Cursus dui egestas eget eros et hac magna massa mollis
natoque penatibus sagittis sed tellus urna velit
vestibulum vitae vulputate.

```
\end{document}
```

Document structure

A \LaTeX document always has two parts:

```
\documentclass[11pt,french]{article}  
\usepackage[utf8]{inputenc}  
\usepackage[T1]{fontenc}  
\usepackage{babel}  
\usepackage[autolanguage]{numprint}
```

```
\begin{document}
```

```
\section{Primo}
```

Ac class dis donec erat facilisis magna mattis
placerat potenti praesent primis sed tellus turpis
ut vehicula. Ad amet eleifend eros fames habitant
imperdiet integer laoreet leo magna magnis neque
netus senectus taciti torquent.

```
\section{Deuxio}
```

Cursus dui egestas eget eros et hac magna massa mollis
natoque penatibus sagittis sed tellus urna velit
vestibulum vitae vulputate.

```
\end{document}
```

← Document body

Preamble

Document Class

The preamble's **first command** usually is the document class declaration.

```
\documentclass[options]{class}
```

Preamble

Document Class

The preamble's **first command** usually is the document class declaration.

```
\documentclass[options]{class}
```

MAIN CLASSES

- article, book, letter, report
- memoir, **hecthes**
- slides, beamer, **hecppt**

Preamble

Document Class

The preamble's **first command** usually is the document class declaration.

```
\documentclass[options]{class}
```

MAIN CLASSES

- article, book, letter, report
- memoir, **hecthes**
- slides, beamer, **hecppt**

MAIN OPTIONS

- 10pt, 11pt, 12pt
- oneside, twoside
- openright, openany
- english, french

Preamble

Packages

Packages allow you to **modify existing commands** and to **add features** to the system. They are loaded in the preamble with the `\usepackage[options]{package}` command.

```
\documentclass[options]{class}  
  
\usepackage{package}  
\usepackage[options]{package}  
\usepackage{package1,package2,package3,...}
```

Each package's documentation can be found on the [Comprehensive T_EX Archive Network Website](#).

Commands

- Always begin with a \
- Three main forms:

```
\commandname[optional_args]{mandatory_args}  
\commandname*[optional_args]{mandatory_args}  
\commandname
```


- Mandatory arguments between { and }
- Optional arguments between [and]
- Commands without arguments: the command's name ends with any character that isn't a letter or with a blank space.
- A command's scope is limited between { and }.

Environments

- Delimited by

```
\begin{environment}  
...  
\end{environment}
```

- An environment's content is treated differently from the remainder of the text.
- Changes apply only to the environment's content.



Writing

- You write your text in the document environment:

```
\begin{document}  
  The content of your document goes here ...  
\end{document}
```

- You write your document in plain text and use commands and environments to structure your text;
- You write your text like anywhere else:
 - Words are separated by one or more blank spaces;
 - Paragraphs are separated by one or more empty lines;
 - All extra white space is deleted on compilation.

Reserved Characters

T_EX's Reserved Characters

- # Argument number in commands
- \$ Math Mode delimiter
- & Table column delimiter
- % Starts a comment
- _ Indices (math)
- ^ Exponents (math)
- ~ No-break space
- { Opens a command or an environment definition
- } Closes a command or an environment definition

Reserved Characters

T_EX's Reserved Characters

- # Argument number in commands
- \$ Math Mode delimiter
- & Table column delimiter
- % Starts a comment
- _ Indices (math)
- ^ Exponents (math)
- ~ No-break space
- { Opens a command or an environment definition
- } Closes a command or an environment definition

TO USE THE CHARACTERS:

\#

\\$

\&

\%

_

\textasciicircum

\textasciitilde


\{

\}

Reserved Characters

- Quotation marks
 - The quotation marks " found on a keyboard are not used in typesetting.
 - Single (') or double (") beginning marks and single (') or double (") end marks are used to surround quotes.
- We type hyphens once (—), twice (— —) or three times (— — —) to produce hyphens, *en dashes* and *em dashes*.

Document Organization



Class Choice

The first thing you need to do when writing a \LaTeX document is to choose a document class.

Class	Divisions	Organization	Header	Footer
article	parts, sections, ...	one-sided	empty	centered page number
report	parts, chapters, sections, ...	one-sided	empty	centered page number
book	parts, chapters, sections, ...	two-sided	page numbers, titles	empty
hectthese	chapters, sections, subsections	two-sided	empty	centered page number

Titles and Title Page

Automatic layout:

```
% Preamble commands
\title[short title]{long title}
\author[short author name]{long author name}
\date[short date]{long date}
[...]

% Document body command
\maketitle
```

Manual layout:

STANDARD CLASSES

```
\begin{titlepage}
...
\end{titlepage}
```

MEMOIR AND HECTHESE CLASSES

```
\begin{titlingpage}
...
\end{titlingpage}
```

In the **hecthes** document class, title pages are automatically generated.

Abstract

- **article**, **report** or **memoir** classes : abstract generated with the abstract environment

```
\begin{abstract}  
...  
\end{abstract}
```

- **hecthese** class: french and english abstracts treated as normal, unnumbered chapters

Sections

- The document is subdivided with the following commands:

```
\part[short title]{long title}  
\chapter[short title]{long title}  
\section[short title]{long title}  
\subsection[short title]{long title}  
  
\subsubsection[short title]{long title}    % avoid using in books  
  
\paragraph[short title]{long title}        % evil! never use!  
\subparagraph[short title]{long title}    % EVIL! never EVER use!
```

- Automatic numbering
- Commands followed by an * = unnumbered section
- Short title as an optional argument

Appendices

- Appendices are sections and chapters with an alphanumeric numbering (A, A.1, ...).
- Sections following the `\appendix` command are all considered appendices.
- In the title, “Chapter” is changed into “Appendix”.

A Book's Logical Structure

book, memoir, hecthese classes

`\frontmatter`

- preface, table of contents, etc.
- roman page numbering (i, ii, ...)
- unnumbered chapters

`\mainmatter`

- the book's content
- arabic page numbering, starting at 1
- numbered chapters

A Book's Logical Structure

book, memoir, hecthesse classes

`\backmatter`

- everything else (bibliography, index, etc.)
- the page numbering continues
- unnumbered chapters



Table of Contents and Referencing



HEC MONTRÉAL

Table of Contents

- The table of contents is automatically generated with `\tableofcontents` .
- Needs **more than one** compilation to be generated.
- Unnumbered sections are not included.
- With the **hyperref** package, `\tableofcontents` generates the .pdf file's table of contents.

Table of Contents

- The table of contents is automatically generated with `\tableofcontents` .
- Needs **more than one** compilation to be generated.
- Unnumbered sections are not included.
- With the **hyperref** package, `\tableofcontents` generates the .pdf file's table of contents.
- `\tableofcontents*` , from the memoir document class, doesn't include the table of contents in the table of contents.

Table of Contents

- The table of contents is automatically generated with `\tableofcontents` .
- Needs **more than one** compilation to be generated.
- Unnumbered sections are not included.
- With the **hyperref** package, `\tableofcontents` generates the .pdf file's table of contents.
- `\tableofcontents*` , from the memoir document class, doesn't include the table of contents in the table of contents.
- `\listoffigures` generates the list of figures.
- `\listoftables` generates the list of tables.

Labels and Automatic Referencing

Because your computer will do it better than you...

- **Never** refer manually to a section, an equation, a table, etc.
- “Name” an element with `\label`
- Refer to that label with `\ref`
- Needs 2 to 3 compilations to generate

```
\section{Definitions}
\label{sec:definitions}

Lorem ipsum dolor sit amet, consectetur adipiscing elit,
sed do eiusmod tempor incididunt ut labore et dolore magna aliqua.
Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris
nisi ut aliquip ex ea commodo consequat.

\section{History}
As seen in Section \ref{sec:definitions}...
```

Labels and Automatic Referencing


Because your computer will do it better than you...

- The **hyperref** package generates hyperlinks to the references in the .pdf files.
- The `\autoref{}` command...
 - ① automatically identifies the reference type (section, equation, table, etc.);
 - ② generates a hyperlink with the text **and** number of the reference.

As seen in `\autoref{sec:definitions}`...

- The `\pageref{}` command refers to a page number.
- The **amsmath** package provides the `\eqref{}` command to refer to equations.

Text Appearance





Fonts



HEC MONTRÉAL

Fonts

- By default, all \LaTeX documents use the same font, Computer Modern.
- You should choose high-quality and complete fonts (diacritics, great choice of symbols).
- Very few fonts are adapted to maths: Palatino, Times, Lucida (\$) are safe choices.
- In the **hecthes** document class, mathptmx and mathpazo packages are preloaded so you can choose between Times and Palatino fonts.

Font Attributes

families

roman	<code>\rmfamily</code>	<code>\textrm{<text>}</code>
fixed width	<code>\ttfamily</code>	<code>\texttt{<text>}</code>
sans serif	<code>\sffamily</code>	<code>\textsf{<text>}</code>

shapes

upright	<code>\upshape</code>	<code>\textup{<text>}</code>
<i>italic</i>	<code>\itshape</code>	<code>\textit{<text>}</code>
<i>slanted</i>	<code>\slshape</code>	<code>\textsl{<text>}</code>
SMALL CAPS	<code>\scshape</code>	<code>\textsc{<text>}</code>

series

medium	<code>\mdseries</code>	<code>\textmd{<text>}</code>
bold	<code>\bfseries</code>	<code>\textbf{<text>}</code>

Font Attributes

families		
roman	<code>\rmfamily</code>	<code>\textrm{<text>}</code>
fixed width	<code>\ttfamily</code>	<code>\texttt{<text>}</code>
sans serif	<code>\sffamily</code>	<code>\textsf{<text>}</code>
shapes		
upright	<code>\upshape</code>	<code>\textup{<text>}</code>
<i>italic</i>	<code>\itshape</code>	<code>\textit{<text>}</code>
<i>slanted</i>	<code>\slshape</code>	<code>\textsl{<text>}</code>
SMALL CAPS	<code>\scshape</code>	<code>\textsc{<text>}</code>
series		
medium	<code>\mdseries</code>	<code>\textmd{<text>}</code>
bold	<code>\bfseries</code>	<code>\textbf{<text>}</code>
applies to all the following text		

Font Attributes

families

roman	<code>\rmfamily</code>
fixed width	<code>\ttfamily</code>
sans serif	<code>\sffamily</code>

`\textrm{<text>}`
`\texttt{<text>}`
`\textsf{<text>}`

shapes

upright	<code>\upshape</code>
<i>italic</i>	<code>\itshape</code>
<i>slanted</i>	<code>\slshape</code>
SMALL CAPS	<code>\scshape</code>

`\textup{<text>}`
`\textit{<text>}`
`\textsl{<text>}`
`\textsc{<text>}`

series

medium	<code>\mdseries</code>
bold	<code>\bfseries</code>

`\textmd{<text>}`
`\textbf{<text>}`

applies to the text in
the command

Italics

When using italics to put *emphasis* on parts of a text, you should use the following semantic command instead:

```
\emph{text}
```

`\emph{<text>}` commands can be nested in one another. Text in italics becomes upright and vice versa.

```
This house lacks a certain  
\emph{je ne sais quoi}\ldots
```


This house lacks a certain *je ne sais quoi*...

```
He said: " \emph{Enough  
\emph{poutine} for the week!}"
```

He said: « *Enough poutine for the week!* »

Font size

Standard commands	Size
<code>\tiny</code>	tiny
<code>\scriptsize</code>	script size
<code>\footnotesize</code>	footnote size
<code>\small</code>	small
<code>\normalsize</code>	normal size
<code>\large</code>	large
<code>\Large</code>	larger
<code>\LARGE</code>	largest
<code>\huge</code>	huge
<code>\Huge</code>	humongous



Lists

- Two main types of lists:
 - ① **unordered** with the `\itemize` environment
 - ② **ordered** with the `\enumerate` environment
- Lists can be nested into one another
- Markers are adapted to up to four nesting levels

Lists

- Two main types of lists:
 - ① **unordered** with the `\itemize` environment
 - ② **ordered** with the `\enumerate` environment
- Lists can be nested into one another
- Markers are adapted to up to four nesting levels

```
\begin{itemize}
  \item Two main types of lists :
  \begin{enumerate}
    \item \textbf{unordered} with the \verb=itemize= environment
    \item \textbf{ordered} with the \verb=enumerate= environment
  \end{enumerate}
  \item Lists can be nested into one another
  \item Markers are adapted to up to four nesting levels
\end{itemize}
```

Lists

- Two main types of lists:
 - ① **unordered** with the `\itemize` environment
 - ② **ordered** with the `\enumerate` environment
- Lists can be nested into one another
- Markers are adapted to up to four nesting levels

```
\begin{itemize}
  \item Two main types of lists :
  \begin{enumerate}
    \item \textbf{unordered} with the \verb=itemize= environment
    \item \textbf{ordered} with the \verb=enumerate= environment
  \end{enumerate}
  \item Lists can be nested into one another
  \item Markers are adapted to up to four nesting levels
\end{itemize}
```

- A third list type is available: description

Quotations

Short Quotes

We use the quote environment to insert a short, one-paragraph quote in our text.

```
\begin{quote}  
  Life is what happens to you while  
  you're busy making other plans.  
  — John Lennon  
\end{quote}
```

*Life is what happens to you while
you're busy making other plans. –
John Lennon*

Quotations

Long Quotations

We use the quotation environment to insert long quotations.

```
\begin{quotation}  
  I've missed more than 9000 shots in my  
  career. I've lost almost 300 games. 26  
  times I've been trusted to take the game  
  winning shot and missed.  
  
  I've failed over and over and over again  
  in my life. And that is why I succeed.  
  — Michael Jordan  
\end{quotation}
```

*I've missed more than 9000 shots
in my career. I've lost almost 300
games. 26 times I've been trusted to
take the game winning shot and
missed.*

*I've failed over and over and over
again in my life. And that is why I
succeed. – Michael Jordan*

Footnotes

- A footnote is inserted with the following command:

```
\footnote{text}
```

- The command must immediately follow the annotated text.
- Recommended method:

```
... fera remarquer que Pierre Lasou\footnote{%  
Spécialiste en ressources documentaires} %  
fut une grande aide dans la préparation de ...
```

- Footnote numbering and display are automatically generated.

Source Code

- To write source code in our text, we use the `verbatim` environment.

```
\begin{verbatim}  
  Text displayed as is in a  
    fixed-width font.  
\end{verbatim}
```

- To write source code inline in our text, we use the `\verb` command. Its syntax is `\verbcsourcec` where *c* can be any character not found in *source*.
- For more thorough inclusions of source code, you should use the **listings** package.

¹taken from the r4stats.com Website.

Source Code

Example¹ :

```
# ---Writing Your Own Functions (Macros)---  
  
# A good function that just prints.  
mystats <- function(x) {  
  print( mean(x, na.rm = TRUE) )  
  print(   sd(x, na.rm = TRUE) )  
}  
mystats(myvar)  
  
# A function with vector output.  
mystats <- function(x) {  
  mymean <- mean(x, na.rm = TRUE)  
  mysd   <- sd(x, na.rm = TRUE)  
  c(mean = mymean, sd = mysd )  
}  
mystats(myvar)  
myVector <- mystats(myvar)  
myVector
```

¹taken from the r4stats.com Website.


hecthese Document Class



hecthes Document Class

- Document class made specifically for HEC Montréal's M.Sc. and Ph.D. students;
- Available at <https://ctan.org/pkg/hecthes>;
- Document layout fully complies to the [Guidelines for Writing an Academic Work at a Graduate Level](#);
- Based on the **memoir** document class;
- Homemade commands for title creation and more. . . ;
- New homemade environments;
- You choose a template as a starting point (templates are available once the document class has been installed in a working directory);
- You use separate files for each chapter in your document.

Bibliographie



Bibliographie

Pour les nostalgiques de l'odeur de l'encre



Kopka, Helmut et Patrick W. Daly (2004).

Guide to \LaTeX , Fourth Edition,

Addison-Wesley,

ISBN 978-0-321-17385-0, 597 p.



Mittelbach, Frank *et al.* (2004).

The \LaTeX Companion, Second Edition,

Addison-Wesley,

ISBN 978-0201362992, 1120p.



Goossens, Michel et Franck Mittelbach (2007).

The \LaTeX Graphics Companion, Second Edition,

Addison-Wesley,

ISBN 978-0321508928, 976p.

Bibliographie

Pour les consciencieux de la forêt boréale



Goulet, Vincent (2016).

formation-latex-ul – Introductory L^AT_EX course in French,

Comprehensive T_EX Archive Network,

Consulté le 22 février 2018 à <https://ctan.org/pkg/formation-latex-ul>



Lees-Miller, John D. (2018).

Free & Interactive Online Introduction to L^AT_EX,

Overleaf,

Consulté le 22 février 2018 à <https://www.overleaf.com/latex/learn/free-online-introduction-to-latex-part-1>



ShareL^AT_EX Documentation,

ShareL^AT_EX,

Consulté le 22 février à https://fr.sharelatex.com/learn/Main_Page

Bibliographie

Pour les consciencieux de la forêt boréale

-  [L^AT_EX WikiBook](#)
-  [ShareL^AT_EX Documentation](#)
-  [T_EX - L^AT_EX Stack Exchange](#)
-  [L^AT_EX Community](#)
-  [Comprehensive T_EX Archive Network](#)
-  [UK List of TEX Frequently Asked Questions](#)
-  [Google. . .](#)

Période de questions

DOCUMENTATION DE LA FORMATION

<http://bit.ly/ltxhec1>

ÉVALUATION DE LA FORMATION

<http://bit.ly/ltxsurvey1>

SUPPORT T_EXNIQUE

Benoit Hamel : <benoit.2.hamel@hec.ca>