Bureau
International des
Poids et
Mesures

Le système international d'unités
The International System of Units

9 édition 2019

Annexe 2
Annex 2

Valeurs recommandées des fréquences étalons destinées à la mise en pratique de la définition du mètre et aux représentations secondaires de la seconde

Recommended values of standard frequencies for applications including the practical realization of the metre and secondary representations of the second

Partie 2
Part 2

Strontium 88 Ion ()

Strontium 88 Ion ()



CCL-CCTF Frequency Standards Working Group

Bureau International
des Poids et Mesures

Recommended values of standard frequencies for applications including the practical realization of the metre and secondary representations of the second
Part 2: Strontium 88 Ion ()

CCL-CCTF Frequency Standards Working Group

9th edition 2019

Appendix 2

1. Recommended value [1] of the frequency in the CIPM List of Frequencies

$f\left({}^{88}Sr^{+}\right) = 444\ 779\ 044\ 095\ 486.5\ \text{Hz}$

equivalent to

$\lambda\left({}^{88}Sr^{+}\right) = 674\ 025\ 590.863\ 134\ \text{fm},$

with a relative standard uncertainty of 1.5×10^{-15}.

This radiation was endorsed by the CIPM as a secondary representation of the definition of the second [2].

2. Source data

Adopted value $f\left({}^{88}Sr^{+}\right) = 444\ 779\ 044\ 095\ 486.5\ \text{Hz}$

With relative standard uncertainty: 1.5×10^{-15}

calculated from

$f\left({}^{88}Sr^{+}\right)$/ Hz	u/ Hz	source data
444 779 044 095 484.6	1.5	[3]
444 779 044 095 484	15	[4]
444 779 044 095 485.5	0.9	[5]
444 779 044 095 486.71	0.24	[6] (*a*)
444 779 044 095 485.27	0.75	[7]

(*a*) Since the result is largely dominated by the single measurement of ref. [6], the final uncertainty has been increased by a factor of three following the procedures outlined in ref. [8].

as a weighted mean of the above values.

$^{88}Sr^{+}$, $5s\ ^{2}S_{1/2} - 4d\ ^{2}D_{5/2}$ unperturbed optical transition

References

[1] Consultative Committee for Time and Frequency (CCTF): Report of the 21st meeting (8-9 June 2017) to the International Committee for Weights and Measures; https://www.bipm.org/utils/common/pdf/CC/CCTF/CCTF21.pdf

[2] CIPM Recommendation 1 (CI-2006): RECOMMENDATION 1 (CI-2006): Concerning secondary representations of the second https://www.bipm.org/utils/en/pdf/CIPMOutcomes/CI-2006-Recommendation-1.pdf

[3] H. S. Margolis, G.P. Barwood, G. Huang, H. A. Klein, S. N. Lea, K. Szymaniec, P. Gill: Hertz-Level Measurement of the Optical Clock Frequency in a Single $^{88}Sr^{+}$ Ion; *Science* **306** 1355 – 1358 (2004)

[4] P. Dubé, A. A. Madej, J. E. Bernard, L. Marmet, J.-S. Boulanger, S. Cundy: Electric Quadrupole Shift Cancellation in Single-ion Optical Frequency Standards; *Phys. Rev. Lett.* **95** 033001-1-4 (2005)

[5] A.A. Madej, P. Dubé, Z. Zhu, J. E. Bernard, M. Gertsvolf: $^{88}Sr^{+}$ 445-THz Single Ion Reference at the 10^{-17} Level via Control and Cancellation of Systematic Uncertainties and its Measurement against the SI Second; *Phys. Rev. Lett.* **109**, 203002 (2012)

[6] G. P. Barwood, G. Huang, H. A. Klein, L. A. M. Johnson, S. A. King, H. S. Margolis, K. Szymaniec, P. Gill: Agreement between two $^{88}Sr^{+}$ optical clocks to 4 parts in 1017; *Phys. Rev. A* **89**, 050501 (2014)

[7] P. Dubé, J. Bernard, M. Gertsvolf: Absolute frequency measurement of the $^{88}Sr^{+}$ clock transition using a GPS link to the SI second; *Metrologia* **54**, 290 – 298 (2017)

[8] F. Riehle, P. Gill, F. Arias, L. Robertsson: The CIPM List of Recommended Frequency Standard Values: Guidelines and Procedures; *Metrologia* **55**, 188 – 200 (2018)