

# Data Controlled Frequency Generator

Audio Signal Generation Unit  
User Manual And Technical Reference

ACOUSTIC RESEARCH





In this our 20th year of operation, and on behalf of the entire company; I would personally like to express my deepest gratitude for your continued support of our products and services.

Here at Acoustic Research, we pride ourselves in the quality of our instruments and ensure that every one meets the high standards that our customers deserve. I have no doubt, that the equipment that you have received today will meet those standards just as they did 20 years ago.

I wish you the greatest success in your research

*James Chaffinch*  
James Chaffinch, CEO

References in this publication to Acoustic Research products, programs, or services do not imply that Acoustic Research intends to make these available in all countries in which Acoustic Research operates. Any reference to an Acoustic Research product, program or service is not intended to state or imply that only Acoustic Research's product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any of Acoustic Research's intellectual property rights or other legally protectable rights may be used instead of the Acoustic Research product, program, or service. Evaluation and verification of operation in conjunction with other products, programs, or services, except those expressly designated by Acoustic Research, are the user's responsibility.

Acoustic Research may have patents or pending patent applications covering subject matter in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to an Acoustic Research authorized dealer or your Acoustic Research marketing representative, who will be able to forward on the request.

The following terms in this publication are trademarks of Acoustic Research Inc. In the European Union and/or other countries / economic areas.

- Acoustic Research

This publication could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. Acoustic Research may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time.

It is possible that this publication may contain reference to, or information about, Acoustic Research products (machines and programs), programming, or services that are not announced in your country. Such references or information must not be construed to mean that Acoustic Research intends to announce such Acoustic Research products, programming, or services in your country.

Requests for technical information about Acoustic Research products or services for those products, whether they be repair, maintenance or upgrade; should be made to your Acoustic Research authorized dealer or your Acoustic Research marketing representative.

This product's connections follow the Coordinated Universal Interworking Standard (C UIS) and as such can be used with any other product from any manufacturer that also adheres to this standard.

# Contents

Description	1
Gain	1
Detune	2
Wavetypes and Adjust	2
Sine	3
Triangle	3
Square	4
Interface	5
Unit Specifications	7

# Description

The Data Controlled Frequency Generator is a waveform generator, which accepts data transmissions of the “midinumber” format to define which frequencies to produce. In addition, the unit provides the ability to modify the generated waveform in a number of ways; selection of wavetype, gain control, detune control and adjustment for wavetypes which will modify those types in a manner consistent with their nature.


Most powerfully, these attribute values can be defined using audio signals, allowing for detailed and swift modification of the produced waveform. One can even use the output of the same unit as an input for these values, producing self-referential waveforms.

The values can be set in three ways; either manually with the dial, using the Voltage Control, or with the Audio Signal Control. The dial and the Voltage Control port are tied internally, and adjusting the value will move the dial. The Control Select switch is used to select between using the dial/voltage input pair, or Audio Signal Control input.

The following sections discuss these aspects in more detail.


## Gain

This attribute defines the value that will be used to determine the size of the generated waveform. Its range is from positive 1 to negative 1, which allows for the waveform to be inverted.



# Detune

This attribute defines modifies the selected frequency of the generated waveform. Its range is from 0 to 2. The generated frequency is a product of the selected frequency multiplied by this value. For example; with a setting of '1' the generated frequency will match the selected frequency. With a setting of '2' the generated frequency will be twice the selected frequency. With a setting of '0' the generated frequency will be zero.




# Wavetypes and Adjust

There are three main wavetypes available; Sine, Triangle and Square. The Adjust dial is used to modify the wavetypes in different ways. The manner of the modification is related to the wavetype.

The wavetype can be selected either with the three Waveform Select Buttons, or using the Waveform Select Toggle port.

## Sine

A simple Sine wave. The Adjust dial has no effect on this wavetype.




a simple sine wave

## Triangle

A linear ‘rise-and-fall’ waveform. In a Triangle wave both the ‘rise’ and ‘fall’ periods take 50% of the wave cycle time. The Adjust dial will modify these percentages.

For example, setting the dial to ‘zero’ will result in the ‘rise’ period taking 0% of the wave cycle time, while setting the ‘fall’ period to 100%. Such an arrangement results in a “Negative Ramp Saw Wave”. Setting the dial to ‘one’ will reverse the ‘rise’ and ‘fall’ values, resulting in a “Positive Ramp Saw Wave”.

Interstitial values will result in proportional ‘rise-and-fall’ percentages.




## Square


A logical ‘up-and-down’ waveform. In a Square wave both the ‘up’ and ‘down’ periods take 50% of the wave cycle time. The Adjust dial will modify these percentages.

For example, setting the dial to ‘zero’ will result in the ‘up’ period lasting 0% of the wave cycle time, while setting the ‘down’ period to 100%. Such an arrangement would result in the generated signal only consisting of the lower value of the waveform; essentially a constant value. Setting the dial to ‘one’ will reverse the ‘up’ and ‘down’ values, resulting in a constant higher value.

Interstitial values will result in proportional ‘up-and-down’ percentages.



# Interface



1. Sine Waveform Select Button
2. Triangle Sine Waveform Select Button
3. Square Sine Waveform Select Button
4. Gain Control Select  
This switch is used to select between using the dial/voltage input pair (5 and 13), or Audio Signal Gain Control input (12)
5. Gain Dial  
Used for manually selecting the gain value
6. Detune Control Select  
This switch is used to select between using the dial/voltage input pair (7 and 15), or Audio Signal Detune Control input (14)
7. Detune Dial  
Used for manually selecting the detune value
8. Adjust Control Select  
This switch is used to select between using the dial/voltage input pair (9 and 17), or Audio Signal Adjust Control input (16)
9. Adjust Dial  
Used for manually selecting the adjust value
10. Audio Signal Output  
The audio signal output connection  
  
CUIIS type: Orange
11. Waveform Select Toggle  
Used to externally select the waveform.  
Repeated "Active" signals will cycle through all options in a loop  
  
CUIIS type: Red
12. Audio Signal Gain Control  
  
CUIIS type: Orange
13. Voltage Gain Control

CUIS type: Green

14. Audio Signal Detune Control

CUIS type: Orange

15. Voltage Detune Control

CUIS type: Green

16. Audio Signal Adjust Control

CUIS type: Orange


17. Voltage Adjust Control

CUIS type: Green

18. Musical Note Data Input

CUIS type: Blue

# Unit Specifications





© Copyright Acoustic Research Inc. 1981. All rights reserved